SPARK LENS: AUTONOMOUS REPOSITORY INTELLIGENCE AND VULNERABILITY VERIFICATION PLATFORM

A Project Report Submitted in Partial Fulfillment of the Requirement
for the Award of the Degree of

BACHELOR OF TECHNOLOGY
IN
COMPUTER SCIENCE AND ENGINEERING

SUBMITTED BY

Candidate Name	University Roll No.	Contact Email
Siddharth Kumar	2301301422	sidkumar1525@gmail.com
Tushar Saini	2301301463	tusharsaini.in@gmail.com
Shobhit Singh	2301301417	shobhitsinghsingh.2019@gmail.com



DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

SCHOOL OF TECHNOLOGY

QUANTUM UNIVERSITY, ROORKEE
UTTARAKHAND - 247667, INDIA

ACADEMIC YEAR: 2025 – 2026

CERTIFICATE

This is to certify that the project report entitled "SPARK LENS: AUTONOMOUS REPOSITORY INTELLIGENCE AND VULNERABILITY VERIFICATION PLATFORM" being submitted by **Siddharth Kumar, Tushar Saini and Shobhit Singh** in partial fulfillment for the award of the Degree of Bachelor of Technology in Computer Science and Engineering from the Department of Computer Science & Engineering, Quantum University, Roorkee, is a record of bona fide work carried out by them under my guidance and supervision.

The results embodied in this report have not been submitted to any other University or Institute for the award of any degree or diploma. The conceptual framework, workflow architecture, and execution models formulated in this report represent original engineering work.

Ms. Rimmy Chhabra **Project Guide**	**Ms. Shilpy Sharma** **Program Officer**	**Dr. Mridula** **Head of Department**
_____	_____	_____

DECLARATION

We hereby declare that the project entitled "**SPARK LENS: AUTONOMOUS REPOSITORY INTELLIGENCE AND VULNERABILITY VERIFICATION PLATFORM**" submitted for the B. Tech Degree in Computer Science and Engineering is our original work. This project has not formed the basis or been submitted for the award of any degree, diploma, associateship, fellowship, or any other similar title in any other college, institute, or university.

We have adhered to all academic ethics and integrity standards, and proper acknowledgments have been made wherever external literature, benchmarks, or architectural paradigms have been referenced.

Candidate Name	Roll Number	Signature
Siddharth Kumar	2301301422	_____
Tushar Saini	2301301463	_____
Shobhit Singh	2301301417	_____

Place: Roorkee, Uttarakhand
Date: 29 November 2026

ACKNOWLEDGEMENT

We express our deep sense of gratitude and sincere indebtedness to our respected Project Guide, **Ms. Rimmy Chhabra**, Assistant Professor, Department of Computer Science and Engineering, Quantum University, Roorkee, for her invaluable guidance, constant motivation, insightful suggestions, and constructive criticism throughout the conception and architectural implementation of this project titled "**Spark Lens: Autonomous Repository Intelligence and Vulnerability Verification Platform**".

We are profoundly thankful to **Ms. Shilpy Sharma**, Assistant Professor & Program Officer, Department of Computer Science and Engineering, and to **Dr. Mridula**, Professor & Head of Department, CSE & Dean Academics, Quantum University, for providing exceptional academic infrastructure, computing facilities, and administrative support that enabled the thorough execution of our engineering models.

Lastly, we extend our heartfelt appreciation to our parents, peers, and faculty members for their unwavering encouragement, patience, and moral support during the entirety of our undergraduate studies.

Siddharth Kumar
Tushar Saini
Shobhit Singh
Department of CSE, Quantum University

ABSTRACT

Modern agile development environments and automated Continuous Integration / Continuous Deployment (CI/CD) pipelines suffer from an insidious crisis: extreme alert fatigue generated by legacy Static Application Security Testing (SAST) and basic Software Composition Analysis (SCA) utilities. Industry studies reveal that 70% to 85% of warnings produced by static code analyzers represent theoretical, non-exploitable, or false-positive issues. Meanwhile, contemporary artificial intelligence coding assistants generate speculative code patches without any verification of runtime correctness or test regression, placing heavy triage burdens onto overburdened developers.

In response to this industry-wide challenge, we have designed and implemented Spark Lens, an autonomous repository intelligence and vulnerability verification platform. Unlike disjointed developer tooling, Spark Lens establishes a singular, cohesive architectural lifecycle termed the Golden Path: Connect & Ingest, Analyze & Explain, Verify (The Sandbox), Prioritize, Fix & Remediate, and Validate. By connecting directly to GitHub via an autonomous application integration, Spark Lens operates as an autonomous security engineer that not only identifies potential weaknesses but actively proves their exploitability and provides pre-tested remediations.

The foundational technological moat of Spark Lens lies in our proprietary 'Verify' phase. While conventional scanners halt at syntactic analysis, Spark Lens automatically constructs executable Proof of Concept (PoC) test harnesses and launches them inside strictly isolated, zero-egress ephemeral container sandboxes (Docker / Kubernetes micro-VMs). If and only if the flaw executes reproducibly under sandbox conditions, it is confirmed as a verified threat. Spark Lens then utilizes an AST-aware Context Engine to synthesize surgical, non-breaking code patches and automatically validates them inside the regression sandbox to verify zero functional regressions before opening a 1-click Pull Request.

Empirical evaluation demonstrates that our verification sandbox eliminates over 82% of false positives, reduces Mean Time to Remediate (MTTR) from days to minutes, and restores developer trust in automated security tooling.

Keywords: *Autonomous Repository Intelligence, Ephemeral Container Sandboxes, Proof of Concept Verification, Static Code Analysis, Large Language Models, Automated Remediation, CI/CD DevSecOps.*

TABLE OF CONTENTS

CERTIFICATE OF THE SUPERVISOR **i**

CANDIDATE DECLARATION **ii**

ACKNOWLEDGEMENTS **iii**

ABSTRACT **iv**

TABLE OF CONTENTS **v-vi**

LIST OF TABLES **vii**

LIST OF FIGURES **viii**

LIST OF ABBREVIATIONS **ix**

CHAPTER 1: INTRODUCTION **1-3**

1.1 Background and Problem Statement 1

1.2 The False Positive Crisis & Alert Fatigue 1

1.3 Project Motivation & Vision: Spark Lens 2

1.4 Primary Engineering Objectives 2

1.5 Project Scope and Operating Boundaries 3

1.6 Organization of the Project Report 3

CHAPTER 2: LITERATURE SURVEY & PROBLEM FORMULATION **4-8**

2.1 Evolution of Static Application Security Testing (SAST) 4

2.2 Dynamic Analysis, Taint Tracking & Fuzzing 4

2.3 Pre-Trained Code Models and Generative Foundation Models in Security 5

2.4 Theoretical Foundations of Vulnerability Detection Paradigms 6

2.4.1 Deterministic Static Analysis Theory (Syntactic Over-Approximation) 6

2.4.2 Generative Semantic Inference Theory (Probabilistic Contextual Attention) 6

2.4.3 Comparative Analytical Framework of Detection Paradigms 7

2.5 Comparative Analysis of Incumbent Security Solutions 7

2.6 Identified Technical Gaps & The Spark Lens Advantage 8

CHAPTER 3: METHODOLOGY & THE GOLDEN PATH FRAMEWORK **9-11**

3.1 Architectural Paradigm: The Golden Path Workflow 9

3.2 Phase 1: Connect & Ingest (Repository Context Acquisition) 9

3.3 Phase 2: Analyze & Explain (Dual-Engine Semantic Triage) 10

3.4 Phase 3: Verify (The Core Ephemeral Sandbox Moat) 10

3.5 Phase 4: Prioritize (Risk & Exploitability Ranking) 10

3.6 Phase 5: Fix & Remediate (Context-Aware Code Synthesis) 11

3.7 Phase 6: Validate (Automated Regression Verification) 11

3.8 System Hardware and Software Requirements 11

CHAPTER 4: SYSTEM DESIGN & CONCEPTUAL STRUCTURE **12-16**

4.1 High-Level Multi-Tier System Architecture 12
4.2 Conceptual Structure & End-to-End Workflow Dynamics 13
4.3 Component Interaction & Data Flow Architecture (DFD Levels 0 & 1) 14
4.4 UML Use Case Analysis & Actor Modeling 15
4.5 UML Sequence Modeling (The Autonomous Verification Loop) 15
4.6 UML Component & Class Design Structure 16
4.7 Ephemeral Sandbox Security Boundaries & Isolation Protocols 16
CHAPTER 5: IMPLEMENTATION DETAILS & CORE ENGINES 17-18
5.1 Presentation Tier & Interactive Developer Views 17
5.2 Backend Orchestrator & GitHub Integration Engine 17
5.3 AI Context Engine & AST Chunking Pipeline 18
5.4 The Ephemeral Sandbox Execution Rig (Docker & K8s) 18
5.5 Automated Remediation Synthesizer & PR Generator 18
CHAPTER 6: EXPERIMENTAL TESTING, RESULTS & DISCUSSIONS 19-28
6.1 Contrastive Benchmark Architecture & Empirical Verification Methodology 19
6.2 Aggregate Detection Accuracy and False-Positive Suppression (RQ1) 20
6.3 Language-Stratified Performance Analysis: Python vs. JavaScript vs. Java 22
6.4 Line-Level Fault Localization Precision and Tokenization Drift Mitigation (RQ2) 24
6.5 Operational Overhead: Latency, Token Cost, and Developer Inspection Effort (RQ3) 25
6.6 Verification Robustness, Component Ablation & Residual Failure Analysis (RQ4) 26
6.7 Empirical PoC Synthesis & Sandbox Verification in Open-Source Repositories 27
6.8 Remediation Integrity & Test Regression Validation 28
CHAPTER 7: CONCLUSION & FUTURE WORK 29-30
7.1 Summary of Engineering Contributions & Research Milestones 29
7.2 Technical Impact on Modern DevSecOps Practices 29
7.3 Architectural Limitations & Boundary Constraints 29
7.4 Ethical Considerations & Defensive AI Guardrails 30
7.5 Technical Roadmap for Future Development 30
REFERENCES / BIBLIOGRAPHY 31-32
APPENDIX A: SAMPLE EPHEMERAL SANDBOX RECIPE 33
APPENDIX B: SAMPLE AI-GENERATED POC & REMEDIATION DIFF 34
APPENDIX C: SYSTEM CONFIGURATION & ENVIRONMENT SETUP 35-36

LIST OF TABLES

Table No.	Title	Page No.
Table 2.1	Theoretical Comparison of Vulnerability Detection Paradigms	7
Table 2.2	Comparative Evaluation: Spark Lens vs Existing DevSecOps Tools	8
Table 3.1	Minimum Hardware Specifications for Production Deployment	11
Table 4.1	State Transition Matrix for Vulnerability Verification	14
Table 6.1	Contrastive Benchmark Vulnerability Verification Test Suite Scenarios	19
Table 6.2	Aggregate Vulnerability Detection and False-Positive Suppression Performance	20
Table 6.3	Line-Level Fault Localization Performance Across Controlled Baseline Configurations	24
Table 6.4	Operational Resource, Latency, and Economic Efficiency Metrics Across Configurations	25
Table 6.5	Component Attribution and Ablation Analysis Across Verification Stages	26
Table 6.6	False Positive Elimination Benchmark Across Production Open-Source Repositories	27

LIST OF FIGURES

Figure No.	Title	Page No.
Figure 3.1	The Golden Path: Six-Stage Autonomous Remediation Lifecycle	9
Figure 4.1	Spark Lens Multi-Tier Architectural Overview	12
Figure 4.2	UML Use Case Diagram: Actor Interactions with Spark Lens Engine	15
Figure 4.3	UML Sequence Diagram: Autonomous Verification & PR Flow	16
Figure 6.1	Comparative Performance Evaluation Across Contrastive Benchmark (Top Panel)	21
Figure 6.2	False-Positive Rate (FPR) Suppression Across Baseline Verification Configurations	22
Figure 6.3	Category-Level Evaluation of Correct Classifications Across 10 Python Weakness Classes	23

LIST OF ABBREVIATIONS

Abbreviation	Full Expansion
AI	Artificial Intelligence
API	Application Programming Interface
AST	Abstract Syntax Tree
BOLA	Broken Object-Level Authorization
CI/CD	Continuous Integration / Continuous Deployment
CVE	Common Vulnerabilities and Exposures
CWE	Common Weakness Enumeration
DAST	Dynamic Application Security Testing
ERD	Entity Relationship Diagram
HTTP	Hypertext Transfer Protocol
JSON	JavaScript Object Notation
LLM	Large Language Model
MTTR	Mean Time to Remediate
OAuth	Open Authorization Protocol
PoC	Proof of Concept
PR	Pull Request
RAG	Retrieval-Augmented Generation
RCE	Remote Code Execution
REST	Representational State Transfer
SAST	Static Application Security Testing
SCA	Software Composition Analysis
SQLi	Structured Query Language Injection
UML	Unified Modeling Language
XSS	Cross-Site Scripting

CHAPTER 1
INTRODUCTION

1.1 Background and Problem Statement

In the contemporary landscape of software engineering, velocity and agility have emerged as the paramount metrics of organizational success. The advent of modern DevOps methodologies, automated Continuous Integration and Continuous Deployment (CI/CD) pipelines, and extensive reliance on distributed microservices have accelerated feature deployment cycles from months to mere hours. Modern web and cloud-native applications are constructed upon vast hierarchies of open-source dependencies, third-party libraries, and intricate REST/GraphQL APIs. However, this remarkable acceleration in development throughput has precipitated an unprecedented crisis in application security engineering.

As code repositories expand across thousands of commits and pull requests every week, security review has become an acute operational bottleneck. Software vulnerabilities—ranging from injection attacks (SQLi, Command Injection) and Broken Object-Level Authorization (BOLA) to memory corruptions, hardcoded credentials, and prototype pollutions—are routinely introduced into production codebases. Traditional security audits conducted manually by specialized penetration testers or application security teams cannot scale with daily release rhythms. In response, enterprises have mandated the integration of automated security scanners into developer workflows. Yet, this automation has introduced a foundational engineering challenge that threatens the very productivity it was designed to protect.

1.2 The False Positive Crisis & Alert Fatigue

The fundamental deficiency of prevailing automated security tooling—predominantly Static Application Security Testing (SAST) and Software Composition Analysis (SCA)—is their over-reliance on pattern matching and heuristic syntax analysis without any runtime execution awareness. Static analyzers examine Abstract Syntax Trees (ASTs) or regex-based pattern banks in isolation. When a scanner detects a syntax structure that theoretically resembles a tainted data flow or an outdated library import, it immediately generates a security alert. However, in real-world application architectures, theoretical taint sinks are frequently

neutralized by preceding sanitization routines, framework-level middleware, dead code branches, or private network boundaries that the static scanner cannot comprehend.

Consequently, empirical investigations across enterprise engineering organizations indicate that between 70% and 85% of all alerts emitted by static scanners represent non-exploitable false positives. This flood of false alarms creates acute 'alert fatigue'. Developers, confronted with hundreds of theoretical warnings on every pull request, rapidly become desensitized to security notifications. Critical, genuinely exploitable vulnerabilities become buried beneath mountains of synthetic noise, remaining unaddressed until catastrophic production breaches occur. Moreover, the adversarial friction between security teams and development teams intensifies, as developers view security scanners as disruptive impediments rather than collaborative engineering assets.

1.3 Project Motivation & Vision: Spark Lens

To decisively dismantle this crisis, we conceptualized and implemented Spark Lens. Our core philosophy is that an automated security tool must never ask a software developer to investigate or fix a vulnerability unless the tool can definitively prove that the vulnerability is actively exploitable in a realistic execution environment. We observed that existing artificial intelligence developer tools and code assistants operate in a disjointed fashion: some provide static summaries, others suggest hallucinated code fixes, and none verify whether the recommended patch resolves the flaw without breaking existing application features.

Spark Lens reimagines the security lifecycle as an autonomous, unified pipeline that functions as an intelligent tier-1 security engineer. By connecting directly to GitHub via an autonomous application integration, Spark Lens ingests repository context, performs deep dual-engine semantic analysis, synthesizes executable Proof of Concept (PoC) exploits, and verifies them inside isolated, ephemeral container sandboxes. By converting abstract alerts into reproducible runtime proofs and verified pull requests, Spark Lens bridges the chasm between static analysis and dynamic validation.

1.4 Primary Engineering Objectives

In our implementation of Spark Lens, we formulated five primary engineering objectives:

1. Autonomous Version Control Integration: To engineer a seamless GitHub integration via OAuth 2.0 and event-driven Webhooks that automatically ingests full repository context,

commit histories, Abstract Syntax Trees (ASTs), and dependency graphs upon every code push.

2. Dual-Engine Semantic Analysis & Natural Explanation: To combine deterministic static rule scanning with Large Language Model (LLM) reasoning, translating complex taint traces into intuitive, human-readable explanations of vulnerability mechanisms.

3. Ephemeral Sandbox Verification (The Core Technical Moat): To eliminate false positives by autonomously spinning up isolated, ephemeral Docker/Kubernetes container environments that safely execute AI-generated Proof of Concept (PoC) test harnesses to empirically verify exploitability.

4. Risk-Weighted Threat Prioritization: To construct an intelligent scoring engine that ranks security findings based strictly upon demonstrated sandbox exploitability and business blast radius, filtering out theoretical alerts.

1.5 Project Scope and Operating Boundaries

The functional scope of Spark Lens encompasses web application ecosystems across Node.js/TypeScript, Python, and Go hosted on modern version control platforms (primarily GitHub). The analysis encompasses Common Weakness Enumerations (CWEs) including injection flaws, cross-site scripting, prototype pollution, path traversal, hardcoded secrets, and vulnerable dependencies. The execution sandbox is strictly isolated with zero external network connectivity (--network none) and strict resource caps to guarantee absolute execution safety.

1.6 Organization of the Project Report

This project report is structured into seven comprehensive chapters: Chapter 2 reviews literature, existing static/dynamic tools, and formulates the core research gaps. Chapter 3 details our Golden Path methodology and operational requirements. Chapter 4 provides extensive UML modeling, sequence flows, and relational database schemas. Chapter 5 delves into the implementation of our core engines (Ingestion, Context Chunking, Ephemeral Sandbox Rig, Remediation Synthesizer). Chapter 6 presents empirical evaluation, test cases, and false-positive elimination metrics. Chapter 7 concludes the report and outlines our technical roadmap.

CHAPTER 2
LITERATURE SURVEY & PROBLEM FORMULATION

2.1 Evolution of Static Application Security Testing (SAST)

Static Application Security Testing (SAST) represents one of the foundational pillars of software assurance. Pioneering frameworks such as Coverity, Fortify, SonarQube, CodeQL, and Semgrep compile source code into Abstract Syntax Trees (ASTs), Control Flow Graphs (CFGs), and Program Dependence Graphs (PDGs) without executing the application. Taint analysis engines track untrusted data flow from user-controlled entry points (sources) to security-sensitive operations (sinks). While mathematically rigorous in strictly typed, constrained environments, deterministic rule-based analysis suffers from acute structural degradation when applied to modern dynamically typed languages such as Python and JavaScript.

In dynamically typed ecosystems, reflections, dynamic function dispatches, asynchronous event loops, and mutable prototype chains obscure data-flow reachability. Consequently, static analyzers are forced to adopt conservative, over-approximating heuristics: if an untrusted data path might theoretically reach a sensitive sink under any hypothetical runtime execution condition, the analyzer flags it as a vulnerability. Empirical investigations across industry codebases confirm that this conservative over-approximation yields a staggering 70% to 85% false-positive rate, inducing pervasive alert fatigue that causes software developers to ignore genuine security advisories.

2.2 Dynamic Analysis, Taint Tracking & Fuzzing

Dynamic Application Security Testing (DAST) analyzes running applications from an external perspective by dispatching crafted HTTP payloads to exposed API endpoints and observing runtime responses. Because DAST operates on live services, any triggered vulnerability represents a verified exploit condition, eliminating static false positives. However, DAST frameworks suffer from severe coverage limitations: they require fully deployed staging environments, complex mock databases, and active authentication state machines. Crucially, DAST tools cannot pinpoint the exact source code line responsible for a flaw, nor can they synthesize targeted source code repairs.

Fuzzing frameworks, such as American Fuzzy Lop (AFL) and libFuzzer, employ coverage-guided genetic mutations to discover edge-case memory crashes. While highly effective for low-level system binaries and network protocols, fuzzers are notoriously inefficient when applied to multi-tiered web applications with complex relational databases and multi-step business logic. Furthermore, fuzzing produces crash dumps rather than actionable developer explanations, demanding specialized security expertise for manual root-cause triage.

2.3 Pre-Trained Code Models and Generative Foundation Models in Security

Automated software vulnerability analysis has evolved across four distinct yet overlapping methodological epochs over the past decade. In the foundational representation learning epoch, researchers formulated deep learning models over token streams and graph structures (such as SySeVR by Li et al. and CodeBERT/GraphCodeBERT by Guo et al.) to overcome the manual rule-engineering bottleneck of SAST. While these models captured semantic associations, they exhibited vulnerability shortcut learning and struggled to generalize across diverse software repositories.

In the second epoch, pre-trained transformer foundation models (such as GPT-4, Claude, and CodeLlama) demonstrated remarkable capabilities in code comprehension and natural language reasoning. However, empirical benchmarking by Gnieciak & Szandala (IEEE Access 2025) and Pearce et al. (IEEE S&P 2022) revealed an operational paradox: while frontier LLMs substantially elevate true vulnerability recall (up to 88.3%), their probabilistic attention mechanisms suffer from acute 'associative hypersensitivity'. LLMs frequently over-analyze legitimate sanitization logic, inventing speculative exploit bypasses on safe code and generating severe false-positive rates (exceeding 40%).

In the third and fourth epochs, researchers explored repository-scale coding agents (such as JITVul by Yildiz et al. and CVE-Bench by Wang et al.) and continuous integration developer impact studies (such as Sun et al., IEEE TSE 2026, analyzing over 22,000 AI review comments). These studies established that ungrounded AI code review comments are overwhelmingly ignored by maintainers unless they provide exact line anchoring, reproducible execution proofs, and verified non-breaking remediation patches. Tufano et al. (IEEE TSE 2024) demonstrated that human reviewers spend over 100 person-hours triaging

noisy benchmark predictions, underscoring the urgent imperative for deterministic evidence verification.

2.4 Theoretical Foundations of Vulnerability Detection Paradigms

2.4.1 Deterministic Static Analysis Theory (Syntactic Over-Approximation)

Deterministic Static Analysis Theory posits that software vulnerabilities are structural properties of a program's intermediate representation. During compilation, the analyzer transforms source text into an Abstract Syntax Tree (AST), where every node is bound to exact line and column byte coordinates. Taint propagation is formalized over a finite lattice L = (P(V), subseteq, union, intersect, empty, V), where V is the set of program variables. A variable v is deemed tainted if there exists any path in the Control Flow Graph from a source statement to v without an intervening recognized sanitizer node.

Because determining whether a path is dynamically reachable is undecidable (equivalent to the halting problem), static taint analysis adopts conservative over-approximation: if a path is syntactically connected, it is assumed to be reachable. This causes severe failure modes on custom sanitizers (such as regular-expression hostname allowlists or canonical path checks), which rule-based engines cannot interpret. Furthermore, static analysis exhibits complete blindness to semantic vulnerabilities caused by the absence of domain checks, such as Missing Authorization (CWE-862) and Prototype Pollution (CWE-1321), where no forbidden syntactic token is present.

2.4.2 Generative Semantic Inference Theory (Probabilistic Contextual Attention)

Generative Semantic Inference Theory models source code as token sequences over which a multi-head self-attention mechanism computes probabilistic contextual dependencies: H = Softmax(Q K^T / sqrt(d_k)) V. Unlike rigid syntactic pattern matchers, transformer models can interpret developer intent, infer business logic constraints, and detect when a route handler omits essential permission checks.

However, generative models lack axiomatic soundness. When presented with code containing security-sensitive keywords (such as execute, shell, or eval), the model's self-attention triggers associative hypersensitivity: it assumes the code is vulnerable and hallucinates speculative bypasses around robust sanitizers. Furthermore, because LLMs process code via Byte-Pair Encoding (BPE) subword tokenization—where consecutive

newlines and indentation blocks are compressed—frontier models suffer from line-counting drift of 1 to 3 lines, corrupting inline review comments.

2.4.3 Comparative Analytical Framework of Detection Paradigms

Recognizing that deterministic static analysis and generative semantic inference operate at complementary levels of program abstraction, Spark Lens unifies both paradigms into Evidence-Guided Hybrid Verification. Table 2.1 formalizes this comparative analytical framework.

Verification Dimension	1. Deterministic SAST	2. Standalone Generative LLM	3. Spark Lens Hybrid Platform
Primary Analysis Theory	Syntactic AST & Data-Flow Lattice	Probabilistic Token Self-Attention	Evidence-Guided Hybrid Verification
Input Program Representation	Compiler AST, CFG, PDG Graph	Linear Subword Token Stream	Line-Indexed AST Slices + Sink Coordinates
Detection Precision & FPR	Low Precision (67.3%), High FPR (30.0%)	Moderate Precision (67.1%), Very High FPR (43.3%)	High Precision (93.3%), Ultra-Low FPR (6.7%)
True Vulnerability Recall	Moderate Recall (61.7%)	High Recall (88.3%)	Very High Recall (93.3%)
Line-Level Fault Localization	High on Single-Line, Low on Multi-Line (75.7%)	Degraded by BPE Tokenization Drift (54.7%)	Exact 1-Based Coordinates via AST Binding (92.9%)
Handling of Custom Sanitizers	Fails (Flags Valid Sanitizers as Flaws)	Fails (Over-Analyzes & Hallucinates Bypasses)	Verifies Sanitizer Invariants via Slices & Sandbox
Missing Control & Logic Flaws	Complete Blindness (0% Coverage on CWE-862)	Detects via Implicit Intent Reasoning	Detects via Structural Route Hooks + Sliced LLM
Execution Determinism & Audit	100% Deterministic & Locally Auditable	Stochastic Non-Deterministic	Deterministic Candidate Anchoring + Schema Constrained
Remediation & Repair Action	Generic Rule Warning Text	Synthesizes Untested, Breaking Patches	Synthesizes & Docker-Validates Tested Pull Requests

Table 2.1: Theoretical Comparison of Vulnerability Detection Paradigms

2.5 Comparative Analysis of Incumbent Security Solutions

To position Spark Lens within the contemporary DevSecOps landscape, we conducted a rigorous comparative evaluation against established industry platforms, including SonarQube, Snyk, and GitHub Dependabot. The analytical matrix is detailed in Table 2.2.

Capability / Feature	SonarQube	Snyk	GitHub Dependabot	Spark Lens (Our Platform)
Analysis Paradigm	Static AST Pattern Matching	Static Taint + SCA Scanning	Dependency Graph Manifests	Hybrid Static Slicing + Ephemeral Sandbox
False Positive Elimination	None (Manual developer triage)	Heuristic suppression filters	None (Flags unreferenced CVEs)	Automated PoC Sandbox Verification
Exploit Reproducibility Proof	None (Theoretical alerts)	None (Static severity scoring)	None (Advisory links only)	Isolated Ephemeral Docker PoC Harness
Root-Cause Localization	Line-level syntactic flagging	File / line annotation	Manifest line number only	Exact AST Coordinate + Data-Flow Span
Remediation Generation	Generic documentation snippets	Automated dependency PRs	Automated dependency bumps	Surgical, Regression-Tested Source Patches

Table 2.2: Comparative Evaluation: Spark Lens vs Existing DevSecOps Tools

2.6 Identified Technical Gaps & The Spark Lens Advantage

Our theoretical and empirical survey revealed three profound systemic gaps in the modern software assurance ecosystem:

1. Disconnected Security Workflow: Modern development organizations rely on fragmented tools—SAST scans pull requests, dependency scanners audit manifests, and developers manually attempt to reconstruct exploit scenarios. There is no unified system that autonomously bridges static detection, dynamic exploit reproduction, and automated patch validation.

2. The Verification Vacuum: No existing commercial or open-source tool attempts to dynamically verify candidate vulnerabilities in isolated ephemeral cleanrooms before alerting developers. By stopping at theoretical detection, traditional tools inevitably dump speculative alerts onto developers.

3. Untested Remediation: Tools offering automated pull requests (such as Dependabot) merely increment version strings, frequently introducing breaking API changes, while generative code assistants emit unverified code diffs that fail build assertions. Spark Lens directly closes these gaps through our six-stage Golden Path, establishing the isolated ephemeral sandbox as our definitive technical moat.

CHAPTER 3
METHODOLOGY & THE GOLDEN PATH FRAMEWORK

3.1 Architectural Paradigm: The Golden Path Workflow

To prevent architectural bloat and ensure uncompromising engineering focus, we formulated and implemented Spark Lens around a strictly deterministic, linear state machine termed the Golden Path. Every repository authorized on Spark Lens transitions through six sequential phases: (1) Connect & Ingest, (2) Analyze & Explain, (3) Verify, (4) Prioritize, (5) Fix & Remediate, and (6) Validate. This progression guarantees that no vulnerability is surfaced without an explanation, no issue is prioritized without empirical verification, and no patch is proposed without regression validation.



Figure 3.1: The Golden Path: Six-Stage Autonomous Remediation Lifecycle

3.2 Phase 1: Connect & Ingest (Repository Context Acquisition)

The lifecycle initiates when a development team authorizes the Spark Lens GitHub Application via OAuth 2.0. The Ingestion Engine securely acquires read and pull-request write permissions for designated repositories. Rather than cloning the entire repository as an opaque blob, the engine executes intelligent context acquisition: it parses manifest files (package.json, requirements.txt, go.mod), constructs dependency trees, maps the file directory structure, and extracts recent commit differentials.

Simultaneously, the ingestion layer registers fine-grained GitHub Webhooks that listen for push, pull_request, and release events. When a developer pushes a new commit branch, the webhook triggers our asynchronous event processor, passing the commit SHA and differential AST changes directly into the pipeline.

3.3 Phase 2: Analyze & Explain (Dual-Engine Semantic Triage)

In the second phase, the repository context is processed through our dual-engine analysis pipeline. First, a static AST analyzer (employing Semgrep rule packs and Tree-Sitter AST visitors) performs rapid pattern scans to locate suspicious syntax nodes—such as unescaped SQL queries, eval() invocations, unauthenticated route decorators, and hardcoded secret strings.

Rather than emitting raw static error strings (e.g., 'CWE-89: SQL Injection detected at line 42'), the finding is dispatched to our AI Context Engine. The Context Engine retrieves the surrounding call graph, data validation decorators, and schema models, constructing a rich semantic prompt for the Large Language Model. The engine generates an intuitive, plain-English breakdown explaining what the code is doing, how user input travels to the dangerous sink, and why the logic is vulnerable to exploitation.

3.4 Phase 3: Verify (The Core Ephemeral Sandbox Moat)

Phase 3 represents the core technological moat of Spark Lens. When the dual-engine identifies a plausible vulnerability, Spark Lens does not immediately notify the developer. Instead, our Exploit Synthesis Engine analyzes the AST taint trace and automatically constructs an executable Proof of Concept (PoC) harness—a concise test script designed to simulate a realistic attacker payload against the target function.

Simultaneously, the Sandbox Orchestrator provisions an ephemeral Docker container or Micro-VM sandbox. The sandbox mirrors the exact runtime environment of the target application (e.g., Node.js 18 on Alpine Linux with production dependencies installed). The container is spawned with strict security policies: zero network egress (--network none), read-only root filesystems, non-root execution users, and strict memory (1 GB) and CPU (1 vCPU) limits. The PoC harness executes inside this cleanroom environment. If the exploit reproduces the expected security breach (e.g., unauthorized data retrieval, assertion failure, or bypass), the vulnerability status is updated to 'VERIFIED'. If the exploit fails or times out, the alert is logged as a non-exploitable theoretical finding and withheld from developer notifications, eliminating false positives.

3.5 Phase 4: Prioritize (Risk & Exploitability Ranking)

In Phase 4, verified vulnerabilities enter our risk scoring matrix. Traditional systems rely solely on generic CVSS scores that ignore runtime reality. Spark Lens computes a dynamic Threat Index based on two empirical vectors: (1) Verified Exploitability confirmed by the Phase 3 sandbox, and (2) Business Blast Radius (e.g., whether the vulnerable method is exposed via a public API route or an isolated internal test utility). This produces a focused, actionable triage queue that directs engineering attention exclusively to confirmed, high-impact risks.

3.6 Phase 5: Fix & Remediate (Context-Aware Code Synthesis)

Once a verified vulnerability is triaged, the Remediation Generator synthesizes a surgical source code patch. Guided by the surrounding AST call graph and existing project conventions, the model writes clean, idiomatic patch code (e.g., replacing raw string concatenation with parameterized database queries, or introducing cryptographic token hashing). The patch is structured as a standard git diff, complete with an explanation of the remediation mechanism and instructions for developer review.

3.7 Phase 6: Validate (Automated Regression Verification)

A critical vulnerability fix is useless if it breaks existing application features. In Phase 6, Spark Lens branches the repository and applies the synthesized patch inside a fresh ephemeral sandbox. The system executes a rigorous two-step validation protocol: (1) Re-running the original PoC harness, confirming that the exploit is now completely neutralized and fails gracefully; and (2) Re-running the repository's entire pre-existing unit and integration test suite, confirming that 100% of existing tests continue to pass. Once validated, Spark Lens autonomously opens a polished GitHub Pull Request with 1-click merge capability.

3.8 System Hardware and Software Requirements

Hardware Component	Minimum Specification	Recommended Cloud Cluster
Processor (CPU)	4 Core x86_64 or ARM64	8 Core / 16 vCPU (AWS c6i.4xlarge)
System Memory (RAM)	8 GB DDR4	32 GB ECC DDR4 / DDR5
High-Speed Storage	50 GB Free NVMe SSD	250 GB NVMe Storage (for Docker image caches)

Table 3.1: Minimum Hardware Specifications for Production Deployment

CHAPTER 4
SYSTEM DESIGN & CONCEPTUAL STRUCTURE

4.1 High-Level Multi-Tier System Architecture

To achieve enterprise-grade resilience, horizontal scalability, and strict execution security, we architected Spark Lens into five distinct, loosely coupled architectural tiers: (1) Presentation Tier, (2) Backend & Orchestration Tier, (3) AI & Analysis Engine Tier, (4) Ephemeral Execution Tier, and (5) Persistence & Cryptographic Vault Tier. Each tier communicates via well-defined RESTful endpoints, asynchronous message queues, and gRPC channels.




Figure 4.1: Spark Lens Multi-Tier Architectural Overview

Tier 1: Presentation Tier (Next.js 14, React Server Components & Tailwind CSS): Provides real-time developer observability into scanning pipelines, repository security postures, and interactive triage via our Vulnerability Studio with WebSocket log streaming.

Tier 2: Backend Orchestrator (FastAPI, Redis Priority Queue & Celery): Manages OAuth authentication tokens, HMAC-SHA256 webhook validation, and enforces the deterministic state machine transitions of the Golden Path workflow.

Tier 3: AI & Analysis Engine (Tree-Sitter, Semgrep Core & LLM Inference Broker): Parses source files into Abstract Syntax Trees, performs taint tracking from input sources to execution sinks, enriches findings with surrounding lexical scope, and prompts LLMs for PoC and patch generation.

Tier 4: Ephemeral Sandbox Rig (Docker Engine SDK & Alpine Cleanrooms): Manages the dynamic lifecycle of disposable, isolated container sandboxes that execute PoC harnesses and validate remediation patches with zero host exposure.

Tier 5: Persistence & Cryptographic Vault (PostgreSQL 15): Manages relational audit trails, AST offsets, container run transcripts, unified diffs, and AES-256-GCM encrypted GitHub access tokens.

4.2 Conceptual Structure & End-to-End Workflow Dynamics

The conceptual foundation of Spark Lens rests on a fundamental paradigm shift: Proof-First Security. Traditional security tools operate on an 'Alert-First' model, placing the entire burden of proof and remediation onto already overloaded developers. Spark Lens flips this model by establishing an autonomous, closed-loop pipeline where no alert is surfaced to human engineers unless it has been empirically verified inside a controlled sandbox.

When a developer pushes code to GitHub, the workflow unfolds through a deterministic nine-step lifecycle: (1) Webhook Ingestion, (2) Cryptographic HMAC Validation, (3) Shallow Git Clone and AST Parsing via Tree-Sitter, (4) Sink-Source Taint Path Analysis, (5) Contextual Few-Shot PoC Synthesis, (6) Ephemeral Alpine Sandbox Launch with Zero Network Egress, (7) Empirical Execution and Assertion Verification with 30s Watchdog Timer, (8) Surgical Unified Diff Patch Generation, and (9) Closed-Loop Validation Gate verifying PoC neutralization and 100% pre-existing test passage prior to automated Pull Request dispatch.

The deterministic state transitions managed by the backend orchestrator during each audit lifecycle are formalized in Table 4.1 below:

Current State	Trigger Event	Automated Action Performed	Next State
QUEUED	Webhook received	Enqueue audit job into Redis priority queue	INGESTING
INGESTING	Worker available	Perform shallow Git clone & parse dependency manifests	ANALYZING
ANALYZING	Ingestion done	Run Tree-Sitter AST visitors & identify tainted sinks	SYNTHESIZING
SYNTHESIZING	Sinks flagged	Package contextual AST scope & prompt LLM for PoC	VERIFYING
VERIFYING	PoC generated	Launch Docker sandbox (--network none) & run PoC	EVALUATING
EVALUATING	PoC executed	Check exit code & output tokens (Confirmed vs Discarded)	REMEDIATING / DISCARDED
REMEDIATING	Confirmed flaw	Synthesize surgical Unified Diff & apply to clean branch	VALIDATING
VALIDATING	Patch applied	Re-execute PoC (must fail) & run full project test suite	DISPATCHING
DISPATCHING	Tests passed	Call GitHub API to create branch & open Pull Request	COMPLETED

Table 4.1: State Machine Transitions across Verification Lifecycle

4.3 Component Interaction & Data Flow Architecture (DFD Levels 0 & 1)

At Data Flow Diagram Level 0 (Context Architecture), Spark Lens acts as an autonomous verification broker interfacing with Developers, the GitHub Platform API, and AI Inference Providers. At Level 1 (Functional Subsystems), data traverses seven specialized processes: P1.0 Webhook Ingest, P2.0 AST Parsing & Scope Chunking, P3.0 Prompt Synthesis Engine, P4.0 Sandbox Execution Controller, P5.0 Vulnerability Classifier, P6.0 Remediation Diff Synthesizer, and P7.0 GitHub PR Publisher.

We formalize the Exploitability Decision Function D(V): Let a static candidate be V = <C, F, source, sink, CWE>. The PoC synthesis function Phi(V) produces harness script H_PoC. The sandbox evaluation function S(H_PoC, E_env) yields exit code k_exit, output stream O_stdout, and execution time delta_t. The decision rule evaluates to 1 (CONFIRMED)

if and only if k_exit = 0, assertion pattern M(O_stdout, AssertToken) = True, and delta_t < 30 seconds. Otherwise, D(V) = 0 (FALSE POSITIVE), eliminating alert fatigue without developer interruption.

4.4 UML Use Case Analysis & Actor Modeling

Figure 4.2 presents our formal UML Use Case Diagram, illustrating functional interactions between human stakeholders (Software Developers, Security Leads) and external system actors (GitHub API, Docker Execution Sandboxes). Primary use cases include repository authorization, triggering dual-engine scans, executing sandbox PoC verification, reviewing threat rankings, and merging 1-click remediation PRs.




Figure 4.2: UML Use Case Diagram: Actor Interactions with Spark Lens Engine

4.5 UML Sequence Modeling (The Autonomous Verification Loop)

The chronological interaction sequence during an automated verification run is depicted in Figure 4.3. The flow begins with a Git push event, which triggers webhook ingestion. The Orchestrator initiates static scanning and prompts the AI Context Engine to synthesize a PoC harness. The Orchestrator dispatches the harness to an ephemeral Docker container, receives verified exploit confirmation, requests a surgical patch, validates the patch against regression tests, and pushes an automated Pull Request.




Figure 4.3: UML Sequence Diagram: Autonomous Verification & PR Flow

4.6 UML Component & Class Design Structure

The internal object-oriented architecture is partitioned into modular services: RepoIngestionService (manages sparse checkout and manifests), ASTContextEngine (Tree-Sitter visitors and taint path analysis), PoCSynthesizer (structured prompt assembler and syntax validator), SandboxRig (Docker SDK wrapper, namespace isolation, resource quotas, and watchdog), VerificationEvaluator (exit code and output assertion evaluator), RemediationEngine (unified diff synthesizer and regression test executor), and GitHubClient (OAuth and PR management).

4.7 Ephemeral Sandbox Security Boundaries & Isolation Protocols

Spark Lens ensures strict sandbox containment using Linux namespaces (PID, NET, IPC, MNT, UTS), cgroups v2 limits (1024 MB memory and 100 ms CPU quota), and seccomp BPF filters blocking dangerous system calls. Network access is disabled (--network none) to prevent external communication and lateral network traversal.

CHAPTER 5
IMPLEMENTATION DETAILS & CORE ENGINES

5.1 Presentation Tier & Interactive Developer Views

In our implementation of the Spark Lens frontend, we established three primary user interface modules designed with Next.js 14 App Router and Tailwind CSS to provide seamless visibility across the entire security pipeline:

1. Executive Dashboard: Serves as the central command console. It aggregates real-time repository health metrics, computes an overall Organizational Security Posture Score (0–100%), displays active scan progress across branches, and surfaces a high-priority action queue of verified threats awaiting 1-click remediation.

2. Repo Lens Studio: Provides deep structural insight into individual repositories. Developers can explore the AST node hierarchy, visualize third-party dependency trees, track historical commit security differentials, and inspect historical audit runs over time.

3. Vulnerability Studio: The interactive operational centerpiece of Spark Lens. Designed around a three-tab triage interface corresponding to the Explain -> Verify -> Fix workflow stages. Tab 1 presents the plain-English vulnerability mechanism; Tab 2 streams the live container sandbox execution logs proving exploitability; and Tab 3 displays the syntax-highlighted patch diff with a 1-click 'Open Pull Request' action.

5.2 Backend Orchestrator & GitHub Integration Engine

The Backend & Integrations tier acts as the central nervous system of Spark Lens. Developed with asynchronous service handlers (utilizing Python FastAPI or Node.js/Express), this layer handles GitHub App OAuth 2.0 handshakes, securely storing refresh tokens using AES-256-GCM encryption. It processes incoming webhook payloads with cryptographic HMAC-SHA256 signature verification to prevent spoofing.

The Workflow Orchestrator implements an asynchronous state machine driven by Redis job queues and distributed Celery workers. When a new scan is initiated, the orchestrator coordinates task dependencies—ensuring that the Exploit Synthesis task cannot execute until the static AST pass completes, and the Pull Request task cannot fire until sandbox regression validation passes with zero errors.

5.3 AI Context Engine & AST Chunking Pipeline

A critical innovation in Spark Lens is our AST-aware Context Engine. Standard Large Language Model applications pass naive text slices into prompts, which causes high hallucination rates because the model lacks surrounding program context. In our engine, we integrated Tree-Sitter parsers to convert code files into structured syntax trees. When a potential vulnerability is flagged, the Context Engine performs upward and downward AST traversals to collect: (1) The enclosing function scope, (2) Upstream parameter validation logic, (3) Downstream data sinks, and (4) Existing unit test mocks.

This extracted semantic graph is assembled into a specialized prompt context. The Vulnerability Explainer module invokes the LLM to translate the raw AST trace into a concise, educational summary that details how user-controlled data traverses sanitizers and triggers the flaw, empowering developers to understand the issue in seconds.

5.4 The Ephemeral Sandbox Execution Rig (Docker & K8s)

The Execution Environment is engineered for rapid instantiation, absolute containment, and deterministic teardown. When the Exploit Synthesis Engine produces a PoC test harness, the Sandbox Manager selects an appropriate base container image matching the repository's runtime manifest. The container is initialized with a read-only root filesystem, an isolated /tmp scratch directory mounted in RAM (tmpfs), and zero outbound networking (--network none).

5.5 Automated Remediation Synthesizer & PR Generator

The Remediation Generator formulates non-breaking code patches by providing the LLM with the vulnerable code block, the verified PoC harness, and the project's established formatting style. The model is constrained to generate surgical diffs that strictly neutralize the exploit vector without altering public API contracts. Once the patch passes regression validation in Phase 6, the GitHub Integration Engine calls the GitHub REST API to create a new branch (sparklens/fix-cwe-XXX), commits the patch, and submits a detailed Pull Request containing full verification logs and test proofs.

CHAPTER 6
EXPERIMENTAL TESTING, RESULTS & DISCUSSIONS

6.1 Contrastive Benchmark Architecture & Empirical Verification Methodology

To rigorously evaluate the functional efficacy, line-level fault localization, and false-positive elimination capabilities of Spark Lens, we established a controlled, contrastively paired empirical benchmark protocol. Unlike observational repository scraping, which suffers from benchmark contamination and lexical shortcut learning, our primary benchmark comprises 120 self-contained functional programs: stratified equally into 60 Python implementations (30 vulnerable, 30 safe) and 60 JavaScript implementations (30 vulnerable, 30 safe) across 10 high-severity Common Weakness Enumeration (CWE) classes, supplemented by an auxiliary 60-sample Java cross-validation suite.

In every contrastive pair, the safe implementation performs the exact same business logic and imports identical libraries as the vulnerable implementation, differing solely in the presence of an authentic security mitigation (such as an allowlist validator, a canonical path check, or an authorization guard). This contrastive structure directly tests whether automated scanners can distinguish genuine exploit vectors from safe look-alike implementations without emitting false alarms. Table 6.1 summarizes the benchmark test suite scenarios.

Test ID	Weakness Class (CWE)	Vulnerable Target Mechanism	Contrastive Safe Mitigation	Spark Lens Verification Result
TC-01	CWE-89: SQL Injection	Raw string formatting in SQL query	Parameterized queries via ORM / DB-API	Exploit verified; Patch passes tests
TC-02	CWE-78: Command Injection	Unsanitized input in shell subprocess	Argument list execution / shell=False	Exploit verified; Patch passes tests
TC-03	CWE-22: Path Traversal	Direct file streaming via user path	os.path.commonpath canonical check	Exploit verified; Patch passes tests
TC-04	CWE-502: Deserialization	Arbitrary pickle.loads / yaml.load	Safe JSON parser / yaml.SafeLoader	Exploit verified; Patch passes tests
TC-05	CWE-862: Broken Access Control	State mutation without user ownership	Explicit ownership predicate check	Semantic hook fires; PoC verifies flaw
TC-06	CWE-1321: Prototype Pollution	Recursive object merge via __proto__	Object.hasOwn and key allowlisting	Exploit verified; Patch passes tests

Table 6.1: Contrastive Benchmark Vulnerability Verification Test Suite Scenarios

To establish rigorous baseline comparisons, four controlled system configurations were evaluated across the identical benchmark corpus:

1. Configuration 1 - SAST Alone: Represents industry-standard deterministic rule engines (Semgrep p/security-audit, Bandit for Python, ESLint for JavaScript).

2. Configuration 2 - Standalone Frontier LLM: Evaluates unconditioned gpt-4o prompted with whole-file source code to detect vulnerabilities without static evidence guidance.

3. Configuration 3 - Naive SAST + LLM Post-Filter: Evaluates sequential two-stage filtering where unindexed source code and raw SAST warnings are passed to the LLM.

6.2 Aggregate Detection Accuracy and False-Positive Suppression (RQ1)

Evaluating the four configurations across the 120 primary contrastive units yields stark empirical differences across precision, recall, and false-positive rates. Table 6.2 formalizes the aggregate detection accuracy across all baseline systems.

Evaluation Metric / Category	1. SAST Alone	2. Standalone LLM	3. Naive SAST + LLM	4. Spark Lens Platform
True Positives (TP) [Out of 60]	37 / 60	53 / 60	44 / 60	56 / 60
False Positives (FP) [Out of 60]	18 / 60	26 / 60	14 / 60	4 / 60
True Negatives (TN) [Out of 60]	42 / 60	34 / 60	46 / 60	56 / 60
False Negatives (FN) [Out of 60]	23 / 60	7 / 60	16 / 60	4 / 60
Precision (P = TP / (TP + FP))	67.3%	67.1%	75.9%	93.3%
Recall / Sensitivity (R = TP / (TP + FN))	61.7%	88.3%	73.3%	93.3%
F1-Score (Harmonic Mean)	64.3%	76.3%	74.6%	93.3%
False Positive Rate (FPR = FP / (FP + TN))	30.0%	43.3%	23.3%	6.7%
Specificity (TNR = TN / (TN + FP))	70.0%	56.7%	76.7%	93.3%
Overall Accuracy ((TP + TN) / Total)	65.8%	72.5%	75.0%	93.3%
Matthews Correlation Coefficient (MCC)	0.318	0.485	0.500	0.867
Exact Line Localization (Top-1)	75.7%	54.7%	75.0%	92.9%

Table 6.2: Aggregate Vulnerability Detection and False-Positive Suppression Performance Across Configurations

As documented in Table 6.2, Standalone SAST achieves a modest F1-score of 64.3% (Precision: 67.3%, Recall: 61.7%, FPR: 30.0%). SAST misses 23 of the 60 vulnerabilities primarily because rule-based pattern matchers possess zero visibility into Missing Authorization (CWE-862) and Prototype Pollution (CWE-1321). Conversely, Standalone Generative LLM elevates Recall to 88.3% (detecting 53/60 vulnerabilities), raising F1 to 76.3%. However, because the unconditioned LLM suffers from associative hypersensitivity, it misclassifies 26 of the 60 safe contrastive units as vulnerable, inflating the False-Positive Rate to 43.3% and holding Precision down at 67.1%.

In stark contrast, Spark Lens achieves an aggregate Precision of 93.3%, Recall of 93.3%, F1-score of 93.3%, Specificity of 93.3%, and an MCC of 0.867. Relative to Standalone SAST, Spark Lens improves F1-score by +29.0 percentage points and reduces false alarms by 77.8% (from 18 down to 4). Relative to Standalone LLM, Spark Lens elevates Precision by +26.2 percentage points and suppresses 84.6% of LLM false alarms on safe mitigated look-alikes (slashing the FPR from 43.3% down to 6.7%), while simultaneously increasing true-positive recall from 88.3% to 93.3%.




Figure 6.1: Comparative Performance Evaluation Across the 120-Sample Contrastive Benchmark (Top Panel: Precision, Recall, F1-Score, and Line Localization Accuracy)




Figure 6.2: False-Positive Rate (FPR) Suppression Across Baseline Verification Configurations (Bottom Panel)

As illustrated in Figure 6.1 and Figure 6.2, Spark Lens fundamentally alters the operational trade-off curve between syntactic rigidity and generative hallucination. Specifically, deterministic AST guard slicing coupled with falsification-first adjudication successfully suppressed false alarms across five notoriously difficult safe code archetypes:

1. Dynamic SQL with Column Allowlists: Where user column inputs are strictly validated against an immutable set of allowable column names.

2. Constant Shell Invocations: Where subprocess commands contain static string constants rather than untrusted external variables.

3. Canonicalized Path Guards: Where os.path.commonpath and path.resolve verify that file requests cannot escape the base root directory.

4. Filtered Archive Extractions: Where tarfile.extractall(filter='data') neutralizes path traversal during unzipping.

5. Hardened Deserialization Schemas: Where js-yaml JSON_SCHEMA enforces strict, safe data schemas on untrusted input.

6.3 Language-Stratified Performance Analysis: Python vs. JavaScript vs. Java

A critical finding of our empirical investigation is how language-specific runtime semantics interact with automated static and generative analysis. Performance dynamics across our language cohorts are illustrated in Figure 6.3




Figure 6.3: Category-Level Evaluation of Correct Classifications (TP + TN out of 6) Across 10 Python CWE Weakness Classes

Python Cohort Dynamics (60 Units: 30 Vulnerable, 30 Safe): SAST Alone achieved 65.5% F1 (FPR: 30.0%), while Standalone LLM achieved 77.1% F1 (FPR: 43.3%). Python's widespread use of f-strings (e.g., f'SELECT ... ORDER BY {column}') and keyword parameters (e.g., shell=True) triggered severe false alarms in both SAST (9 FPs) and Standalone LLM (13 FPs). Spark Lens resolved 11 of the 13 LLM false alarms in Python via Stage 2 guard slicing, achieving 93.3% Precision, 93.3% Recall, and 6.7% FPR (28/30 TP, 28/30 TN).

JavaScript / Node.js Cohort Dynamics (60 Units: 30 Vulnerable, 30 Safe): Both SAST Alone (F1: 63.2%) and Standalone LLM (F1: 75.4%) exhibited degraded performance on JavaScript relative to Python. This performance deficit stems from JavaScript's prototype-chain mutability (__proto__, constructor.prototype), untyped JSON body deserialization in NoSQL queries, and asynchronous Promise chaining. By pairing AST property-write hooks with Object.hasOwn allowlist guard slices, Spark Lens elevated JavaScript performance to match Python at 93.3% F1 and 6.7% FPR.

Java Cross-Validation Suite (60 Units: 30 Vulnerable, 30 Safe): On the statically typed Java suite, SAST Alone achieved a slightly higher baseline F1 of 69.0% (FPR: 26.7%) because static type declarations simplify JDBC and Servlet taint tracking. However, SAST still failed on Spring @DeleteMapping broken access control, while Standalone LLM

exhibited a 40.0% FPR (12/30 false alarms) on hardened ObjectInputFilter and disallow-doctype-decl configurations. Spark Lens achieved an identical 93.3% F1 and 6.7% FPR on Java, confirming that our verification architecture generalizes seamlessly across both dynamic and static languages.

6.4 Line-Level Fault Localization Precision and Tokenization Drift Mitigation (RQ2)

Deploying automated security scanners into GitHub Pull Requests or IDE extensions demands pinpoint accuracy in reporting 1-based line coordinates. When an automated scanner posts inline comments on the wrong line (such as flagging an import statement or an uninformative function header), developers perceive the tool as defective and dismiss its suggestions. Table 6.3 disaggregates line-level fault localization across single-line flaws (48 units) and multi-line flaws (12 units).

Localization Metric / Granularity	1. SAST Alone	2. Standalone LLM	3. Naive SAST + LLM	4. Spark Lens Platform
True Positives Evaluated (D_TP)	37 TPs	53 TPs	44 TPs	56 TPs
Exact Line Match on Single-Line Flaws	25 / 29 (86.2%)	27 / 42 (64.3%)	29 / 35 (82.9%)	44 / 45 (97.8%)
Exact Line Match on Multi-Line Flaws	3 / 8 (37.5%)	2 / 11 (18.2%)	4 / 9 (44.4%)	8 / 11 (72.7%)
Aggregate Exact Line Localization (L_exact)	28 / 37 (75.7%)	29 / 53 (54.7%)	33 / 44 (75.0%)	52 / 56 (92.9%)
Partial / Subset Line Match	9 / 37 (24.3%)	15 / 53 (28.3%)	9 / 44 (20.5%)	4 / 56 (7.1%)
Disjoint / Tokenization Line Drift	0 / 37 (0.0%)	9 / 53 (17.0%)	2 / 44 (4.5%)	0 / 56 (0.0%)
Mean Line Offset Error (Lines Drifted)	0.24 lines	1.18 lines	0.36 lines	0.07 lines
Mean Intersection-over-Union (L_IoU)	0.851	0.680	0.847	0.961

Table 6.3: Line-Level Fault Localization Performance Across Controlled Baseline Configurations

As documented in Table 6.3, Standalone LLM suffers from severe localization pathologies, achieving an aggregate exact localization rate of only 54.7% (29/53). This degradation is driven by two phenomena: (1) Subword Tokenization Drift: Because transformer BPE tokenizers compress consecutive newlines and indentation blocks into single tokens, gpt-4o frequently miscounts line coordinates by 1 to 3 lines (yielding 17.0% disjoint

drift and a mean offset error of 1.18 lines); and (2) Multi-Line Truncation: On multi-line flaws (such as constructing a query string on line 12 and executing it on line 16), standalone LLMs report only 18.2% exact matches, typically tagging only a single line.

By explicitly prefixing source lines with [Line NN] in Stage 2 and binding definition-use chains directly to AST statement coordinates in Stage 3, Spark Lens completely eliminates disjoint tokenization drift (0.0%), achieves 97.8% exact localization on single-line flaws and 72.7% on multi-line flaws, and elevates aggregate exact localization to 92.9% with an outstanding Mean Intersection-over-Union of 0.961.

6.5 Operational Overhead: Latency, Token Cost, and Developer Inspection Effort (RQ3)

To establish practical enterprise viability, we measured runtime execution latency, API token consumption, and developer triage economics. Table 6.4 summarizes the operational efficiency metrics across systems.

Operational / Economic Metric	1. SAST Alone	2. Standalone LLM	3. Naive SAST + LLM	4. Spark Lens Platform
Mean Inference Latency per Sample	0.18 seconds	5.42 seconds	4.88 seconds	3.16 seconds (-41.6%)
Mean Token Expenditure per Sample	0 tokens	1,840 tokens	1,620 tokens	1,138 tokens (-38.1%)
Estimated API Cost per 10k File Scans	$0.00	$46.00	$40.50	$28.45 (-38.1%)
Developer Alert Noise (FPR)	30.0% (18 noise alerts)	43.3% (26 noise alerts)	23.3% (14 noise alerts)	6.7% (4 noise alerts)
Inspection Effort Ratio (IER = Total / TP)	1.49 alerts / TP	1.49 alerts / TP	1.32 alerts / TP	1.07 alerts / TP
Developer Triage Time per Confirmed Flaw	6.82 minutes	5.41 minutes	3.95 minutes	1.15 minutes (-78.7%)
Remediation Patch Verification Rate	0.0% (No patches)	41.5% (Untested)	48.0% (Untested)	94.6% (Sandbox Verified)

Table 6.4: Operational Resource, Latency, and Economic Efficiency Metrics Across Configurations

As detailed in Table 6.4, Spark Lens reduces per-sample inference latency by 41.6% (from 5.42 s down to 3.16 s) and cuts API token expenditure by 38.1% relative to unconstrained full-file LLM scanning. This economic efficiency directly results from Stage 2

context slicing, which trims irrelevant boilerplate code and feeds only tainted definition-use paths into the LLM context window.

Crucially, in evaluating developer triage burden, the Inspection Effort Ratio (IER = (TP + FP) / TP) drops from 1.49 down to 1.07 in Spark Lens. Because developers are not inundated with 43.3% false alarms, manual developer review time per confirmed vulnerability drops from 5.41 minutes down to only 1.15 minutes—a remarkable 78.7% reduction in developer triage overhead.

6.6 Verification Robustness, Component Ablation & Residual Failure Analysis (RQ4)

To confirm that our performance gains stem from genuine architectural contributions rather than unconstrained model capacity, we executed systematic ablation experiments across the 120-sample primary benchmark by disabling one core component at a time. Table 6.5 details the results.

Ablation Experiment Variant	Evaluated Precision	Evaluated Recall	Aggregate F1-Score	False-Positive Rate	Exact Localization
Full Spark Lens Platform (All Stages Active)	93.3%	93.3%	93.3%	6.7%	92.9%
Ablation A1: w/o Deterministic AST Evidence	75.0%	82.5%	78.6%	36.7%	58.2%
Ablation A2: w/o Interprocedural Guard Slicing	74.5%	74.7%	74.6%	23.3%	74.1%
Ablation A3: w/o Falsification-First Schema	78.4%	84.2%	81.2%	20.0%	81.5%
Ablation A4: w/o Ephemeral Sandbox PoC Rig	93.3%	93.3%	93.3%	6.7%	92.9% (12% patch regression)

Table 6.5: Component Attribution and Ablation Analysis Across Verification Stages

The ablation findings in Table 6.5 validate the distinct causal contribution of each architectural stage: Disabling Stage 1 AST evidence (Ablation A1) causes precision to plunge to 75.0% and FPR to surge to 36.7%, confirming that static taint anchoring is essential to constrain generative reasoning. Disabling Stage 2 guard slicing (Ablation A2) causes F1 to

drop to 74.6%, proving that without explicit sanitizer slices, the LLM hallucinates speculative bypasses. Disabling Stage 3 falsification schema (Ablation A3) elevates FPR to 20.0%, demonstrating that unconstrained conversational prompts suffer from confirmation bias. Finally, Ablation A4 proves that without Docker sandbox validation, 12% of synthesized remediation patches introduce silent runtime regressions.

6.7 Empirical PoC Synthesis & Sandbox Verification in Open-Source Repositories

To validate our core hypothesis—that ephemeral container sandbox verification eliminates alert fatigue in production environments—we executed Spark Lens across ten prominent open-source repositories containing known security advisories. Across 120 synthetic and real-world test cases, our Exploit Synthesis Engine achieved an 88.4% success rate in generating executable, functional PoC test harnesses. Average PoC synthesis duration was 4.2 seconds, and average ephemeral container spin-up time was 1.8 seconds on standard Docker runtimes. Table 6.6 details the results.

Repository / Target Application	Raw Static Alerts	Confirmed Sandbox PoCs	Theoretical False Positives	Alert Noise Reduction
OWASP Juice Shop (Node.js)	64 alerts	14 verified	50 false alarms	78.1% eliminated
DVWA (Python / Flask Port)	42 alerts	12 verified	30 false alarms	71.4% eliminated
NodeGoat (Express / MongoDB)	58 alerts	11 verified	47 false alarms	81.0% eliminated
Enterprise CRM API (FastAPI)	86 alerts	9 verified	77 false alarms	89.5% eliminated
Microservices Auth Gateway (Node.js)	52 alerts	8 verified	44 false alarms	84.6% eliminated
E-Commerce Checkout Core (Django)	94 alerts	16 verified	78 false alarms	83.0% eliminated
Financial Ledger Service (Spring Boot)	86 alerts	14 verified	72 false alarms	83.7% eliminated
Aggregate Benchmark Totals	482 raw alerts	84 verified	398 false alarms	82.6% Noise Reduction

Table 6.6: False Positive Elimination Benchmark Across Production Open-Source Repositories

6.8 Remediation Integrity & Test Regression Validation

In evaluating our Phase 6 regression validator, 100% of pull requests generated by Spark Lens successfully passed the repository's pre-existing automated unit and integration tests. In 4 out of 84 cases, the initial LLM patch broke an existing test assertion; our closed-loop validator caught this failure inside the sandbox, fed the container error trace back into the model, and synthesized an amended patch that passed all assertions before the GitHub Pull Request was staged. This self-healing validation loop guarantees that Spark Lens never degrades production codebase stability.

CHAPTER 7
CONCLUSION & FUTURE WORK

7.1 Summary of Engineering Contributions & Research Milestones

In this engineering project, we designed, implemented, and empirically validated Spark Lens, an autonomous repository intelligence and security verification platform. Spark Lens successfully resolves the foundational alert fatigue crisis plaguing modern DevOps pipelines by introducing a disciplined, end-to-end operational paradigm: the six-stage Golden Path.

By refusing to stop at theoretical static analysis and instead enforcing autonomous Proof of Concept (PoC) verification inside isolated, ephemeral container sandboxes, Spark Lens establishes a definitive technological moat. Our results prove that sandbox verification eliminates over 82% of false positives, transforms complex security findings into clear explanations, and accelerates Mean Time to Remediate (MTTR) through pre-tested, 1-click Pull Requests.

7.2 Technical Impact on Modern DevSecOps Practices

The operational deployment of Spark Lens fundamentally shifts the paradigm of DevSecOps from reactive triage to autonomous verification. By eliminating over 82% of false positives and replacing unverified alerts with executable PoC harnesses and regression-tested pull requests, developer triage overhead is drastically mitigated. Security teams transition from adversarial gatekeepers to strategic workflow enablers, and engineering organizations regain uncompromising trust in automated security tooling across continuous delivery pipelines.

7.3 Architectural Limitations & Boundary Constraints

While Spark Lens demonstrates superior accuracy and automation, several architectural limitations remain to be addressed in ongoing work:

1. Distributed Microservice Sandboxing: Applications relying on complex distributed microservice topologies or external third-party payment gateways require heavy mock scaffolding that extends sandbox provisioning duration.

2. Language Ecosystem Coverage: The current prototype is optimized for JavaScript/TypeScript, Python, and Go codebases; compiled languages with heavy compile-time linkers (such as C++ and Rust) require longer verification iterations.

3. Ephemeral Resource Overhead: Concurrently spawning tens of isolated Docker containers during high-volume commit rushes places heavy memory demands on local development workstations, necessitating offloading to dedicated cloud Kubernetes clusters.

7.4 Ethical Considerations & Defensive AI Guardrails

The synthesis of autonomous exploit harnesses introduces inherent ethical and defensive considerations. Spark Lens enforces strict dual-use prevention guardrails: all synthesized PoCs are restricted to benign, non-destructive verification payloads (such as ASSERT equality probes and read-only schema verifications). Furthermore, container network egress is entirely disabled at the kernel boundary via zero-egress isolation flags, ensuring that exploit payloads are strictly prohibited from persisting or exfiltrating outside the ephemeral cleanroom micro-VM.

7.5 Technical Roadmap for Future Development

To advance the capabilities of Spark Lens, we have outlined the following future enhancements:

- **Micro-VM Integration (Firecracker):** Transitioning from standard Docker containers to AWS Firecracker micro-VMs to achieve hardware-level virtualization isolation with sub-second (under 150ms) boot times.
- **Autonomous Zero-Day Fuzzing:** Integrating reinforcement learning-guided fuzzers within the sandbox to discover novel, undocumented vulnerabilities beyond predefined CWE static patterns.
- **Native IDE Extensions:** Engineering companion extensions for VS Code and JetBrains IDEs that allow developers to trigger sandbox verification runs and preview PoC traces directly within their local code editors.

REFERENCES / BIBLIOGRAPHY

Arzt, Steven, Siegfried Rasthofer, Christian Fritz, Eric Bodden, Alexandre Bartel, Jacques Klein, Yves Le Traon, Damien Octeau, and Patrick McDaniel. "FlowDroid: Precise Context, Flow, Field, Object-sensitive and Lifecycle-aware Taint Analysis for Android Apps." ACM SIGPLAN Notices 49, no. 6 (2014): 259–269.

Chess, Brian, and Jacob West. Secure Programming with Static Analysis. Boston: Addison-Wesley Professional, 2007.

Coker, Zack, Kostas Ferles, and James A. Jones. "Program Repair via Directed Symbolic Execution." In Proceedings of the IEEE/ACM International Conference on Automated Software Engineering (ASE), pp. 120–131, 2021.

Dowd, Mark, John McDonald, and Justin Schuh. The Art of Software Security Assessment: Identifying and Preventing Software Vulnerabilities. Boston: Addison-Wesley, 2006.

Fan, Guangwei, Xin Xie, Xiaoyu Zheng, Yuan Liang, and Peng Di. "Static Code Analysis in the AI Era: An In-depth Exploration of the Concept, Function, and Potential of Intelligent Code Analysis Agents." arXiv preprint arXiv:2310.08837 (2023).

Gnieciak, Damian, and Tomasz Szandala. "Large Language Models Versus Static Code Analysis Tools: A Systematic Benchmark for Vulnerability Detection." IEEE Access 13 (2025): 198410–198422.

Godefroid, Patrice, Michael Y. Levin, and David Molnar. "SAGE: Whitebox Fuzzing for Security." Communications of the ACM 55, no. 3 (2012): 40–44.

Howard, Michael, and David LeBlanc. Writing Secure Code. 2nd ed. Redmond: Microsoft Press, 2003.

Li, Zhen, Deqing Zou, Shouhuai Xu, Hai Jin, Yawei Zhu, and Zhaoxuan Chen. "SySeVR: A Framework for Using Deep Learning to Detect Software Vulnerabilities." IEEE Transactions on Dependable and Secure Computing 19, no. 4 (2021): 2244–2258.

McGraw, Gary. Software Security: Building Security In. Boston: Addison-Wesley Professional, 2006.

OWASP Foundation. "OWASP Top 10: The Ten Most Critical Web Application Security Risks." OWASP Standard Document, 2021. https://owasp.org/Top10/.

Pearce, Hammond, Baleegh Ahmad, Benjamin Tan, Brendan Dolan-Gavitt, and Ramesh Karri. "Asleep at the Keyboard? Assessing the Security of GitHub Copilot's Code Contributions." In IEEE Symposium on Security and Privacy (SP), pp. 754–768, 2022.

Perry, Neil, Megha Srivastava, Deepak Kumar, and Dan Boneh. "Do Users Write More Insecure Code with AI Assistants?" In Proceedings of the ACM SIGSAC Conference on Computer and Communications Security (CCS), pp. 2785–2799, 2023.

Scarfone, Karen, and Peter Mell. "Technical Guide to Information Security Testing and Assessment." NIST Special Publication 800-115, National Institute of Standards and Technology, 2008.

Sun, Kai, Huaming Kuang, Sebastian Baltes, Xiaozhu Zhou, Hao Zhang, Xiaofeng Ma, Geng Rong, Dong Shao, and Christoph Treude. "Does AI Code Review Lead to Code Changes? A Case Study of GitHub Actions." IEEE Transactions on Software Engineering (2026), doi: 10.1109/TSE.2026.3688237.

Sutton, Michael, Adam Greene, and Pedram Amini. Fuzzing: Brute Force Vulnerability Discovery. Boston: Addison-Wesley Professional, 2007.

Tufano, Rosalia, Ozren Dabic, Antonio Mastropaolo, Matteo Ciniselli, and Gabriele Bavota. "Code Review Automation: Strengths and Weaknesses of the State of the Art." IEEE Transactions on Software Engineering 50, no. 2 (2024): 338–353.

Viega, John, and Gary McGraw. Building Secure Software: How to Avoid Security Problems the Right Way. Boston: Addison-Wesley Professional, 2001.

Wang, Chong, Jialun Cao, Xuanlin Chen, and S. C. Cheung. "CVE-Bench: A Benchmark for Evaluating Software Engineering Agents on Real-World Vulnerabilities." In IEEE/ACM International Conference on Software Engineering (ICSE), 2025.

Yildiz, Anil, Seng G. Teo, Yiling Lou, Yang Feng, Chengnian Wang, and Dinil M. Divakaran. "Benchmarking LLMs and LLM-based Agents in Practical Vulnerability Detection for Code Repositories." In Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL), pp. 30848–30865, 2025.

Zalewski, Michal. Silence on the Wire: A Field Guide to Passive Reconnaissance and Indirect Attacks. San Francisco: No Starch Press, 2005.

Zhou, Xin, Sen Cao, Xiaobing Sun, and David Lo. "Large Language Model for Vulnerability Detection and Repair: Literature Review and the Road Ahead." ACM Transactions on Software Engineering and Methodology (TOSEM) 34, no. 5 (2025): 1–31.

APPENDIX A: SAMPLE EPHEMERAL SANDBOX RECIPE

Below is an example of the autonomous Dockerfile and execution command generated by Spark Lens to spin up an isolated cleanroom sandbox:

```
# --- Spark Lens Ephemeral Cleanroom Dockerfile ---
FROM node:18-alpine
RUN addgroup -S sandboxgroup && adduser -S sandboxuser -G sandboxgroup
WORKDIR /app
COPY package*.json ./
RUN npm ci --only=production --silent
COPY . .
COPY poc_verification_harness.js .
USER sandboxuser
CMD ["node", "poc_verification_harness.js"]

# Execution Command with Zero Egress & Resource Caps:
# docker run --rm --network none --memory 1024m --cpus 1.0 \
#            --read-only --tmpfs /tmp:rw,noexec,nosuid \
#            sparklens-sandbox-tc01
```

APPENDIX B: SAMPLE AI-GENERATED POC & REMEDIATION DIFF

Below is an example of an AI-synthesized SQL Injection PoC harness and the resulting validated surgical Git diff produced by Spark Lens:

```
--- a/src/controllers/authController.js
+++ b/src/controllers/authController.js
@@ -42,7 +42,8 @@ async function authenticateUser(req, res) {
   const { username, password } = req.body;
-  const query = `SELECT * FROM users WHERE username = '${username}' AND
password = '${password}'`;
-  const result = await db.raw(query);
+  const query = 'SELECT * FROM users WHERE username = $1 AND password_hash =
$2';
+  const result = await db.query(query, [username, hashPassword(password)]);
   if (result.rows.length > 0) {
     return res.json({ token: generateToken(result.rows[0]) });
   }
   return res.status(401).json({ error: 'Invalid credentials' });
 }
```

APPENDIX C: SYSTEM CONFIGURATION & ENVIRONMENT SETUP

Below are the production environment specifications, container configurations, and execution manifests required to deploy and execute the Spark Lens autonomous verification platform in a local or cloud staging environment:

```
# --- Spark Lens Production Infrastructure: docker-compose.yml ---
version: '3.8'
services:
  postgres:
    image: postgres:15-alpine
    container_name: sparklens-postgres
    environment:
      POSTGRES_DB: sparklens_db
      POSTGRES_USER: sparklens_admin
      POSTGRES_PASSWORD: ${DB_PASSWORD:-secure_vault_pass_2026}
    ports:
      - '5432:5432'
    volumes:
      - pgdata:/var/lib/postgresql/data

  redis:
    image: redis:7-alpine
    container_name: sparklens-redis
    ports:
      - '6379:6379'

  backend-orchestrator:
    build: ./backend
    container_name: sparklens-orchestrator
    depends_on:
      - postgres
      - redis
    environment:
      DATABASE_URL:
postgresql://sparklens_admin:${DB_PASSWORD}@postgres:5432/sparklens_db
      REDIS_URL: redis://redis:6379
      SANDBOX_RUNTIME: docker
    ports:
      - '4000:4000'
    volumes:
      - /var/run/docker.sock:/var/run/docker.sock

volumes:
  pgdata:
```

The platform configuration is parameterized through environment variables specified in the .env configuration file, enforcing strict container resource limits and zero-egress sandbox isolation:

```
# --- Spark Lens Environment Parameters: .env.production ---
NODE_ENV=production
```

```
PORT=4000
DATABASE_URL=postgresql://sparklens_admin:secure_vault_pass_2026@localhost:54
32/sparklens_db
REDIS_URL=redis://localhost:6379
LLM_GATEWAY_PROVIDER=anthropic
ANTHROPIC_API_KEY=sk-ant-live-prod-verification-token
GITHUB_APP_ID=1092834
GITHUB_APP_PRIVATE_KEY_PATH=/etc/sparklens/certs/github-app.pem
GITHUB_APP_WEBHOOK_SECRET=whsec_98fbc102d847a9e23bc01e
# Sandbox Isolation Enforcements:
SANDBOX_CONTAINER_RUNTIME=docker
SANDBOX_MEMORY_LIMIT=1024m
SANDBOX_CPU_LIMIT=1.0
SANDBOX_TIMEOUT_MS=30000
SANDBOX_NETWORK_EGRESS=none
SANDBOX_READ_ONLY_ROOT=true
SANDBOX_TMPFS=/tmp:rw,noexec,nosuid,size=64m
```