My Python Course Notes

Structured Revision for Every Lesson

Siddharth Patel HTW Berlin

June 4, 2025

Contents

1	Lesson 1: Print Function – Full Usage Guide	3
2	Lesson 2: Input Function – Full Usage Guide	4
3	Lesson 3: Math Operators – Full Usage Guide	5
4	Lesson 4: Strings – Full Usage Guide	6
5	Lesson 5: If, Else, and Conditional Operators	8
6	Lesson 6: While Loop – Full Usage Guide	10
7	Lesson 7: For Loop – Full Usage Guide	12
8	Lesson 8: Functions – Full Usage Guide	13
9	Lesson 9: Lists – Introduction	15
10	Lesson 10.1: List Methods – General Usage	16
11	Lesson 10.2: List Methods – Numeric Lists Only	17

1 Lesson 1: Print Function – Full Usage Guide

```
1 # PRINT FUNCTION - FULL USAGE GUIDE
3 # Basic Syntax:
4 # print(*objects, sep=' ', end='\n', file=sys.stdout, flush=False)
6 # Parameters:
7 # *objects → One or more objects to be printed (comma-separated).
             → String inserted between objects. Default is ' ' (space).
             → String appended after the last object. Default is '\n' (new line).
           → A file-like object (stream); default is sys.stdout.
10 # file
   \# flush \to If True, forcibly flush the stream. Default is False.
13
# 1. Basic print
print("Hello, World!") # Hello, World!
# 2. Printing multiple objects
print("Hello", "Python", 3) # Hello Python 3
# 3. Using 'sep' to change separator
22 print("2025", "05", "27", sep="-") # 2025-05-27
24 # 4. Using 'end' to avoid new line
print("Loading", end="...") # Loading...
# 5. Using custom separator and end together
28 print("Name", "Age", sep=": ", end=" years\n") # Name: Age years
30 # 6. Printing to a file
with open("output.txt", "w") as f:
      print("Saving this line to a file.", file=f)
# 7. Forcing flush (useful in loops/real-time output)
35 import time
36 for i in range(3):
       print(i, end=" ", flush=True)
37
       time.sleep(0.5) # Output appears immediately
38
39
40 # 8. Printing escape characters
41 print("Line1\nLine2") # New line
42 print("Tabbed\tSpace")
                              # Tab space
43 print("He said \"hello\"") # Quotes inside string
45 # 9. Printing with formatted strings (f-strings)
46 name = "Siddhart"
47 \text{ age} = 21
48 print(f"Hello, my name is {name} and I am {age} years old.")
50 # 10. Using print with unpacking
nums = [1, 2, 3, 4]
   print(*nums)
                              # 1 2 3 4
   print(*nums, sep=", ")
                             # 1, 2, 3, 4
# 11. Printing Unicode/emojis (note: removed for LaTeX safety)
56 print("Python is fun")
```

Additional Functions Used in This Lesson

Referenced Functions - Syntax and Output Type

Function	Syntax	Return / Output Type
with open()	<pre>with open("file.txt", "w") as f:</pre>	File object
<pre>print(, file=f)</pre>	<pre>print("text", file=f)</pre>	Writes to file, returns None
range()	<pre>range(3) or range(start, stop, step)</pre>	Range object (it- erable)
time.sleep()	time.sleep(seconds)	None (pauses execution)

2 Lesson 2: Input Function – Full Usage Guide

```
1 # INPUT FUNCTION - FULL USAGE GUIDE
3 # Basic Syntax:
4 # input(prompt='')
6 # Parameters:
7 # prompt → A string, written to standard output without a trailing newline,
             to ask the user for input. Default is an empty string ''.
9 # Returns → A string entered by the user (always str type).
10 # Notes → Always returns a string. You need to convert it using int(), float(), etc. if needed.
11
12
13
14 # 1. Basic usage with no prompt
user_input = input()
print("You entered:", user_input)
18 # 2. Input with a prompt
19 name = input("Enter your name: ")
20 print("Hello,", name)
21
22 # 3. Converting input to integer
23 age = int(input("Enter your age: "))
print("You will be", age + 1, "next year.")
# 4. Converting input to float
27 height = float(input("Enter your height in meters: "))
28 print("Your height in cm is", height * 100)
30 # 5. Reading multiple values (as strings)
31 x, y = input("Enter two words separated by space: ").split()
32 print("Word 1:", x)
33 print("Word 2:", y)
35 # 6. Reading and converting multiple values to int
36 a, b = map(int, input("Enter two integers: ").split())
   print("Sum =", a + b)
39 # 7. Reading many values into a list of ints
40 numbers = list(map(int, input("Enter multiple numbers: ").split()))
41 print("You entered:", numbers)
```

```
# 8. Handling invalid input using try/except

try:

salary = float(input("Enter your monthly salary: "))

print("Yearly salary:", salary * 12)

except ValueError:

print("Invalid input! Please enter a number.")

print("Invalid input! Please enter a number.")
```

Referenced Functions - Syntax and Output Type

Function / Statement	Syntax		Return / Output Type
.split()	<pre>string.split() string.split("delimiter")</pre>	or	List of strings
map()	map(function, iterable)		Map object (can be converted to list)
list()	list(iterable)		List object
try / except	<pre>try: code except ErrorType: fallback</pre>		Flow control – no return value; handles runtime errors

3 Lesson 3: Math Operators – Full Usage Guide

```
1 # MATH OPERATORS - FULL USAGE GUIDE
3 # Basic Syntax:
4 # <operand1> <operator> <operand2>
  # Operators:
7 # + Addition
                          → a + b
8 # - Subtraction
                         → a - b
9 # * Multiplication
                        + a * b
10 # / Division
                          → a / b
                        → a // b
11 # // Floor Division
12 # % Modulus (Remainder) → a % b
13 # ** Exponentiation
                         → a ** b
16
# 1. Addition
18 print("1 + 1 =", 1 + 1)
20 # 2. Subtraction
21 print("2 - 3 =", 2 - 3)
23 # 3. Multiplication
24 print("4 * 5 =", 4 * 5)
26 # 4. Division (always returns float)
```

```
27 print("6 / 3 =", 6 / 3)
29 # 5. Floor Division (truncates decimals)
30 print("7 // 2 =", 7 // 2)
# 6. Rounded division result using round()
number1 = 1.85
34 \text{ number2} = 1.35
number 3 = 1.5
print(f"{number1} rounded is:", round(number1)) # 2
print(f"{number2} rounded is:", round(number2)) # 1
38 print(f"{number3} rounded is:", round(number3)) # 2
40 # 7. Exponentiation
41 print("3 ** 3 =", 3 ** 3) # 27
# 8. Modulus (Remainder)
44 print("20 / 6 =", 20 / 6)  # Division
45 print("20 % 6 =", 20 % 6)  # Remainder (2)
47 # 9. Operator Precedence in Python:
48 # 1. ()
49 # 2. **
50 # 3. * and /
51 # 4. + and -
52 # Evaluated left to right within same level
```

4 Lesson 4: Strings - Full Usage Guide

```
1 # STRINGS - FULL USAGE GUIDE
3 # Basic Explanation:
4 # A string is a sequence of characters enclosed in single (' ') or double (" ") quotes.
5 # Strings are immutable in Python.
  # -----
8 # 1. Creating Strings
9 name = 'math' # single-quoted string
subject = "math" # double-quoted string
11
12 # 2. String Addition and Printing
print("math" + "works") # mathworks
print("math", "works")
                            # math works
# 3. String Multiplication
17 string1 = "hello"
18 string2 = "world"
19 \quad number = 5
                           # hello world
21 print(string1, string2)
print(string1 + string2) # helloworld
                            # hellohellohellohello
23 print(string1 * number)
25 # 4. Invalid Concatenation Example
26 # print(string1 + number) # TypeError: can only concatenate str (not "int")
28 # STRING METHODS - TOP 10 DEFINITIONS
```

```
30 text = "hello WORLD"
32 # 5. capitalize()
33 # Returns string with first character uppercased, rest lowercased.
34 print(text.capitalize()) # Hello world
36 # 6. lower()
# Converts all characters to lowercase.
38 print(text.lower())
                          # hello world
40 # 7. title()
# Capitalizes first letter of each word.
42 print(text.title()) # Hello World
44 # 8. casefold()
# Aggressive lowercase, suitable for comparisons.
46 text2 = "Straße"
47 print(text2.casefold()) # strasse
49 # 9. upper()
50 # Converts all characters to uppercase.
51 print(text.upper()) # HELLO WORLD
53 # 10. count()
54 # Counts how many times a substring appears.
print(text.count("1")) # 3
56 print(text.count("1", 3, 6))
                                  # 1
58 # 11. find()
59 # Finds index of substring, or -1 if not found.
60 print(text.find("WORLD")) # 6
61 print(text.find("not_here")) # -1
63 # 12. replace()
# Replaces substring with another.
                                         # hello Python
print(text.replace("WORLD", "Python"))
                                          # heXXo WORLD
print(text.replace("l", "X", 2))
68 # 13. swapcase()
# Swaps uppercase to lowercase and vice versa.
70 print("Hello World".swapcase()) # hELLO wORLD
72 # 14. join()
73 # Joins elements of iterable with separator.
74 words = ["hello", "world"]
75 print("-".join(words))
                                   # hello-world
```

Referenced Methods – Syntax and Output Type

Method / Function	Syntax	Return / Output Type
.capitalize()	str.capitalize()	str
.lower()	str.lower()	str
.title()	str.title()	str
.casefold()	str.casefold()	str
.upper()	str.upper()	str
.count()	<pre>str.count(substring, start, end)</pre>	int
.find()	<pre>str.find(substring, start, end)</pre>	int
.replace()	<pre>str.replace(old, new, count)</pre>	str
.swapcase()	str.swapcase()	str
.join()	"separator".join(iterable)	str

5 Lesson 5: If, Else, and Conditional Operators

```
1 # IF / ELSE / ELIF - FULL USAGE GUIDE
3 # Basic Syntax:
4 # if condition:
        block of code
6 # elif another_condition:
7 #
         another block
8 # else:
9 # fallback block
10
# Conditional Operators:
12 # == → Equal to
13 # != → Not equal to
                                          \rightarrow (x == y)
                                         → (x != y)
           → Less than
                                         \rightarrow (x < y)
15 # <= → Less than or equal to
                                         \rightarrow   (x \le y) 
  \rightarrow   (x > y) 
16 # >
          → Greater than
17 # >= \rightarrow Greater than or equal to \rightarrow (x >= y)
# Logical Operators:
20 # and \rightarrow True if both are True \rightarrow (x > 5 and x < 10)
# or \rightarrow True if at least one is True \rightarrow (x > 5 or x < 3)
22 # not \rightarrow Inverts the truth value \rightarrow not (x > 5)
26 # 1. Simple if statement
27 x = 10
28 if x > 5:
      print("x is greater than 5")
31 # 2. if-else statement
32 if x % 2 == 0:
print("x is even")
34 else:
      print("x is odd")
35
36
37 # 3. if-elif-else ladder
38 grade = 85
39 if grade >= 90:
print("Grade: A")
```

```
elif grade >= 80:
       print("Grade: B")
42
   elif grade >= 70:
43
       print("Grade: C")
44
45
   else:
       print("Grade: F")
46
47
48 # 4. Nested if statements
_{49} number = 42
if number > 0:
      if number % 2 == 0:
52
          print("Positive even number")
53
       else:
          print("Positive odd number")
54
55 else:
     print("Negative number or zero")
56
57
58 # 5. Using logical 'and'
59 age = 25
60 if age > 18 and age < 65:
61
       print("Adult and working age")
62
# 6. Using logical 'or'
64 language = "Python"
if language == "Python" or language == "Java":
       print("Popular programming language")
66
67
68 # 7. Using logical 'not'
69 is_logged_in = False
70 if not is_logged_in:
     print("User not logged in")
71
72
# 8. Short form if-else (Ternary Expression)
74 # → Python provides a one-line shorthand for simple if-else statements.
75 # → Syntax: value_if_true if condition else value_if_false
76 # \rightarrow Returns: One of two values based on the boolean result of the condition.
77
78 value = 8
79
  # Traditional if-else version:
80
   if value % 2 == 0:
81
       result = "Even"
82
   else:
83
       result = "Odd"
84
86 print("Traditional form:", result) # Even
88 # Shortened using ternary expression:
result = "Even" if value % 2 == 0 else "Odd"
90 print("Ternary form:", result)
91
```

Referenced Operators - Syntax and Output Type

Operator	Syntax	Return / Output Type
== (Equal)	x == y	bool
!= (Not Equal)	x != y	bool
< (Less Than)	x < y	bool
<= (Less Than or Equal)	x <= y	bool
> (Greater Than)	x > y	bool
>= (Greater Than or Equal)	x >= y	bool
and (Logical AND)	x > 5 and $x < 10$	bool
or (Logical OR)	x < 5 or x > 10	bool
not (Logical NOT)	not $(x > 5)$	bool
Ternary Expression	value1 if condition else value2	Result of value1 or value2

6 Lesson 6: While Loop - Full Usage Guide

```
1 # WHILE LOOP - FULL USAGE GUIDE
3 # Basic Syntax:
4 # while condition:
5 # block of code
7 # The code inside the loop runs repeatedly as long as the condition is True.
10
# 1. Basic while loop
12 counter = 0
while counter < 5:</pre>
print("Counter is:", counter)
     counter += 1 # same as: counter = counter + 1
# 2. Using break to exit loop early
18 i = 0
19 while True:
   if i == 3:
20
          print("Breaking at", i)
21
          break
23
     print(i)
      i += 1
24
^{26} # 3. Using continue to skip to next iteration
27 x = 0
28 while x < 5:
     x += 1
      if x == 3:
30
31
          continue # skips printing 3
32
     print("x =", x)
34 # 4. while loop with else block
35 z = ∅
36 while z < 3:
```

```
print("z =", z)
37
       z += 1
38
   else:
39
      print("Loop ended normally (no break)")
40
# 5. Infinite loop (be careful!)
43 # while True:
# print("This runs forever")
46 # 6. Compound condition
47 n = 0
48 while n < 10 and n != 7:
49 print(n)
50
      n += 2
51
52 # -----
53 # Counter update operators
54
55 # \rightarrow counter += 1 \rightarrow same as counter = counter + 1
56 # \rightarrow counter -= 1 \rightarrow same as counter = counter - 1
57 # \rightarrow counter *= 2 \rightarrow same as counter = counter * 2
  # → counter /= 2 → same as counter = counter / 2
60 # Note:
61 # Python does NOT support the ++ or -- operators like other languages.
# Using x++ or x-- will cause a SyntaxError.
```

Referenced Keywords and Operators - Syntax and Output Type

Keyword / Operator	Syntax	Return / Effect
while	while condition:	Repeats block while condition is True
break	break	Immediately exits the nearest enclosing loop
continue	continue	Skips current iter- ation and contin- ues with the next
+=	x += y	Updates: x = x + y
-=	x -= y	Updates: x = x - y
*=	x *= y	Updates: x = x * y
/=	x /= y	Updates: x = x / y
++ / -	Not supported in Python	Causes SyntaxError

7 Lesson 7: For Loop – Full Usage Guide

```
1 # FOR LOOP - FULL USAGE GUIDE
  # Basic Syntax:
  # for variable in iterable:
     block of code
8 # 1. Using range()
9 # range(stop) → from 0 to stop-1
# range(start, stop) → from start to stop-1
# range(start, stop, step)
for i in range(5):
     print("i =", i)
16 for i in range(2, 6):
     print("From 2 to 5:", i)
17
18
19 for i in range(10, 0, -2):
     print("Countdown by 2:", i)
20
21
22 # -----
23 # 2. Iterating over a list
fruits = ["apple", "banana", "cherry"]
25 for fruit in fruits:
     print("Fruit:", fruit)
28 # 3. Iterating over a string
29 text = "hello"
30 for char in text:
      print("Char:", char)
31
32
33 # 4. Iterating over a tuple
34 # A tuple is an ordered, immutable collection.
35 # You can iterate through it just like a list.
36 coordinates = (10, 20, 30)
37 for value in coordinates:
38
       print("Value:", value)
39
40
# 5. Iterating over a set
42 # A set is an unordered collection of unique elements.
# Iteration works, but order is not guaranteed.
   unique_numbers = \{1, 2, 3\}
   for num in unique_numbers:
       print("Unique:", num)
47
49 # 6. Iterating over a dictionary
50 # A dictionary stores key-value pairs.
51 # Iterating over it by default gives you the keys.
52 person = {"name": "Alice", "age": 25}
53 for key in person:
       print("Key:", key, "| Value:", person[key])
54
56 # 7. Iterating with .items()
# .items() returns a list of (key, value) pairs from a dictionary.
# Useful when you need both key and value at once.
for key, value in person.items():
print(f"{key} => {value}")
```

```
62 # 8. Using enumerate()
# enumerate() gives both the index and the item during iteration.
colors = ["red", "green", "blue"]
65 for index, color in enumerate(colors):
       print(f"{index}: {color}")
66
67
68
69 # 9. Using break
70 for n in range(5):
     if n == 3:
71
72
          break
      print("Breaking loop at:", n)
73
74
# 10. Using continue
76 for n in range(5):
     if n == 2:
77
          continue
78
79
      print("Continuing:", n)
80
81 # 11. Using else with for
82 for n in range(3):
     print(n)
84 else:
      print("Loop completed without break.")
85
87 # -----
88 # range() - Recap:
89 # range(stop)
90 # range(start, stop)
91 # range(start, stop, step)
92 # returns a range object which is an iterable of numbers
```

Referenced Iteration Helpers - Syntax and Output Type

Function / Method	Syntax	Return / Output Type
tuple	(a, b, c)	Iterable (ordered, immutable)
set	{a, b, c}	Iterable (un- ordered, unique)
<pre>dict.items()</pre>	<pre>dict.items()</pre>	Iterable of (key, value) pairs
enumerate()	enumerate(iterable)	Iterable of (index, item) tuples

8 Lesson 8: Functions - Full Usage Guide

```
# FUNCTIONS - FULL USAGE GUIDE

# Basic Syntax:
# def function_name(parameters):
```

```
5 # block of code
8 # 1. Defining a basic function
9 def greet():
   print("Hello from the function!")
10
11
# Call the function AFTER defining it
13 greet()
14
15 # -----
16 # 2. DOs and DON'Ts
# Don't call a function before it's defined:
# greet() # This would raise NameError if called before definition
20 # Always define before calling:
21 def welcome():
   print("Welcome to Python!")
22
23
24 welcome()
25
27 # 3. Function that performs a task (prints something)
28 def print_sum(a, b):
   print("The sum is:", a + b)
29
print_sum(4, 5) # Output: The sum is: 9
32
33 # -----
34 # 4. Function that calculates and returns a value
35 def get_sum(a, b):
     return a + b
36
38 result = get_sum(10, 20)
39 print("Returned sum:", result)
42 # 5. Local vs Global Variables
43
44 # Global variable
45 counter = 100
46
  def increase_counter():
47
     # Local variable (does not affect global counter)
      counter = 0
49
      counter += 1
50
      print("Local counter:", counter)
51
53 increase_counter()
54 print("Global counter remains:", counter)
55
57 # 6. Using 'global' keyword to modify global variable
58 count = 0
60 def modify_global():
global count
     count += 1
62
     print("Modified global count:", count)
63
65 modify_global()
66 print("Global count after function:", count)
```

9 Lesson 9: Lists - Introduction

```
1 # LISTS - INTRODUCTION
3 # What is a list?
4 # A list is a built-in data structure in Python that stores an ordered collection of items.
5 # Lists are mutable, meaning you can change their contents after creation.
6 # Defined using square brackets: []
9 # 1. Defining a simple list (homogeneous)
fruits = ["apple", "banana", "cherry"]
  print("Fruits:", fruits)
13 # 2. List of numbers
14 numbers = [1, 2, 3, 4, 5]
print("Numbers:", numbers)
# 3. List of mixed data types
18 mixed = ["hello", 42, 3.14, True]
19 print("Mixed list:", mixed)
21 # 4. Empty list
22 empty = []
23 print("Empty list:", empty)
# 5. Nested list (list inside a list)
26 matrix = [[1, 2], [3, 4]]
27 print("Nested list:", matrix)
29 # 6. List using list() constructor
30 from_string = list("hello")
  print("List from string:", from_string) # ['h', 'e', 'l', 'l', 'o']
33 # 7. List from range()
34 range_list = list(range(5))
35 print("List from range():", range_list) # [0, 1, 2, 3, 4]
```

List Types and Creation Methods

List Type	Syntax / Example	Notes
Homogeneous List	[1, 2, 3, 4]	All elements of the same type
String List	["apple", "banana"]	List of strings
Mixed-Type List	["hi", 42, 3.14, True]	Supports multi- ple data types
Empty List	[]	No elements yet
Nested List	[[1, 2], [3, 4]]	List inside a list
From String	list("abc")	Converts string into list of characters
From Range	list(range(5))	Converts range object into list

10 Lesson 10: List Methods – General Usage

```
# LIST METHODS - GENERAL PURPOSE
  # Lists are mutable and support many built-in methods for adding, removing, searching, and modifying.
5 # 1. append()
6 # → Adds a single element to the end
7 items = ["pen", "book"]
8 items.append("pencil")
9 print("append():", items)
11 # 2. insert()
# → Inserts an element at a specific index
items.insert(1, "eraser")
print("insert():", items)
16 # 3. remove()
17 # → Removes the first matching value
18 items.remove("book")
print("remove():", items)
21 # 4. pop()
22 # → Removes and returns element at index (default = last)
23 removed = items.pop()
24 print("pop():", removed)
25 print("After pop:", items)
27 # 5. clear()
28 # → Empties the list
29 temp = ["a", "b"]
30 temp.clear()
31 print("clear():", temp)
33 # 6. copy()
34 # → Returns a shallow copy
35 original = ["x", "y", "z"]
36 cloned = original.copy()
37 print("copy():", cloned)
39 # 7. extend()
40 # → Adds multiple elements from another iterable
41 tools = ["pen", "pencil"]
tools.extend(["marker", "sharpener"])
43 print("extend():", tools)
44
45 # 8. index() [Use with care]
46 # → Finds index of first match; raises error if not found
47 names = ["Alice", "Bob", "Charlie"]
48
   try:
       idx = names.index("Bob")
49
       print("index():", idx)
50
51 except ValueError:
       print("Name not found")
52
54 # Alternative using 'in'
55 print("Eve" in names) # False
57 # 9. count()
58 # → Counts number of times an item appears
59 letters = ["a", "b", "a", "c", "a"]
60 print("count():", letters.count("a")) # 3
```

```
61
62 # 10. reverse()
63 # → Reverses the list in-place
64 words = ["start", "middle", "end"]
65 words.reverse()
66 print("reverse():", words)
67
68 # 11. sort() [Only works if items are comparable]
69 # → Sorts the list (only if all items can be compared)
70 languages = ["python", "c", "java"]
71 languages.sort()
72 print("sort():", languages)
```

Common List Methods - Overview Table

Method	Description	Return Value
append(x)	Add element x to the end	None
<pre>insert(i,x)</pre>	Insert x at index i	None
remove(x)	Remove first occurrence of x	None
pop(i)	Remove and return item at index i (last by default)	Element
clear()	Remove all items from the list	None
copy()	Return a shallow copy of the list	List copy
extend(iter)	Append elements from iterable	None
index(x)	Return first index of x (error if not found)	Integer
count(x)	Count occurrences of x	Integer
reverse()	Reverse items in-place	None
sort()	Sort the list in-place	None

11 Lesson 11: List Methods - Numeric Lists Only

```
# LIST METHODS - NUMERIC LISTS ONLY

# These methods are especially useful and commonly used with lists that contain only numbers.

# Numeric list for demonstration
numbers = [5, 2, 8, 3, 5, 1, 8]

# 1. sort()
# # Sorts the list in ascending order (in-place)
numbers.sort()
print("sort():", numbers) # [1, 2, 3, 5, 5, 8, 8]

# 2. reverse()
# # Reverses the list order in-place
numbers.reverse()
print("reverse():", numbers) # [8, 8, 5, 5, 3, 2, 1]

# 3. count()
# # Counts occurrences of a specific number
print("count(5):", numbers.count(5)) # 2
```

```
22 # 4. max()
23 # → Returns the largest number in the list
print("max():", max(numbers)) # 8
26 # 5. min()
27 # → Returns the smallest number in the list
28 print("min():", min(numbers)) # 1
30 # 6. sum()
31 # → Returns the sum of all elements
32 print("sum():", sum(numbers)) # 32
34 # 7. average (manual)
35 # → Average = sum / count
36 average = sum(numbers) / len(numbers)
print("Average:", average) # 4.571...
39 # 8. sorted()
40 # → Returns a new sorted list without modifying the original
41 original = [10, 3, 7]
42 sorted_list = sorted(original)
43 print("original:", original) # [10, 3, 7]
44 print("sorted():", sorted_list) # [3, 7, 10]
```

List Methods for Numbers - Reference Table

Method	Description	Return Value
sort()	Sort list in ascending order (inplace)	None
reverse()	Reverse the list (in-place)	None
count(x)	Count how many times x appears	Integer
max(lst)	Return maximum element	Element
min(lst)	Return minimum element	Element
sum(lst)	Sum of all list items	Numeric
sorted(lst)	Return a new sorted list	New list
<pre>avg = sum()/len()</pre>	Compute average (manual)	Float