My Python Course Notes

Structured Revision for Every Lesson

Siddharth Patel
HTW Berlin

May 28, 2025

Contents

1 Lesson 1: Print Function – Full Usage Guide

```python
# PRINT FUNCTION – FULL USAGE GUIDE

# Basic Syntax:
# print(*objects, sep=' ', end='\n', file=sys.stdout, flush=False)

# Parameters:
# *objects → One or more objects to be printed (comma-separated).
# sep      → String inserted between objects. Default is ' ' (space).
# end      → String appended after the last object. Default is '\n' (new line).
# file     → A file-like object (stream); default is sys.stdout.
# flush    → If True, forcibly flush the stream. Default is False.

# ------------------------------------------

# 1. Basic print
print("Hello, World!")  # Hello, World!

# 2. Printing multiple objects
print("Hello", "Python", 3)  # Hello Python 3

# 3. Using 'sep' to change separator
print("2025", "05", "27", sep="-")  # 2025-05-27

# 4. Using 'end' to avoid new line
print("Loading", end="...")  # Loading...

# 5. Using custom separator and end together
print("Name", "Age", sep=": ", end=" years\n")  # Name: Age years

# 6. Printing to a file
with open("output.txt", "w") as f:
    print("Saving this line to a file.", file=f)

# 7. Forcing flush (useful in loops/real-time output)
import time
for i in range(3):
    print(i, end=" ", flush=True)
    time.sleep(0.5)  # Output appears immediately

# 8. Printing escape characters
print("Line1\nLine2")         # New line
print("Tabbed\tSpace")        # Tab space
print("He said \"hello\"")    # Quotes inside string

# 9. Printing with formatted strings (f-strings)
name = "Siddhart"
age = 21
print(f"Hello, my name is {name} and I am {age} years old.")

# 10. Using print with unpacking
nums = [1, 2, 3, 4]
print(*nums)               # 1 2 3 4
print(*nums, sep=", ")     # 1, 2, 3, 4

# 11. Printing Unicode/emojis (note: removed for LaTeX safety)
print("Python is fun")
```

Additional Functions Used in This Lesson

Referenced Functions – Syntax and Output Type

Function	Syntax	Return / Output Type
with open()	`with open("file.txt", "w") as f:`	File object
print(..., file=f)	`print("text", file=f)`	Writes to file, returns None
range()	`range(3)` or `range(start, stop, step)`	Range object (iterable)
time.sleep()	`time.sleep(seconds)`	None (pauses execution)

2 Lesson 2: Input Function – Full Usage Guide

```
# INPUT FUNCTION - FULL USAGE GUIDE

# Basic Syntax:
# input(prompt='')

# Parameters:
# prompt → A string, written to standard output without a trailing newline,
#           to ask the user for input. Default is an empty string ''.
# Returns → A string entered by the user (always str type).
# Notes   → Always returns a string. You need to convert it using int(), float(), etc. if needed.

# ---------------------------------------------

# 1. Basic usage with no prompt
user_input = input()
print("You entered:", user_input)

# 2. Input with a prompt
name = input("Enter your name: ")
print("Hello,", name)

# 3. Converting input to integer
age = int(input("Enter your age: "))
print("You will be", age + 1, "next year.")

# 4. Converting input to float
height = float(input("Enter your height in meters: "))
print("Your height in cm is", height * 100)

# 5. Reading multiple values (as strings)
x, y = input("Enter two words separated by space: ").split()
print("Word 1:", x)
print("Word 2:", y)

# 6. Reading and converting multiple values to int
a, b = map(int, input("Enter two integers: ").split())
print("Sum =", a + b)

# 7. Reading many values into a list of ints
numbers = list(map(int, input("Enter multiple numbers: ").split()))
print("You entered:", numbers)
```

```

# 8. Handling invalid input using try/except
try:
    salary = float(input("Enter your monthly salary: "))
    print("Yearly salary:", salary * 12)
except ValueError:
    print("Invalid input! Please enter a number.")


```

Referenced Functions – Syntax and Output Type

Function / Statement	Syntax	Return / Output Type
.split()	string.split() or string.split("delimiter")	List of strings
map()	map(function, iterable)	Map object (can be converted to list)
list()	list(iterable)	List object
try / except	try: code except ErrorType: fallback	Flow control – no return value; handles runtime errors

3 Lesson 3: Math Operators – Full Usage Guide

```
# MATH OPERATORS - FULL USAGE GUIDE

# Basic Syntax:
# <operand1> <operator> <operand2>

# Operators:
# +   Addition            → a + b
# -   Subtraction         → a - b
# *   Multiplication      → a * b
# /   Division            → a / b
# //  Floor Division      → a // b
# %   Modulus (Remainder) → a % b
# **  Exponentiation      → a ** b

# ------------------------------------------

# 1. Addition
print("1 + 1 =", 1 + 1)

# 2. Subtraction
print("2 - 3 =", 2 - 3)

# 3. Multiplication
print("4 * 5 =", 4 * 5)

# 4. Division (always returns float)
```

```
print("6 / 3 =", 6 / 3)

# 5. Floor Division (truncates decimals)
print("7 // 2 =", 7 // 2)

# 6. Rounded division result using round()
number1 = 1.85
number2 = 1.35
number3 = 1.5
print(f"{number1} rounded is:", round(number1))  # 2
print(f"{number2} rounded is:", round(number2))  # 1
print(f"{number3} rounded is:", round(number3))  # 2

# 7. Exponentiation
print("3 ** 3 =", 3 ** 3)  # 27

# 8. Modulus (Remainder)
print("20 / 6 =", 20 / 6)      # Division
print("20 % 6 =", 20 % 6)      # Remainder (2)

# 9. Operator Precedence in Python:
# 1. ()
# 2. **
# 3. * and /
# 4. + and -
# Evaluated left to right within same level
```

4 Lesson 4: Strings – Full Usage Guide

```
# STRINGS – FULL USAGE GUIDE

# Basic Explanation:
# A string is a sequence of characters enclosed in single (' ') or double (" ") quotes.
# Strings are immutable in Python.

# ------------------------------------------
# 1. Creating Strings
name = 'math'     # single-quoted string
subject = "math"  # double-quoted string

# 2. String Addition and Printing
print("math" + "works")     # mathworks
print("math", "works")      # math works

# 3. String Multiplication
string1 = "hello"
string2 = "world"
number = 5

print(string1, string2)     # hello world
print(string1 + string2)    # helloworld
print(string1 * number)     # hellohellohellohellohello

# 4. Invalid Concatenation Example
# print(string1 + number)   # TypeError: can only concatenate str (not "int")
```

```python

# STRING METHODS - TOP 10 DEFINITIONS

text = "hello WORLD"

# 5. capitalize()
# Returns string with first character uppercased, rest lowercased.
print(text.capitalize())  # Hello world

# 6. lower()
# Converts all characters to lowercase.
print(text.lower())       # hello world

# 7. title()
# Capitalizes first letter of each word.
print(text.title())       # Hello World

# 8. casefold()
# Aggressive lowercase, suitable for comparisons.
text2 = "Straße"
print(text2.casefold())   # strasse

# 9. upper()
# Converts all characters to uppercase.
print(text.upper())       # HELLO WORLD

# 10. count()
# Counts how many times a substring appears.
print(text.count("l"))            # 3
print(text.count("l", 3, 6))      # 1

# 11. find()
# Finds index of substring, or -1 if not found.
print(text.find("WORLD"))         # 6
print(text.find("not_here"))      # -1

# 12. replace()
# Replaces substring with another.
print(text.replace("WORLD", "Python"))     # hello Python
print(text.replace("l", "X", 2))           # heXXo WORLD

# 13. swapcase()
# Swaps uppercase to lowercase and vice versa.
print("Hello World".swapcase())  # hELLO wORLD

# 14. join()
# Joins elements of iterable with separator.
words = ["hello", "world"]
print("-".join(words))           # hello-world
```

Referenced Methods – Syntax and Output Type

Method / Function	Syntax	Return / Output Type
.capitalize()	str.capitalize()	str
.lower()	str.lower()	str
.title()	str.title()	str
.casefold()	str.casefold()	str
.upper()	str.upper()	str
.count()	str.count(substring, start, end)	int
.find()	str.find(substring, start, end)	int
.replace()	str.replace(old, new, count)	str
.swapcase()	str.swapcase()	str
.join()	"separator".join(iterable)	str

5 Lesson 5: If, Else, and Conditional Operators

```
# IF / ELSE / ELIF – FULL USAGE GUIDE

# Basic Syntax:
# if condition:
#     block of code
# elif another_condition:
#     another block
# else:
#     fallback block

# Conditional Operators:
# ==   → Equal to                  → (x == y)
# !=   → Not equal to              → (x != y)
# <    → Less than                 → (x < y)
# <=   → Less than or equal to     → (x <= y)
# >    → Greater than              → (x > y)
# >=   → Greater than or equal to  → (x >= y)

# Logical Operators:
# and  → True if both are True     → (x > 5 and x < 10)
# or   → True if at least one is True → (x > 5 or x < 3)
# not  → Inverts the truth value   → not (x > 5)

# ------------------------------------------

# 1. Simple if statement
x = 10
if x > 5:
    print("x is greater than 5")

# 2. if-else statement
if x % 2 == 0:
    print("x is even")
else:
    print("x is odd")

# 3. if-elif-else ladder
grade = 85
if grade >= 90:
    print("Grade: A")
```

```python
elif grade >= 80:
    print("Grade: B")
elif grade >= 70:
    print("Grade: C")
else:
    print("Grade: F")

# 4. Nested if statements
number = 42
if number > 0:
    if number % 2 == 0:
        print("Positive even number")
    else:
        print("Positive odd number")
else:
    print("Negative number or zero")

# 5. Using logical 'and'
age = 25
if age > 18 and age < 65:
    print("Adult and working age")

# 6. Using logical 'or'
language = "Python"
if language == "Python" or language == "Java":
    print("Popular programming language")

# 7. Using logical 'not'
is_logged_in = False
if not is_logged_in:
    print("User not logged in")

# 8. Short form if-else (Ternary Expression)
# → Python provides a one-line shorthand for simple if-else statements.
# → Syntax: value_if_true if condition else value_if_false
# → Returns: One of two values based on the boolean result of the condition.

value = 8

# Traditional if-else version:
if value % 2 == 0:
    result = "Even"
else:
    result = "Odd"

print("Traditional form:", result)  # Even

# Shortened using ternary expression:
result = "Even" if value % 2 == 0 else "Odd"
print("Ternary form:", result)      # Even

```

Referenced Operators – Syntax and Output Type

Operator	Syntax	Return / Output Type
== (Equal)	`x == y`	`bool`
!= (Not Equal)	`x != y`	`bool`
< (Less Than)	`x < y`	`bool`
<= (Less Than or Equal)	`x <= y`	`bool`
> (Greater Than)	`x > y`	`bool`
>= (Greater Than or Equal)	`x >= y`	`bool`
and (Logical AND)	`x > 5 and x < 10`	`bool`
or (Logical OR)	`x < 5 or x > 10`	`bool`
not (Logical NOT)	`not (x > 5)`	`bool`
Ternary Expression	`value1 if condition else value2`	Result of `value1` or `value2`