



Vidyavardhini's College of Engineering and Technology
Department of Artificial Intelligence & Data Science

AY: 2023-24

Class:		Semester:	
Course Code:		Course Name:	

Name of Student:	
Roll No. :	
Experiment No.:	10
Title of the Experiment:	Implement container orchestration using Kubernetes
Date of Performance:	
Date of Submission:	

Evaluation

Performance Indicator	Max. Marks	Marks Obtained
Performance	5	
Understanding	5	
Journal work and timely submission	10	
Total	20	

Performance Indicator	Exceed Expectations (EE)	Meet Expectations (ME)	Below Expectations (BE)
Performance	4-5	2-3	1
Understanding	4-5	2-3	1
Journal work and timely submission	8-10	5-8	1-4

Checked by

Name of Faculty :

Signature :

Date



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No. 10

Aim: To study and implement container orchestration using Kubernetes

Objective: To understand container orchestration using Kubernetes.

Theory:

Container orchestration automates the deployment, management, scaling, and networking of containers. Container orchestration can be used in any environment where you use containers. It can help you to deploy the same application across different environments without needing to redesign it. And microservices in containers make it easier to orchestrate services, including storage, networking, and security. container orchestration to automate and manage tasks such as:

- Provisioning and deployment
- Configuration and scheduling
- Resource allocation
- Container availability
- Scaling or removing containers based on balancing workloads across your infrastructure
- Load balancing and traffic routing
- Monitoring container health
- Configuring applications based on the container in which they will run
- Keeping interactions between containers secure

Kubernetes is an open-source container management (orchestration) tool. Its container management responsibilities include container deployment, scaling & descaling of containers & container load balancing.

Features of Kubernetes

- Automatic Bin packing
- Service Discovery and Load Balancing
- Storage Orchestration
- Self-Healing
- Secrete and configuration management.
- Batch execution
- Horizontal Scaling
- Automatic Rollbacks and Rollouts



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Steps:

----Enable Kubernetes---

1. After installing Docker Desktop, you should see a Docker icon in your system tray. Right-click on it, and navigate **Settings > Kubernetes**.
2. Check the checkbox labeled **Enable Kubernetes**, and click **Apply & Restart**. Docker Desktop will automatically set up Kubernetes for you. You'll know that Kubernetes has been successfully enabled when you see a green light beside 'Kubernetes *running*' in the **Settings** menu.
3. In order to confirm that Kubernetes is up and running, create a text file called pod.yaml with the following content:

```
apiVersion: v1
kind: Pod
metadata:
  name: demo
spec:
  containers:
  - name: testpod
    image: alpine:latest
    command: ["ping", "8.8.8.8"]
```

This describes a pod with a single container, isolating a simple ping to 8.8.8.8.

4. In PowerShell, navigate to where you created pod.yaml and create your pod:
\$ kubectl apply -f pod.yaml
5. Check that your pod is up and running:

```
$ kubectl get pods
```

You should see something like:

NAME	READY	STATUS	RESTARTS
demo		Running	4

6. Check that you get the logs you'd expect for a ping process:
\$ kubectl logs demo
7. Finally, tear down your test pod:

```
$ kubectl delete -f pod.yaml
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

---Deploy Kubernetes---

Prerequisite

- Download and install Docker Desktop as described in [Get Docker](#).
- Work through containerizing an application in [Part 2](#).
- Make sure that Kubernetes is enabled on your Docker Desktop:
 - **Windows:** Click the Docker icon in the system tray and navigate to **Settings** and make sure there's a green light beside 'Kubernetes'.

Describing apps using Kubernetes YAML

1. Place the following in a file called bb.yaml: apiVersion:

```
apps/v1
kind: Deployment
metadata:
  name: bb-demo
  namespace: default
spec:
  replicas: 1
  selector:
    matchLabels:
      bb: web
  template:
    metadata:
      labels:
        bb: web
    spec:
      containers:
        - name: bb-site
          image: getting-started
          imagePullPolicy: Never
```

```
apiVersion: v1
kind: Service
metadata:
  name: bb-entripoint
  namespace: default
spec:
  type: NodePort
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

selector:

bb: web

ports:

- port: 3000

targetPort: 3000

nodePort: 30001

--Deploy and check application--

1. In a terminal, navigate to where you created bb.yaml and deploy your application to Kubernetes:

```
$ kubectl apply -f bb.yaml
```

2. Make sure everything worked by listing your deployments:

```
$ kubectl get deployments
```

3. Open a browser and visit your Todo app at localhost:30001; you should see your Todo application.
4. Once satisfied, tear down your application:

```
$ kubectl delete -f bb.yaml
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Output/Observation:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Conclusion:

Comment on implementation of Containerization using Kubernetes



Vidyavardhini's College of Engineering and Technology, Vasai

Department of Artificial Intelligence & Data Science
