

A

Project Report

Submitted in partial fulfilment of the requirements for the completion of the Course

EDS Lab Codetantra

Practical No.2

(2304102L)

Submitted by,

Siddhi Kundan Shivthare (202501090108)

Under the Guidance of,

Ms. Savita Mane(SM)



(An Autonomous Institute Affiliated to Savitribai Phule Pune University)

Department of Mechanical Engineering,

MIT Academy of Engineering,

Alandi road, Pune - 412 105,

Maharashtra (India)

2.1.1. List operations

08:32

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:

1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu. Depending on the choice selected, the program should perform the following actions:

Add: Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".

Remove: Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".

Display : Displays the current list of integers. If the list is empty, display "List is empty".

Quit: Exits the program.

The program should handle invalid menu choices by displaying "Invalid choice". Ensure that the program continues to prompt the user until they choose to quit (option 4).

listOps.py

```
int_list = []
```

```
while True: print("1.
```

```
    Add") print("2.
```

```
    Remove") print("3.
```

```
    Display") print("4.
```

```
    Quit")
```

```
choice = input("Enter choice: ")
```

```
if choice == '1': # Add value
```

```
    value = input("Integer: ") try:
```

```
        num = int(value)
```

```
    int_list.append(num) print("List
```

```
    after adding:", int_list) except
```

```
    ValueError:
```

```
        print("Invalid input")
```

```
elif choice == '2': #
```

```
    Remove if not int_list:
```

```
        print("List is empty") else:
```

```
        value = input("Integer: ")
```

```
        try:
```

```
            num = int(value)
```

```
    if num in int_list:
        int_list.remove(num) print("List after
removing:", int_list) else:
        print("Element not found") except
ValueError:
    print("Invalid input")
```

```
elif choice == '3': #
```

```
    Display if not int_list:
```

```
    print("List is empty") else:
```

```
        print(int_list)
```

```
elif choice == '4': # Quit break
```

```
else:
```

```
    print("Invalid choice")
```

Explore

Average time
0.037 s
37.33 ms

Maximum time
0.056 s
56.00 ms

2 out of 2 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Test case 130 msDebug

Expected output

Actual output

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 11

List after adding: [11]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 25

List after adding: [11, 25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 26

Element not found

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 11

List after removing: [25]

1. Add

2. Remove

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 11

List after adding: [11]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 1

Integer: 25

List after adding: [11, 25]

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 26

Element not found

1. Add

2. Remove

3. Display

4. Quit

Enter choice: 2

Integer: 11

List after removing: [25]

1. Add

2. Remove

Terminal

Test cases

< Prev

Reset

Submit

Next >

Debugger

Explorer

Average time

0.072 s

71.67 ms

Maximum time

0.089 s

89.00 ms

2 out of 2 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Debugger

Integer: 11
List after removing: [25]
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
Integer: 25
List after removing: []
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 3
List is empty
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
List is empty
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 8
Invalid choice
1. Add
2. Remove

Integer: 11
List after removing: [25]
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
Integer: 25
List after removing: []
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 3
List is empty
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 2
List is empty
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 8
Invalid choice
1. Add
2. Remove

< Prev

Reset

Submit

Next >

List is empty
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 8
Invalid choice
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 4

List is empty
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 8
Invalid choice
1. Add
2. Remove
3. Display
4. Quit
Enter choice: 4

< Prev

Reset

Submit

Next >

2.1.2. Dictionary Operations

07:23

Write a Python program to perform insertion, update, deletion, and traversal operations on a dictionary. An initial dictionary containing 10 predefined records is already given in the program.

Operations to be Performed:

1. Insertion – Insert a new key-value pair into the dictionary using user input.
2. Update – Update the value of an existing key using user input.
3. Deletion – Delete a specified key from the dictionary using user input.
4. Traversal – Traverse the final dictionary and display all key-value pairs.

Input and Output Format:

1. Read an integer representing the key to be inserted and a string representing its value. Insert this new key-value pair into the dictionary and display the dictionary after insertion.
2. Read an integer representing the key to be updated and a string representing the new value. Update the value of the specified key (only if it exists) and display the dictionary after the update.
3. Read an integer representing the key to be deleted. Delete the specified key from the dictionary (only if it exists) and display the dictionary after deletion.
4. Finally, traverse the dictionary and display all key-value pairs.

The program should also display the original dictionary before performing any operations. Each output should be printed with appropriate messages.

Note:

All operations must be performed using dictionary methods.

Perform deletion only if possible; leave the dictionary unchanged.

Refer to the visible test cases for better understanding and strictly match with the input/outputs.

```
# Initial dictionary with 10 predefined records
student = {
```



```
1: "Amit",  
2: "Riya",  
3: "Kiran",  
4: "Neha",  
5: "Arjun",  
6: "Pooja",  
7: "Rahul",  
8: "Sneha",  
9: "Vikram",  
10: "Anjali"  
}
```

```
# Display original dictionary print("Original  
Dictionary:", student)
```

```
# Insertion key  
= int(input())  
value = input()  
student[key] =  
value  
print("After Insertion:", student)
```

```
# Update upd_key =  
int(input()) upd_value =  
input() if upd_key in  
student: student[upd_key]
```

```
= upd_value print("After  
Update:", student)
```

```
# Deletion del_key =
int(input()) if del_key
in student:

    student.pop(del_key)

print("After Deletion:", student)

# Traversal print("Traversing
Dictionary:") for k, v in
student.items(): print(k, ":", v)
```

Average time: 0.027 s
27.00 ms

Maximum time: 0.044 s
44.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Expected output	Actual output
Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}	Original Dictionary: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali'}
11	11
Suresh	Suresh
After-Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After-Insertion: {1: 'Amit', 2: 'Riya', 3: 'Kiran', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
3	3
Karthik	Karthik
After-Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After-Update: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 5: 'Arjun', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
5	5
After-Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}	After-Deletion: {1: 'Amit', 2: 'Riya', 3: 'Karthik', 4: 'Neha', 6: 'Pooja', 7: 'Rahul', 8: 'Sneha', 9: 'Vikram', 10: 'Anjali', 11: 'Suresh'}
Traversing Dictionary:	Traversing Dictionary:
1: Amit	1: Amit
2: Riya	2: Riya
3: Karthik	3: Karthik
4: Neha	4: Neha
6: Pooja	6: Pooja
7: Rahul	7: Rahul
8: Sneha	8: Sneha
9: Vikram	9: Vikram
10: Anjali	10: Anjali
11: Suresh	11: Suresh

Terminal Test cases

< Prev Reset Submit Next >

2.2.1. Linear search

Technique 04:45

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

The first line of input contains the array of integers which are separated by space

The last line of input contains the key element to be searched

Output format:

If the element is found, print the index.

If the element is not found, print **Not found** .

Sample Test Case:**Input:**

1 2 3 4 3 5 6

3

Output:

2

Read input array

```
arr = list(map(int, input().split()))
```

Read key element

```
key = int(input())
```

Linear search found

= False

```
for i in range(len(arr)):
```

```
    if arr[i] == key:
```

```
        print(i)
```

```
        found = True
```

```
        break
```

If not found if

not found:

print("Not found")

The screenshot displays a code execution environment with the following details:

- Performance Metrics:**
 - Average time: 0.010 s (9.75 ms)
 - Maximum time: 0.012 s (12.00 ms)
- Test Results:**
 - 2 out of 2 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Test Case 1 Details:**
 - Status: Passed (10 ms)
 - Buttons: Debug, Menu, Calendar
 - Expected output:**
1 2 3 4 3 5 6
3
2
 - Actual output:**
1 2 3 4 3 5 6
3
2
- Test Case 2:** Passed (12 ms)

2.2.2. Captain of the

Team 01:32

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the tallest player, who will be selected as the captain of the team.

Input Format:

The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format

The output should be the height (in centimeters) of the tallest player.

```
# Read heights of 11 players heights
```

```
= list(map(int, input().split()))
```

```
# Find the tallest player tallest
```

```
= max(heights)
```

```
# Output the tallest height print(tallest)
```

The screenshot displays a coding platform interface with the following components:

- Performance Metrics:**
 - Average time: 0.005 s (5.33 ms)
 - Maximum time: 0.006 s (6.00 ms)
- Test Results:**
 - 1 out of 1 shown test case(s) passed
 - 2 out of 2 hidden test case(s) passed
- Test Case 1 Details:**
 - Status: Passed (6 ms)
 - Buttons: Debug, Menu, Expand
 - Expected output:**
171 169 185 156 174 191 186 190 187 172 160
191
 - Actual output:**
171 169 185 156 174 191 186 190 187 172 160
191
- Navigation:**
 - Terminal (selected), Test cases
 - Footer: < Prev, Reset, Submit, Next >