

Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

Experiment No 1.

Aim: To implement DDA algorithms for drawing a line segment between two given end points.

Objective: Draw the line using (vector) generation algorithms which determine the pixels that should be turned ON are called as digital differential analyzer (DDA). It is one of the techniques for obtaining a rasterized straight line. This algorithm can be used to draw the line in all the quadrants.

Theory:

DDA algorithm is an incremental scan conversion method. Here we perform calculations at each step using the results from the preceding step. The characteristic of the DDA algorithm is to take unit steps along one coordinate and compute the corresponding values along the other coordinate. Digital Differential Analyzer (DDA) algorithm is the simple line generation algorithm which is explained step by step here.

Algorithm:

```
Step1: Start Algorithm
```

Step2: Declare $x_1, y_1, x_2, y_2, dx, dy, x, y$ as integer variables.

```
Step3: Enter value of x_1, y_1, x_2, y_2.
```

```
Step4: Calculate dx = x_2 - x_1
```

Step5: Calculate $dy = y_2-y_1$

```
Step6: If ABS (dx) > ABS (dy)
Then step = abs (dx)
Else
```

```
Step7: x_{inc}=dx/step

y_{inc}=dy/step

assign x = x_1

assign y = y_1
```

Step8: Set pixel (x, y)

```
Step9: x = x + x_{inc}

y = y + y_{inc}

Set pixels (Round (x), Round (y))
```



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

Step10: Repeat step 9 until $x = x_2$

Step11: End Algorithm

Program:

```
#include<graphics.h>
#include<stdio.h>
#include<math.h>
#include<dos.h>
int main()
{
       float x,y,x1,y1,x2,y2,dx,dy,step;
       int i,gd=DETECT,gm;
       //detectgraph(&gd,&gm);
       initgraph(&gd,&gm,"");
       printf("\nEnter the x-coordinate of the first point:");
       scanf("%f",&x1);
       printf("\nEnter the y-coordinate of the first point:");
       scanf("%f",&y1);
       printf("\nEnter the x-coordinate of the second point:");
       scanf("%f",&x2);
       printf("\nEnter the y-coordinate of the second point:");
       scanf("%f",&y2);
       dx=abs(x2-x1);
       dy=abs(y2-y1);
       if(dx>dy)
              step=dx;
       }
       else
       {
              step=dy;
       dx=dx/step;
       dy=dy/step;
       x=x1;
       y=y1;
       i=1;
       while(i<=step)
              putpixel(x,y,14);
              x=x+dx;
              y=y+dy;
              i=i+1;
              delay(100);
```



Vidyavardhini's College of Engineering & Technology

Department of Artificial Intelligence and Data Science

```
getch();
closegraph();
}
```

Output:

```
Enter the x-coordinate of the first point:150
Enter the x-coordinate of the second point:400
Enter the y-coordinate of the second point:250
```

Conclusion: Comment on -

- Pixel
- 2. Equation for line
- 3. Need of line drawing algorithm
- 4. Slow or fast