

Bottom-Up Algorithms

Going **bottom-up** is a way to avoid recursion, saving the **memory cost** that recursion incurs when it builds up the **call stack**.

Put simply, a bottom-up algorithm "starts from the beginning," while a recursive algorithm often "starts from the end and works backwards."

For example, if we wanted to multiply all the numbers in the range $1..n$, we could use this cute, **top-down**, recursive one-liner:

```
public static int product1ToN(int n) {  
    // we assume n >= 1  
    return (n > 1) ? (n * product1ToN(n-1)) : 1;  
}
```

Java ▼

This approach has a problem: it builds up a **call stack** of size $O(n)$, which makes our total memory cost $O(n)$. This makes it vulnerable to a **stack overflow error**, where the call stack gets too big and runs out of space.

To avoid this, we can instead go **bottom-up**:

```
public static int product1ToN(int n) {  
    // we assume n >= 1  
  
    int result = 1;  
    for (int num = 1; num <= n; num++) {  
        result *= num;  
    }  
  
    return result;  
}
```

This approach uses $O(1)$ space ($O(n)$ time).

Some compilers and interpreters will do what's called **tail call optimization** (TCO), where it can optimize some recursive methods to avoid building up a tall call stack. Python and Java decidedly do not use TCO. Some Ruby implementations do, but most don't. Some C implementations do, and the JavaScript spec recently *allowed* TCO. Scheme is one of the few languages that *guarantee* TCO in all implementations. In general, best not to assume your compiler/interpreter will do this work for you.

Going bottom-up is a common strategy for **dynamic programming** problems, which are problems where the solution is composed of solutions to the same problem with smaller inputs (as with multiplying the numbers $1..n$, above). The other common strategy for dynamic programming problems is **memoization (/concept/memoization)**.

See also:

- Overlapping Subproblems (/concept/overlapping-subproblems)
- Memoization (/concept/memoization)

Bottom-Up/Dynamic Programming Coding Interview Questions

5 **Making Change »**

Write a function that will replace your role as a cashier and make everyone rich or something. keep reading »

(/question/coin)

15 **Compute nth Fibonacci Number »**

Computer the nth Fibonacci number. Careful--the recursion can quickly spin out of control! keep reading »

(/question/nth-fibonacci)

16 **The Cake Thief »**

You've hit the motherload: the cake vault of the Queen of England. Figure out how much of each cake to carry out to maximize profit. keep reading »

(/question/cake-thief)

All Questions → (/all-questions)

Want more coding interview help?

Check out **interviewcake.com** for more advice, guides, and practice questions.