


Let's deep dive into **@Profile** annotation to understand it better




This "username", "password" is just one example.
There are so many other configuration, which are different for different environments, like:

- URL and Port number
- Connection timeout values
- Request timeout values
- Throttle values
- Retry values etc.

How to do it?
We put the configurations in "application.properties" file.
But how to handle, different environment configurations?

That’s where **Profiling** comes into the picture



```
@Component
public class MySQLConnection {

    @Value("${username}")
    String username;

    @Value("${password}")
    String password;

    @PostConstruct
    public void init(){
        System.out.println("username: " + username + " password: " + password);
    }
}
```

application.properties

username=defaultUsername
password=defaultPassword

application-dev.properties

username=devUsername
password=devPassword

application-qa.properties

username=qaUsername
password=qaPassword

application-prod.properties

username=prodUsername
password=prodPassword

```
2024-06-01T22:55:24.548+05:30 INFO 48119 --- [main] c.c.l.SpringbootApplication
2024-06-01T22:55:24.549+05:30 INFO 48119 --- [main] c.c.l.SpringbootApplication
2024-06-01T22:55:24.982+05:30 INFO 48119 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer
2024-06-01T22:55:24.990+05:30 INFO 48119 --- [main] o.apache.catalina.core.StandardService
2024-06-01T22:55:24.990+05:30 INFO 48119 --- [main] o.apache.catalina.core.StandardEngine
2024-06-01T22:55:25.016+05:30 INFO 48119 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/]
2024-06-01T22:55:25.016+05:30 INFO 48119 --- [main] w.s.c.ServletWebServerApplicationContext
username: defaultUsername password: defaultPassword
2024-06-01T22:55:25.175+05:30 INFO 48119 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer
2024-06-01T22:55:25.179+05:30 INFO 48119 --- [main] c.c.l.SpringbootApplication
```

And during application startup, we can tell spring boot to pick specific "application properties" file, Using "spring.profiles.active" configuration.

```
@Component
public class MySqlConnection {

    @Value("${username}")
    String username;

    @Value("${password}")
    String password;

    @PostConstruct
    public void init(){
        System.out.println("username: " + username + " password: " + password);
    }
}
```

```
application.properties

username=defaultUsername
password=defaultPassword
spring.profiles.active=qa
```

application-dev.properties	application-qa.properties	application-prod.properties
username=devUsername password=devPassword	username=qaUsername password=qaPassword	username=prodUsername password=prodPassword

```
2024-06-02T08:04:23.599+05:30 INFO 52175 --- [main] c.c.l.SpringbootApplication : The following 1 profile is active: "qa"
2024-06-02T08:04:24.802+05:30 INFO 52175 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2024-06-02T08:04:24.808+05:30 INFO 52175 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2024-06-02T08:04:24.808+05:30 INFO 52175 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.19]
2024-06-02T08:04:24.833+05:30 INFO 52175 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2024-06-02T08:04:24.833+05:30 INFO 52175 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 413 ms
username: qaUsername password: qaPassword
2024-06-02T08:04:24.192+05:30 INFO 52175 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path ''
2024-06-02T08:04:24.198+05:30 INFO 52175 --- [main] c.c.l.SpringbootApplication : Started SpringbootApplication in 0.78 seconds (process running for 0.959)
```

We can pass the value to this configuration "spring.profiles.active" during application startup itself.

mvn spring-boot:run -Dspring-boot.run.profiles=prod

or

Add this in Pom.xml

```
<profiles>
  <profile>
    <id>local</id>
    <properties>
      <spring-boot.run.profiles>dev</spring-boot.run.profiles>
    </properties>
  </profile>
  <profile>
    <id>production</id>
    <properties>
      <spring-boot.run.profiles>prod</spring-boot.run.profiles>
    </properties>
  </profile>
  <profile>
    <id>stage</id>
    <properties>
      <spring-boot.run.profiles>qa</spring-boot.run.profiles>
    </properties>
  </profile>
</profiles>
```

mvn spring-boot:run -Pproduction

```
2024-06-02T08:21:57.336+05:30 INFO 53096 --- [main] c.c.l.SpringbootApplication : The following 1 profile is active: "prod"
2024-06-02T08:21:57.647+05:30 INFO 53096 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2024-06-02T08:21:57.652+05:30 INFO 53096 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2024-06-02T08:21:57.652+05:30 INFO 53096 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.19]
2024-06-02T08:21:57.673+05:30 INFO 53096 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2024-06-02T08:21:57.673+05:30 INFO 53096 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 318 ms
username: prodUsername password: prodPassword
2024-06-02T08:21:57.804+05:30 INFO 53096 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path ''
```

So, now we know, what's Profiling is. Lets see what is @Profile annotation.

Using @Profile annotation, we can tell spring boot, to create bean only when particular profile is set.

```
@Component
@Profile("prod")
public class MySqlConnection {

    @Value("${username}")
    String username;

    @Value("${password}")
    String password;

    @PostConstruct
    public void init(){
        System.out.println("MySql username: " + username + " password: " + password);
    }
}
```

```
application.properties

username=defaultUsername
password=defaultPassword
spring.profiles.active=qa
```

application-dev.properties	application-qa.properties	application-prod.properties
username=devUsername password=devPassword	username=qaUsername password=qaPassword	username=prodUsername password=prodPassword

```
@Component
@Profile("dev")
public class NoSqlConnection {

    @Value("${username}")
    String username;

    @Value("${password}")
    String password;

    @PostConstruct
    public void init(){
        System.out.println("NoSQL username: " + username + " password: " + password);
    }
}
```

mvn spring-boot:run

```
2024-06-02T00:38:46.935+05:30 INFO 55048 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2024-06-02T00:38:46.940+05:30 INFO 55048 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2024-06-02T00:38:46.941+05:30 INFO 55048 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.19]
2024-06-02T00:38:46.964+05:30 INFO 55048 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2024-06-02T00:38:46.964+05:30 INFO 55048 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 410 ms
2024-06-02T00:38:47.109+05:30 INFO 55048 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path ''
```

mvn spring-boot:run -Dspring-boot.run.profiles=prod

```
2024-06-02T00:42:30.245+05:30 INFO 55216 --- [main] e.c.l.SpringbootApplication : The following 1 profile is active: "prod"
2024-06-02T00:42:30.563+05:30 INFO 55216 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2024-06-02T00:42:30.568+05:30 INFO 55216 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2024-06-02T00:42:30.568+05:30 INFO 55216 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.19]
2024-06-02T00:42:30.591+05:30 INFO 55216 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2024-06-02T00:42:30.591+05:30 INFO 55216 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 327 ms
MySQL username: prodUsername password: prodPassword
2024-06-02T00:42:30.731+05:30 INFO 55216 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path ''
```

We can also set multiple profiles at a time.

```
@Component
@Profile("prod")
public class MySQLConnection {

    @Value("${username}")
    String username;

    @Value("${password}")
    String password;

    @PostConstruct
    public void init(){
        System.out.println("MySQL username: " + username + " password: " + password);
    }
}
```

```
@Component
@Profile("qa")
public class NoSQLConnection {

    @Value("${username}")
    String username;

    @Value("${password}")
    String password;

    @PostConstruct
    public void init(){
        System.out.println("NoSQL username: " + username + " password: " + password);
    }
}
```

application.properties

```
username=defaultUsername
password=defaultPassword
spring.profiles.active=prod,qa
```

application-dev.properties

```
username=devUsername
password=devPassword
```

application-qa.properties

```
username=qaUsername
password=qaPassword
```

application-prod.properties

```
username=prodUsername
password=prodPassword
```

```
2024-06-02T00:45:36.744+05:30 INFO 56836 --- [main] e.c.l.SpringbootApplication : The following 2 profiles are active: "prod", "qa"
2024-06-02T00:45:37.149+05:30 INFO 56836 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8080 (http)
2024-06-02T00:45:37.156+05:30 INFO 56836 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2024-06-02T00:45:37.156+05:30 INFO 56836 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.19]
2024-06-02T00:45:37.179+05:30 INFO 56836 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2024-06-02T00:45:37.179+05:30 INFO 56836 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 413 ms
MySQL username: qaUsername password: qaPassword
NoSQL username: qaUsername password: qaPassword
2024-06-02T00:45:37.327+05:30 INFO 56836 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path ''
```

Now lets come back to the previous question, which I asked:

You have 2 Application and 1 common code base, how you will make sure that, BEAN is only created for 1 Application, not for other?

Common Codebase

```
@Component
@Profile("app1")
public class NoSQLConnection {

    @Value("${username}")
    String username;

    @Value("${password}")
    String password;

    @PostConstruct
    public void init(){
        System.out.println("NoSQL username: " + username + " password: " + password);
    }
}
```

Application1
(application.properties)

```
spring.profiles.active=app1
```

Application2
(application.properties)

```
spring.profiles.active=app2
```