

OSSP (Operating Systems And Systems Programming) - 25CS2104E

Roll No. : 2520030029

Name: S.Pujith Pavan Kumar

SEC-8

SKILL-8:

Aim: To Detect Variable References, Expand Values, Handle Undefined Variables, Update Tokens, Support Nested Variables, Test Expansion Logic.

To Identify Built-ins, Create Dispatch Table, Execute In-Process Commands, Handle Invalid Commands, Maintain State, Test Dispatch Logic.

PROCEDURE :

1.Compilation & \$HOME + pwd output:

```
siddinapujith07@DESKTOP-FdHCAIT:~$ cd skill8
siddinapujith07@DESKTOP-FdHCAIT:~/skill8$ nano shell_features.c
siddinapujith07@DESKTOP-FdHCAIT:~/skill8$ gcc shell_features.c -o shell_features
l_features
siddinapujith07@DESKTOP-FdHCAIT:~/skill8$ ./shell_features
=== Variable Expansion ===
Enter a variable (example: $HOME): $HOME
HOME = /home/siddinapujith07

=== Built-in Command ===
Enter a command (pwd/cd/exit): pwd
Built-in command: pwd
/home/siddinapujith07/skill8
siddinapujith07@DESKTOP-FdHCAIT:~/skill8$ ./shell_features
=== Variable Expansion ===
Enter a variable (example: $HOME): $USER
USER = siddinapujith07

=== Built-in Command ===
Enter a command (pwd/cd/exit): cd
Built-in command: cd
cd command detected. State maintained.
```

2. Undefined variable + invalid command output :

```
siddinapujith07@DESKTOP-FdHCAIT:~/skill8$ ./shell_features
=== Variable Expansion ===
Enter a variable (example: $HOME): $ABC
ABC = Undefined variable
=== Built-in Command ===
Enter a command (pwd/cd/exit): hello
Invalid built-in command: hello
```

Code:

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

void expand_variable(char *input)
{
    char variable[100];

    if (input[0] == '$')
    {
        strcpy(variable, input + 1);

        char *value = getenv(variable);

        if (value != NULL)
            printf("%s = %s\n", variable, value);
        else
            printf("%s = Undefined variable\n", variable);
    }
}

void execute_builtin(char *command)
{
    if (strcmp(command, "pwd") == 0)
    {
        printf("Built-in command: pwd\n");
        system("pwd");
    }
    else if (strcmp(command, "cd") == 0)
    {
        printf("Built-in command: cd\n");
        printf("cd command detected. State maintained.\n");
    }
    else if (strcmp(command, "exit") == 0)
    {
        printf("Built-in command: exit\n");
    }
}
```

```

    else if (strcmp(command, "exit") == 0)
    {
        printf("Built-in command: exit\n");
    }
    else
    {
        printf("Invalid built-in command: %s\n", command);
    }
}

int main()
{
    char input[100];

    printf("=== Variable Expansion ===\n");

    printf("Enter a variable (example: $HOME): ");
    scanf("%s", input);

    expand_variable(input);

    printf("\n=== Built-in Command ===\n");

    printf("Enter a command (pwd/cd/exit): ");
    scanf("%s", input);

    execute_builtin(input);

    return 0;
}

```

Observation :

- 1)\$HOME was detected and its value was expanded successfully.
- 2)An undefined variable such as \$ABC was detected and displayed as **Undefined variable**.
- 3)The built-in command pwd was identified and executed successfully.
- 4)An invalid command such as hello was detected and an error message was displayed.
- 5)The shell state was maintained during command processing.

Result :

The program successfully performed **variable detection and expansion** and handled **built-in commands**. It correctly expanded defined variables, handled undefined variables, executed valid built-in commands, and rejected invalid commands.