



SPECIFICATION SHEET

SMPS based Battery Charger (Auto Float Boost)

MODEL

: 230V AC / 12V DC 6A



INPUT SPECIFICATIONS :

- * I/P Range : 180V - 270V AC
- * Fuse Protection
- * I/P MOV
- * Soft Start

OUTPUT SPECIFICATIONS :

- * Voltage : 12V DC ; Float - 13.5V ; Boost - 14.4V
- * Current : 6A(max) [2-6A adj.]
- * Line & Load Regulation : Less Than 0.5%
- * Ripple : 1%(p-p)
- * Noise : 1%
- * Reverse polarity protection by fuse.
- * Short circuit protection auto recovery type.
- * Over Voltage Protection Latching type.
- * Overload Protection auto recovery type.
- * Precise current limit with CVCC.
- * Operating temperature upto 50⁰ C.
- * I/O Isolation : 1.5 KV
- * Natural cooling.
- * Nett Weight : approx. 900 gms

INDICATIONS LED :

- 1) Input OK
- 2) Output OK
- 3) Output OVP
- 4) FLOAT
- 5) BOOST

DIMENSION : 165(W) X 105(D) X 60(H)mm.
Panel Mtg.box or Din rail Mtg.

MODEL

: 230V AC / 12V DC 10A.



INPUT SPECIFICATIONS :

- * I/P Range : 150V - 300V AC.
- * Fuse Protection.
- * I/P MOV.
- * Soft Start.

OUTPUT SPECIFICATIONS :

- * Voltage : 12V DC ; Float - 13.5V ; Boost - 14.4V
- * Current : 10A(max) [5-10A adj.]
- * Line & Load Regulation : Less Than 0.5%
- * Ripple : 1%(p-p)
- * Noise : 1%
- * Reverse polarity protection by Relay.
- * Alarm contact-Potential Free contact.
- * Short circuit protection auto recovery type.
- * Precise current limit with CVCC.
- * Operating temperature upto 50⁰ C.
- * I/O Isolation : 2 KV
- * Fan cooling.

INDICATIONS LED :

- 1) Input OK
- 2) Output ON
- 3) BATT. REVERSE
- 4) FLOAT
- 5) BOOST

DIMENSION : 180(W) X 125(D) X 90(H)mm.
Panel Mtg.box

MODEL

: 230V AC / 30V DC 15A.



INPUT SPECIFICATIONS :

- * I/P Range : 180 - 270V AC 50Hz
- * **MCB at input.**
- * I/P MOV.
- * Soft Start.

OUTPUT SPECIFICATIONS :

- * Voltage : 30V DC
in AUTO Mode: Float-33.75V, Boost-36V, Top
up - 39V
in MANUAL Mode : 30V - 40.5V (adj.)
- * Current : 15A (adj. 4-15A)
- * Line & Load Regulation : Less Than 0.5%
- * Ripple : 1% (p-p)
- * Noise : 1%
- * **MCB at output.**
- * Short circuit protection auto recovery type.
- * OVP Protection Latching type.
- * Battery Reverse Polarity protection by fuse.
- * Precise current limit with CVCC.
- * Operating temperature upto 50⁰ C.
- * I/O Isolation : 2 KV
- * Fan Cooled.
- * **Current & Voltage meters at Output.**
- * **Auto / Manual Mode** Selection Switch provided.
 - Voltage(only in manual mode) & current Adj. on front side.
 - Type of Battery to be specified by customer : Lead Acid or SMF.

INDICATIONS LED :

1) Boost, Eql, T/U, Float

DIMENSION : 260(W) X 155(D) X 220(H)mm. Panel/Wall
Mtg.Box.