



Rugged True Online UPS



INPUT SPECIFICATIONS

Input AC Voltage: 80-265 VAC, single phase

Frequency: 47-400 Hz

AC Input Circuit Breaker Rating: 40A

Input Power Factor: 0.99 typical

Efficiency with 2000W load: AC_{in} = 0.86 DC_{in} = 0.82

OUTPUT SPECIFICATIONS

Continuous Output Power: 2000VA/ 2000W

Peak Output Current: 44A (2000W AC Output)

100A (2000W 28VDC Output [No AC Output])

Note: 71.4A continuous)

AC Output Voltage: 230 VAC +/- 5%

AC Output Frequency: 50 Hz +/- 0.5% (Also available in 220VAC/60Hz)

AC Output Waveform: Sinusoidal

DC Output: 250W, 600W, 1000W or 2000W @ 12, 24, 28 or 48VDC

+/- 5%, 200mVPP, 20MHz bandwidth at full load

Total Harmonic Distortion: <1% with 2000W resistive load

ENVIRONMENTAL

Operating Temperature: -18° C to 50° C (without battery -30°C to 65 °C)

Storage Temperature: -32° C to 66° C (without battery -40°C to 70 °C)

Humidity: 10% to 95% (non condensing)

Altitude: 0 to 15,000 ft operating, 0 to 40,000 ft non-operating

Rain: operates in blown precipitation

BATTERY SPECIFICATIONS

Battery: two ea. 12V/ 33Ah

Type: Zero-maintenance VRLA

Typical Run Time: 8.5 minutes full load (30 min with XR units)

Recharge Time: 4 hours to 90%; temperature compensated float voltage

MECHANICAL

Chassis Size (H x W x D): 7" x 17" x 21"

Weight: 135 lbs. (85 lbs. w/o battery pack)

Connectors: (MIL-C-5015 type)

AC Input: CA02COME22-2PB

DC Input: CA02COME28A16PB

AC Output: CA02COME22-2SWB-F80

DC Output: CA02COME18-10SB