

TECHNICAL SPECIFICATIONS
1 KVA - 10 KVA / 7.5 KVA - 30 KVA / 15 KVA - 150 KVA
OF TRUE ONLINE UPS SYSTEMS

Standard Rating			
	1 KVA - 10 KVA	7.5 KVA - 30 KVA	15 KVA - 150 KVA
INPUT			
Voltage	230 V AC - 1 Ph	415 V AC - 3 PH 4 Wire	415 V AC - 3 Ph 4 Wire
Opening Range	170 V - 265 V	345 V - 475 V	345 V - 475 V
Frequency	50 Hz		
Frequency Range	47 - 53 Hz		
Power Factor	> 0.8		> 0.92
OUTPUT			
Rating	1/2/3/5/7.5/10 KVA	10/15/20/25/30 KVA	15/20/25/30/40/45/50/60
			75/80/100/120/150 KVA
Voltage	220 / 230 V AC		400 / 415 V AC
Voltage Regulation	± 1%		
Power Factor	0.8 lag to unity		
Crest Factor	3 : 1		
Frequency	50 / 60 Hz		
Frequency Regulation	± 0.1%		
Wave form	True Sine wave		
Harmonic Distortion	THD < 3%		
Overload Rating	150% for 30 seconds		
Transient Response	± 5% for full load change		
Response Time	Recovery to ± 2% within 5 msec		
DC Link			
Nominal DC Voltage	2,3 KVA :48-144V	10,15KVA : 240 / 360 V	15 KVA : 240 / 360 V
	5 KVA : 120/144/180V	20 KVA : 300 / 360V	20 KVA :300 / 360V
	7.5,10KVA : 180 / 240V	25,30 KVA : 360V	25 KVA & above : 360V
DC Bus Volts Ripple	< 2%		
Battery Type	VRLA Sealed Maintenance Free (SMF) / Lead Acid Tubular (Rooded type) / Ni-Cd		
Isolation	DC Circuit Breaker		
EFFICIENCY (Typical)			
Inverter Efficiency	> 95%		
Overload Efficiency	> 92%		
PROTECTIONS			
Rectifier	I/P AC Over voltage / Under voltage		
	DC Over voltage & DC Low		
	Battery Charging Over current		
		I/P Single Phasing	
		I/P Phase Reversal	
Inverter	O/P Over voltage / Under voltage		
	O/P Overload		
	O/P Short circuit		
	O/P Under voltage		
	Over Temperature		

GI ENERGY SOLUTIONS PRIVATE LIMITED

204,B.K.Apartment
247, Deccan College Road
Yerwada, PUNE - 411 006. INDIA
Telefax: 020 26683974
Mobile : +91 9372741876
Email : info@g1energysolutions.com

Standard Rating			
	1 KVA - 10 KVA	7.5 KVA - 30 KVA	15 KVA -150 KVA
AUDIO ALARM			
	Rectifier Trip		
	Overload		
	Mains Fail		
	Battery Low with Pre-alarm		
	System Trip		
METERING	Multifunction LCD Display to read following parameters with user friendly Mimic Diagram		
	I/P Voltage & Current		1 Ph Parameters upto 30 KVA
	I/P Frequency		
	Battery Voltage		
	Battery charging / discharging current		
	OP Voltage		
	OP Current		
	OP Frequency		
PHYSICAL			
Dimensions	260(w)x545(d)x600(h)mm	325(w)x650(d)x650(h)mm	400(w)x900(d)x850(h)mm
	(1 - 5 KVA)	(7.5 - 15 KVA)	15 KVA
	325(w)x550(d)x650(h)mm	400(w)x800(d)x850(h)mm	400(w)x900(d)x950(h)mm
	(6 -10 KVA)	(20 - 30 KVA)	(20 - 40 KVA)
			800(w)x800(d)x1800(h)mm
			(50 - 100 KVA) - A
			A+1000(w)x800(d)x1800(h)mm
			(120 - 150 KVA)
Enclosure	IP 21		
Cable Entry	Bottom / As per requirement		
Colour	Siemens gray / Sea Blue		
ENVIRONMENT			
Operating Temperature	0 to 45 ⁰		
Storage	- 10 to 70 ⁰		
Humidity	up to 95% RH (non - condensing)		
Cooling	Forced Air Cooling		
Noise	< 55 db	< 60 db	< 65 db
Altitude	< 3000 mtr.above mean sea level.		
OPTIONAL FEATURES			
Enclosure	IP 42 / Industrial Grade		
Cable Entry	Top		
Input Power Factor	0.99		
Operating Temperature	50 ⁰ C		
Auto Changeover to Bypass supply (Static Bypass)			
Remote Indicating Panel			
Computer Interface			
Data Logger and Self Diagnostics Feature			
SNMP			
Output Frequency	UP to 400 Hz		
Auto / Manual Battery Test / Discharge Facility			
Parallel Load Sharing / N + 1 Conifiguration is available			
Individual Battery Monitoring system			
19"Rack mounting type Models available			
IEC Conformance on request			
ECO mode with 98% Efficiency			
Custom Built / Mil - Grade System			