



Frequent fluctuations or variations of power not only causes financial but manpower loss too! SERVO CONTROLLED VOLTAGE STABILIZERS beat these happenings and provides all extra care needed to your valuable equipments.

Single Phase

SPECIFICATION :

- Rating : As Specified
- Input Voltage Range : As Specified (Eg. 170V-270 V)
- Input Supply Frequency : 45Hz-55Hz
- Output Voltage: As specified (Eg. 230V/240V + 1%)
- Voltage Regulation : + 1%
- Rate of Correction: Usually 25V/ SEC/Phase but depends on rating
- Efficiency: Better than 97 %
- Waveform Distortion : Nil
- Effect of Load Power Factor : Nil
- Ambient Temperature: 0-50°C Max.
- Type : 1 Phase



FEATURES :



- Output voltage sensing for voltage correction & for U/V & O/V trip
- Overvoltage & undervoltage trip by means of contractor / relay's
- Voltmeter with selector switch to see input & output voltages
- Short circuit & overload protection by means of MCB/ FUSE MCCB
- Adjustment : Output voltages adjustment of + 5V/ Phase will be provided by means of potentiometer on front plate.
- Controls: Auto/Manual in case of auto mode failure you can set output voltage through manual mode.

FEATURES :

- By pass facilities
- RFI Filter & Spike suppressor
- Generator compatible circuit
- Time delay circuit : output power on with specified time delay
- Isolation transformer / Ultra isolation transformer at output
- Ammeter: To see load current's
- Digital voltmeter & digital ammeter



1Ø SCVS (Both Air Cooled & Oil Cooled) Models Available

From 500VA 1 Ø to 50 kVA 1Ø

APPROXIMATE DIMENSIONS OF 1Ø STABILIZERS

	CAPACITY	WIDTH (MM)	DEPTH (MM)	HIGHT (MM)
1	2 kVA	200	300	200
2	3 kVA	200	300	310
3	5 kVA	250	450	350
4	7.5 kVA	500	425	425
5	10 kVA	550	425	425
6	15 kVA	650	525	475
7	20 kVA	550	425	650
8	25 kVA	750	550	550
9	30 kVA	750	550	550
10	40 kVA	800	600	600
11	50 kVA	750	600	800

INDICATIONS MAINS ON OUTPUT ON OVER VOLTAGE UNDER VOLTAGE TRIP OVER LOAD SINGLE PHASING.

ALL THE DIMENSIONS ARE GIVEN FOR AIR COOLED, WITH I/P RANGE OF 170V TO 270V

Three Phase

SPECIFICATION :

- Rating : As Specified
- Input Voltage Range : As Specified (Eg. 300V To 470 V; 4Wire, 50Hz, Unbalance)
- Input Supply Frequency : 45Hz To 55Hz
- Output Voltage: As specified (Eg. 400V/415V + 1%, 4 Wire, 50 Hz, Balance)
- Voltage Regulation : + 1%
- Rate of Correction: Usually 25V/ SEC/Phase but depends on rating
- Efficiency: Better than 97 %
- Waveform Distortion : Nil
- Effect of Load Power Factor : Nil
- Ambient Temperature : 0-50°C Max.
- Type : 3 Phase



FEATURES :



- Output voltage sensing for voltage correction & for U/V & O/V trip
- Overvoltage & undervoltage trip by means of contractor / relay's
- Voltmeter with selector switch to see input & output voltages
- Short circuit & overload protection by means of MCB/ MCCB / SFU
- Adjustment : Output voltages adjustment of + 5V Per Phase will be provided by means of potentiometer on front plate.
- Controls: Auto/Manual in case of auto mode failure you can set output voltage through manual mode.
- Built in single phase preventer.

OPTIONAL FEATURES :

- By pass facilities
- RFI Filter & Spike suppressor
- Generator compatible circuit
- Time delay circuit : output power on with specified time delay
- Isolation transformer / Ultra isolation transformer at output
- Ammeter: To see load current's
- Digital voltmeter & digital ammeter



3 Ø SCVS (Both Air Cooled & Oil Cooled)

Models Available From 3kVA 3 Ø To 1000 kVA 3 Ø

APPROXIMATE DIMENSIONS OF 3 Ø STABILIZERS

	CAPACITY	WIDTH (MM)	DEPTH (MM)	HIGHT (MM)
1	5 kVA	650	350	350
2	10 kVA	550	400	650
3	15 kVA	650	400	675
4	20 kVA	750	425	750
5	25 kVA	750	425	750
6	30 kVA	850	450	850
7	50 kVA	1200	550	1200
8	75 kVA	1350	675	1400
9	100 kVA	1350	675	1500
10	150 kVA	1500	720	1800
11	200 kVA	1500	720	1800
12	250 kVA	1600	800	2000
13	300 kVA	1600	800	2000
14	400 kVA	1800	900	2000
15	500 kVA	1800	900	2000

INDICATIONS MAINS ON OUTPUT ON OVER VOLTAGE UNDER VOLTAGE TRIP OVER LOAD SINGLE PHASING.

ALL THE DIMENSIONS ARE GIVEN FOR AIR COOLED, WITH I/P RANGE OF 170V TO 270V

APPLICATION:

- COMPUTER SYSTEMS
- COMMUNICATION EQUIPMENT
- ELECTRO MEDICAL AND
- LABORATORY INSTRUMENTS
- CNC MACHINES
- AIR CONDITIONING SYSTEMS
- PAPER COPIES AND OFFICE
- AUTOMATION PRODUCTS
- RADARS AND OTHER EQUIPMENTS
- LIFTS AND ELEVATORS
- CATHLAB
- MOTORS AND COMPRESSORS
- OPERATION THEATERS
- TEXTILE MACHINES
- PACKAGING MACHINES
- GARMENT INDUSTRIES
- BANKING TERMINALS

- CHEMICAL AND R&D LABORATORIES
- DEFENCE AND NUCLEAR FACILITIES
- MACHINES TOOLS AND ROBOTICS

WE ARE SPECIALIST IN:

1. SCVS Available for any input range and any output voltage in air cooled version up to 2000 kVA.
 2. Also available the SCVS for 3 Ø /3 wire in & 3 Ø 4 wire out (this helps to adopt SCVS at locations where good neutral not available or neutral related problems in systems).
 3. Also models available with three phase / 3 wire input and single phase output (isolated or unisolated both).
- Out door application models available in air cooled / oil cooled version (IP 43/ IP 54 construction)