

*Delivers centimeter level accuracy within seconds based on U-blox triple-band L1/L2/L5 **ZED-F20P** GNSS RTK module.
Onboard **RM3100** magnetometer.*

[Datasheet - In Production](#)



Features

- 5V - 150mA power supply
- LEDs status: PPS/Power/RTK
- Timepulse & External Interrupt
- USB-C/I²C/UART digital interfaces
- Onboard PNI RM3100 compass
- Onboard L1/L2/L5 active antenna

Applications

- Drones
- RTK Base
- Ground vehicles
- Precise navigation

Description

The Siderion **Sirius F20P** is an affordable, compact, and high-precision triple-band L1/L2/L5 GNSS RTK (Real-Time Kinematic) device with an onboard GNSS active antenna.

Powered by the latest generation of u-blox **ZED-F20P** modules, the Sirius F20P supports concurrent reception of GPS, Galileo, BeiDou, QZSS, and NavIC signals. Consequently, the device delivers reliable performance and fast convergence, achieving centimeter-level accuracy in seconds.

The Sirius F20P embeds an active L1/L2/L5 GNSS antenna and a professional grade RM3100 magnetometer.

Its JST-GH connectors make it ideal for integration with Pixhawk or other autopilot systems.

The Sirius F20P operates across a temperature range from -40°C to +70°C.

Table 1. Device summary

Order ref code	Temperature [°C]	Product size [mm]	Weight [g]
SID-GNSS-RTK-SIRIUS_F20P	-40 to +70	74.0 x 74.0 x 22.0	100


Contents

1. Block diagram and pin description	3
1.1 Block diagram	3
1.2 LED description	3
1.3 Pin description	4
2. Absolute maximum ratings	5
3. Specifications	6
3.1 Ublox ZED-F20P specifications	6
3.2 PNI RM3100 specifications	8
3.3 Embedded L1/L2/L5 GNSS antenna specifications	10
4. Applications	11
5. Communication interfaces	12
5.1 UART Interface	12
5.2 Slave I2C interface	13
5.3 USB interface	13
6. Mechanical drawings	14
7. Revision history	15
8. Appendix	15

1. Block diagram and pin description

1.1 Block diagram

Figure 1. Sirius F20P block diagram & connectivity (top view)



1.2 LED description

Table 2. Sirius F20P LED sequence status

LED name	Color	Light sequence	Comment
Timepulse	Green		Blinking LED at the defined PPS rate
Power	Blue		Solid blue LED when powered ON
RTK Status	Green		3D fix mode / No RTK fix
			RTK fix but no FIXED RTK fix
			FIXED RTK fix

1.3 Pin description

Figure 3. Sirius F20P pinout (top view)




Table 3. Pinout configuration

	Pin	Name	Type	Function
GPS	A1	GND	P	Ground reference
	A2	I2C SDA	I/O	I2C data
	A3	I2C SCL	I	I2C clock
	A4	UART1 TX	O	UART1 transmit
	A5	UART1 RX	I	UART1 receive
	A6	5V IN	P	5V input
UART	B1	5V IN	P	5V input
	B2	UART2 TX	O	UART2 transmit NMEA/RTCM data
	B3	UART2 RX	I	UART2 receive NMEA/RTCM data
	B4	EXTINT	O	External interrupt
	B5	TIMEPULSE	O	PPS output
	B6	GND	P	Ground reference

P : Power / I : Input / O : Output

2. Absolute maximum ratings

Stresses above those listed as “absolute maximum ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device under these conditions is not implied. Exposure to maximum rating conditions for extended periods may affect device reliability.

Table 4. Sirius F20P absolute maximum ratings

Symbol	Parameter	Maximum value	Units
Vusb	USB supply voltage	-0.3 to +6	V
Vdd	Internal supply voltage	-0.5 to +3.6	V
Vdd_IO	I/O pins supply voltage	-0.5 to Vdd+0.1	V
Icc_RF	RF output current	300	mA
Prfin	Input power at RF_IN	10	dBm
W	Product weight	100	g
TOP	Operating temperature	-40 to +70	°C
TSTG	Storage temperature	-40 to +80	°C



This device is sensitive to electrostatic discharge (ESD), improper handling can cause permanent damage to the part.

3. Specifications

3.1 Ublox ZED-F20P specifications

Table 5. ZED-F20P mechanical and electrical specifications

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Units
Vusb	USB supply voltage		4.5	5.0	5.5	V
Vdd	Internal supply voltage			3.3		V
Vdd_IO	Supply voltage for I/O			3.3		V
Idd	Current consumption	w/o active antenna		50		mA
		w/ active antenna		130		mA
Vdd_RF	Output RF voltage			Vdd-0.1		V
Idd_RF	Output RF current			50		mA
Vil	IO pin low lvl input volt		0		0.8	V
Vih	IO pin high level input voltage		2		Vdd +0.3	V
Vol	IO pin low level output voltage	Iol = 1mA			0.4	V
Voh	IO pin high level output voltage	Ioh = 1mA	Vdd-0.4			V
Top	Operating temperature		-40		+70	°C
I2Cadd	Default 7bit I ² C address	0b1000010 (0x42)				

Table 6. ZED-F20P general performance

Parameter	Specifications	Value
Receiver type	Multi-band GNSS high precision	
Accuracy of Timepulse	RMS	30 ns
Frequency of Timepulse		0.25 Hz to 10 MHz
Operational limits	Dynamics Altitude Velocity	< 4g 80,000 m 500 m/s
Velocity accuracy		0.03 m/s

Table 7. ZED-F20P performance in different GNSS mode

GNSS	Parameter	GPS+GAL+BDS	GPS+BDS	GPS+GAL	GPS
Acquisition	Cold start Hot start Aided start	25 s 2 s 2 s	-	-	-
Update rate	RTK PVT RAW	25 Hz 25 Hz 25 Hz	-	-	-
Convergence time	RTK	< 7 s	-	-	-
Horizontal pos. accuracy	PVT RTK	1.2 m CEP 0.006 m + 1ppm CEP	-	-	-
Vertical pos. accuracy	RTK	0.01 m + 1ppm CEP	-	-	-
Sensitivity	Tracking & Nav. Reacquisition Cold start Hot start	-167 dBm -160 dBm -148 dBm -158 dBm	-	-	-

Table 8. ZED-F20P supported GNSS constellations and signals

System	Signal	Frequency
GPS	L1C/A L2C L5	1575.420 MHz 1227.600 MHz 1176.450 MHz
Galileo	E1-B/C E5a	1575.420 MHz 1176.450 MHz
BeiDou	B1I B1C B2a	1561.098 MHz 1575.420 MHz 1176.450 MHz
QZSS	L1C/A, L1C/B L2C L5	1575.420 MHz 1227.600 MHz 1176.450 MHz
NavIC	L1-SPS Data L5-SPS	1575.420 MHz 1176.450 MHz

3.2 PNI RM3100 specifications

Table 9. RM3100 electrical specifications

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Units
Vdd	Internal supply voltage		2.0	3.0	3.6	V
Vdd_IO	Supply voltage for I/O		2.0	3.0	3.6	V
Vdd_Ripple	Vdd ripple voltage				0.05	Vpp
Idd	Current consumption				1	mA
Vil	IO pin low level input voltage		0		0.3* Vdd	V
Vih	IO pin high level input voltage		0.7* Vdd		Vdd	V
Iidle	Idle Mode Current				1	μA
Ileak	Leakage Current @ DVDD pin (AVDD=AVSS=DVSS=0V, DVDD=3.6V)				100	nA
Top	Operating temperature		-20		+85	°C
I2Cadd	7bit I2C address	0b0100000				

Table 10. RM3100 Geomagnetic Sensor Performance

Parameter	Cycle counts			Units
	50	100	200	
Field Measurement Range	-800 to +800			μT
Gain	20	38	75	LSB/ μT
Sensitivity	50	26	13	nT
Noise	30	20	15	nT
Noise Density @ Max. Single-Axis Sample Rate	1.2			nT/ $\sqrt{\text{Hz}}$
Repeatability over $\pm 200 \mu\text{T}$	15	8	8	nT
Hysteresis over $\pm 200 \mu\text{T}$	15			nT
Linearity over $\pm 200 \mu\text{T}$	0.5			%
Maximum Single-Axis Sample Rate (divide by 3 for max. 3-axis sample rate)	1600	850	440	Hz
Single-Axis Average Current @ 24 Hz Sample Rate (equivalent to 3-axis @ 8 Hz)	70	135	260	μA
Bias Resistor, R_b	121			Ω
Ext. Timing Resistor for Clock, R_{EXT}	33			K Ω
Circuit Oscillation Frequency	180			kHz

3.3 Embedded L1/L2/L5 GNSS antenna specifications

Table 11. Internal multi-band antenna mechanical and electrical specifications

Symbol	Parameter	Value
ANTENNA		
Arch	Antenna architecture	Quadrifilar helix
Gband	GNSS signal bands	GPS: L1/L2/L5 GLONASS: G1/G2/G3 BDS: B1/B2 Galileo: E1/E2/E5
Gpp	Peak gain	≥ 2.0 dBi
Pol	Polarization	RHCP
VSWR	V.S.W.R.	≤ 2.0
Acov	Azimuth coverage	360°
Z	Impedance	50 Ω
LNA		
Glna	LNA gain	28 $\pm$ 2.0dB (Typ. @25°C)
Idd	Operating current	≤ 50 mA
Nfig	Nois Figure	<1.5dB
Pbf	Pass band fluctuation	± 1.5 dB
MECHANICAL & ENVIRONMENTAL		
IP	IP rating	IP66
Top	Operating temperature	-40°C to +85°C
Size	Antenna dimensions	60.0 x 60.0 x 20mm

4. Applications

5. Communication interfaces

There are several communication interfaces, including UART, I2C, and USB. All inputs have internal pull-up resistors in normal operation and can be left open if not in use. All the PIOs are supplied by VCC, therefore all the voltage levels of the PIO pins are related to Vdd supply voltage.

5.1 UART Interface

There are two UART interfaces: UART1 and UART2. UART1 and UART2 operate up to and including a speed of 8 Mbaud. No hardware flow control on UART1 and UART2 is supported. UART1 is enabled by default if D_SEL is not tied to ground.

Figure 3. UART chronogram specifications




Table 12. ZED-F20P serial UART timing specifications

Symbol	Parameter	Min.	Max.	Units
V_{IL}	LOW-LEVEL input voltage	0	$0.2 \times V_{DD}$	V
V_{IH}	HIGH-LEVEL input voltage	$0.7 \times V_{DD}$	$V_{DD} + 0.3$	V
t_{ECH}	HIGH period of external data input	0	0.4	μs
t_{ECL}	LOW period of external data input	TBA	TBA	μs
R_u	Baudrate	4800	8	Mbps
t_{CR}	Rise time of data		5	ns
t_{CF}	Fall time of data		5	ns

5.2 Slave I2C interface

An I2C compliant interface is available for communication with an external host CPU. The interface can be operated in slave mode only. It is fully compatible with Fast-Mode-Plus of the I2C industry standard. Since the maximum SCL clock frequency is 1 MHz (in Fast-Mode-Plus), the maximum bit rate is 1 Mbit/s. The interface stretches the clock when slowed down while serving interrupts, therefore the real bit rates may be slightly lower.

Figure 4. I2C chronogram specifications




Table 13. Sirius F20P I2C timing specifications

Symbol	Parameter	Min	Max	Units
Vil	LOW-LEVEL input voltage	Vss-0.3	0.3xVdd	V
Vih	HIGH-LEVEL input voltage	0.7xVdd	Vdd+0.3	V
Cb	Capacitive load for each bus line	400 (standard & fast modes)	550 (fast mode plus)	pF
Fscl	SCL clock frequency	0	1	MHz

5.3 USB interface

A USB type C interface, which is compatible with USB version 2.0 FS (Full Speed, 12 Mbit/s), can be used for communication as an alternative to the UART.

6. Mechanical drawings

Figure 5. Sirius F20P v2.1 mechanical drawings

7. Revision history

Table 14. Document revision history

Date	Revision	Changes
01-Sep-2025	1.0	SiderionDoc_SiriusF20P / Initial release

8. Appendix

U-blox ZED-F20P datasheet: [ZED-F20P-00B Data sheet](#)

U-blox ZED-F20P integration manual: [ZED-F20P Integration manual](#)

U-blox ZED-F20P interface description: [u-blox F20 HPG 2.02 Interface description](#)

Siderion user's guide:

Siderion tutorials:

IMPORTANT NOTICE – PLEASE READ CAREFULLY

Siderion reserves the right to make changes, corrections, enhancements, modifications, and improvements to Siderion products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on Siderion products before placing orders. Siderion products are sold pursuant to Siderion's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of Siderion products and Siderion assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by Siderion herein.

Resale of Siderion products with provisions different from the information set forth herein shall void any warranty granted by Siderion for such product.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

2026 Siderion – All rights reserved

