



---

## PRACTICAL - 2

### Implementation and Time Analysis of Linear and Binary Search

#### Aim of the Practical:

To implement Linear Search and Binary Search in C++ and derive their time and space complexities.

#### 2.1 Linear Search

##### Program:

```
#include <iostream>
using namespace std;
int linearSearch(int a[], int n, int key) {
    for (int i = 0; i < n; i++)
        if (a[i] == key) return i;
    return -1;
}
int main() {
    int a[] = {10, 25, 7, 40, 15, 30};
    int n = sizeof(a) / sizeof(a[0]);
    int key = 40;
    cout << linearSearch(a, n, key);
}
```

##### Output:

3

##### Time Analysis:

##### Derivation of Time Complexity:

Let  $n$  be the number of elements.

Best case: the key is the first element, so only one comparison is required.

$$T_{\text{best}}(n) = c = \Theta(1)$$

Worst case: the key is the last element or absent, so  $n$  comparisons are performed.

$$T_{\text{worst}}(n) = c_1 \cdot n + c_2 = \Theta(n)$$

Average case: assuming the key is equally likely to be at any position, expected comparisons are:

$$C_{\text{avg}}(n) = (1 + 2 + \dots + n) / n$$

$$C_{\text{avg}}(n) = [n(n + 1)/2] / n = (n + 1)/2$$

$$T_{\text{avg}}(n) = \Theta(n)$$

##### Final Time Analysis:

- Best Case:  $\Theta(1)$ .
- Average Case:  $\Theta(n)$ .
- Worst Case:  $\Theta(n)$ .
- Auxiliary Space:  $\Theta(1)$ .

##### Result:

Linear Search was implemented successfully and its comparison count was derived for best, average and worst cases.

#### 2.2 Binary Search

##### Program:

```
#include <iostream>
using namespace std;
int binarySearch(int a[], int n, int key) {
    int low = 0, high = n - 1;
    while (low <= high) {
```



```
int mid = low + (high - low) / 2;
if (a[mid] == key) return mid;
if (a[mid] < key) low = mid + 1;
else high = mid - 1;
}
return -1;
}
int main() {
    int a[] = {5, 10, 15, 20, 25, 30, 35, 40};
    int n = sizeof(a) / sizeof(a[0]);
    cout << binarySearch(a, n, 30);
}
```

**Output:**

5

**Time Analysis:**

**Derivation using Recurrence / Master Method:**

At every step Binary Search discards half of the remaining elements.

$$T(n) = T(n/2) + c$$

Compare with  $T(n) = aT(n/b) + f(n)$ :

$$a = 1, \quad b = 2, \quad f(n) = \Theta(1)$$

$$n^{(\log_b a)} = n^{(\log_2 1)} = n^0 = 1$$

$$f(n) = \Theta(1) = \Theta(n^{(\log_b a)})$$

Therefore Master Theorem Case 2 applies:

$$T(n) = \Theta(\log n)$$

Equivalently, after  $k$  halvings  $n/2^k = 1$ , so  $k = \log_2 n$ .

**Final Time Analysis:**

- Best Case:  $\Theta(1)$ .
- Average Case:  $\Theta(\log n)$ .
- Worst Case:  $\Theta(\log n)$ .
- Auxiliary Space (iterative):  $\Theta(1)$ .

**Result:**

Binary Search was implemented successfully, and its logarithmic complexity follows directly from repeated halving.