

REST-GET COUNTRY BASED ON COUNTRY CODE

The screenshot shows an IDE with the following components:

- EXPLORER:** Displays the project structure for 'spring-country-code-api'. The 'src' directory contains 'main' (with 'com/cognizant/springcountrycodeapi') and 'test' (with 'com/cognizant/springcountrycodeapi').
- Editor:** Shows the file 'CountryService.java' with the following code:

```
1 package com.cognizant.springcountrycodeapi;  
2  
3 import static org.junit.jupiter.api.Assertions.assertNotNull;  
4 import static org.springframework.test.web.servlet.request.MockMvcRequestBuilders.get;  
5 import static org.springframework.test.web.servlet.result.MockMvcResultMatchers.jsonPath;  
6 import static org.springframework.test.web.servlet.result.MockMvcResultMatchers.status;  
7  
8 import org.junit.jupiter.api.Test;  
9 import org.springframework.beans.factory.annotation.Autowired;  
10 import org.springframework.boot.test.autoconfigure.web.servlet.AutoConfigureMockMvc;  
11 import org.springframework.boot.test.context.SpringBootTest;  
12 import org.springframework.test.web.servlet.MockMvc;  
13 import org.springframework.test.web.servlet.ResultActions;  
14  
15 import com.cognizant.springcountrycodeapi.controller.CountryController;  
16  
17 @SpringBootTest  
18 @AutoConfigureMockMvc
```
- OUTPUT:** Displays the execution output of the application. It shows the Spring Boot logo and the following log messages:

```
19:12:49.564 [Thread-0] DEBUG org.springframework.boot.devtools.restart.classloader.RestartClassLoader - Created RestartClassLoader org.springframework.boot.devtools.re  
start.classloader.RestartClassLoader@30e42b8e  
19:12:49.568 [restartedMain] INFO com.cognizant.springcountrycodeapi.SpringCountryCodeApiApplication - START - SpringCountryCodeApiApplication.main()  
  
260704|19:12:49.913|restartedMain | INFO|CountryCodeApiApplication| logStarting|Starting SpringCountryCodeApiApplication using Java 17.0.19 on Siddzz  
with PID 29796 (C:\Users\HP\OneDrive\Desktop\spring-country-code-api\target\classes started by HP in C:\Users\HP\OneDrive\Desktop\spring-country-code-api)  
260704|19:12:49.915|restartedMain | DEBUG|CountryCodeApiApplication| logStarting|Running with Spring Boot v2.7.0, Spring v5.3.20  
260704|19:12:49.915|restartedMain | INFO|CountryCodeApiApplication| logStartupProfileInfo|No active profile set, falling back to 1 default profile: "default"  
260704|19:12:49.962|restartedMain | INFO|ertyDefaultsPostProcessor| log|Devtools property defaults active| Set 'spring.devtools.add-property  
s' to 'false' to disable  
260704|19:12:49.962|restartedMain | INFO|ertyDefaultsPostProcessor| log|For additional web related logging consider setting the 'logging.level
```