

THE CYBERSECURITY PENETRATION LOG: OPERATIONS ARCHIVE

Security Analyst: Abdoulaye Sidibe | **Specialization:** Defensive Auditing

A unified operational log capturing hands-on training, network footprinting, and interface remediation across Linux and automated security environments.

SECURITY AUDITING ARCHIVE

Target ID	Audit Method	CLI vs. GUI Penetration & Footprinting Methodology
SEC-001	Network Layer Triage (Linux DHCP Warmup)	Remediation: Simulated a network interface link failure on a Linux system. Used administrative tools to force-release the interface configuration lease via dhclient -r, cleared the network footprint, and successfully re-initialized the discovery protocol mapping via dhclient eth0 to restore routing connectivity.
SEC-002	Local Footprinting (Nmap Recon)	CLI Path: Executed local loopback host reconnaissance natively inside Kali Linux via nmap -sV 127.0.0.1 to analyze running daemon version controls and verify network service hardening boundaries. GUI Path: Deployed the graphical Zenmap software interface window, inputting the target node parameter directly into the Target bar and selecting an Intense Scan execution profile loop.

COMMAND INFRASTRUCTURE DEPLOYED:

[DHCP Blackout Clear]
dhclient -r && dhclient eth0

[CLI Target Recon]
nmap -sV 127.0.0.1

[GUI Navigation Path]
Launch Zenmap Application -> Input '127.0.0.1' into Target Field -> Set Profile to 'Intense Scan' -> Click Scan Button