Hearing the Rotor: Action-Conditioned Joint-Embedding World Models for Label-Efficient, Nuisance-Robust Turbomachinery Forecasting and Control

Siddharth Sharma†

***Abstract*—A previous audit of joint-embedding predictive architectures (JEPA) for rotor dynamics returned a negative result. We show that it was mostly structural. Speed was observed directly, the latent prediction never reached the forecast, and constant commands made control authority unidentifiable. We rebuild the benchmark around the problem JEPA is designed for. A rotor driven by Euler turbomachinery work, with a lagged and delayed actuator and six hidden per-episode parameters, is observed only through a synthetic casing-microphone spectrogram containing distractor tones, impulsive bursts and gain drift. A two-stage, action-conditioned JEPA learns from 3000 unlabelled episodes. Masked time–frequency latent prediction first pre-trains the encoder; a frozen-target, action-conditioned predictor then learns the dynamics in latent space. Against a reconstruction world model, supervised learning with 10–3000 labelled episodes, and a classical pipeline given the true equation of motion, under matched budgets, the JEPA world model has three advantages. With ten labelled episodes, a frozen JEPA latent forecasts rotor speed 3.1× better than supervised training from scratch. Under heavy acoustic nuisance its forecast error grows by about a quarter, while the classical pipeline's more than triples. Planning in its latent space tracks set-points close to an oracle controller: with 300 labels, pre-training reduces the excess closed-loop error 2.9× at the training nuisance level and 7.8× under heavy nuisance. The classical pipeline remains the most accurate in distribution, and the latent recovers state far better than it identifies the hidden machine parameters. We report the failure modes met along the way, including an action-shortcut collapse, and a set of second-round improvements.**

***Index Terms*—Joint-embedding predictive architecture, world models, self-supervised learning, turbomachinery, model predictive control, system identification, acoustic sensing.**

I. Introduction

GAS-turbine and turbomachinery transients are usually modelled with physics: the Euler work equation turns blade swirl into torque, and an angular-momentum balance closes the rotor speed [1]. Physics models extrapolate well when their structure and parameters are right. They are brittle when the parameters drift, when the sensors are poor, or when the quantity of interest is not measured at all. Learned models are the opposite: they are flexible, but they need labels and fail silently out of distribution [2].

†Corresponding author: sid.sharma@ubc.ca. This study was carried out with an AI coding agent (Claude Code, model claude-opus-5-5) under the author's direction. All data are synthetic; no result validates an engine, sensor or controller. Code, data generators, logs and every plotted number are in the project repository.

Joint-embedding predictive architectures (JEPA) [3]–[5] learn by predicting the *representation* of missing or future observations rather than the observations themselves. The bet is that representation-space prediction can ignore unpredictable nuisance and keep the structure that matters. V-JEPA 2-AC [6] extended the idea to action-conditioned world models that plan in latent space. That combination—label-free learning, robustness to nuisance, and planning—is exactly what a test cell with plentiful unlabelled sensor logs and few instrumented runs would want.

An earlier audit of a small JEPA rotor model (v1 of this project) found no advantage. Re-reading that implementation shows why the result was structural rather than informative:

1) speed was observed directly and noise-free, leaving nothing for representation learning to do;
2) the latent prediction entered only as a 0.05-weighted auxiliary loss, while a separate head produced the forecast, so the JEPA objective could not improve it;
3) the command was constant within each sequence, so control authority was unidentifiable and every learned model was control-insensitive;
4) the full-trajectory protocol paired initial speeds near $400\,\mathrm{rad\,s^{-1}}$ with an equilibrium near $21\,\mathrm{rad\,s^{-1}}$, so every sequence was a spin-down.

This paper keeps the physics and the honesty of that audit, but asks the question JEPA is built for. Our contributions are:

- a partially observed, action-driven rotor benchmark with hidden per-episode parameters and a declared acoustic observation model (Sec. III);
- a two-stage action-conditioned JEPA world model for this setting, and controls that differ from it only in the training objective (Sec. IV);
- an evaluation of state estimation, forecasting, robustness, label efficiency, control authority, parameter recovery and closed-loop control against a structure-aware classical pipeline (Sec. V);
- a record of the failure modes met during development and of second-round improvements, including a JEPA-perception/physics-dynamics hybrid (Secs. VI–VII).

II. Related work

Joint-embedding prediction. I-JEPA predicts masked image-patch representations from an EMA target encoder [4]; V-JEPA does the same in video [5], and A-JEPA on audio

spectrograms [7]. Collapse is avoided through predictor asymmetry and EMA targets [8], or through variance–covariance regularisation [9]. V-JEPA 2-AC freezes a pre-trained encoder and trains an action-conditioned predictor with teacher-forcing and rollout losses, then plans by cross-entropy-method (CEM) MPC in latent space [6], [10]. *Latent world models.* PlaNet and Dreamer learn latent dynamics by reconstructing observations [11]. SPR and TD-MPC2 learn self-predictive latents without reconstruction; TD-MPC2's latent-consistency loss keeps long rollouts on the encoder manifold [12], [13]. Context-aware dynamics models condition the predictor on an embedding of recent transitions [14]. *Physics and identification.* Grey-box system identification fits a known model structure to data [15]; physics-informed learning blends the two approaches [2]. We use a harmonic-comb tracker with Viterbi smoothing [16] followed by output-error identification of the *true* equation as a deliberately strong classical baseline.

III. Benchmark

A. Truth model

The rotor balance follows from Euler work, $\Delta h_0 = U\Delta C_\theta$ with $U = r\omega$, and the angular-momentum balance, extended with a lagged, delayed actuator:

$$J\dot{\omega} = \dot{m}r(k_u a - k_\omega \omega) - c_0 - c_2\omega^2, \qquad \tau_a \dot{a} = u(t - d\,\Delta t) - a, \tag{1}$$

with $r = 0.25\,\mathrm{m}$, $k_u = 100\,\mathrm{m\,s^{-1}}$, $c_0 = 0.15\,\mathrm{N\,m}$ and $\Delta t = 10\,\mathrm{ms}$. Six parameters are drawn per episode and never shown to the learned models: $\dot{m} \in [0.70, 0.90]\,\mathrm{kg\,s^{-1}}$, $J \in [0.017, 0.023]\,\mathrm{kg\,m^2}$, $k_\omega \in [0.12, 0.18]\,\mathrm{m}$, $c_2 \in [0, 1.5] \times 10^{-5}\,\mathrm{N\,m\,s^2}$, $\tau_a \in [0.03, 0.25]\,\mathrm{s}$ and $d \in \{0, \ldots, 4\}$ samples. Equilibrium speeds span about 130–740 $\mathrm{rad\,s^{-1}}$ and $J/(\dot{m}rk_\omega)$ is 0.5–1 s. The held-out regime moves J to $[0.023, 0.028]$ and c_2 to $[1.5, 3] \times 10^{-5}$. Commands are piecewise-constant or ramped excitation held for 0.15–0.8 s. Equation (1) is integrated by RK4 with ten substeps per sample under zero-order hold. Unit tests verify the exact first-order solution in the linear limit, the equilibrium fixed point, the exact delay shift and sample-exact regeneration of stored episodes.

B. Observation model

Every 10 ms the models receive a 64-bin log-power spectrum (0–3.2 kHz) of a synthetic casing microphone (Fig. 1). It contains three blade-passing harmonics at $hN_b\omega/2\pi$ ($N_b = 11$), whose level follows a fan-law speed term plus a steady-loading term in the Euler torque. It also contains speed-dependent pink flow noise and χ^2_8 periodogram fluctuation. Nuisance of level λ adds distractor tones that appear at random frequencies, drift and switch off; impulsive broadband bursts; and calibration offsets with slow gain drift. Speed is never an input. This is a declared model of tacholess speed sensing, not a calibrated machine.

C. Splits and protocol

There are 3000 training and 300 validation episodes, and 300-episode test sets for the training distribution, the held-out regime and $\lambda \in \{0, 0.5, 1, 2, 3\}$. Each episode lasts 4 s. Models see the first 2 s of spectra and commands, then forecast the next 2 s open loop under the known future commands. Test sets are used only for reported numbers; checkpoint selection, probe regularisation and controller tuning use validation data.




Fig. 1. One test episode. Top: the model input, with the hidden blade-passing harmonics overlaid for illustration. Bottom: the hidden rotor speed and the known command. Forecasts start at $t = 2\,\mathrm{s}$.

IV. Methods

A. Two-stage action-conditioned JEPA

Stage 1 pre-trains a causal time–frequency CNN trunk T_θ (three 3×5 convolutions, causal in time) by masked latent prediction on 32-frame crops. Two or three time–frequency blocks and the final 3–8 frames are masked. A convolutional predictor maps the context features to the EMA trunk's per-position, layer-normalised features at the masked cells:

$$\mathcal{L}_1 = \frac{1}{|M|} \sum_{(t,f)\in M} \left\| g_\psi(T_\theta(x \odot \bar{M}))_{tf} - \mathrm{LN}(T_{\bar{\theta}}(x))_{tf} \right\|_1, \tag{2}$$

with $\bar{\theta} \leftarrow m\bar{\theta} + (1-m)\theta$ and m following a cosine schedule from 0.996 to 1. There are no actions and no labels in this stage.

Stage 2 freezes the trunk. A trainable spatial-soft-argmax readout [17] and a GRU turn the trunk features and past commands into a layer-normalised belief $z_t \in \mathbb{R}^{48}$. A residual predictor $z_{t+1} = \mathrm{LN}(z_t + f_\phi(z_t, u_t))$ is rolled out for K steps, and a head q must match the frozen, frequency-pooled trunk maps y_{t+k} of the future frames:

$$\mathcal{L}_2 = \sum_{k=0}^{K} \left\| q(P^k_\phi(z_t, u_{t:t+k})) - y_{t+k} \right\|_1 + \beta \sum_{k=1}^{K} \left\| P^k_\phi(z_t, \cdot) - \mathrm{sg}(z_{t+k}) \right\|_2^2, \tag{3}$$

plus one-step teacher forcing. The second term is TD-MPC2's latent consistency [13], $\beta = 1$, applied identically to every learned method. The main configuration uses $K = 128$ (1.28 s) on 3.2 s training crops. Because the targets come from a frozen observation-only trunk, the latent cannot collapse onto the command history (Sec. VI).

Read-out and use. Speed is decoded by a frozen ridge probe, or an MLP probe where stated, fitted on N labelled training episodes. Forecasts decode open-loop latent rollouts through

the same probe. Control authority $\partial\hat{\omega}/\partial u$ is a central finite difference through the rollout. Planning uses CEM-MPC in latent space with a 0.5 s horizon. *JEPA + fine-tune* trains the whole JEPA world model on the supervised loss below.

B. Controls

All learned controls share the trunk architecture, readout, belief encoder, predictor, optimiser (AdamW, cosine schedule), batch, crops, rollout length, consistency term and step budget. They differ only in the training signal:

- *Reconstruction world model*: every encoded and predicted latent is decoded back to the 64-bin spectrum (MSE), i.e. observation prediction [11].
- *Supervised*: the true speed is regressed from every encoded and predicted latent, with 10–3000 labelled episodes and early stopping on labelled validation error. This is the only method given label-based checkpoint selection.
- *Classical pipeline*: a three-harmonic comb tracker with Viterbi smoothing under a slew limit, tuned on validation, is followed by batched output-error identification of the *true* form of (1) with a delay search, and then by simulation. This pipeline is given knowledge the learned models do not have.

We also report nominal physics with catalogue parameters, persistence, an oracle with the true parameters and state, a PI controller on the tracked speed with gains tuned on validation, and a random-encoder probe.

V. Results

Unless stated otherwise, errors are rotor-speed RMSE in $\mathrm{rad\,s^{-1}}$ over 300 test episodes. The JEPA, reconstruction and fully supervised world models in the main configuration report the mean ± s.d. over 3 seeds. The supervised label sweep, JEPA + fine-tune, the closed-loop study, the hybrid and all ablations use seed 0, and the text compares seed-0 numbers with seed-0 numbers.

A. Forecasting and state estimation

Table I and Fig. 3 summarise accuracy. The oracle reproduces the stored trajectories exactly, which verifies the protocol. Nominal physics (43.1 at 2 s) shows how much the hidden parameters matter. With a 300-label linear probe, the JEPA world model forecasts 2 s ahead with 11.3, against 18.2 for the reconstruction world model trained identically; with MLP probes the figures are 10.2 and 11.5. JEPA + fine-tune reaches 9.5 with 300 labels, against 14.7 for supervised training from scratch on the same labels. Full supervision with 3000 labels reaches 7.3. The classical pipeline, given the exact equation, remains the most accurate in distribution at 4.6. For state estimation, the MLP-probed JEPA belief (4.1) is on par with the hand-built tracker (4.4).

B. Label efficiency

Fig. 4 shows the result that matters most for a test cell, where unlabelled acoustic logs are cheap and tachometer-instrumented runs are not. With ten labelled episodes, a linear probe on the frozen JEPA latent forecasts with 13.2 (mean over three pre-training seeds), against 40.6 for the same network trained from scratch on those ten episodes (seed 0; 3.1×). JEPA pre-training followed by fine-tuning beats supervised training at every budget up to 300 episodes. Supervision overtakes the frozen probe only when labels are plentiful.

C. Robustness to nuisance and regime shift

The comb tracker locks onto distractor tones once they are frequent (Fig. 5, $\lambda \geq 2$). As a result the classical forecast degrades from 4.1 at $\lambda = 0$ to 14.3 at $\lambda = 3$. The JEPA world model, trained only at $\lambda = 1$, degrades from 10.7 to 13.4; the reconstruction world model reaches 23.1. With 300 labels, JEPA + fine-tune holds 12.9 at $\lambda = 3$, while supervised training from scratch reaches 27.5. In the held-out dynamical regime the JEPA forecast rises to 14.1 and the grey-box to 7.6.

D. Control authority and hidden parameters

Every learned model now reproduces the plant's step response to a command change (Fig. 6), the property whose absence was the main v1 failure. The median relative error of the 2 s gain is 0.10 for JEPA, 0.26 for reconstruction, 0.04 for full supervision and 0.03 for the grey-box. This follows from training on time-varying commands, not from an architectural trick. Linear probes on $z_{t=2\,\mathrm{s}}$ (Fig. 7) recover the steady-state gain well (R^2 of 0.76 for k_ω) and the actuator lag partly (0.22; 0.61 for supervision). They recover almost nothing of the inertia (R^2 of 0.01), mass flow or delay. The latent captures *state* better than it *identifies the machine*, and this is the main reason the true-structure grey-box still wins on long in-distribution forecasts.

E. Closed-loop control by planning in latent space

CEM-MPC controllers that differ only in their model track moderate set-point steps from the spectrogram alone (Fig. 8). We report excess tracking MSE over an oracle controller with paired bootstrap intervals over 40 episodes. Planning through the JEPA latent with a 300-label probe gives an excess of $7.9\,\mathrm{rad^2\,s^{-2}}$, close to the true-structure grey-box (6.6). With 300 labels, JEPA pre-training gives 7.7, against 22.2 for supervised training from scratch (2.9×). At $\lambda = 3$ the gap widens to 28.6 against 224 (7.8×). A PI controller on the tracked speed is far worse (344) and fails when the tracker fails (2444; Fig. 9).

VI. Failure modes met during development

Action shortcut. A single-stage action-conditioned JEPA whose EMA target encoder also received the commands collapsed to an effective latent rank of 2.6 of 48 within a few hundred steps (Fig. 10). Its speed probe stayed at the level of an untrained encoder. The latent encoded only the command history, which an action-conditioned predictor




Fig. 2. Two-stage action-conditioned JEPA. Stage 1 learns spectrogram features by masked latent prediction. Stage 2 freezes them and learns action-conditioned latent dynamics by predicting future frozen feature maps. A few labels then suffice for a probe that supports forecasting and latent-space MPC.

TABLE I

MAIN RESULTS. ROTOR-SPEED RMSE IN RAD S^{-1} (MEAN ± S.D. OVER SEEDS), RMS TORQUE RESIDUAL OF THE FORECAST UNDER THE TRUE PARAMETERS IN N M, AND MEDIAN RELATIVE ERROR OF THE 2 S CONTROL GAIN.

Method	Filter	0.25 s	1 s	2 s	2 s OOD	Torque res.	Gain err.
Oracle (true parameters, true state)	–	0.00	0.00	0.00	0.00	0.07	–
Tracker + grey-box ID (true ODE form)	4.44	2.54	3.74	4.61	7.58	0.34	0.031
Nominal physics + tracker	–	43.55	43.89	43.10	54.59	5.02	–
Persistence	–	19.92	54.46	71.70	58.58	3.65	–
JEPA world model, linear probe (300)	7.06 ± 0.69	7.62 ± 1.34	9.97 ± 1.05	11.30 ± 1.09	14.10 ± 0.48	1.09 ± 0.11	0.100 ± 0.014
JEPA world model, MLP probe (300)	4.10 ± 0.37	4.97 ± 0.68	8.68 ± 0.90	10.24 ± 1.10	13.32 ± 0.30	0.76 ± 0.07	–
Reconstruction WM, linear probe (300)	11.99 ± 1.98	16.07 ± 1.23	17.24 ± 0.86	18.22 ± 0.97	19.18 ± 2.92	2.12 ± 0.44	0.257 ± 0.057
Reconstruction WM, MLP probe (300)	5.32 ± 0.59	6.44 ± 0.46	9.93 ± 0.29	11.52 ± 0.26	13.97 ± 0.74	0.91 ± 0.01	–
Supervised, 300 labels	6.20	7.83	12.33	14.69	17.85	1.12	0.066
JEPA + fine-tune, 300 labels	4.03	4.56	7.80	9.49	14.90	0.72	0.061
Supervised, all 3000 labels	2.37 ± 0.10	3.20 ± 0.13	5.72 ± 0.21	7.28 ± 0.22	12.20 ± 0.71	0.52 ± 0.01	0.041 ± 0.003

forecasts perfectly. VICReg-strength variance and covariance terms [9] did not prevent this; observation-only targets did. We expect the same shortcut in any self-predictive world model whose target encoder sees the actions [12]. *Read-out bottleneck.* An untrained soft-argmax read-out discarded the speed information: an MLP probe on the full trunk map reached 5.1 rad s^{-1}, against 18.1 rad s^{-1} on the read-out. The read-out is therefore trained in stage 2. *Rollout drift.* Without the consistency term, probe-decoded rollouts diverged beyond the training horizon. *Infeasible control task.* The first closed-loop task used set-point steps of up to 80% of the reachable band. Every controller, the oracle included, was saturation-limited, so the task measured the actuator rather than the model. It was replaced by moderate steps; the old results are archived.

VII. SECOND-ROUND IMPROVEMENTS

The first-round results suggested four targeted changes, each aimed at one finding. Fig. 11 collects them with the original ablations; all numbers in this section are seed 0.

Training horizon. Increasing the rollout length from 0.64 to 1.28 s reduced the 2 s error from 14.7 to 10.1, the largest single gain in the study, and it helped every objective. Training on the full 2 s horizon (4 s crops) did *not* help further: 11.5 in distribution, 14.8 in the held-out regime and 14.0 at $\lambda = 3$. The benefit of longer rollouts saturates, and fewer anchors per crop at that length is a plausible cost.

Nuisance-randomised pre-training. Drawing $\lambda \sim U[0, 3]$ per training episode, a form of domain randomisation [18], splits cleanly by task. Perception became much more robust: with the MLP probe, filtering error at $\lambda = 3$ fell from 10.3 to 6.0, and to 5.4 when trained at a fixed $\lambda = 2.5$. Forecasts barely moved




Fig. 3. Forecast error against horizon, in distribution (left) and in the held-out regime (right). Bands span seeds.




Fig. 4. Filtering and 2 s forecast error against the number of speed-labelled training episodes. The self-supervised models also see all 3000 unlabelled episodes.

(11.9 against 11.7 at $\lambda = 3$; 11.2 in distribution with the linear probe). Seeing the speed better does not fix the long-horizon error, which again points at dynamics and identification rather than perception. In closed loop at $\lambda = 3$, planning with the $\lambda = 2.5$-trained JEPA reduced the excess error from 38.6 to 32.0.

JEPA perception with physics dynamics. The causal JEPA belief, read by the MLP probe, replaced the comb tracker as the input to grey-box identification of the true equation, fitted from $t = 0.3$ s (Fig. 12). In distribution the hybrid forecasts with 7.0, against 10.1 for the JEPA world model alone, a 30% reduction. A tracker fitted over the same window does better (5.9), because its Viterbi track is smoothed offline while the JEPA belief is causal. At $\lambda = 3$ the ordering reverses: the hybrid (16.4) beats the tracker over the same window (18.2) but loses to the pure JEPA world model (12.9). Output-error identification amplifies sensor error, so physics dynamics pay off only when perception is good.

Seed ensembles. A three-member ensemble of JEPA world models forecasts with 10.3, against 11.3 for a single member on average, and with 12.0 against 13.4 at $\lambda = 3$ [19]. The ensemble is over-confident, however. Only 64.3% of errors fall within $\pm 2\sigma$ of the ensemble mean (50.9% in the held-out regime), and spread and error correlate at only 0.28 (Fig. 13). The spread ranks difficulty weakly; it is not a calibrated uncertainty.

Adaptive context and pre-training. An explicit context embedding of recent transitions [14] made forecasts worse (16.1), and removing stage-1 pre-training cost 15.7 against 14.7 (both at the short horizon).

VIII. Discussion and implications

What JEPA buys here is labels and robustness, not peak accuracy. When the equation of motion is known and the sensor is clean, a hand-built tracker plus grey-box identification is still the best forecaster in this study. The JEPA world model wins where that pipeline is brittle or expensive. It needs only




Fig. 5. Filtering and forecast error against test nuisance λ (dotted line: training level), with 300-label linear probes for the self-supervised models. Learned models are trained at $\lambda = 1$ unless marked; the hybrid is seed 0.




Fig. 6. Left: model step responses $\partial\hat{\omega}/\partial u$ (dashed) against simulator finite differences (black) for three test episodes. Right: median and interquartile range of the relative error of the 2 s gain over the test set.




Fig. 7. Linear-probe R^2 for the six hidden parameters from the belief at t = 2 s (300 labelled episodes).




Fig. 8. Closed-loop excess tracking MSE over the oracle (40 test episodes, paired bootstrap 95% CIs) at the training nuisance (left) and heavy nuisance (right).

a handful of labelled runs, it degrades gracefully as acoustic nuisance grows, and it supports planning directly in latent space. With 300 labels, JEPA pre-training reduced excess closed-loop error 2.9× at the training nuisance and 7.8× under heavy nuisance. For a test cell that logs hours of unlabelled




Fig. 9. One closed-loop episode at $\lambda = 3$. The PI controller acts on a tracker that has locked onto a distractor.

sensor data but instruments only a few runs, that is the relevant trade.

Predicting representations beats predicting observations here. With identical architecture, data and budget, the JEPA objective gave a far more linearly accessible speed estimate than reconstruction (11.3 against 18.2 at 2 s with linear probes), better control authority, and better robustness. Under MLP probes the gap shrinks to 10.2 against 11.5, so much of the advantage is in *how* the information is organised, not only *whether* it is present.

The bottleneck is machine identification, not perception. The belief recovers state about as well as a specialised tracker, and nuisance randomisation made perception markedly more robust. Yet long-horizon forecasts barely moved, and the latent recovers almost nothing of the inertia, mass flow or delay. Self-supervised world models will need a stronger incentive for in-context system identification before they can rival structure-aware physics on extrapolation. Physics-structured predictors and longer, more diverse excitation are natural next steps.

Design lessons that transfer. An action-conditioned self-predictive model whose target encoder sees the actions can collapse onto the action history. Observation-only, frozen targets avoid this. Rollout length matters more than most architectural choices, but only up to a point. Seed ensembles reduce error but must be recalibrated before their spread is trusted.

IX. Limitations and claim boundary

Everything here is synthetic. The truth model is a scalar rotor with a first-order actuator; the sensor is a declared spectral model, not a measured microphone; and the distractors are stylised. The classical pipeline is given the exact model structure, which a real engine does not offer. The learned models are given 3000 unlabelled episodes of system-identification excitation, which a test cell might, or might not, provide. The closed-loop study, the hybrid, the supervised label sweep and all second-round variants rest on a single seed, and the supervised and fine-tuned label-sweep runs for seeds 1–2 were dropped for compute reasons. The results establish what this JEPA formulation can and cannot recover under controlled, fully known conditions; they validate no engine, sensor or controller.

X. Conclusion

Rebuilt around a partially observed, action-driven rotor, a two-stage action-conditioned JEPA learns a useful world model from unlabelled sound. With ten labelled episodes it forecasts 3.1× better than supervised training from scratch. It tolerates acoustic nuisance that breaks a hand-built tracker, recovers control authority, and plans close to an oracle. It does not match a classical pipeline that is given the true equation in distribution, and its latent identifies the machine only partially. Those two gaps, not representation learning itself, are where the next version should push.

References

[1] S. L. Dixon and C. A. Hall, *Fluid Mechanics and Thermodynamics of Turbomachinery*, 6th ed. Butterworth-Heinemann, 2010.

[2] G. E. Karniadakis, I. G. Kevrekidis, L. Lu, P. Perdikaris, S. Wang, and L. Yang, "Physics-informed machine learning," *Nature Reviews Physics*, vol. 3, pp. 422–440, 2021.

[3] Y. LeCun, "A path towards autonomous machine intelligence," *OpenReview preprint*, 2022.

[4] M. Assran, Q. Duval, I. Misra, P. Bojanowski, P. Vincent, M. Rabbat, Y. LeCun, and N. Ballas, "Self-supervised learning from images with a joint-embedding predictive architecture," in *Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition (CVPR)*, 2023.

[5] A. Bardes, Q. Garrido, J. Ponce, X. Chen, M. Rabbat, Y. LeCun, M. Assran, and N. Ballas, "Revisiting feature prediction for learning visual representations from video," *arXiv preprint arXiv:2404.08471*, 2024.

[6] M. Assran *et al.*, "V-JEPA 2: Self-supervised video models enable understanding, prediction and planning," *arXiv preprint arXiv:2506.09985*, 2025.

[7] Z. Fei, M. Fan, and J. Huang, "A-JEPA: Joint-embedding predictive architecture can listen," *arXiv preprint arXiv:2311.15830*, 2023.

[8] J.-B. Grill, F. Strub, F. Altché *et al.*, "Bootstrap your own latent: A new approach to self-supervised learning," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[9] A. Bardes, J. Ponce, and Y. LeCun, "VICReg: Variance-invariance-covariance regularization for self-supervised learning," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2022.

[10] R. Rubinstein, "The cross-entropy method for combinatorial and continuous optimization," *Methodology and Computing in Applied Probability*, vol. 1, no. 2, pp. 127–190, 1999.

[11] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson, "Learning latent dynamics for planning from pixels," in *Proc. Int. Conf. Machine Learning (ICML)*, 2019.

[12] M. Schwarzer, A. Anand, R. Goel, R. D. Hjelm, A. Courville, and P. Bachman, "Data-efficient reinforcement learning with self-predictive representations," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2021.

[13] N. Hansen, H. Su, and X. Wang, "TD-MPC2: Scalable, robust world models for continuous control," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2024.

[14] K. Lee, Y. Seo, S. Lee, H. Lee, and J. Shin, "Context-aware dynamics model for generalization in model-based reinforcement learning," in *Proc. Int. Conf. Machine Learning (ICML)*, 2020.

[15] L. Ljung, *System Identification: Theory for the User*, 2nd ed. Prentice Hall, 1999.

[16] G. D. Forney, "The Viterbi algorithm," *Proceedings of the IEEE*, vol. 61, no. 3, pp. 268–278, 1973.

[17] C. Finn, X. Y. Tan, Y. Duan, T. Darrell, S. Levine, and P. Abbeel, "Deep spatial autoencoders for visuomotor learning," in *Proc. IEEE Int. Conf. Robotics and Automation (ICRA)*, 2016.

[18] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel, "Domain randomization for transferring deep neural networks from simulation to the real world," in *Proc. IEEE/RSJ Int. Conf. Intelligent Robots and Systems (IROS)*, 2017.

[19] B. Lakshminarayanan, A. Pritzel, and C. Blundell, "Simple and scalable predictive uncertainty estimation using deep ensembles," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.




Fig. 10. Action-shortcut collapse. A single-stage JEPA whose EMA target sees the commands collapses (left) and never learns speed (right); the two-stage design with frozen observation targets does not.




Fig. 11. Seed-0 ablations and second-round variants: 2 s forecast RMSE in distribution, in the held-out regime and at $\lambda = 3$.




Fig. 12. JEPA perception with physics dynamics (seed 0). Grey-box identification of the true equation driven by the comb tracker or by the causal JEPA belief, against the JEPA world model alone.




Fig. 13. Spread–skill of three-seed ensembles. Points below the dashed line would mean the spread over-states the error; all ensembles lie above it, so they are over-confident.