

Chapter 2

Instructions: Language of the Computer

Instruction Set

- The collection of instructions of a computer
- Different computers have different instruction sets
 - But with many aspects in common
- Early computers had very simple instruction sets
 - Simplified implementation
- Many modern computers also have simple instruction sets

The MIPS* Instruction Set

- Used as the example throughout the book
- Stanford MIPS commercialized by MIPS Technologies (www.mips.com)
- Large share of embedded core market
 - Applications in consumer electronics, network/storage equipment, cameras, printers, ...
- Typical of many modern ISAs
 - See MIPS Reference Data tear-out card, and Appendixes B and E

*Originally acronym for Microprocessor without Interlocked Pipeline Stages

Arithmetic Operations

- Add and subtract, three operands
 - Two sources and one destination

add a, b, c # a gets b + c
- All arithmetic operations have this form
- *Design Principle 1: Simplicity favours regularity*
 - Regularity makes implementation simpler
 - Simplicity enables higher performance at lower cost

Arithmetic Example

- C code:

$f = (g + h) - (i + j);$

- Compiled MIPS code:

```
add t0, g, h    # temp t0 = g + h
add t1, i, j    # temp t1 = i + j
sub f, t0, t1   # f = t0 - t1
```

Register Operands

- Arithmetic instructions use register operands
- MIPS has 32 32-bit registers
 - Use for frequently accessed data
 - Numbered 0 to 31
 - 32-bit data called a “word”
- Assembler names
 - \$t0, \$t1, ..., \$t9 for temporary values
 - \$s0, \$s1, ..., \$s7 for saved variables
- *Design Principle 2: Smaller is faster*
 - Not a large number of registers

Register Operand Example

- C code:

$f = (g + h) - (i + j);$

- f, \dots, j in $\$s0, \dots, \$s4$

- Compiled MIPS code:

add $\$t0, \$s1, \$s2$

add $\$t1, \$s3, \$s4$

sub $\$s0, \$t0, \$t1$

Memory Operands

- Main memory used for composite data
 - Arrays, structures, dynamic data
- To apply arithmetic operations
 - Load values from memory into registers
 - Store result from register to memory
- Memory is byte addressed
 - Each address identifies an 8-bit byte
- Words are aligned in memory
 - Address must be a multiple of 4
- MIPS is Big Endian
 - Most-significant byte at least address of a word
 - *c.f.* Little Endian: least-significant byte at least address

Memory Operand Example 1

- C code:

`g = h + A[8];`

- `g` in `$s1`, `h` in `$s2`, base address of `A` in `$s3`

- Compiled MIPS code:

- Index 8 requires offset of 32

- 4 bytes per word

```
lw    $t0, 32($s3)    # load word
add   $s1, $s2, $t0
```

offset

base register

Memory Operand Example 2

- C code:

`A[12] = h + A[8];`

- `h` in `$s2`, base address of `A` in `$s3`

- Compiled MIPS code:

- Index 8 requires offset of 32

```
lw    $t0, 32($s3)    # load word
add   $t0, $s2, $t0
sw    $t0, 48($s3)    # store word
```

Registers vs. Memory

- Registers are faster to access than memory
- Operating on memory data requires loads and stores
 - More instructions to be executed
- Compiler must use registers for variables as much as possible
 - Only spill to memory for less frequently used variables
 - Register optimization is important!

Immediate Operands

- Constant data specified in an instruction
`addi $s3, $s3, 4`
- No subtract immediate instruction
 - Just use a negative constant
`addi $s2, $s1, -1`
- *Design Principle 3: Make the common case fast*
 - Small constants are common
 - Immediate operand avoids a load instruction

The Constant Zero

- MIPS register 0 (\$zero) is the constant 0
 - Cannot be overwritten
- Useful for common operations
 - E.g., move between registers
`add $t2, $s1, $zero`

Unsigned Binary Integers

- Given an n-bit number

$$x = x_{n-1}2^{n-1} + x_{n-2}2^{n-2} + \dots + x_12^1 + x_02^0$$

- Range: 0 to $+2^n - 1$

- Example

- $0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 0000\ 1011_2$
 $= 0 + \dots + 1 \times 2^3 + 0 \times 2^2 + 1 \times 2^1 + 1 \times 2^0$
 $= 0 + \dots + 8 + 0 + 2 + 1 = 11_{10}$

- Using 32 bits

- 0 to +4,294,967,295

2s-Complement Signed Integers

- Given an n-bit number

$$x = -x_{n-1}2^{n-1} + x_{n-2}2^{n-2} + \dots + x_12^1 + x_02^0$$

- Range: -2^{n-1} to $+2^{n-1} - 1$

- Example

- $1111\ 1111\ 1111\ 1111\ 1111\ 1111\ 1111\ 1100_2$
 $= -1 \times 2^{31} + 1 \times 2^{30} + \dots + 1 \times 2^2 + 0 \times 2^1 + 0 \times 2^0$
 $= -2,147,483,648 + 2,147,483,644 = -4_{10}$

- Using 32 bits

- $-2,147,483,648$ to $+2,147,483,647$

2s-Complement Signed Integers

- Bit 31 is sign bit
 - 1 for negative numbers
 - 0 for non-negative numbers
- $-(-2^n - 1)$ can't be represented
- Non-negative numbers have the same unsigned and 2s-complement representation
- Some specific numbers
 - 0: 0000 0000 ... 0000
 - -1: 1111 1111 ... 1111
 - Most-negative: 1000 0000 ... 0000
 - Most-positive: 0111 1111 ... 1111

Signed Negation

- Complement and add 1
 - Complement means $1 \rightarrow 0, 0 \rightarrow 1$

$$x + \bar{x} = 1111\dots111_2 = -1$$

$$\bar{x} + 1 = -x$$

- Example: negate +2
 - $+2 = 0000\ 0000 \dots 0010_2$
 - $-2 = 1111\ 1111 \dots 1101_2 + 1$
 $= 1111\ 1111 \dots 1110_2$

Sign Extension

- Representing a number using more bits
 - Preserve the numeric value
- In MIPS instruction set
 - `addi`: extend immediate value
 - `lb`, `lh`: extend loaded byte/halfword
 - `beq`, `bne`: extend the displacement
- Replicate the sign bit to the left
 - c.f. unsigned values: extend with 0s
- Examples: 8-bit to 16-bit
 - `+2`: 0000 0010 => 0000 0000 0000 0010
 - `-2`: 1111 1110 => 1111 1111 1111 1110

Representing Instructions

- Instructions are encoded in binary
 - Called machine code
- MIPS instructions
 - Encoded as 32-bit instruction words
 - Small number of formats encoding operation code (opcode), register numbers, ...
 - Regularity!
- Register numbers
 - \$t0 – \$t7 are reg's 8 – 15
 - \$t8 – \$t9 are reg's 24 – 25
 - \$s0 – \$s7 are reg's 16 – 23

MIPS R-format Instructions



■ Instruction fields

- op: operation code (opcode)
- rs: first source register number
- rt: second source register number
- rd: destination register number
- shamt: shift amount (00000 for now)
- funct: function code (extends opcode)

R-format Example

op	rs	rt	rd	shamt	funct
6 bits	5 bits	5 bits	5 bits	5 bits	6 bits

add \$t0, \$s1, \$s2

special	\$s1	\$s2	\$t0	0	add
---------	------	------	------	---	-----

0	17	18	8	0	32
---	----	----	---	---	----

000000	10001	10010	01000	00000	100000
--------	-------	-------	-------	-------	--------

$00000010001100100100000000100000_2 = 02324020_{16}$

Hexadecimal

■ Base 16


- Compact representation of bit strings
- 4 bits per hex digit

0	0000	4	0100	8	1000	c	1100
1	0001	5	0101	9	1001	d	1101
2	0010	6	0110	a	1010	e	1110
3	0011	7	0111	b	1011	f	1111

■ Example: eca8 6420

- 1110 1100 1010 1000 0110 0100 0010 0000


MIPS I-format Instructions



- Immediate arithmetic and load/store instructions
 - rt: destination or source register number
 - Constant: -2^{15} to $+2^{15} - 1$
 - Address: offset added to base address in rs
- *Design Principle 4: Good design demands good compromises*
 - Different formats complicate decoding, but allow 32-bit instructions uniformly
 - Keep formats as similar as possible – first three fields have same name and format for R and I

Stored Program Computers

The BIG Picture



- Instructions represented in binary, just like data
- Instructions and data stored in memory
- Programs can operate on programs
 - e.g., compilers, linkers, ...
- Binary compatibility allows compiled programs to work on different computers
 - Standardized ISAs

Logical Operations

- Instructions for bitwise manipulation

Operation	C	Java	MIPS
Shift left	<<	<<	sll
Shift right	>>	>>>	srl
Bitwise AND	&	&	and, andi
Bitwise OR			or, ori
Bitwise NOT	~	~	nor

- Useful for extracting and inserting groups of bits in a word

Shift Operations

op	rs	rt	rd	shamt	funct
6 bits	5 bits	5 bits	5 bits	5 bits	6 bits

- shamt: how many positions to shift
- Shift left logical
 - Shift left and fill with 0 bits
 - `sll` by i bits multiplies by 2^i
- Shift right logical
 - Shift right and fill with 0 bits
 - `srl` by i bits divides by 2^i (unsigned only)

AND Operations

- Useful to mask bits in a word
 - Select some bits, clear others to 0

and \$t0, \$t1, \$t2

\$t2	0000 0000 0000 0000 0000 1101 1100 0000
\$t1	0000 0000 0000 0000 0011 1100 0000 0000
\$t0	0000 0000 0000 0000 0000 1100 0000 0000

OR Operations

- Useful to include bits in a word
 - Set some bits to 1, leave others unchanged
- or \$t0, \$t1, \$t2

\$t2	0000 0000 0000 0000 0000 1101 1100 0000
\$t1	0000 0000 0000 0000 0011 1100 0000 0000
\$t0	0000 0000 0000 0000 0011 1101 1100 0000

NOT Operations

- Useful to invert bits in a word
 - Change 0 to 1, and 1 to 0
- MIPS has NOR 3-operand instruction
 - $a \text{ NOR } b == \text{NOT} (a \text{ OR } b)$

`nor $t0, $t1, $zero` ←

Register 0: always
read as zero

\$t1 0000 0000 0000 0000 0011 1100 0000 0000

\$t0 1111 1111 1111 1111 1100 0011 1111 1111

Conditional Operations

- Branch to a labeled instruction if a condition is true
 - Otherwise, continue sequentially
- `beq rs, rt, L1`
 - if (`rs == rt`) branch to instruction labeled L1;
- `bne rs, rt, L1`
 - if (`rs != rt`) branch to instruction labeled L1;
- `j L1`
 - unconditional jump to instruction labeled L1

Compiling If Statements


- C code:

```
if (i==j) f = g+h;  
else f = g-h;
```

- f, g, ... in \$s0, \$s1, ...

- Compiled MIPS code:

```
        bne $s3, $s4, Else  
        add $s0, $s1, $s2  
        j   Exit  
Else:   sub $s0, $s1, $s2  
Exit:   ...
```



Assembler calculates addresses

Compiling Loop Statements

- C code:

```
while (save[i] == k) i += 1;
```


- i in \$s3, k in \$s5, base address of save in \$s6

- Compiled MIPS code:

```
Loop:  sll    $t1, $s3, 2
       add    $t1, $t1, $s6
       lw     $t0, 0($t1)
       bne    $t0, $s5, Exit
       addi   $s3, $s3, 1
       j      Loop
Exit:  ...
```


Basic Blocks

- A basic block is a sequence of instructions with
 - No embedded branches (except at end)
 - No branch targets (except at beginning)



- A compiler identifies basic blocks for optimization
- An advanced processor can accelerate execution of basic blocks

More Conditional Operations

- Set result to 1 if a condition is true
 - Otherwise, set to 0
- `slt rd, rs, rt` (Set on Less Than)
 - if ($rs < rt$) $rd = 1$; else $rd = 0$;
- `slti rt, rs, constant`
 - if ($rs < \text{constant}$) $rt = 1$; else $rt = 0$;
- Use in combination with `beq`, `bne`

```
    slt $t0, $s1, $s2    # if ($s1 < $s2)
    bne $t0, $zero, L    #   branch to L
```

Branch Instruction Design

- Why not b1t, bge, etc?
- Hardware for $<$, \geq , ... slower than $=$, \neq
 - Combining with branch involves more work per instruction, requiring a slower clock
 - All instructions penalized!
- beq and bne are the common case
- This is a good design compromise

Signed vs. Unsigned

- Signed comparison: `slt`, `slti`
- Unsigned comparison: `sltu`, `sltui`
- Example
 - `$s0 = 1111 1111 1111 1111 1111 1111 1111 1111`
 - `$s1 = 0000 0000 0000 0000 0000 0000 0000 0001`
 - `slt $t0, $s0, $s1 # signed`
 - $-1 < +1 \Rightarrow \$t0 = 1$
 - `sltu $t0, $s0, $s1 # unsigned`
 - $+4,294,967,295 > +1 \Rightarrow \$t0 = 0$

Procedure Calling

- Steps required
 1. Place parameters in registers
 2. Transfer control to procedure
 3. Acquire storage for procedure
 4. Perform procedure's operations
 5. Place result in register for caller
 6. Return to place of call

Register Usage

- \$a0 – \$a3: arguments (reg's 4 – 7)
- \$v0, \$v1: result values (reg's 2 and 3)
- \$t0 – \$t9: temporaries
 - Can be overwritten by callee
- \$s0 – \$s7: saved
 - Must be saved/restored by callee
- \$gp: global pointer for static data (reg 28)
- \$sp: stack pointer (reg 29)
- \$fp: frame pointer (reg 30)
- \$ra: return address (reg 31)

Procedure Call Instructions

- Procedure call: jump and link
`jal ProcedureLabel`
 - Address of following instruction put in `$ra`
 - Jumps to target address
- Procedure return: jump register
`jr $ra`
 - Copies `$ra` to program counter
 - Can also be used for computed jumps
 - e.g., for case/switch statements

Leaf Procedure Example

- C code:

```
int leaf_example (int g, h, i, j)
{ int f;
  f = (g + h) - (i + j);
  return f;
}
```

- Arguments g, ..., j in \$a0, ..., \$a3
- f in \$s0 (hence, need to save \$s0 on stack)
- Result in \$v0

Leaf Procedure Example

- MIPS code:

leaf_example:			
addi	\$sp,	\$sp, -4	Save \$s0 on stack
sw	\$s0,	0(\$sp)	
add	\$t0,	\$a0, \$a1	Procedure body
add	\$t1,	\$a2, \$a3	
sub	\$s0,	\$t0, \$t1	
add	\$v0,	\$s0, \$zero	Result
lw	\$s0,	0(\$sp)	Restore \$s0
addi	\$sp,	\$sp, 4	
jr	\$ra		Return

Non-Leaf Procedures

- Procedures that call other procedures
- For nested call, caller needs to save on the stack:
 - Its return address
 - Any arguments and temporaries needed after the call
- Restore from the stack after the call

Non-Leaf Procedure Example

- C code:

```
int fact (int n)
{
    if (n < 1) return f;
    else return n * fact(n - 1);
}
```


- Argument n in \$a0
- Result in \$v0

Non-Leaf Procedure Example

- MIPS code:

fact:		
addi	\$sp, \$sp, -8	# adjust stack for 2 items
sw	\$ra, 4(\$sp)	# save return address
sw	\$a0, 0(\$sp)	# save argument
slti	\$t0, \$a0, 1	# test for n < 1
beq	\$t0, \$zero, L1	
addi	\$v0, \$zero, 1	# if so, result is 1
addi	\$sp, \$sp, 8	# pop 2 items from stack
jr	\$ra	# and return
L1:	addi \$a0, \$a0, -1	# else decrement n
	jal fact	# recursive call
lw	\$a0, 0(\$sp)	# restore original n
lw	\$ra, 4(\$sp)	# and return address
addi	\$sp, \$sp, 8	# pop 2 items from stack
mul	\$v0, \$a0, \$v0	# multiply to get result
jr	\$ra	# and return


Local Data on the Stack



- Local data allocated by callee
 - e.g., C automatic variables
- Procedure frame (activation record)
 - Used by some compilers to manage stack storage

Memory Layout

- Text: program code
- Static data: global variables
 - e.g., static variables in C, constant arrays and strings
 - \$gp initialized to address allowing \pm offsets into this segment
- Dynamic data: heap
 - E.g., malloc in C, new in Java
- Stack: automatic storage



Character Data

- Byte-encoded character sets
 - ASCII: 128 characters
 - 95 graphic, 33 control
 - Latin-1: 256 characters
 - ASCII, +96 more graphic characters
- Unicode: 32-bit character set
 - Used in Java, C++ wide characters, ...
 - Most of the world's alphabets, plus symbols
 - UTF-8, UTF-16: variable-length encodings

Byte/Halfword Operations

- Could use bitwise operations
- MIPS byte/halfword load/store
 - String processing is a common case

`lb rt, offset(rs)` `lh rt, offset(rs)`

- Sign extend to 32 bits in `rt`

`lbu rt, offset(rs)` `lhu rt, offset(rs)`

- Zero extend to 32 bits in `rt`

`sb rt, offset(rs)` `sh rt, offset(rs)`

- Store just rightmost byte/halfword

String Copy Example

- C code (naïve):

- Null-terminated string

```
void strcpy (char x[], char y[])  
{ int i;  
  i = 0;  
  while ((x[i]=y[i])!='\0')  
    i += 1;  
}
```

- Addresses of x, y in \$a0, \$a1
- i in \$s0

String Copy Example

- MIPS code:

strcpy:		
	addi \$sp, \$sp, -4	# adjust stack for 1 item
	sw \$s0, 0(\$sp)	# save \$s0
	add \$s0, \$zero, \$zero	# i = 0
L1:	add \$t1, \$s0, \$a1	# addr of y[i] in \$t1
	lbu \$t2, 0(\$t1)	# \$t2 = y[i]
	add \$t3, \$s0, \$a0	# addr of x[i] in \$t3
	sb \$t2, 0(\$t3)	# x[i] = y[i]
	beq \$t2, \$zero, L2	# exit loop if y[i] == 0
	addi \$s0, \$s0, 1	# i = i + 1
	j L1	# next iteration of loop
L2:	lw \$s0, 0(\$sp)	# restore saved \$s0
	addi \$sp, \$sp, 4	# pop 1 item from stack
	jr \$ra	# and return

32-bit Constants

- Most constants are small
 - 16-bit immediate is sufficient
- For the occasional 32-bit constant

`lui rt, constant`

 - Copies 16-bit constant to left 16 bits of `rt`
 - Clears right 16 bits of `rt` to 0

`lui $s0, 61`


0000 0000 0111 1101	0000 0000 0000 0000
---------------------	---------------------

`ori $s0, $s0, 2304`

0000 0000 0111 1101	0000 1001 0000 0000
---------------------	---------------------

Branch Addressing


- Branch instructions specify
 - Opcode, two registers, target address
- Most branch targets are near branch
 - Forward or backward



- PC-relative addressing
 - Target address = $PC + \text{offset} \times 4$
 - PC already incremented by 4 by this time

Jump Addressing

- Jump (j and jal) targets could be anywhere in text segment
 - Encode full address in instruction



- (Pseudo)Direct jump addressing
 - Target address = $PC_{31...28} : (\text{address} \times 4)$

Target Addressing Example

- Loop code from earlier example
 - Assume Loop at location 80000

```
Loop: slt    $t1, $s3, 2    80000
      add    $t1, $t1, $s6  80004
      lw     $t0, 0($t1)    80008
      bne    $t0, $s5, Exit 80012
      addi   $s3, $s3, 1    80016
      j      Loop          80020
Exit: ...                  80024
```

0	0	19	9	4	0
0	9	22	9	0	32
35	9	8	0		
5	8	21	2		
8	19	19	1		
2	20000				

Branching Far Away

- If branch target is too far to encode with 16-bit offset, assembler rewrites the code
- Example

```
beq $s0,$s1, L1
```

↓

```
bne $s0,$s1, L2
```

```
j L1
```

```
L2: ...
```

Addressing Mode Summary


1. Immediate addressing




2. Register addressing




3. Base addressing



4. PC-relative addressing



5. Pseudodirect addressing



C Sort Example

- Illustrates use of assembly instructions for a C bubble sort function

- Swap procedure (leaf)

```
void swap(int v[], int k)
{
    int temp;
    temp = v[k];
    v[k] = v[k+1];
    v[k+1] = temp;
}
```

- v in \$a0, k in \$a1, temp in \$t0

The Procedure Swap

swap: sll \$t1, \$a1, 2	# \$t1 = k * 4
add \$t1, \$a0, \$t1	# \$t1 = v+(k*4)
	# (address of v[k])
lw \$t0, 0(\$t1)	# \$t0 (temp) = v[k]
lw \$t2, 4(\$t1)	# \$t2 = v[k+1]
sw \$t2, 0(\$t1)	# v[k] = \$t2 (v[k+1])
sw \$t0, 4(\$t1)	# v[k+1] = \$t0 (temp)
jr \$ra	# return to calling routine

The Sort Procedure in C

- Non-leaf (calls swap)

```
void sort (int v[], int n)
{
    int i, j;
    for (i = 0; i < n; i += 1) {
        for (j = i - 1;
             j >= 0 && v[j] > v[j + 1];
             j -= 1) {
            swap(v, j);
        }
    }
}
```

- v in \$a0, n in \$a1, i in \$s0, j in \$s1

The Procedure Body

	move \$s2, \$a0	# save \$a0 into \$s2	Move params
	move \$s3, \$a1	# save \$a1 into \$s3	
	move \$s0, \$zero	# i = 0	
for1tst:	slt \$t0, \$s0, \$s3	# \$t0 = 0 if \$s0 ≥ \$s3 (i ≥ n)	Outer loop
	beq \$t0, \$zero, exit1	# go to exit1 if \$s0 ≥ \$s3 (i ≥ n)	
	addi \$s1, \$s0, -1	# j = i - 1	
for2tst:	slti \$t0, \$s1, 0	# \$t0 = 1 if \$s1 < 0 (j < 0)	
	bne \$t0, \$zero, exit2	# go to exit2 if \$s1 < 0 (j < 0)	
	sll \$t1, \$s1, 2	# \$t1 = j * 4	Inner loop
	add \$t2, \$s2, \$t1	# \$t2 = v + (j * 4)	
	lw \$t3, 0(\$t2)	# \$t3 = v[j]	
	lw \$t4, 4(\$t2)	# \$t4 = v[j + 1]	
	slt \$t0, \$t4, \$t3	# \$t0 = 0 if \$t4 ≥ \$t3	
	beq \$t0, \$zero, exit2	# go to exit2 if \$t4 ≥ \$t3	
	move \$a0, \$s2	# 1st param of swap is v (old \$a0)	Pass params & call
	move \$a1, \$s1	# 2nd param of swap is j	
	jal swap	# call swap procedure	
	addi \$s1, \$s1, -1	# j -= 1	
	j for2tst	# jump to test of inner loop	Inner loop
exit2:	addi \$s0, \$s0, 1	# i += 1	
	j for1tst	# jump to test of outer loop	Outer loop

The Full Procedure

sort:	addi \$sp,\$sp, -20	# make room on stack for 5 registers
	sw \$ra, 16(\$sp)	# save \$ra on stack
	sw \$s3,12(\$sp)	# save \$s3 on stack
	sw \$s2, 8(\$sp)	# save \$s2 on stack
	sw \$s1, 4(\$sp)	# save \$s1 on stack
	sw \$s0, 0(\$sp)	# save \$s0 on stack
...		# procedure body
...		
exit1:	lw \$s0, 0(\$sp)	# restore \$s0 from stack
	lw \$s1, 4(\$sp)	# restore \$s1 from stack
	lw \$s2, 8(\$sp)	# restore \$s2 from stack
	lw \$s3,12(\$sp)	# restore \$s3 from stack
	lw \$ra,16(\$sp)	# restore \$ra from stack
	addi \$sp,\$sp, 20	# restore stack pointer
	jr \$ra	# return to calling routine

The Intel x86 ISA

- Evolution with backward compatibility
 - 8080 (1974): 8-bit microprocessor
 - Accumulator, plus 3 index-register pairs
 - 8086 (1978): 16-bit extension to 8080
 - Complex instruction set (CISC)
 - 8087 (1980): floating-point coprocessor
 - Adds FP instructions and register stack
 - 80286 (1982): 24-bit addresses, Memory Management Unit
 - Segmented memory mapping and protection
 - 80386 (1985): 32-bit extension (now IA-32)
 - Additional addressing modes and operations
 - Paged memory mapping as well as segments

The Intel x86 ISA

- Further evolution...
 - i486 (1989): pipelined, on-chip caches and FPU
 - Compatible competitors: AMD, Cyrix, ...
 - Pentium (1993): superscalar, 64-bit datapath
 - Later versions added MMX (Multi-Media eXtension) instructions
 - The infamous FDIV bug
 - Pentium Pro (1995), Pentium II (1997)
 - New microarchitecture (see Colwell, *The Pentium Chronicles*)
 - Pentium III (1999)
 - Added SSE (Streaming SIMD Extensions) and associated registers
 - Pentium 4 (2001)
 - New microarchitecture
 - Added SSE2 instructions

The Intel x86 ISA

- And further...
 - AMD64 (2003): extended architecture to 64 bits
 - EM64T – Extended Memory 64 Technology (2004)
 - AMD64 adopted by Intel (with refinements)
 - Added SSE3 instructions
 - Intel Core (2006)
 - Added SSE4 instructions, virtual machine support
 - AMD64 (announced 2007): SSE5 instructions
 - Intel declined to follow, instead...
 - Advanced Vector Extension (announced 2008)
 - Longer SSE registers, more instructions
- If Intel didn't extend with compatibility, its competitors would!
 - Technical elegance ≠ market success

Basic x86 Registers

Name	31	0	Use
EAX			GPR 0
ECX			GPR 1
EDX			GPR 2
EBX			GPR 3
ESP			GPR 4
EBP			GPR 5
ESI			GPR 6
EDI			GPR 7
	CS		Code segment pointer
	SS		Stack segment pointer (top of stack)
	DS		Data segment pointer 0
	ES		Data segment pointer 1
	FS		Data segment pointer 2
	GS		Data segment pointer 3
EIP			Instruction pointer (PC)
EFLAGS			Condition codes

Basic x86 Addressing Modes

- Two operands per instruction

Source/dest operand	Second source operand
Register	Register
Register	Immediate
Register	Memory
Memory	Register
Memory	Immediate

- Memory addressing modes
 - Address in register
 - $\text{Address} = R_{\text{base}} + \text{displacement}$
 - $\text{Address} = R_{\text{base}} + 2^{\text{scale}} \times R_{\text{index}}$ (scale = 0, 1, 2, or 3)
 - $\text{Address} = R_{\text{base}} + 2^{\text{scale}} \times R_{\text{index}} + \text{displacement}$

Fallacies

- Powerful instruction \Rightarrow higher performance
 - Fewer instructions required
 - But complex instructions are hard to implement
 - May slow down all instructions, including simple ones
 - Compilers are good at making fast code from simple instructions
- Use assembly code for high performance
 - But modern compilers are better at dealing with modern processors
 - More lines of code \Rightarrow more errors and less productivity

Pitfalls

- Sequential words are not at sequential addresses
 - Increment by 4, not by 1!
- Keeping a pointer to an automatic variable after procedure returns
 - e.g., passing pointer back via an argument
 - Pointer becomes invalid when stack popped

Concluding Remarks

- Design principles
 1. Simplicity favors regularity
 2. Smaller is faster
 3. Make the common case fast
 4. Good design demands good compromises
- Layers of software/hardware
 - Compiler, assembler, hardware
- MIPS: typical of RISC ISAs
 - c.f. x86
- RISC vs. CISC

Concluding Remarks

- Measure MIPS instruction executions in benchmark programs
 - Consider making the common case fast
 - Consider compromises

Instruction class	MIPS examples	SPEC2006 Int	SPEC2006 FP
Arithmetic	add, sub, addi	16%	48%
Data transfer	lw, sw, lb, lbu, lh, lhu, sb, lui	35%	36%
Logical	and, or, nor, andi, ori, sll, srl	12%	4%
Cond. Branch	beq, bne, slt, slti, sltiu	34%	8%
Jump	j, jr, jal	2%	0%

Sections to Read from the Book

- 5th Edition Sections to read
 - 2.1, 2.2, 2.3, 2.4, 2.5, 2.6
 - 2.7 (Except Case/Switch)
 - 2.8
 - 2.9 (Except Characters and Strings in Java)
 - 2.10 (Except Decoding Machine Language)
 - 2.13
 - 2.17 (Only what was covered in the Class on August 25, 2022)
 - 2.19
 - 2.20