



Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

Module 25: Programming in C++

Inheritance: Part 5 (private & protected Inheritance)

Sourangshu Bhattacharya

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

sourangshu@cse.iitkgp.ac.in

Slides taken from NPTEL course on Programming in C++

by **Prof. Partha Pratim Das**



Module Objectives

- Explore restricted forms of inheritance (`private` and `protected`) in C++ and their semantic implications

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

`private`
Inheritance

`protected`
Inheritance

Visibility

Use &
Examples

Summary



Module Outline

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

- ISA Relationship
- Inheritance in C++
 - Semantics
 - Data Members and Object Layout
 - Member Functions
 - Overriding
 - Overloading
 - protected Access
 - Constructor & Destructor
 - Object Lifetime
- Example – Phone Hierarchy
- Inheritance in C++ (private)
 - Implemented-As Semantics



Inheritance in C++: Semantics

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

- Derived **ISA** Base



```
class Base; // Base Class = Base  
class Derived: public Base; // Derived Class = Derived
```

- Use keyword **public** after class name to denote inheritance
- Name of the Base class follow the keyword



Inheritance Exercise: What is the output?

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

```
class B {
public:
    B() { cout << "B "; }
    ~B() { cout << "~B "; } };

class C {
public:
    C() { cout << "C "; }
    ~C() { cout << "~C "; } };

class D : public B {
    C data_;
public:
    D() { cout << "D " << endl; }
    ~D() { cout << "~D "; }
};

int main() {
    D d;

    return 0;
}
```



Inheritance Exercise: What is the output?

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

```
class B {
public:
    B() { cout << "B "; }
    ~B() { cout << "~B "; } };

class C {
public:
    C() { cout << "C "; }
    ~C() { cout << "~C "; } };

class D : public B {
    C data_;
public:
    D() { cout << "D " << endl; }
    ~D() { cout << "~D "; }
};

int main() {
    D d;

    return 0;
}
```

Output:

```
B C D
~D ~C ~B
```



private Inheritance

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

- private Inheritance

- Definition

```
class Base;  
class Derived: private Base;
```

- Use keyword **private** after class name
 - Name of the Base class follow the keyword
 - **private** inheritance **does not** mean generalization / specialization

- Private inheritance means nothing during software design, only during software implementation

- Private inheritance means is-implemented-in-terms of. It's usually inferior to composition, but it makes sense when a derived class needs access to protected base class members or needs to redefine inherited virtual functions

- Scott Meyers in Item 32, Effective C++ (3rd. Edition)



private Inheritance

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

public Inheritance

```
class Person {...};

class Student:
    public Person {...};

// anyone can eat
void eat(const Person& p);

// only students study
void study(const Student& s);

Person p; // p is a Person

Student s; // s is a Student

eat(p); // fine, p is a Person

eat(s); // fine, s is a Student,
        // and a Student is-a Person

study(s); // fine

study(p); // error! p isn't a Student
```

Compilers converts a derived class object (Student) into a base class object (Person) if the inheritance relationship is public

private Inheritance

```
class Person { ... };

class Student: // inheritance is now private
    private Person { ... };

// anyone can eat
void eat(const Person& p);

// only students study
void study(const Student& s);

Person p; // p is a Person

Student s; // s is a Student

eat(p); // fine, p is a Person

eat(s); // error! a Student isn't a Person
```

Compilers will not convert a derived class object (Student) into a base class object (Person) if the inheritance relationship is private



protected Inheritance

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

**protected
Inheritance**

Visibility

Use &
Examples

Summary

- protected Inheritance

- Definition

```
class Base;  
class Derived: protected Base;
```

- Use keyword **protected** after class name
 - Name of the Base class follow the keyword
 - **protected** inheritance **does not** mean generalization / specialization

● Private inheritance means something entirely different (from public inheritance), and protected inheritance is something whose meaning eludes me to this day


– Scott Meyers in Item 32, Effective C++ (3rd. Edition)



Visibility across Access and Inheritance

• Visibility Matrix

		Inheritance		
Visibility		public	protected	private
	public	public	protected	private
	protected	protected	protected	private
	private	private	private	private





Inheritance Exercise: What is the output?

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

```
class B {  
protected:  
    B() { cout << "B "; }  
    ~B() { cout << "~B "; }  
};  
class C : public B {  
protected:  
    C() { cout << "C "; }  
    ~C() { cout << "~C "; }  
};  
class D : private C {  
    C data_;  
public:  
    D() { cout << "D " << endl; }  
    ~D() { cout << "~D "; }  
};  
  
int main() {  
    D d;  
  
    return 0;  
}
```



Inheritance Exercise: What is the output?

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

```
class B {  
protected:  
    B() { cout << "B "; }  
    ~B() { cout << "~B "; }  
};  
class C : public B {  
protected:  
    C() { cout << "C "; }  
    ~C() { cout << "~C "; }  
};  
class D : private C {  
    C data_;  
public:  
    D() { cout << "D " << endl; }  
    ~D() { cout << "~D "; }  
};  
  
int main() {  
    D d;  
  
    return 0;  
}
```

Output:

```
B C B C D  
~D ~C ~B ~C ~B
```



Inheritance Exercise: Access Rights

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

Inaccessible Members

```
class A {  
private: int x;  
protected: int y;  
public: int z;  
};  
class B : public A {  
private: int u;  
protected: int v;  
public: int w; void f() { x; }  
};  
class C: protected A {  
private: int u;  
protected: int v;  
public: int w; void f() { x; }  
};  
class D: private A {  
private: int u;  
protected: int v;  
public: int w; void f() { x; }  
};  
class E : public B {  
public: void f() { x; u; }  
};  
class F : public C {  
public: void f() { x; u; }  
};  
class G : public D {  
public: void f() { x; y; z; u; }  
};
```

Accessible Members

```
void f(A& a,  
      B& b, C& c, D& d,  
      E& e, F& f, G& g) {  
    a.z;  
  
    b.z;  
    b.w;  
  
    c.w;  
  
    d.w;  
  
    e.z;  
    e.w;  
  
    f.w;  
  
    g.w;  
}
```



Car HAS-A Engine: Composition OR private Inheritance?

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

Simple Composition

```
#include <iostream>
using namespace std;

class Engine {
public:
    Engine(int numCylinders) { }
    // Starts this Engine
    void start() { }
};

class Car {
public:
    // Initializes this Car with 8 cylinders
    Car() : e_(8) { }

    // Start this Car by starting its Engine
    void start() { e_.start(); }
private:
    Engine e_; // Car has-a Engine
};

int main() {
    Car c;

    c.start();

    return 0;
}
```

private Inheritance

```
#include <iostream>
using namespace std;

class Engine {
public:
    Engine(int numCylinders) { }
    // Starts this Engine
    void start() { }
};

class Car : private Engine { // Car has-a Engine
public:
    // Initializes this Car with 8 cylinders
    Car() : Engine(8) { }

    // Start this Car by starting its Engine
    using Engine::start;
};

int main() {
    Car c;

    c.start();

    return 0;
}
```



private Inheritance

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

- Use composition when you can, private inheritance when you have to

- **Private inheritance means nothing during software design, only during software implementation**

- **Private inheritance means is-implemented-in-terms of. It's usually inferior to composition, but it makes sense when a derived class needs access to protected base class members or needs to redefine inherited virtual functions**

- Scott Meyers in Item 32, Effective C++ (3rd. Edition)



Module Summary

Module 25

Sourangshu
Bhattacharya

Objectives &
Outline

Inheritance in
C++

private
Inheritance

protected
Inheritance

Visibility

Use &
Examples

Summary

- Introduced restricted forms of inheritance and protected specifier
- Discussed how private inheritance is used for *Implemented-As* Semantics