

MAGE

Generated by Doxygen 1.8.12

Contents

1	Namespace Index	1
1.1	Namespace List	1
2	Hierarchical Index	3
2.1	Class Hierarchy	3
3	Class Index	5
3.1	Class List	5
4	Namespace Documentation	7
4.1	Image Namespace Reference	7
4.1.1	Enumeration Type Documentation	9
4.1.1.1	ReadWriteMutexLockType	9
4.1.1.2	VariableType	9
4.1.2	Function Documentation	9
4.1.2.1	AllocAligned() [1/2]	9
4.1.2.2	AllocAligned() [2/2]	10
4.1.2.3	AtomicAdd() [1/2]	10
4.1.2.4	AtomicAdd() [2/2]	11
4.1.2.5	AtomicCompareAndSwap()	11
4.1.2.6	AtomicCompareAndSwapPointer()	11
4.1.2.7	BitsPerPixel()	12
4.1.2.8	ComboBoxAdd()	12
4.1.2.9	ComboBoxContains()	12
4.1.2.10	ComboBoxCount()	13

4.1.2.11	ComboBoxSelect() [1/2]	13
4.1.2.12	ComboBoxSelect() [2/2]	13
4.1.2.13	ComboBoxSelected()	14
4.1.2.14	ComboBoxSomethingSelected()	14
4.1.2.15	EnqueueTasks()	15
4.1.2.16	Error()	15
4.1.2.17	FindWordEnd()	15
4.1.2.18	FreeAligned()	15
4.1.2.19	Info()	16
4.1.2.20	NumberOfSystemCores()	16
4.1.2.21	PrintConsoleHeader()	16
4.1.2.22	ProcessError()	16
4.1.2.23	SettingsDialogProcDelegate()	17
4.1.2.24	Severe()	17
4.1.2.25	task_entry()	17
4.1.2.26	TasksCleanup()	18
4.1.2.27	TasksInit()	18
4.1.2.28	TerminalWidth()	18
4.1.2.29	WaitForAllTasks()	18
4.1.2.30	Warning()	18
4.1.2.31	WindowProc()	18
4.1.3	Variable Documentation	19
4.1.3.1	g_device_enumeration	19
4.1.3.2	g_driver_types	19
4.1.3.3	g_engine	19
4.1.3.4	g_feature_levels	20
4.1.3.5	g_logging_configuration	20
4.1.3.6	g_pixel_formats	20
4.1.3.7	lvertex_input_element_desc	20
4.1.3.8	nb_unfinished_tasks	21
4.1.3.9	task_queue	21
4.1.3.10	task_queue_mutex	21
4.1.3.11	tasks_running_condition	21
4.1.3.12	threads	21
4.1.3.13	tlvertex_input_element_desc	21
4.1.3.14	vertex_input_element_desc	22
4.1.3.15	worker_semaphore	22

5	Class Documentation	23
5.1	mage::AABB Struct Reference	23
5.1.1	Detailed Description	23
5.1.2	Constructor & Destructor Documentation	23
5.1.2.1	AABB() [1/2]	23
5.1.2.2	AABB() [2/2]	23
5.1.3	Member Function Documentation	24
5.1.3.1	EnclosedBy()	24
5.1.3.2	Encloses() [1/2]	24
5.1.3.3	Encloses() [2/2]	24
5.1.4	Member Data Documentation	25
5.1.4.1	p_max	25
5.1.4.2	p_min	25
5.2	mage::Variable::AbstractValue Struct Reference	25
5.2.1	Detailed Description	25
5.2.2	Constructor & Destructor Documentation	26
5.2.2.1	~AbstractValue()	26
5.2.3	Member Function Documentation	26
5.2.3.1	GetValue()	26
5.3	mage::ConditionVariable Class Reference	26
5.3.1	Detailed Description	26
5.3.2	Member Enumeration Documentation	26
5.3.2.1	anonymous enum	26
5.3.3	Constructor & Destructor Documentation	27
5.3.3.1	ConditionVariable()	27
5.3.3.2	~ConditionVariable()	27
5.3.4	Member Function Documentation	27
5.3.4.1	Lock()	27
5.3.4.2	Signal()	27
5.3.4.3	Unlock()	27

5.3.4.4	Wait()	27
5.3.5	Member Data Documentation	28
5.3.5.1	m_condition_mutex	28
5.3.5.2	m_events	28
5.3.5.3	m_nb_waiters	28
5.3.5.4	m_nb_waiters_mutex	28
5.4	mage::DeviceEnumeration Class Reference	28
5.4.1	Detailed Description	29
5.4.2	Constructor & Destructor Documentation	29
5.4.2.1	DeviceEnumeration()	29
5.4.2.2	~DeviceEnumeration()	29
5.4.3	Member Function Documentation	29
5.4.3.1	Enumerate()	29
5.4.3.2	GetAdapter()	30
5.4.3.3	GetDisplayMode()	30
5.4.3.4	IsFullScreen()	30
5.4.3.5	IsVSynced()	30
5.4.3.6	IsWindowed()	30
5.4.3.7	SettingsDialogProc()	30
5.4.4	Friends And Related Function Documentation	31
5.4.4.1	Engine	31
5.4.4.2	SettingsDialogProcDelegate	31
5.4.5	Member Data Documentation	31
5.4.5.1	m_adapter	31
5.4.5.2	m_display_modes	32
5.4.5.3	m_selected_display_mode	32
5.4.5.4	m_settings_script	32
5.4.5.5	m_vsync	32
5.4.5.6	m_windowed	32
5.5	mage::Edge Struct Reference	32

5.5.1	Detailed Description	32
5.5.2	Constructor & Destructor Documentation	32
5.5.2.1	Edge()	32
5.5.3	Member Data Documentation	33
5.5.3.1	v0	33
5.5.3.2	v1	33
5.6	mage::Engine Class Reference	33
5.6.1	Detailed Description	34
5.6.2	Constructor & Destructor Documentation	34
5.6.2.1	Engine()	34
5.6.2.2	~Engine()	34
5.6.3	Member Function Documentation	34
5.6.3.1	GetInput()	35
5.6.3.2	GetRenderer()	35
5.6.3.3	GetScriptManager()	35
5.6.3.4	GetStateManager()	35
5.6.3.5	GetWindow()	35
5.6.3.6	InitializeConsole()	36
5.6.3.7	InitializeSystems()	36
5.6.3.8	InitializeWindow()	36
5.6.3.9	Run()	36
5.6.3.10	SetDeactiveFlag()	36
5.6.3.11	UninitializeSystems()	38
5.6.3.12	UninitializeWindow()	38
5.6.4	Member Data Documentation	38
5.6.4.1	m_deactive	38
5.6.4.2	m_hwindow	38
5.6.4.3	m_input	38
5.6.4.4	m_renderer	39
5.6.4.5	m_script_manager	39

5.6.4.6	m_setup	39
5.6.4.7	m_state_manager	39
5.7	mage::EngineSetup Struct Reference	39
5.7.1	Detailed Description	39
5.7.2	Constructor & Destructor Documentation	39
5.7.2.1	EngineSetup() [1/2]	39
5.7.2.2	EngineSetup() [2/2]	40
5.7.3	Member Data Documentation	40
5.7.3.1	m_hinstance	40
5.7.3.2	m_name	40
5.7.3.3	StateSetup	40
5.8	mage::Face Struct Reference	40
5.8.1	Detailed Description	41
5.8.2	Constructor & Destructor Documentation	41
5.8.2.1	Face()	41
5.8.3	Member Data Documentation	41
5.8.3.1	v0	41
5.8.3.2	v1	41
5.8.3.3	v2	42
5.9	mage::Font Class Reference	42
5.9.1	Constructor & Destructor Documentation	42
5.9.1.1	Font()	42
5.9.1.2	~Font()	42
5.9.2	Member Function Documentation	43
5.9.2.1	PrepareFont()	43
5.9.2.2	Render()	43
5.9.3	Member Data Documentation	43
5.9.3.1	m_spacing	43
5.9.3.2	m_texture	43
5.9.3.3	m_texture_coords	43

5.9.3.4	m_texture_height	43
5.9.3.5	m_texture_width	43
5.9.3.6	m_vb	43
5.10	mage::IndexedEdge Struct Reference	44
5.10.1	Detailed Description	44
5.10.2	Member Data Documentation	44
5.10.2.1	iv0	44
5.10.2.2	iv1	44
5.11	mage::IndexedFace Struct Reference	44
5.11.1	Detailed Description	44
5.11.2	Member Data Documentation	45
5.11.2.1	iv0	45
5.11.2.2	iv1	45
5.11.2.3	iv2	45
5.12	mage::Input Class Reference	45
5.12.1	Detailed Description	46
5.12.2	Constructor & Destructor Documentation	46
5.12.2.1	Input()	46
5.12.2.2	~Input()	47
5.12.3	Member Function Documentation	47
5.12.3.1	GetDeltaWheel()	47
5.12.3.2	GetDeltaX()	47
5.12.3.3	GetDeltaY()	47
5.12.3.4	GetKeyPress()	47
5.12.3.5	GetMouseButtonPress()	48
5.12.3.6	GetPosX()	48
5.12.3.7	GetPosY()	48
5.12.3.8	InitializeDI()	49
5.12.3.9	InitializeKeyboard()	49
5.12.3.10	InitializeMouse()	49

5.12.3.11 UninitializeDI()	49
5.12.3.12 UninitializeKeyboard()	49
5.12.3.13 UninitializeMouse()	50
5.12.3.14 Update()	50
5.12.4 Friends And Related Function Documentation	50
5.12.4.1 Engine	50
5.12.5 Member Data Documentation	50
5.12.5.1 m_di	50
5.12.5.2 m_hwindow	50
5.12.5.3 m_key_press_stamp	50
5.12.5.4 m_key_state	51
5.12.5.5 m_keyboard	51
5.12.5.6 m_mouse	51
5.12.5.7 m_mouse_button_press_stamp	51
5.12.5.8 m_mouse_position	51
5.12.5.9 m_mouse_state	51
5.12.5.10 m_press_stamp	52
5.13 mage::Loadable Class Reference	52
5.13.1 Detailed Description	52
5.13.2 Constructor & Destructor Documentation	52
5.13.2.1 Loadable()	52
5.13.2.2 ~Loadable()	53
5.13.3 Member Function Documentation	53
5.13.3.1 IsLoaded()	53
5.13.3.2 SetLoaded()	53
5.13.4 Member Data Documentation	53
5.13.4.1 m_loaded	53
5.14 mage::LoggingConfiguration Struct Reference	53
5.14.1 Detailed Description	54
5.14.2 Constructor & Destructor Documentation	54

5.14.2.1	LoggingConfiguration()	54
5.14.3	Member Function Documentation	54
5.14.3.1	IsQuiet()	54
5.14.3.2	IsVerbose()	54
5.14.4	Member Data Documentation	55
5.14.4.1	m_quiet	55
5.14.4.2	m_verbose	55
5.15	mage::LVertex Struct Reference	55
5.15.1	Detailed Description	55
5.15.2	Constructor & Destructor Documentation	55
5.15.2.1	LVertex() [1/2]	55
5.15.2.2	LVertex() [2/2]	55
5.15.3	Member Data Documentation	56
5.15.3.1	diffuse	56
5.15.3.2	p	56
5.15.3.3	tex	56
5.16	mage::MemoryArena Class Reference	56
5.16.1	Detailed Description	57
5.16.2	Constructor & Destructor Documentation	57
5.16.2.1	MemoryArena()	57
5.16.2.2	~MemoryArena()	57
5.16.3	Member Function Documentation	57
5.16.3.1	Alloc() [1/2]	57
5.16.3.2	Alloc() [2/2]	57
5.16.3.3	FreeAll()	59
5.16.4	Member Data Documentation	59
5.16.4.1	m_available_blocks	59
5.16.4.2	m_block_size	59
5.16.4.3	m_current_block	59
5.16.4.4	m_current_block_pos	60

5.16.4.5	<code>m_used_blocks</code>	60
5.17	<code>mage::Mutex</code> Class Reference	60
5.17.1	Detailed Description	60
5.17.2	Constructor & Destructor Documentation	60
5.17.2.1	<code>Mutex()</code> [1/2]	60
5.17.2.2	<code>Mutex()</code> [2/2]	60
5.17.2.3	<code>~Mutex()</code>	61
5.17.3	Member Function Documentation	61
5.17.3.1	<code>Create()</code>	61
5.17.3.2	<code>Destroy()</code>	61
5.17.3.3	<code>operator=()</code>	61
5.17.4	Friends And Related Function Documentation	61
5.17.4.1	<code>MutexLock</code>	62
5.17.5	Member Data Documentation	62
5.17.5.1	<code>m_critical_section</code>	62
5.18	<code>mage::MutexLock</code> Struct Reference	62
5.18.1	Detailed Description	62
5.18.2	Constructor & Destructor Documentation	62
5.18.2.1	<code>MutexLock()</code> [1/2]	62
5.18.2.2	<code>~MutexLock()</code>	63
5.18.2.3	<code>MutexLock()</code> [2/2]	63
5.18.3	Member Function Documentation	63
5.18.3.1	<code>operator=()</code>	63
5.18.4	Member Data Documentation	63
5.18.4.1	<code>m_mutex</code>	63
5.19	<code>mage::ProgressReporter</code> Class Reference	64
5.19.1	Detailed Description	64
5.19.2	Constructor & Destructor Documentation	64
5.19.2.1	<code>ProgressReporter()</code>	64
5.19.2.2	<code>~ProgressReporter()</code>	65

5.19.3	Member Function Documentation	65
5.19.3.1	Done()	65
5.19.3.2	Update()	65
5.19.4	Member Data Documentation	65
5.19.4.1	m_buffer	65
5.19.4.2	m_current_pos	65
5.19.4.3	m_fout	65
5.19.4.4	m_mutex	66
5.19.4.5	m_nb_plusses_printed	66
5.19.4.6	m_nb_plusses_total	66
5.19.4.7	m_nb_work_done	66
5.19.4.8	m_nb_work_total	66
5.19.4.9	m_timer	66
5.20	mage::ReadWriteMutex Class Reference	66
5.20.1	Detailed Description	67
5.20.2	Constructor & Destructor Documentation	67
5.20.2.1	ReadWriteMutex() [1/2]	67
5.20.2.2	ReadWriteMutex() [2/2]	67
5.20.2.3	~ReadWriteMutex()	68
5.20.3	Member Function Documentation	68
5.20.3.1	AcquireRead()	68
5.20.3.2	AcquireWrite()	68
5.20.3.3	Create()	68
5.20.3.4	Destroy()	68
5.20.3.5	operator=()	68
5.20.3.6	ReleaseRead()	69
5.20.3.7	ReleaseWrite()	69
5.20.4	Friends And Related Function Documentation	69
5.20.4.1	ReadWriteMutexLock	69
5.20.5	Member Data Documentation	69

5.20.5.1	m_active_writer_readers	69
5.20.5.2	m_critical_section	69
5.20.5.3	m_nb_readers_waiting	70
5.20.5.4	m_nb_writers_waiting	70
5.20.5.5	m_ready_to_read_handle	70
5.20.5.6	m_ready_to_write_handle	70
5.21	mage::ReadWriteMutexLock Struct Reference	70
5.21.1	Detailed Description	71
5.21.2	Constructor & Destructor Documentation	71
5.21.2.1	ReadWriteMutexLock() [1/2]	71
5.21.2.2	~ReadWriteMutexLock()	71
5.21.2.3	ReadWriteMutexLock() [2/2]	71
5.21.3	Member Function Documentation	71
5.21.3.1	DowngradeToRead()	71
5.21.3.2	operator=()	72
5.21.3.3	UpgradeToWrite()	72
5.21.4	Member Data Documentation	72
5.21.4.1	m_mutex	72
5.21.4.2	m_type	72
5.22	mage::Reference< T > Class Template Reference	72
5.22.1	Detailed Description	73
5.22.2	Constructor & Destructor Documentation	73
5.22.2.1	Reference() [1/2]	73
5.22.2.2	Reference() [2/2]	73
5.22.2.3	~Reference()	73
5.22.3	Member Function Documentation	74
5.22.3.1	GetPtr()	74
5.22.3.2	operator bool()	74
5.22.3.3	operator->() [1/2]	74
5.22.3.4	operator->() [2/2]	74

5.22.3.5	<code>operator=()</code> [1/2]	74
5.22.3.6	<code>operator=()</code> [2/2]	75
5.22.4	Member Data Documentation	75
5.22.4.1	<code>m_ptr</code>	75
5.23	<code>mage::ReferenceCounted</code> Class Reference	75
5.23.1	Detailed Description	76
5.23.2	Constructor & Destructor Documentation	76
5.23.2.1	<code>ReferenceCounted()</code>	76
5.23.3	Member Function Documentation	76
5.23.3.1	<code>DecrementReferenceCount()</code>	76
5.23.3.2	<code>IncrementReferenceCount()</code>	76
5.23.4	Member Data Documentation	76
5.23.4.1	<code>m_reference_count</code>	76
5.24	<code>mage::Renderer</code> Class Reference	77
5.24.1	Detailed Description	77
5.24.2	Constructor & Destructor Documentation	78
5.24.2.1	<code>Renderer()</code>	78
5.24.2.2	<code>~Renderer()</code>	79
5.24.3	Member Function Documentation	79
5.24.3.1	<code>InitializeDevice()</code>	79
5.24.3.2	<code>IsFullScreen()</code>	79
5.24.3.3	<code>IsWindowed()</code>	79
5.24.3.4	<code>Render()</code>	79
5.24.3.5	<code>SwitchMode()</code>	80
5.24.3.6	<code>UnitalizeDevice()</code>	80
5.24.4	Friends And Related Function Documentation	80
5.24.4.1	<code>Engine</code>	80
5.24.5	Member Data Documentation	80
5.24.5.1	<code>m_depth_stencil</code>	80
5.24.5.2	<code>m_depth_stencil_view</code>	80

5.24.5.3	m_device2	80
5.24.5.4	m_device_context2	80
5.24.5.5	m_driver_type	81
5.24.5.6	m_feature_level	81
5.24.5.7	m_hwindow	81
5.24.5.8	m_render_target_view	81
5.24.5.9	m_swap_chain2	81
5.24.5.10	m_windowed	81
5.25	mage::Resource Class Reference	81
5.25.1	Detailed Description	82
5.25.2	Constructor & Destructor Documentation	82
5.25.2.1	Resource()	82
5.25.2.2	~Resource()	82
5.25.3	Member Function Documentation	82
5.25.3.1	DecrementResourceReferenceCount()	82
5.25.3.2	GetFilename()	83
5.25.3.3	GetName()	83
5.25.3.4	GetPath()	83
5.25.3.5	IncrementResourceReferenceCount()	83
5.25.4	Friends And Related Function Documentation	84
5.25.4.1	ResourceManager	84
5.25.5	Member Data Documentation	84
5.25.5.1	m_name	84
5.25.5.2	m_path	84
5.25.5.3	m_resource_reference_count	84
5.26	mage::ResourceManager< T > Class Template Reference	84
5.26.1	Detailed Description	84
5.26.2	Constructor & Destructor Documentation	85
5.26.2.1	ResourceManager()	85
5.26.2.2	~ResourceManager()	85

5.26.3	Member Function Documentation	85
5.26.3.1	AddResource()	85
5.26.3.2	ClearResources()	86
5.26.3.3	GetResource()	86
5.26.3.4	RemoveResource()	86
5.26.4	Member Data Documentation	86
5.26.4.1	CreateResource	86
5.26.4.2	m_resources	87
5.27	mage::Semaphore Class Reference	87
5.27.1	Detailed Description	87
5.27.2	Constructor & Destructor Documentation	87
5.27.2.1	Semaphore()	87
5.27.2.2	~Semaphore()	87
5.27.3	Member Function Documentation	87
5.27.3.1	Post()	87
5.27.3.2	TryWait()	88
5.27.3.3	Wait()	88
5.27.4	Member Data Documentation	88
5.27.4.1	m_handle	88
5.28	mage::Sphere Struct Reference	88
5.28.1	Detailed Description	89
5.28.2	Constructor & Destructor Documentation	89
5.28.2.1	Sphere() [1/2]	89
5.28.2.2	Sphere() [2/2]	89
5.28.3	Member Function Documentation	89
5.28.3.1	Collides()	89
5.28.3.2	Encloses()	90
5.28.4	Member Data Documentation	90
5.28.4.1	p	90
5.28.4.2	r	90

5.29	mage::State Class Reference	90
5.29.1	Detailed Description	91
5.29.2	Constructor & Destructor Documentation	91
5.29.2.1	State()	91
5.29.3	Member Function Documentation	91
5.29.3.1	Close()	91
5.29.3.2	GetId()	91
5.29.3.3	Load()	92
5.29.3.4	Render()	92
5.29.3.5	RequestViewSetup()	92
5.29.3.6	Update()	92
5.29.4	Friends And Related Function Documentation	92
5.29.4.1	StateManager	92
5.29.5	Member Data Documentation	93
5.29.5.1	m_id	93
5.30	mage::StateManager Class Reference	93
5.30.1	Detailed Description	93
5.30.2	Constructor & Destructor Documentation	94
5.30.2.1	StateManager()	94
5.30.2.2	~StateManager()	94
5.30.3	Member Function Documentation	94
5.30.3.1	AddState()	94
5.30.3.2	ChangeState() [1/2]	94
5.30.3.3	ChangeState() [2/2]	94
5.30.3.4	GetCurrentState()	95
5.30.3.5	IsStateChanged()	95
5.30.3.6	RemoveState()	95
5.30.3.7	Update()	95
5.30.4	Friends And Related Function Documentation	96
5.30.4.1	Engine	96

5.30.5	Member Data Documentation	96
5.30.5.1	m_current_state	96
5.30.5.2	m_state_changed	96
5.30.5.3	m_states	96
5.31	mage::Task Class Reference	96
5.31.1	Detailed Description	97
5.31.2	Constructor & Destructor Documentation	97
5.31.2.1	~Task()	97
5.31.3	Member Function Documentation	97
5.31.3.1	Run()	97
5.32	mage::Timer Class Reference	97
5.32.1	Detailed Description	98
5.32.2	Constructor & Destructor Documentation	98
5.32.2.1	Timer()	98
5.32.2.2	~Timer()	98
5.32.3	Member Function Documentation	98
5.32.3.1	Reset()	98
5.32.3.2	Restart()	98
5.32.3.3	Start()	98
5.32.3.4	Stop()	98
5.32.3.5	Time()	99
5.32.3.6	time()	99
5.32.4	Member Data Documentation	99
5.32.4.1	m_elapsed	99
5.32.4.2	m_performance_counter	99
5.32.4.3	m_performance_frequency	99
5.32.4.4	m_performance_period	99
5.32.4.5	m_running	100
5.32.4.6	m_time0	100
5.33	mage::TLVertex Struct Reference	100

5.33.1 Detailed Description	100
5.33.2 Constructor & Destructor Documentation	100
5.33.2.1 TLVertex() [1/2]	100
5.33.2.2 TLVertex() [2/2]	100
5.33.3 Member Data Documentation	101
5.33.3.1 diffuse	101
5.33.3.2 p	101
5.33.3.3 tex	101
5.34 mage::Variable::Value< T > Struct Template Reference	101
5.34.1 Detailed Description	101
5.34.2 Constructor & Destructor Documentation	102
5.34.2.1 Value()	102
5.34.2.2 ~Value()	102
5.34.3 Member Function Documentation	102
5.34.3.1 GetValue()	102
5.34.4 Member Data Documentation	102
5.34.4.1 m_value	102
5.35 mage::Variable Struct Reference	103
5.35.1 Detailed Description	103
5.35.2 Constructor & Destructor Documentation	103
5.35.2.1 Variable()	103
5.35.2.2 ~Variable()	104
5.35.3 Member Function Documentation	104
5.35.3.1 GetName()	104
5.35.3.2 GetType()	104
5.35.3.3 GetValue()	104
5.35.3.4 operator!=(())	104
5.35.3.5 operator==(())	105
5.35.4 Member Data Documentation	105
5.35.4.1 m_name	105

5.35.4.2	m_type	105
5.35.4.3	m_value	105
5.36	mage::VariableScript Class Reference	106
5.36.1	Detailed Description	106
5.36.2	Constructor & Destructor Documentation	106
5.36.2.1	VariableScript()	106
5.36.2.2	~VariableScript()	107
5.36.3	Member Function Documentation	107
5.36.3.1	AddVariable()	107
5.36.3.2	ExportScript()	107
5.36.3.3	ExportVariable()	108
5.36.3.4	GetValueOfVariable()	108
5.36.3.5	ImportScript()	108
5.36.3.6	ImportVariable()	108
5.36.3.7	RemoveVariable()	109
5.36.3.8	SetValueOfVariable()	109
5.36.4	Member Data Documentation	109
5.36.4.1	m_variables	109
5.37	mage::Vertex Struct Reference	110
5.37.1	Detailed Description	110
5.37.2	Constructor & Destructor Documentation	110
5.37.2.1	Vertex() [1/2]	110
5.37.2.2	Vertex() [2/2]	110
5.37.3	Member Data Documentation	111
5.37.3.1	n	111
5.37.3.2	p	111
5.37.3.3	tex	111
5.38	mage::ViewerSetup Struct Reference	111
5.38.1	Detailed Description	111
5.38.2	Constructor & Destructor Documentation	111
5.38.2.1	ViewerSetup()	111
5.38.3	Member Data Documentation	111
5.38.3.1	m_view_clear_flags	111

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all namespaces with brief descriptions:

mage	7
--------------------------------	---

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

mage::AABB	23
mage::Variable::AbstractValue	25
mage::Variable::Value< T >	101
mage::ConditionVariable	26
mage::DeviceEnumeration	28
mage::Edge	32
mage::EngineSetup	39
mage::Face	40
mage::Font	42
mage::IndexedEdge	44
mage::IndexedFace	44
mage::Loadable	52
mage::Engine	33
mage::Input	45
mage::Renderer	77
mage::LoggingConfiguration	53
mage::LVertex	55
mage::MemoryArena	56
mage::Mutex	60
mage::MutexLock	62
mage::ProgressReporter	64
mage::ReadWriteMutex	66
mage::ReadWriteMutexLock	70
mage::Reference< T >	72
mage::ReferenceCounted	75
mage::Resource	81
mage::VariableScript	106
mage::ResourceManager< T >	84
mage::ResourceManager< mage::VariableScript >	84
mage::Semaphore	87
mage::Sphere	88
mage::State	90
mage::StateManager	93
mage::Task	96

mage::Timer	97
mage::TLVertex	100
mage::Variable	103
mage::Vertex	110
mage::ViewerSetup	111

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

mage::AABB	23
mage::Variable::AbstractValue	25
mage::ConditionVariable	26
mage::DeviceEnumeration	28
mage::Edge	32
mage::Engine	33
mage::EngineSetup	39
mage::Face	40
mage::Font	42
mage::IndexedEdge	44
mage::IndexedFace	44
mage::Input	45
mage::Loadable	52
mage::LoggingConfiguration	53
mage::LVertex	55
mage::MemoryArena	56
mage::Mutex	60
mage::MutexLock	62
mage::ProgressReporter	64
mage::ReadWriteMutex	66
mage::ReadWriteMutexLock	70
mage::Reference< T >	72
mage::ReferenceCounted	75
mage::Renderer	77
mage::Resource	81
mage::ResourceManager< T >	84
mage::Semaphore	87
mage::Sphere	88
mage::State	90
mage::StateManager	93
mage::Task	96
mage::Timer	97
mage::TLVertex	100
mage::Variable::Value< T >	101
mage::Variable	103
mage::VariableScript	106
mage::Vertex	110
mage::ViewerSetup	111

Chapter 4

Namespace Documentation

4.1 image Namespace Reference

Classes

- struct [AABB](#)
- class [ConditionVariable](#)
- class [DeviceEnumeration](#)
- struct [Edge](#)
- class [Engine](#)
- struct [EngineSetup](#)
- struct [Face](#)
- class [Font](#)
- struct [IndexedEdge](#)
- struct [IndexedFace](#)
- class [Input](#)
- class [Loadable](#)
- struct [LoggingConfiguration](#)
- struct [LVertex](#)
- class [MemoryArena](#)
- class [Mutex](#)
- struct [MutexLock](#)
- class [ProgressReporter](#)
- class [ReadWriteMutex](#)
- struct [ReadWriteMutexLock](#)
- class [Reference](#)
- class [ReferenceCounted](#)
- class [Renderer](#)
- class [Resource](#)
- class [ResourceManager](#)
- class [Semaphore](#)
- struct [Sphere](#)
- class [State](#)
- class [StateManager](#)
- class [Task](#)
- class [Timer](#)
- struct [TLVertex](#)
- struct [Variable](#)
- class [VariableScript](#)
- struct [Vertex](#)
- struct [ViewerSetup](#)

Enumerations

- enum [ReadWriteMutexLockType](#) { [READ](#), [WRITE](#) }
- enum [VariableType](#) {
[BoolType](#), [IntType](#), [FloatType](#), [Float3Type](#),
[Float4Type](#), [ColourType](#), [StringType](#), [UnknownType](#) }

Functions

- HRESULT CALLBACK [WindowProc](#) (HWND hWnd, UINT msg, WPARAM wParam, LPARAM lParam)
- void [PrintConsoleHeader](#) ()
- const char * [FindWordEnd](#) (const char *buffer)
- void [ProcessError](#) (const char *format, const va_list args, const string &error_type, int error_disposition)
- void [Info](#) (const char *format,...)
- void [Warning](#) (const char *format,...)
- void [Error](#) (const char *format,...)
- void [Severe](#) (const char *format,...)
- int [TerminalWidth](#) ()
- void * [AllocAligned](#) (size_t size)
- template<typename T >
T * [AllocAligned](#) (uint32_t count)
- void [FreeAligned](#) (void *ptr)
- template<typename T >
T * [AtomicCompareAndSwapPointer](#) (T **destination, T *exchange, T *comparand)
- int32_t [AtomicAdd](#) (AtomicInt32 *addend, int32_t value)
- int32_t [AtomicCompareAndSwap](#) (AtomicInt32 *destination, int32_t exchange, int32_t comparand)
- float [AtomicAdd](#) (volatile float *addend, float value)
- uint32_t [NumberOfSystemCores](#) ()
- static DWORD WINAPI [task_entry](#) (LPVOID lpParameter)
- void [TasksInit](#) ()
- void [TasksCleanup](#) ()
- void [EnqueueTasks](#) (const vector< [Task](#) *> &tasks)
- void [WaitForAllTasks](#) ()
- INT_PTR CALLBACK [SettingsDialogProcDelegate](#) (HWND hwndDlg, UINT uMsg, WPARAM wParam, LPARAM lParam)
- size_t [BitsPerPixel](#) (DXGI_FORMAT format)
- void [ComboBoxAdd](#) (HWND dialog, int id, const void *data, const wchar_t *desc)
- void [ComboBoxSelect](#) (HWND dialog, int id, int index)
- void [ComboBoxSelect](#) (HWND dialog, int id, const void *data)
- const void * [ComboBoxSelected](#) (HWND dialog, int id)
- bool [ComboBoxSomethingSelected](#) (HWND dialog, int id)
- int [ComboBoxCount](#) (HWND dialog, int id)
- bool [ComboBoxContains](#) (HWND dialog, int id, const wchar_t *desc)

Variables

- [LoggingConfiguration](#) [g_logging_configuration](#)
- [Engine](#) * [g_engine](#) = NULL
- const D3D11_INPUT_ELEMENT_DESC [vertex_input_element_desc](#) []
- const D3D11_INPUT_ELEMENT_DESC [lvertex_input_element_desc](#) []
- const D3D11_INPUT_ELEMENT_DESC [tlvertex_input_element_desc](#) []
- static HANDLE * [threads](#)
- static [Mutex](#) * [task_queue_mutex](#) = [Mutex::Create](#)()

- static vector< [Task](#) * > [task_queue](#)
- static [Semaphore](#) * [worker_semaphore](#)
- static uint32_t [nb_unfinished_tasks](#)
- static [ConditionVariable](#) * [tasks_running_condition](#)
- [DeviceEnumeration](#) * [g_device_enumeration](#) = NULL
- const D3D_DRIVER_TYPE [g_driver_types](#) []
- const D3D_FEATURE_LEVEL [g_feature_levels](#) []
- const DXGI_FORMAT [g_pixel_formats](#) []

4.1.1 Enumeration Type Documentation

4.1.1.1 ReadWriteMutexLockType

```
enum mage::ReadWriteMutexLockType
```

Type of read write mutex locks.

Enumerator

READ	
WRITE	

4.1.1.2 VariableType

```
enum mage::VariableType
```

Enumeration of variable types.

Enumerator

BoolType	
IntType	
FloatType	
Float3Type	
Float4Type	
ColourType	
StringType	
UnknownType	

4.1.2 Function Documentation

4.1.2.1 AllocAligned() [1/2]

```
void* mage::AllocAligned (
    size_t size )
```

Allocates memory on an alignment boundary of 64 bytes of the given size.

Parameters

<i>in</i>	<i>size</i>	The requested size in bytes to allocate in memory.
-----------	-------------	--

Returns

NULL if the allocation failed.

A pointer to the memory block that was allocated. The pointer is a multiple of the alignment of 64 bytes.

4.1.2.2 AllocAligned() [2/2]

```
template<typename T >
T* mage::AllocAligned (
    uint32_t count )
```

Allocates memory on an alignment boundary of 64 bytes.

Template Parameters

<i>T</i>	The type of objects to allocate in memory.
----------	--

Parameters

<i>in</i>	<i>count</i>	The number of objects of type <i>T</i> to allocate in memory.
-----------	--------------	---

Returns

NULL if the allocation failed.

A pointer to the memory block that was allocated. The pointer is a multiple of the alignment of 64 bytes.

4.1.2.3 AtomicAdd() [1/2]

```
int32_t mage::AtomicAdd (
    AtomicInt32 * addend,
    int32_t value )
```

Performs an atomic addition operation on the specified values.

Parameters

<i>in, out</i>	<i>addend</i>	A pointer to the first operand. This value will be replaced with the result of the operation.
<i>in</i>	<i>value</i>	The second operand.

Returns

The function returns the result of the operation.

4.1.2.4 AtomicAdd() [2/2]

```
float mage::AtomicAdd (
    volatile float * addend,
    float value )
```

Performs an atomic addition operation on the specified values.

Parameters

in, out	<i>addend</i>	A pointer to the first operand. This value will be replaced with the result of the operation.
in	<i>value</i>	The second operand.

Returns

The function returns the result of the operation.

4.1.2.5 AtomicCompareAndSwap()

```
int32_t mage::AtomicCompareAndSwap (
    AtomicInt32 * destination,
    int32_t exchange,
    int32_t comparand )
```

Performs an atomic compare-and-exchange operation on the specified values. The function compares the original value against a given comparand value and exchanges the original value with a given exchange value in case of equality.

Parameters

in, out	<i>destination</i>	
in	<i>exchange</i>	The exchange value.
in	<i>comparand</i>	The value to compare to <i>destination</i> .

Returns

The function returns the initial value of *destination*.

4.1.2.6 AtomicCompareAndSwapPointer()

```
template<typename T >
T* mage::AtomicCompareAndSwapPointer (
    T ** destination,
    T * exchange,
    T * comparand )
```

Performs an atomic compare-and-exchange operation on the specified pointers. The function compares the original pointer against a given comparand pointer and exchanges the original pointer with a given exchange pointer in case of equality.

Parameters

<i>in, out</i>	<i>destination</i>	
<i>in</i>	<i>exchange</i>	The exchange pointer.
<i>in</i>	<i>comparand</i>	The pointer to compare to <i>destination</i> .

Returns

The function returns the initial pointer of *destination*.

4.1.2.7 BitsPerPixel()

```
size_t mage::BitsPerPixel (
    DXGI_FORMAT format )
```

Returns the number of bits per pixel of the given format.

Returns

The number of bits per pixel of the given format.

4.1.2.8 ComboBoxAdd()

```
void mage::ComboBoxAdd (
    HWND dialog,
    int id,
    const void * data,
    const wchar_t * desc )
```

Adds an item associated with the given data and described with the given descriptor to a combo box.

Parameters

<i>in</i>	<i>dialog</i>	A handle to the dialog box that contains the control.
<i>in</i>	<i>id</i>	The identifier of the control to be retrieved.
<i>in</i>	<i>data</i>	A pointer to the data of the item to add.
<i>in</i>	<i>desc</i>	The description of the item to add.

4.1.2.9 ComboBoxContains()

```
bool mage::ComboBoxContains (
    HWND dialog,
    int id,
    const wchar_t * desc )
```

Checks whether a combo box contains the given descriptor.

Parameters

in	<i>dialog</i>	A handle to the dialog box that contains the control.
in	<i>id</i>	The identifier of the control to be retrieved.
in	<i>desc</i>	The string description to check.

Returns

`true` if the given description is contained in the combo box. `false` otherwise.

4.1.2.10 ComboBoxCount()

```
int mage::ComboBoxCount (
    HWND dialog,
    int id )
```

Returns the number of items in a combo box.

Parameters

in	<i>dialog</i>	A handle to the dialog box that contains the control.
in	<i>id</i>	The identifier of the control to be retrieved.

Returns

The number of items of a combo box.

4.1.2.11 ComboBoxSelect() [1/2]

```
void mage::ComboBoxSelect (
    HWND dialog,
    int id,
    int index )
```

Selects the item at the given index in a combo box.

Parameters

in	<i>dialog</i>	A handle to the dialog box that contains the control.
in	<i>id</i>	The identifier of the control to be retrieved.
in	<i>index</i>	The index of the item.

4.1.2.12 ComboBoxSelect() [2/2]

```
void mage::ComboBoxSelect (
    HWND dialog,
```

```
int id,
const void * data )
```

Selects the item associated with the given data in a combo box.

Parameters

in	<i>dialog</i>	A handle to the dialog box that contains the control.
in	<i>id</i>	The identifier of the control to be retrieved.
in	<i>data</i>	A pointer to the data of the item.

4.1.2.13 ComboBoxSelected()

```
const void * mage::ComboBoxSelected (
    HWND dialog,
    int id )
```

Returns the data associated with the selected item in a combo box.

Parameters

in	<i>dialog</i>	A handle to the dialog box that contains the control.
in	<i>id</i>	The identifier of the control to be retrieved.

Returns

NULL if the combo box has no items.

A pointer to the data associated with the selected item in the combo box.

4.1.2.14 ComboBoxSomethingSelected()

```
bool mage::ComboBoxSomethingSelected (
    HWND dialog,
    int id )
```

Checks whether a valid item is selected in a combo box.

Parameters

in	<i>dialog</i>	A handle to the dialog box that contains the control.
in	<i>id</i>	The identifier of the control to be retrieved.

Returns

true if a valid item is selected in the combo box. false otherwise.

4.1.2.15 EnqueueTasks()

```
void mage::EnqueueTasks (
    const vector< Task * > & tasks )
```

Enqueues the given tasks.

Parameters

in	<i>tasks</i>	The tasks.
----	--------------	------------

4.1.2.16 Error()

```
void mage::Error (
    const char * format,
    ... )
```

Notifies an error message.

Parameters

in	<i>format</i>	Pointer to the message format.
----	---------------	--------------------------------

4.1.2.17 FindWordEnd()

```
const char* mage::FindWordEnd (
    const char * buffer )
```

Finds the end of a word.

Parameters

in	<i>buffer</i>	Pointer to the first character.
----	---------------	---------------------------------

Returns

Pointer to the end of the word. This means the pointer points to a space or null-terminating character.

4.1.2.18 FreeAligned()

```
void mage::FreeAligned (
    void * ptr )
```

Frees a block of memory that was allocated with [mage::AllocAligned\(size_t\)](#) or [mage::AllocAligned<T>\(uint32_t\)](#).

Parameters

in	<i>ptr</i>	A pointer to the memory block that was allocated.
----	------------	---

4.1.2.19 Info()

```
void mage::Info (
    const char * format,
    ... )
```

Notifies an info message.

Parameters

in	<i>format</i>	Pointer to the message format.
----	---------------	--------------------------------

4.1.2.20 NumberOfSystemCores()

```
uint32_t mage::NumberOfSystemCores ( )
```

Returns the number of system cores (i.e. logical processors).

Returns

The number of system cores (i.e. logical processors).

4.1.2.21 PrintConsoleHeader()

```
void mage::PrintConsoleHeader ( )
```

Prints the header of the engine to the console.

4.1.2.22 ProcessError()

```
void mage::ProcessError (
    const char * format,
    const va_list args,
    const string & error_type,
    int error_disposition )
```

Process the given error.

Parameters

in	<i>format</i>	The format of the error string.
in	<i>args</i>	The arguments of the format string.
in	<i>error_type</i>	The type of the error.
in	<i>error_disposition</i>	Disposition of the error.

4.1.2.23 SettingsDialogProcDelegate()

```
INT_PTR CALLBACK mage::SettingsDialogProcDelegate (
    HWND hwndDlg,
    UINT uMsg,
    WPARAM wParam,
    LPARAM lParam )
```

Engine-defined callback function used with the CreateDialog for device enumeration.

Parameters

in	<i>hwndDlg</i>	A handle to the dialog box.
in	<i>uMsg</i>	The message.
in	<i>wParam</i>	Additional message-specific information.
in	<i>lParam</i>	Additional message-specific information.

Returns

`true` if *uMsg* is processed. `false` otherwise.

4.1.2.24 Severe()

```
void mage::Severe (
    const char * format,
    ... )
```

Notifies a severe message.

Parameters

in	<i>format</i>	Pointer to the message format.
----	---------------	--------------------------------

4.1.2.25 task_entry()

```
static DWORD WINAPI mage::task_entry (
    LPVOID lpParameter ) [static]
```

An application-defined function that serves as the starting address for a thread.

Parameters

in	<i>lpParameter</i>	The thread data passed to the function using the <i>lpParameter</i> parameter of CreateThread.
----	--------------------	--

Returns

A value indicating success or failure.

4.1.2.26 TasksCleanup()

```
void mage::TasksCleanup ( )
```

Clean the tasks.

4.1.2.27 TasksInit()

```
void mage::TasksInit ( )
```

Initialize the tasks.

4.1.2.28 TerminalWidth()

```
int mage::TerminalWidth ( )
```

Returns the fixed terminal width.

Returns

The fixed terminal width.

4.1.2.29 WaitForAllTasks()

```
void mage::WaitForAllTasks ( )
```

Waits for all the tasks to finish.

4.1.2.30 Warning()

```
void mage::Warning (
    const char * format,
    ... )
```

Notifies a warning message.

Parameters

in	<i>format</i>	Pointer to the message format.
----	---------------	--------------------------------

4.1.2.31 WindowProc()

```
LRESULT CALLBACK mage::WindowProc (
    HWND hWnd,
    UINT msg,
```



```
WPARAM wParam,
LPARAM lParam )
```

The application-defined function that processes messages sent to the engine window. The WindowProc type defines a pointer to this callback function.

Parameters

in	<i>hWnd</i>	A handle to the window.
in	<i>msg</i>	The message.
in	<i>wParam</i>	Additional message information. The contents of this parameter depend on the value of <i>msg</i> .
in	<i>lParam</i>	Additional message information. The contents of this parameter depend on the value of <i>msg</i> .

Returns

The return value is the result of the message processing and depends on the message sent.

4.1.3 Variable Documentation

4.1.3.1 g_device_enumeration

```
DeviceEnumeration * mage::g_device_enumeration = NULL
```

A (global) pointer to the device enumeration.

4.1.3.2 g_driver_types

```
const D3D_DRIVER_TYPE mage::g_driver_types[ ]
```

Initial value:

```
= {
    D3D_DRIVER_TYPE_HARDWARE,
    D3D_DRIVER_TYPE_WARP,
    D3D_DRIVER_TYPE_REFERENCE
}
```

The supported driver types.

4.1.3.3 g_engine

```
Engine * mage::g_engine = NULL
```

The engine used by the user.

4.1.3.4 g_feature_levels

```
const D3D_FEATURE_LEVEL mage::g_feature_levels[ ]
```

Initial value:

```
= {
    D3D_FEATURE_LEVEL_11_1
}
```

The supported feature levels.

4.1.3.5 g_logging_configuration

```
LoggingConfiguration mage::g_logging_configuration
```

The logging configuration defined by the user and used by the engine.

4.1.3.6 g_pixel_formats

```
const DXGI_FORMAT mage::g_pixel_formats[ ]
```

Initial value:

```
= {
    DXGI_FORMAT_B5G5R5A1_UNORM,
    DXGI_FORMAT_B5G6R5_UNORM,
    DXGI_FORMAT_B8G8R8X8_UNORM,
    DXGI_FORMAT_B8G8R8A8_UNORM,
    DXGI_FORMAT_R10G10B10A2_UNORM,
}
```

The allowed pixel formats.

4.1.3.7 lvertex_input_element_desc

```
const D3D11_INPUT_ELEMENT_DESC mage::lvertex_input_element_desc[ ]
```

Initial value:

```
= {
    { "POSITION", 0, DXGI_FORMAT_R32G32B32_FLOAT, 0, UINT(offsetof(LVertex, p)),
      D3D11_INPUT_PER_VERTEX_DATA, 0 },
    { "DIFFUSE", 0, DXGI_FORMAT_R32G32B32A32_FLOAT, 0, UINT(offsetof(LVertex, diffuse)),
      D3D11_INPUT_PER_VERTEX_DATA, 0 },
    { "TEXCOORD", 0, DXGI_FORMAT_R32G32_FLOAT, 0, UINT(offsetof(LVertex, tex)),
      D3D11_INPUT_PER_VERTEX_DATA, 0 }
}
```

The input element descriptor for a [LVertex](#).

4.1.3.8 nb_unfinished_tasks

```
uint32_t mage::nb_unfinished_tasks [static]
```

The number of unfinished tasks.

4.1.3.9 task_queue

```
vector<Task *> mage::task_queue [static]
```

The task queue.

4.1.3.10 task_queue_mutex

```
Mutex* mage::task_queue_mutex = Mutex::Create() [static]
```

The mutex for exclusive access to the task queue.

4.1.3.11 tasks_running_condition

```
ConditionVariable* mage::tasks_running_condition [static]
```

The running condition variable for exclusive access to the number of unfinished tasks and for signaling on updates.

4.1.3.12 threads

```
HANDLE* mage::threads [static]
```

The thread handles.

4.1.3.13 tlvertex_input_element_desc

```
const D3D11_INPUT_ELEMENT_DESC mage::tlvertex_input_element_desc[]
```

Initial value:

```
= {
    { "POSITION", 0, DXGI_FORMAT_R32G32B32A32_FLOAT, 0, UINT(offsetof(TLVertex, p)),
      D3D11_INPUT_PER_VERTEX_DATA, 0 },
    { "DIFFUSE", 0, DXGI_FORMAT_R32G32B32A32_FLOAT, 0, UINT(offsetof(TLVertex, diffuse)),
      D3D11_INPUT_PER_VERTEX_DATA, 0 },
    { "TEXCOORD", 0, DXGI_FORMAT_R32G32_FLOAT, 0, UINT(offsetof(TLVertex, tex)),
      D3D11_INPUT_PER_VERTEX_DATA, 0 }
}
```

The input element descriptor for a [TLVertex](#)

4.1.3.14 vertex_input_element_desc

```
const D3D11_INPUT_ELEMENT_DESC mage::vertex_input_element_desc[ ]
```

Initial value:

```
= {  
    { "POSITION", 0, DXGI_FORMAT_R32G32B32_FLOAT, 0, UINT(offsetof(Vertex, p)),  
      D3D11_INPUT_PER_VERTEX_DATA, 0 },  
    { "NORMAL", 0, DXGI_FORMAT_R32G32B32_FLOAT, 0, UINT(offsetof(Vertex, n)),  
      D3D11_INPUT_PER_VERTEX_DATA, 0 },  
    { "TEXCOORD", 0, DXGI_FORMAT_R32G32_FLOAT, 0, UINT(offsetof(Vertex, tex)),  
      D3D11_INPUT_PER_VERTEX_DATA, 0 }  
}
```

The input element descriptor for a [Vertex](#).

4.1.3.15 worker_semaphore

```
Semaphore* mage::worker_semaphore [static]
```

The worker semaphore for being able to work.

Chapter 5

Class Documentation

5.1 mage::AABB Struct Reference

```
#include <geometry.hpp>
```

Public Member Functions

- [AABB](#) ()
- [AABB](#) (XMFLOAT3 [p_min](#), XMFLOAT3 [p_max](#))
- bool [Encloses](#) (const [AABB](#) &aabb) const
- bool [Encloses](#) (const [Face](#) &face) const
- bool [EnclosedBy](#) (const list< XMFLOAT4 > &planes) const

Public Attributes

- XMFLOAT3 [p_min](#)
- XMFLOAT3 [p_max](#)

5.1.1 Detailed Description

A struct of Axis-Aligned Bounding Boxes (AABBs).

5.1.2 Constructor & Destructor Documentation

5.1.2.1 [AABB\(\)](#) [1/2]

```
mage::AABB::AABB ( )
```

Constructs an [AABB](#).

5.1.2.2 [AABB\(\)](#) [2/2]

```
mage::AABB::AABB (
    XMFLOAT3 p\_min,
    XMFLOAT3 p\_max )
```

Constructs an [AABB](#).

Parameters

in	<i>p_min</i>	The minimum extents.
in	<i>p_max</i>	The maximum extents.

5.1.3 Member Function Documentation

5.1.3.1 EnclosedBy()

```
bool mage::AABB::EnclosedBy (
    const list< XMFLLOAT4 > & planes ) const
```

Checks whether this [AABB](#) is completely enclosed by the given (closed) volume.

Parameters

in	<i>planes</i>	A reference to a linked list containing the planes of the volume (each plane's coefficients are represented as a XMFLLOAT4).
----	---------------	--

Returns

`true` if this [AABB](#) is completely enclosed by *planes*. `false` otherwise.

5.1.3.2 Encloses() [1/2]

```
bool mage::AABB::Encloses (
    const AABB & aabb ) const
```

Checks whether this [AABB](#) completely encloses the given [AABB](#).

Parameters

in	<i>aabb</i>	A reference to the AABB .
----	-------------	---

Returns

`true` if this [AABB](#) completely encloses *aabb*. `false` otherwise.

5.1.3.3 Encloses() [2/2]

```
bool mage::AABB::Encloses (
    const Face & face ) const
```

Checks whether this [AABB](#) completely encloses the given face.

Parameters

<code>in</code>	<code>face</code>	A reference to the face.
-----------------	-------------------	--------------------------

Returns

`true` if this [AABB](#) completely encloses `face`. `false` otherwise.

5.1.4 Member Data Documentation

5.1.4.1 `p_max`

```
XMFLOAT3 mage::AABB::p_max
```

The maximum extents of this [AABB](#).


5.1.4.2 `p_min`

```
XMFLOAT3 mage::AABB::p_min
```

The minimum extents of this [AABB](#).

5.2 `mage::Variable::AbstractValue` Struct Reference

Inheritance diagram for `mage::Variable::AbstractValue`:



Public Member Functions

- virtual `~AbstractValue()`
- virtual `const void * GetValue()` `const =0`

5.2.1 Detailed Description

A struct of abstract values.

Note

This is an example of the Type Erasure pattern for templates. We need to keep the original type to ensure the right destructor can be called in case of non-primitive types.

5.2.2 Constructor & Destructor Documentation

5.2.2.1 `~AbstractValue()`

```
virtual mage::Variable::AbstractValue::~~AbstractValue ( ) [virtual]
```

Destructs this value.

5.2.3 Member Function Documentation

5.2.3.1 `GetValue()`

```
virtual const void* mage::Variable::AbstractValue::GetValue ( ) const [pure virtual]
```

Returns the value of this value.

Returns

A pointer to the value of this value.

Implemented in [mage::Variable::Value< T >](#).

5.3 `mage::ConditionVariable` Class Reference

```
#include <lock.hpp>
```

Public Member Functions

- [ConditionVariable](#) ()
- [~ConditionVariable](#) ()
- void [Lock](#) ()
- void [Unlock](#) ()
- void [Wait](#) ()
- void [Signal](#) ()

Private Types

- enum { [SIGNAL](#) = 0, [BROADCAST](#) = 1, [NUM_EVENTS](#) = 2 }

Private Attributes

- uint32_t [m_nb_waiters](#)
- CRITICAL_SECTION [m_nb_waiters_mutex](#)
- CRITICAL_SECTION [m_condition_mutex](#)
- HANDLE [m_events](#) [[NUM_EVENTS](#)]

5.3.1 Detailed Description

A class of condition variables.

5.3.2 Member Enumeration Documentation

5.3.2.1 anonymous enum

```
anonymous enum [private]
```

Type of events (indices).

Enumerator

SIGNAL	
BROADCAST	
NUM_EVENTS	

5.3.3 Constructor & Destructor Documentation

5.3.3.1 `ConditionVariable()`

```
mage::ConditionVariable::ConditionVariable ( )
```

Constructs a condition variable.

5.3.3.2 `~ConditionVariable()`

```
mage::ConditionVariable::~~ConditionVariable ( )
```

Destructs this condition variable.

5.3.4 Member Function Documentation

5.3.4.1 `Lock()`

```
void mage::ConditionVariable::Lock ( )
```

Locks this condition variable.

5.3.4.2 `Signal()`

```
void mage::ConditionVariable::Signal ( )
```

Signal a condition change.

5.3.4.3 `Unlock()`

```
void mage::ConditionVariable::Unlock ( )
```

Unlocks this condition variable.

5.3.4.4 `Wait()`

```
void mage::ConditionVariable::Wait ( )
```

Wait for a signal indicating a condition change.

5.3.5 Member Data Documentation

5.3.5.1 m_condition_mutex

```
CRITICAL_SECTION mage::ConditionVariable::m_condition_mutex [private]
```

The critical section object for the mutex guarding the condition of this condition variable.

5.3.5.2 m_events

```
HANDLE mage::ConditionVariable::m_events[NUM\_EVENTS] [private]
```

Signal and broadcast event handles of this condition variable.

5.3.5.3 m_nb_waiters

```
uint32_t mage::ConditionVariable::m_nb_waiters [private]
```

The number of waiters of this condition variable.

5.3.5.4 m_nb_waiters_mutex

```
CRITICAL_SECTION mage::ConditionVariable::m_nb_waiters_mutex [private]
```

The critical section object for the mutex guarding m_nb_waiters of this condition variable.

5.4 mage::DeviceEnumeration Class Reference

```
#include <device_enumeration.hpp>
```

Public Member Functions

- DXGIAdapter2 * [GetAdapter](#) () const
- const DXGI_MODE_DESC1 * [GetDisplayMode](#) () const
- bool [IsWindowed](#) () const
- bool [IsFullScreen](#) () const
- bool [IsVSynched](#) () const

Protected Member Functions

- [DeviceEnumeration](#) ()
- [~DeviceEnumeration](#) ()
- HRESULT [Enumerate](#) ()
- INT_PTR [SettingsDialogProc](#) (HWND hwndDlg, UINT uMsg, WPARAM wParam, LPARAM lParam)

Protected Attributes

- IDXGIAAdapter2 * [m_adapter](#)
- [VariableScript](#) * [m_settings_script](#)
- list< DXGI_MODE_DESC1 > [m_display_modes](#)
- DXGI_MODE_DESC1 [m_selected_display_mode](#)
- bool [m_windowed](#)
- bool [m_vsync](#)

Friends

- class [Engine](#)
- INT_PTR CALLBACK [SettingsDialogProcDelegate](#) (HWND hwndDlg, UINT uMsg, WPARAM wParam, LPARAM lParam)

5.4.1 Detailed Description

A device enumeration.

5.4.2 Constructor & Destructor Documentation

5.4.2.1 DeviceEnumeration()

```
mage::DeviceEnumeration::DeviceEnumeration ( ) [protected]
```

Constructs a device enumeration.

5.4.2.2 ~DeviceEnumeration()

```
mage::DeviceEnumeration::~~DeviceEnumeration ( ) [protected]
```

Destructs this device enumeration.

5.4.3 Member Function Documentation

5.4.3.1 Enumerate()

```
HRESULT mage::DeviceEnumeration::Enumerate ( ) [protected]
```

Enumerates the available display modes on the adapter output of the physical adapter with the most dedicated video memory.

Returns

A success/error value.

5.4.3.2 GetAdapter()

```
IDXGIAAdapter2* mage::DeviceEnumeration::GetAdapter ( ) const
```

Returns the adapter.

Returns

A pointer to the adapter.

5.4.3.3 GetDisplayMode()

```
const DXGI_MODE_DESC1* mage::DeviceEnumeration::GetDisplayMode ( ) const
```

Returns the selected display mode by the user.

Returns

A pointer to the selected display mode.

5.4.3.4 IsFullScreen()

```
bool mage::DeviceEnumeration::IsFullScreen ( ) const
```

Check whether the application should run in full screen mode.

Returns

`true` if the application should run in full screen mode. `false` otherwise.

5.4.3.5 IsVSynced()

```
bool mage::DeviceEnumeration::IsVSynced ( ) const
```

Check whether v-sync should be enabled.

Returns

`true` if v-sync should be enabled. `false` otherwise.

5.4.3.6 IsWindowed()

```
bool mage::DeviceEnumeration::IsWindowed ( ) const
```

Check whether the application should run in windowed mode.

Returns

`true` if the application should run in windowed mode. `false` otherwise.

5.4.3.7 SettingsDialogProc()

```
INT_PTR mage::DeviceEnumeration::SettingsDialogProc (
    HWND hwndDlg,
    UINT uMsg,
    WPARAM wParam,
    LPARAM lParam ) [protected]
```

Engine-defined callback function used with the `CreateDialog` for device enumeration.

Parameters

in	<i>hwndDlg</i>	A handle to the dialog box.
in	<i>uMsg</i>	The message.
in	<i>wParam</i>	Additional message-specific information.
in	<i>lParam</i>	Additional message-specific information.

Returns

true if *uMsg* is processed. false otherwise.

5.4.4 Friends And Related Function Documentation**5.4.4.1 Engine**

```
friend class Engine [friend]
```

5.4.4.2 SettingsDialogProcDelegate

```
INT_PTR CALLBACK SettingsDialogProcDelegate (
    HWND hwndDlg,
    UINT uMsg,
    WPARAM wParam,
    LPARAM lParam ) [friend]
```

Engine-defined callback function used with the CreateDialog for device enumeration.

Parameters

in	<i>hwndDlg</i>	A handle to the dialog box.
in	<i>uMsg</i>	The message.
in	<i>wParam</i>	Additional message-specific information.
in	<i>lParam</i>	Additional message-specific information.

Returns

true if *uMsg* is processed. false otherwise.

5.4.5 Member Data Documentation**5.4.5.1 m_adapter**

```
IDXGIAdapter2* mage::DeviceEnumeration::m_adapter [protected]
```

A pointer to the adapter (or video card).

5.4.5.2 m_display_modes

```
list< DXGI_MODE_DESC1 > mage::DeviceEnumeration::m_display_modes [protected]
```

The linked list of enumerated display modes.

5.4.5.3 m_selected_display_mode

```
DXGI_MODE_DESC1 mage::DeviceEnumeration::m_selected_display_mode [protected]
```

The selected display mode by the user.

5.4.5.4 m_settings_script

```
VariableScript* mage::DeviceEnumeration::m_settings_script [protected]
```

A pointer to the script which stores the device configuration.

5.4.5.5 m_vsync

```
bool mage::DeviceEnumeration::m_vsync [protected]
```

Flag indicating whether v-sync should be enabled.

5.4.5.6 m_windowed

```
bool mage::DeviceEnumeration::m_windowed [protected]
```

Flag indicating whether the application should run in windowed mode.

5.5 mage::Edge Struct Reference

```
#include <geometry.hpp>
```

Public Member Functions

- [Edge](#) ([Vertex](#) *v0, [Vertex](#) *v1)

Public Attributes

- [Vertex](#) * v0
- [Vertex](#) * v1

5.5.1 Detailed Description

A struct of edges.

5.5.2 Constructor & Destructor Documentation

5.5.2.1 Edge()

```
mage::Edge::Edge (
    Vertex * v0,
    Vertex * v1 )
```

Constructs an edge between the two given vertices.

Parameters

in	<i>v0</i>	A pointer to the first vertex.
in	<i>v1</i>	A pointer to the second vertex.

5.5.3 Member Data Documentation

5.5.3.1 v0

`Vertex*` `mage::Edge::v0`

The first vertex of this edge.

5.5.3.2 v1


`Vertex*` `mage::Edge::v1`

The second vertex of this edge.

5.6 mage::Engine Class Reference

```
#include <engine.hpp>
```

Inheritance diagram for `mage::Engine`:



Public Member Functions

- `Engine` (const `EngineSetup` *setup=NULL)
- virtual `~Engine` ()
- void `Run` (int nCmdShow=SW_NORMAL)
- HWND `GetWindow` () const
- void `SetDeactiveFlag` (bool deactive)
- `Renderer` * `GetRenderer` () const
- `StateManager` * `GetStateManager` () const
- `ResourceManager`< `VariableScript` > * `GetScriptManager` () const
- const `Input` * `GetInput` () const

Protected Member Functions

- HRESULT [InitializeWindow](#) ()
- HRESULT [UninitializeWindow](#) ()
- HRESULT [InitializeConsole](#) ()
- HRESULT [InitializeSystems](#) ()
- HRESULT [UninitializeSystems](#) ()

Protected Attributes

- [EngineSetup](#) * [m_setup](#)
- HWND [m_hwindow](#)
- bool [m_deactive](#)
- [Renderer](#) * [m_renderer](#)
- [StateManager](#) * [m_state_manager](#)
- [ResourceManager](#)< [VariableScript](#) > * [m_script_manager](#)
- [Input](#) * [m_input](#)

Additional Inherited Members

5.6.1 Detailed Description

A class of engines.

5.6.2 Constructor & Destructor Documentation

5.6.2.1 Engine()

```
mage::Engine::Engine (
    const EngineSetup * setup = NULL )
```

Constructs an engine from the given engine setup.

Parameters

in	<i>setup</i>	A pointer to an engine setup.
----	--------------	-------------------------------

5.6.2.2 ~Engine()

```
mage::Engine::~~Engine ( ) [virtual]
```

Destructs this engine.

5.6.3 Member Function Documentation

5.6.3.1 GetInput()

```
const Input* mage::Engine::GetInput ( ) const
```

Returns the input object of this engine.

Returns

A pointer to the input object of this engine.

5.6.3.2 GetRenderer()

```
Renderer* mage::Engine::GetRenderer ( ) const
```

Returns the renderer of this engine.

Returns

A pointer to the renderer of this engine.

5.6.3.3 GetScriptManager()

```
ResourceManager< VariableScript >* mage::Engine::GetScriptManager ( ) const
```

Returns the script manager of this engine.

Returns

A pointer to the script manager of this engine.

5.6.3.4 GetStateManager()

```
StateManager* mage::Engine::GetStateManager ( ) const
```

Returns the state manager of this engine.

Returns

A pointer to the state manager of this engine.

5.6.3.5 GetWindow()

```
HWND mage::Engine::GetWindow ( ) const
```

Returns a handle to the window of this engine.

Returns

A handle to the window of this engine.

5.6.3.6 InitializeConsole()

```
HRESULT mage::Engine::InitializeConsole ( ) [protected]
```

Allocates a console to this engine for basic io and redirects stdin, stdout and stderr to the allocated console.

Returns

A success/error value.

5.6.3.7 InitializeSystems()

```
HRESULT mage::Engine::InitializeSystems ( ) [protected]
```

Initializes the different systems of this engine.

Returns

A success/error value.

5.6.3.8 InitializeWindow()

```
HRESULT mage::Engine::InitializeWindow ( ) [protected]
```

Initializes the engine window of this engine.

Returns

A success/error value.

5.6.3.9 Run()

```
void mage::Engine::Run (
    int nCmdShow = SW_NORMAL )
```

Runs this engine.

Parameters

in	<i>nCmdShow</i>	Controls how the engine window is to be shown.
----	-----------------	--

5.6.3.10 SetDeactiveFlag()

```
void mage::Engine::SetDeactiveFlag (
    bool deactive )
```

Sets the deactive flag of this engine to the given value.

Parameters

in	<i>deactive</i>	The new value for the deactive flag.
----	-----------------	--------------------------------------

5.6.3.11 UninitializeSystems()

```
HRESULT mage::Engine::UninitializeSystems ( ) [protected]
```

Unitalize the different systems of this engine.

Returns

A success/error value.

5.6.3.12 UninitializeWindow()

```
HRESULT mage::Engine::UninitializeWindow ( ) [protected]
```

Unitalizes the engine window of this engine.

Returns

A success/error value.

5.6.4 Member Data Documentation**5.6.4.1 m_deactive**

```
bool mage::Engine::m_deactive [protected]
```

Flag indicating whether the application is active or not.

5.6.4.2 m_hwindow

```
HWND mage::Engine::m_hwindow [protected]
```

Main window handle of this engine.

5.6.4.3 m_input

```
Input* mage::Engine::m_input [protected]
```

A pointer to the input object of this engine.

5.6.4.4 m_renderer

`Renderer* mage::Engine::m_renderer` [protected]

A pointer to the renderer of this engine.

5.6.4.5 m_script_manager

`ResourceManager< VariableScript >* mage::Engine::m_script_manager` [protected]

A pointer the script manager of this engine

5.6.4.6 m_setup

`EngineSetup* mage::Engine::m_setup` [protected]

Pointer to a copy of the engine setup structure.

5.6.4.7 m_state_manager

`StateManager* mage::Engine::m_state_manager` [protected]

A pointer to the state manager of this engine.

5.7 mage::EngineSetup Struct Reference

```
#include <engine.hpp>
```

Public Member Functions

- [EngineSetup](#) (const wstring &name=L"Application")
- [EngineSetup](#) (const [EngineSetup](#) *setup)

Public Attributes

- HINSTANCE [m_hinstance](#)
- wstring [m_name](#)
- void(* [StateSetup](#))()

5.7.1 Detailed Description

A struct of engine setups.

5.7.2 Constructor & Destructor Documentation

5.7.2.1 EngineSetup() [1/2]

```
mage::EngineSetup::EngineSetup (
    const wstring & name = L"Application" )
```

Constructs an engine setup with the given application name.

Parameters

in	<i>name</i>	A reference to the name of the application.
----	-------------	---

5.7.2.2 EngineSetup() [2/2]

```
mage::EngineSetup::EngineSetup (
    const EngineSetup * setup )
```

Constructs an engine setup from the given engine setup.

Precondition

setup does not point to NULL.

Parameters

in	<i>setup</i>	A pointer to the engine setup.
----	--------------	--------------------------------

5.7.3 Member Data Documentation**5.7.3.1 m_hinstance**

```
HINSTANCE mage::EngineSetup::m_hinstance
```

Application instance handle.

5.7.3.2 m_name

```
wstring mage::EngineSetup::m_name
```

Name of the application.

5.7.3.3 StateSetup

```
void(* mage::EngineSetup::StateSetup) ()
```

The state setup function.

5.8 mage::Face Struct Reference

```
#include <geometry.hpp>
```

Public Member Functions

- [Face](#) ([Vertex](#) *v0, [Vertex](#) *v1, [Vertex](#) *v2)

Public Attributes

- [Vertex](#) * v0
- [Vertex](#) * v1
- [Vertex](#) * v2

5.8.1 Detailed Description

A struct of faces.

5.8.2 Constructor & Destructor Documentation

5.8.2.1 Face()

```
mage::Face::Face (
    Vertex * v0,
    Vertex * v1,
    Vertex * v2 )
```

Constructs a face for the three given vertices.

Parameters

in	v0	A pointer to the first vertex.
in	v1	A pointer to the second vertex.
in	v2	A pointer to the third vertex.

5.8.3 Member Data Documentation

5.8.3.1 v0

```
Vertex* mage::Face::v0
```

The first vertex of this face.

5.8.3.2 v1

```
Vertex* mage::Face::v1
```

The second vertex of this face.

5.8.3.3 v2

`Vertex* mage::Face::v2`

The third vertex of this face.

5.9 mage::Font Class Reference

```
#include <font.hpp>
```

Public Member Functions

- [Font](#) (const wstring &name=L"Arial", uint16_t size=10, uint32_t bold=FW_NORMAL, bool italic=false)
- virtual [~Font](#) ()
- void [Render](#) (char *text, float x, float y, XMFLOAT4 colour=XMFLOAT4(1.0f, 1.0f, 1.0f, 1.0f))

Private Member Functions

- bool [PrepareFont](#) (HDC hDC, bool measure=false)

Private Attributes

- ID3D11Buffer * [m_vb](#)
- ID3D11Texture2D * [m_texture](#)
- uint32_t [m_texture_width](#)
- uint32_t [m_texture_height](#)
- float [m_texture_coords](#) [96][4]
- uint16_t [m_spacing](#)

5.9.1 Constructor & Destructor Documentation

5.9.1.1 Font()

```
mage::Font::Font (
    const wstring & name = L"Arial",
    uint16_t size = 10,
    uint32_t bold = FW_NORMAL,
    bool italic = false )
```

5.9.1.2 ~Font()

```
virtual mage::Font::~Font ( ) [virtual]
```


5.9.2 Member Function Documentation

5.9.2.1 PrepareFont()

```
bool mage::Font::PrepareFont (
    HDC hDC,
    bool measure = false ) [private]
```

5.9.2.2 Render()

```
void mage::Font::Render (
    char * text,
    float x,
    float y,
    XMFLOAT4 colour = XMFLOAT4(1.0f, 1.0f, 1.0f, 1.0f) )
```

5.9.3 Member Data Documentation

5.9.3.1 m_spacing

```
uint16_t mage::Font::m_spacing [private]
```

5.9.3.2 m_texture

```
ID3D11Texture2D* mage::Font::m_texture [private]
```

5.9.3.3 m_texture_coords

```
float mage::Font::m_texture_coords[96][4] [private]
```

5.9.3.4 m_texture_height

```
uint32_t mage::Font::m_texture_height [private]
```

5.9.3.5 m_texture_width

```
uint32_t mage::Font::m_texture_width [private]
```

5.9.3.6 m_vb

```
ID3D11Buffer* mage::Font::m_vb [private]
```

5.10 mage::IndexedEdge Struct Reference

```
#include <geometry.hpp>
```

Public Attributes

- uint32_t [iv0](#)
- uint32_t [iv1](#)

5.10.1 Detailed Description

A struct of indexed edges.

5.10.2 Member Data Documentation

5.10.2.1 iv0

```
uint32_t mage::IndexedEdge::iv0
```

The index of the edge's first vertex.

5.10.2.2 iv1

```
uint32_t mage::IndexedEdge::iv1
```

The index of the edge's second vertex.

5.11 mage::IndexedFace Struct Reference

```
#include <geometry.hpp>
```

Public Attributes

- uint32_t [iv0](#)
- uint32_t [iv1](#)
- uint32_t [iv2](#)

5.11.1 Detailed Description

A struct of indexed faces.

5.11.2 Member Data Documentation

5.11.2.1 iv0

```
uint32_t mage::IndexedFace::iv0
```

Index of the face's first vertex.

5.11.2.2 iv1

```
uint32_t mage::IndexedFace::iv1
```

Index of the face's second vertex.

5.11.2.3 iv2


```
uint32_t mage::IndexedFace::iv2
```

Index of the face's third vertex.

5.12 mage::Input Class Reference

```
#include <input.hpp>
```

Inheritance diagram for mage::Input:



Public Member Functions

- bool [GetKeyPress](#) (char key, bool ignore_press_stamp=false) const
- bool [GetMouseButtonPress](#) (char mouse_button, bool ignore_press_stamp=false) const
- long [GetPosX](#) () const
- long [GetPosY](#) () const
- long [GetDeltaX](#) () const
- long [GetDeltaY](#) () const
- long [GetDeltaWheel](#) () const

Protected Member Functions

- [Input](#) (HWND hwnd)
- virtual [~Input](#) ()
- HRESULT [InitializeDI](#) ()
- HRESULT [UninitializeDI](#) ()
- HRESULT [InitializeKeyboard](#) ()
- HRESULT [UninitializeKeyboard](#) ()
- HRESULT [InitializeMouse](#) ()
- HRESULT [UninitializeMouse](#) ()
- void [Update](#) ()

Protected Attributes

- HWND [m_hwindow](#)
- IDirectInput8 * [m_di](#)
- uint64_t [m_press_stamp](#)
- IDirectInputDevice8 * [m_keyboard](#)
- char [m_key_state](#) [256]
- uint64_t [m_key_press_stamp](#) [256]
- IDirectInputDevice8 * [m_mouse](#)
- DIMOUSESTATE [m_mouse_state](#)
- uint64_t [m_mouse_button_press_stamp](#) [3]
- POINT [m_mouse_position](#)

Friends

- class [Engine](#)

Additional Inherited Members

5.12.1 Detailed Description

A class of input objects.

5.12.2 Constructor & Destructor Documentation

5.12.2.1 Input()

```
mage::Input::Input (
    HWND hwnd ) [protected]
```

Constructs an input for the given window handle.

Parameters

<code>in</code>	<code><i>hwnd</i></code>	The handle of the parent window.
-----------------	--------------------------	----------------------------------

5.12.2.2 ~Input()

```
mage::Input::~~Input ( ) [protected], [virtual]
```

Destructs this input object.

5.12.3 Member Function Documentation

5.12.3.1 GetDeltaWheel()

```
long mage::Input::GetDeltaWheel ( ) const
```

Returns the change in the mouse's scroll wheel.

Returns

The change in the mouse's mouse's scroll wheel.

5.12.3.2 GetDeltaX()

```
long mage::Input::GetDeltaX ( ) const
```

Returns the change in the mouse's horizontal coordinate.

Returns

The change in the mouse's horizontal coordinate.

5.12.3.3 GetDeltaY()

```
long mage::Input::GetDeltaY ( ) const
```

Returns the change in the mouse's vertical coordinate.

Returns

The change in the mouse's vertical coordinate.

5.12.3.4 GetKeyPress()

```
bool mage::Input::GetKeyPress (
    char key,
    bool ignore_press_stamp = false ) const
```

Checks whether the given key is pressed.

Parameters

in	<i>key</i>	The key.
in	<i>ignore_press_stamp</i>	Flag indicating whether press stamps should be ignored. Consistent presses will return false when using the press stamp.

Returns

true if the given key is pressed. false otherwise.

5.12.3.5 GetMouseButtonPress()

```
bool mage::Input::GetMouseButtonPress (
    char mouse_button,
    bool ignore_press_stamp = false ) const
```

Checks whether the given mouse button is pressed.

Parameters

in	<i>mouse_button</i>	The mouse button.
in	<i>ignore_press_stamp</i>	Flag indicating whether press stamps should be ignored. Consistent presses will return false when using the press stamp.

Returns

true if the given mouse button is pressed. false otherwise.

5.12.3.6 GetPosX()

```
long mage::Input::GetPosX ( ) const
```

Returns the horizontal position of the mouse.

Returns

The horizontal position of the mouse.

5.12.3.7 GetPosY()

```
long mage::Input::GetPosY ( ) const
```

Returns the vertical position of the mouse.

Returns

The vertical position of the mouse.

5.12.3.8 InitializeDI()

```
HRESULT mage::Input::InitializeDI ( ) [protected]
```

Initializes the DirectInput object of this input.

Returns

A success/error value.

5.12.3.9 InitializeKeyboard()

```
HRESULT mage::Input::InitializeKeyboard ( ) [protected]
```

Initializes the keyboard of this input.

Returns

A success/error value.

5.12.3.10 InitializeMouse()

```
HRESULT mage::Input::InitializeMouse ( ) [protected]
```

Initializes the mouse of this input.

Returns

A success/error value.

5.12.3.11 UninitializeDI()

```
HRESULT mage::Input::UninitializeDI ( ) [protected]
```

Uninitializes the DirectInput object of this input.

Returns

A success/error value.

5.12.3.12 UninitializeKeyboard()

```
HRESULT mage::Input::UninitializeKeyboard ( ) [protected]
```

Uninitializes the keyboard of this input.

Returns

A success/error value.

5.12.3.13 UninitializeMouse()

```
HRESULT mage::Input::UninitializeMouse ( ) [protected]
```

Uninitializes the mouse of this input.

Returns

A success/error value.

5.12.3.14 Update()

```
void mage::Input::Update ( ) [protected]
```

Updates the state of both the keyboard and mouse device of this input object.

5.12.4 Friends And Related Function Documentation

5.12.4.1 Engine

```
friend class Engine [friend]
```

5.12.5 Member Data Documentation

5.12.5.1 m_di

```
IDirectInput8* mage::Input::m_di [protected]
```

The DirectInput object.

The methods of the IDirectInput8 interface are used to enumerate, create, and retrieve the status of Microsoft DirectInput device.

5.12.5.2 m_hwindow

```
HWND mage::Input::m_hwindow [protected]
```

The handle of the parent window.

5.12.5.3 m_key_press_stamp

```
uint64_t mage::Input::m_key_press_stamp[256] [mutable], [protected]
```

Stamps the keys pressed in the last frame.

5.12.5.4 m_key_state

```
char mage::Input::m_key_state[256] [protected]
```

[State](#) of the keys.

5.12.5.5 m_keyboard

```
IDirectInputDevice8* mage::Input::m_keyboard [protected]
```

The DirectInput keyboard device.

The methods of the IDirectInputDevice8 interface are used to gain and release access to Microsoft DirectInput devices, manage device properties and information, set behavior, perform initialization, create and play force-feedback effects, and invoke a device's control panel.

5.12.5.6 m_mouse

```
IDirectInputDevice8* mage::Input::m_mouse [protected]
```

DirectInput mouse device.

The methods of the IDirectInputDevice8 interface are used to gain and release access to Microsoft DirectInput devices, manage device properties and information, set behavior, perform initialization, create and play force-feedback effects, and invoke a device's control panel.

5.12.5.7 m_mouse_button_press_stamp

```
uint64_t mage::Input::m_mouse_button_press_stamp[3] [mutable], [protected]
```

Stamps the mouse buttons pressed in the last frame.

5.12.5.8 m_mouse_position

```
POINT mage::Input::m_mouse_position [protected]
```

The position of the mouse cursor on the screen.

5.12.5.9 m_mouse_state

```
DIMOUSESTATE mage::Input::m_mouse_state [protected]
```

[State](#) of the mouse buttons.

Describes the state of a mouse device that has up to four buttons, or another device that is being accessed as if it were a mouse device.

5.12.5.10 m_press_stamp


```
uint64_t mage::Input::m_press_stamp [protected]
```

The current press stamp (incremented every frame).

5.13 mage::Loadable Class Reference

```
#include <loadable.hpp>
```

Inheritance diagram for mage::Loadable:



Public Member Functions

- bool [IsLoaded](#) () const

Protected Member Functions

- [Loadable](#) (bool loaded=false)
- virtual [~Loadable](#) ()
- void [SetLoaded](#) (bool loaded=true)

Private Attributes

- bool [m_loaded](#)

5.13.1 Detailed Description

A class of loadables.

5.13.2 Constructor & Destructor Documentation

5.13.2.1 Loadable()

```
mage::Loadable::Loadable (
    bool loaded = false ) [protected]
```

Constructs a loadable.

Parameters

<i>in</i>	<i>loaded</i>	Flag indicating wether the loadable is loaded.
-----------	---------------	--

5.13.2.2 ~Loadable()

```
virtual mage::Loadable::~~Loadable ( ) [protected], [virtual]
```

Destructs this loadable.

5.13.3 Member Function Documentation**5.13.3.1 IsLoaded()**

```
bool mage::Loadable::IsLoaded ( ) const
```

Checks wether this loadable is loaded.

Returns

`true` if this loadable is loaded. `false` otherwise.

5.13.3.2 SetLoaded()

```
void mage::Loadable::SetLoaded (
    bool loaded = true ) [protected]
```

Set the state of this loadable to the given value.

Parameters

<i>in</i>	<i>loaded</i>	Flag indicating wether this loadable is loaded.
-----------	---------------	---

5.13.4 Member Data Documentation**5.13.4.1 m_loaded**

```
bool mage::Loadable::m_loaded [private]
```

Flag indicating wether this loadable is loaded.

5.14 mage::LoggingConfiguration Struct Reference

```
#include <logging.hpp>
```

Public Member Functions

- [LoggingConfiguration](#) ()
- bool [IsQuiet](#) () const
- bool [IsVerbose](#) () const

Private Attributes

- bool [m_quiet](#)
- bool [m_verbose](#)

5.14.1 Detailed Description

A struct of logging configurations of the engine processing.

5.14.2 Constructor & Destructor Documentation

5.14.2.1 LoggingConfiguration()

```
mage::LoggingConfiguration::LoggingConfiguration ( )
```

Constructs a new logging configuration.

5.14.3 Member Function Documentation

5.14.3.1 IsQuiet()

```
bool mage::LoggingConfiguration::IsQuiet ( ) const
```

Checks whether the logging of the engine processing is quiet.

Returns

`true` if the logging of the engine processing is quiet. `false` otherwise.

5.14.3.2 IsVerbose()

```
bool mage::LoggingConfiguration::IsVerbose ( ) const
```

Checks wheter the logging of the engine processing is verbose.

Returns

`true` if the logging of the engine processing is verbose. `false` otherwise.

5.14.4 Member Data Documentation

5.14.4.1 m_quiet

```
bool mage::LoggingConfiguration::m_quiet [private]
```

Flag indicating the logging of the engine processing is quiet.

5.14.4.2 m_verbose

```
bool mage::LoggingConfiguration::m_verbose [private]
```

Flag indicating the logging of the engine processing is verbose.

5.15 mage::LVertex Struct Reference

```
#include <geometry.hpp>
```

Public Member Functions

- [LVertex](#) ()
- [LVertex](#) (XMFLOAT3 [p](#), XMFLOAT4 [diffuse](#), XMFLOAT2 [tex](#))

Public Attributes

- XMFLOAT3 [p](#)
- XMFLOAT4 [diffuse](#)
- XMFLOAT2 [tex](#)

5.15.1 Detailed Description

A struct of lit vertices.

5.15.2 Constructor & Destructor Documentation

5.15.2.1 LVertex() [1/2]

```
mage::LVertex::LVertex ( )
```

Constructs a lit vertex.

5.15.2.2 LVertex() [2/2]

```
mage::LVertex::LVertex (
    XMFLOAT3 p,
    XMFLOAT4 diffuse,
    XMFLOAT2 tex )
```

Constructs a lit vertex.

Parameters

in	<i>p</i>	The position of the lit vertex (in object space).
in	<i>diffuse</i>	The diffuse colour of the lit vertex.
in	<i>tex</i>	The texture coordinate of the lit vertex.

5.15.3 Member Data Documentation

5.15.3.1 diffuse

XMFLOAT4 mage::LVertex::diffuse

The diffuse colour of this lit vertex.

5.15.3.2 p

XMFLOAT3 mage::LVertex::p

The position of this lit vertex (in object space).

5.15.3.3 tex

XMFLOAT2 mage::LVertex::tex

The texture coordinates of this lit vertex.

5.16 mage::MemoryArena Class Reference

```
#include <arena.hpp>
```

Public Member Functions

- [MemoryArena](#) (uint32_t block_size=32768)
- [~MemoryArena](#) ()
- void [FreeAll](#) ()
- void * [Alloc](#) (uint32_t size)
- template<typename T >
T * [Alloc](#) (uint32_t count=1)

Private Attributes

- uint32_t [m_current_block_pos](#)
- const uint32_t [m_block_size](#)
- char * [m_current_block](#)
- vector< char * > [m_used_blocks](#)
- vector< char * > [m_available_blocks](#)

5.16.1 Detailed Description

A class of memory arena's.

5.16.2 Constructor & Destructor Documentation

5.16.2.1 MemoryArena()

```
mage::MemoryArena::MemoryArena (
    uint32_t block_size = 32768 )
```

Constructs a memory arena with given block size.

Parameters

in	<i>block_size</i>	The block size in bytes.
----	-------------------	--------------------------

5.16.2.2 ~MemoryArena()

```
mage::MemoryArena::~MemoryArena ( )
```

Destructs the given memory arena.

5.16.3 Member Function Documentation

5.16.3.1 Alloc() [1/2]

```
void* mage::MemoryArena::Alloc (
    uint32_t size )
```

Allocates a block of memory of the given size.

Parameters

in	<i>size</i>	The requested size in bytes to allocate in memory.
----	-------------	--

Returns

NULL if the allocation failed.

A pointer to the memory block that was allocated.

5.16.3.2 Alloc() [2/2]

```
template<typename T >
T* mage::MemoryArena::Alloc (
    uint32_t count = 1 )
```

Allocates a block of memory.

Template Parameters

<i>T</i>	The type of objects to allocate in memory.
----------	--

Parameters

<i>in</i>	<i>count</i>	The number of objects of type <i>T</i> to allocate in memory.
-----------	--------------	---

Returns

NULL if the allocation failed.
A pointer to the memory block that was allocated.

Note

The objects will be constructed with their default empty constructor.

5.16.3.3 FreeAll()

```
void mage::MemoryArena::FreeAll ( )
```

Frees all blocks of this memory arena.

5.16.4 Member Data Documentation

5.16.4.1 m_available_blocks

```
vector<char *> mage::MemoryArena::m_available_blocks [private]
```

Pointers to the available blocks of this memory arena.

5.16.4.2 m_block_size

```
const uint32_t mage::MemoryArena::m_block_size [private]
```

The fixed block size of this memory arena.

5.16.4.3 m_current_block

```
char* mage::MemoryArena::m_current_block [private]
```

A pointer to the current block of this memory arena.

5.16.4.4 m_current_block_pos

```
uint32_t mage::MemoryArena::m_current_block_pos [private]
```

The current block position of this memory arena.

5.16.4.5 m_used_blocks

```
vector<char *> mage::MemoryArena::m_used_blocks [private]
```

Pointers to the used blocks of this memory arena.

5.17 mage::Mutex Class Reference

```
#include <lock.hpp>
```

Static Public Member Functions

- static [Mutex](#) * [Create](#) ()
- static void [Destroy](#) ([Mutex](#) *mutex)

Private Member Functions

- [Mutex](#) ()
- [Mutex](#) ([Mutex](#) &mutex)
- [~Mutex](#) ()
- [Mutex](#) & [operator=](#) (const [Mutex](#) &mutex)

Private Attributes

- CRITICAL_SECTION [m_critical_section](#)

Friends

- struct [MutexLock](#)

5.17.1 Detailed Description

A class of mutexes.

5.17.2 Constructor & Destructor Documentation

5.17.2.1 [Mutex\(\)](#) [1/2]

```
mage::Mutex::Mutex ( ) [private]
```

Constructs a mutex.

5.17.2.2 [Mutex\(\)](#) [2/2]

```
mage::Mutex::Mutex (
    Mutex & mutex ) [private]
```

Constructs a mutex from the given mutex.

Parameters

in	<i>mutex</i>	A reference to a mutex.
----	--------------	-------------------------

5.17.2.3 ~Mutex()

```
mage::Mutex::~~Mutex ( ) [private]
```

Destructs this mutex.

5.17.3 Member Function Documentation

5.17.3.1 Create()

```
static Mutex\* mage::Mutex::Create ( ) [static]
```

Creates a mutex.

5.17.3.2 Destroy()

```
static void mage::Mutex::Destroy (
    Mutex * mutex ) [static]
```

Destroys a given mutex.

Parameters

in	<i>mutex</i>	The mutex to destroy.
----	--------------	-----------------------

5.17.3.3 operator=()

```
Mutex& mage::Mutex::operator= (
    const Mutex & mutex ) [private]
```

Copies the given mutex to this mutex.

Parameters

in	<i>mutex</i>	A reference to a mutex.
----	--------------	-------------------------

Returns

A reference to the copy of *mutex*.

5.17.4 Friends And Related Function Documentation

5.17.4.1 MutexLock

```
friend struct MutexLock [friend]
```

5.17.5 Member Data Documentation

5.17.5.1 m_critical_section

```
CRITICAL_SECTION mage::Mutex::m_critical_section [private]
```

The critical section object of this mutex.

5.18 mage::MutexLock Struct Reference

```
#include <lock.hpp>
```

Public Member Functions

- [MutexLock](#) ([Mutex](#) &mutex)
- [~MutexLock](#) ()

Private Member Functions

- [MutexLock](#) (const [MutexLock](#) &mutex_lock)
- [MutexLock](#) & [operator=](#) (const [MutexLock](#) &mutex_lock)

Private Attributes

- [Mutex](#) & [m_mutex](#)

5.18.1 Detailed Description

A struct of mutex locks.

5.18.2 Constructor & Destructor Documentation

5.18.2.1 MutexLock() [1/2]

```
mage::MutexLock::MutexLock (  
    Mutex & mutex )
```

Constructs a mutex lock for the given mutex.

Parameters

in	<i>mutex</i>	A reference to a mutex.
----	--------------	-------------------------

5.18.2.2 `~MutexLock()`

```
mage::MutexLock::~~MutexLock ( )
```

Destructs this mutex lock.

5.18.2.3 `MutexLock()` [2/2]

```
mage::MutexLock::MutexLock (
    const MutexLock & mutex_lock ) [private]
```

Constructs a mutex lock from the given mutex lock.

Parameters

in	<i>mutex_lock</i>	A reference to a mutex lock.
----	-------------------	------------------------------

5.18.3 Member Function Documentation

5.18.3.1 `operator=()`

```
MutexLock& mage::MutexLock::operator= (
    const MutexLock & mutex_lock ) [private]
```

Copies the given mutex lock to this mutex lock.

Parameters

in	<i>mutex_lock</i>	A reference to a mutex lock.
----	-------------------	------------------------------

Returns

A reference to the copy of *mutex_lock*.

5.18.4 Member Data Documentation

5.18.4.1 `m_mutex`

```
Mutex& mage::MutexLock::m_mutex [private]
```

The mutex of this mutex lock.

5.19 mage::ProgressReporter Class Reference

```
#include <progressreporter.hpp>
```

Public Member Functions

- [ProgressReporter](#) (uint32_t nb_work, const string &title, uint32_t bar_length=0)
- virtual [~ProgressReporter](#) ()
- void [Update](#) (uint32_t nb_work=1)
- void [Done](#) ()

Protected Attributes

- const uint32_t [m_nb_work_total](#)
- uint32_t [m_nb_work_done](#)
- uint32_t [m_nb_plusses_total](#)
- uint32_t [m_nb_plusses_printed](#)
- [Timer](#) * [m_timer](#)
- FILE * [m_fout](#)
- char * [m_buffer](#)
- char * [m_current_pos](#)
- [Mutex](#) * [m_mutex](#)

5.19.1 Detailed Description

A class of progress reporters.

5.19.2 Constructor & Destructor Documentation

5.19.2.1 ProgressReporter()

```
mage::ProgressReporter::ProgressReporter (
    uint32_t nb_work,
    const string & title,
    uint32_t bar_length = 0 )
```

Constructs a progress reporter.

Parameters

in	<i>nb_work</i>	The number of parts of the total work.
in	<i>title</i>	A reference to the title.
in	<i>bar_length</i>	The length of the progress bar. If 0 the default length will be chosen.

5.19.2.2 ~ProgressReporter()

```
mage::ProgressReporter::~~ProgressReporter ( ) [virtual]
```

Destructs this progress reporter.

5.19.3 Member Function Documentation

5.19.3.1 Done()

```
void mage::ProgressReporter::Done ( )
```

Finishes this progress reporter.

5.19.3.2 Update()

```
void mage::ProgressReporter::Update (
    uint32_t nb_work = 1 )
```

Updates this progress reporter.

Parameters

in	<i>nb_work</i>	The number of parts of the total work that are done.
----	----------------	--

5.19.4 Member Data Documentation

5.19.4.1 m_buffer

```
char* mage::ProgressReporter::m_buffer [protected]
```

The output buffer of this progress reporter.

5.19.4.2 m_current_pos

```
char* mage::ProgressReporter::m_current_pos [protected]
```

The current (output) position of this progress reporter.

5.19.4.3 m_fout

```
FILE* mage::ProgressReporter::m_fout [protected]
```

The output file stream of this progress reporter.

5.19.4.4 m_mutex

`Mutex* mage::ProgressReporter::m_mutex [protected]`

The mutex needed for updating this progress reporter.

5.19.4.5 m_nb_plusses_printed

`uint32_t mage::ProgressReporter::m_nb_plusses_printed [protected]`

The total number of plusses that are already outputted.

5.19.4.6 m_nb_plusses_total

`uint32_t mage::ProgressReporter::m_nb_plusses_total [protected]`

The total number of plusses to output.

5.19.4.7 m_nb_work_done

`uint32_t mage::ProgressReporter::m_nb_work_done [protected]`

The number of parts of the total work that are already done.

5.19.4.8 m_nb_work_total

`const uint32_t mage::ProgressReporter::m_nb_work_total [protected]`

The number of parts of the total work.

5.19.4.9 m_timer

`Timer* mage::ProgressReporter::m_timer [protected]`

The timer of this progress reporter.

5.20 mage::ReadWriteMutex Class Reference

```
#include <lock.hpp>
```

Static Public Member Functions

- static `ReadWriteMutex * Create ()`
- static void `Destroy (ReadWriteMutex *mutex)`

Private Member Functions

- [ReadWriteMutex](#) ()
- [ReadWriteMutex](#) ([ReadWriteMutex](#) &mutex)
- [~ReadWriteMutex](#) ()
- [ReadWriteMutex](#) & [operator=](#) (const [ReadWriteMutex](#) &mutex)
- void [AcquireRead](#) ()
- void [ReleaseRead](#) ()
- void [AcquireWrite](#) ()
- void [ReleaseWrite](#) ()

Private Attributes

- LONG [m_nb_writers_waiting](#)
- LONG [m_nb_readers_waiting](#)
- DWORD [m_active_writer_readers](#)
- HANDLE [m_ready_to_read_handle](#)
- HANDLE [m_ready_to_write_handle](#)
- CRITICAL_SECTION [m_critical_section](#)

Friends

- struct [ReadWriteMutexLock](#)

5.20.1 Detailed Description

A class of read write mutexes.

5.20.2 Constructor & Destructor Documentation

5.20.2.1 `ReadWriteMutex()` [1/2]

```
mage::ReadWriteMutex::ReadWriteMutex ( ) [private]
```

Constructs a read write mutex.

5.20.2.2 `ReadWriteMutex()` [2/2]

```
mage::ReadWriteMutex::ReadWriteMutex (
    ReadWriteMutex & mutex ) [private]
```

Constructs a read write mutex from the given read write mutex.

Parameters

in	<i>mutex</i>	The read write mutex.
----	--------------	-----------------------

5.20.2.3 ~ReadWriteMutex()

```
mage::ReadWriteMutex::~~ReadWriteMutex ( ) [private]
```

Destructs this read write mutex.

5.20.3 Member Function Documentation

5.20.3.1 AcquireRead()

```
void mage::ReadWriteMutex::AcquireRead ( ) [private]
```

Acquires a read.

5.20.3.2 AcquireWrite()

```
void mage::ReadWriteMutex::AcquireWrite ( ) [private]
```

Acquires a write.

5.20.3.3 Create()

```
static ReadWriteMutex* mage::ReadWriteMutex::Create ( ) [static]
```

Creates a mutex.

5.20.3.4 Destroy()

```
static void mage::ReadWriteMutex::Destroy (
    ReadWriteMutex * mutex ) [static]
```

Destroys a given read write mutex.

Parameters

in	<i>mutex</i>	The read write mutex to destroy.
----	--------------	----------------------------------

5.20.3.5 operator=()

```
ReadWriteMutex& mage::ReadWriteMutex::operator= (
    const ReadWriteMutex & mutex ) [private]
```

Copies the given read write mutex to this read write mutex.

Parameters

in	<i>mutex</i>	A reference to a read write mutex.
-----------	--------------	------------------------------------

Returns

A reference to the copy of *mutex*.

5.20.3.6 ReleaseRead()

```
void mage::ReadWriteMutex::ReleaseRead ( ) [private]
```

Release a read.

5.20.3.7 ReleaseWrite()

```
void mage::ReadWriteMutex::ReleaseWrite ( ) [private]
```

Release a write.

5.20.4 Friends And Related Function Documentation**5.20.4.1 ReadWriteMutexLock**

```
friend struct ReadWriteMutexLock [friend]
```

5.20.5 Member Data Documentation**5.20.5.1 m_active_writer_readers**

```
DWORD mage::ReadWriteMutex::m_active_writer_readers [private]
```

The active group of this read write mutex lock.

HIWORD is the flag indicating a writer is active. LOWORD is the number of active readers.

5.20.5.2 m_critical_section

```
CRITICAL_SECTION mage::ReadWriteMutex::m_critical_section [private]
```

The critical section object of this read write mutex.

5.20.5.3 m_nb_readers_waiting

```
LONG mage::ReadWriteMutex::m_nb_readers_waiting [private]
```

The number of readers waiting for this read write mutex lock.

5.20.5.4 m_nb_writers_waiting

```
LONG mage::ReadWriteMutex::m_nb_writers_waiting [private]
```

The number of writers waiting for this read write mutex lock.

5.20.5.5 m_ready_to_read_handle

```
HANDLE mage::ReadWriteMutex::m_ready_to_read_handle [private]
```

The handle of this read write mutex lock if ready for reading.

5.20.5.6 m_ready_to_write_handle

```
HANDLE mage::ReadWriteMutex::m_ready_to_write_handle [private]
```

The handle of this read write mutex lock if ready for writing.

5.21 mage::ReadWriteMutexLock Struct Reference

```
#include <lock.hpp>
```

Public Member Functions

- [ReadWriteMutexLock](#) ([ReadWriteMutex](#) &mutex, [ReadWriteMutexLockType](#) lock_type)
- [~ReadWriteMutexLock](#) ()
- void [UpgradeToWrite](#) ()
- void [DowngradeToRead](#) ()

Private Member Functions

- [ReadWriteMutexLock](#) (const [ReadWriteMutexLock](#) &mutex_lock)
- [ReadWriteMutexLock](#) & operator= (const [ReadWriteMutexLock](#) &mutex_lock)

Private Attributes

- [ReadWriteMutexLockType](#) m_type
- [ReadWriteMutex](#) & m_mutex

5.21.1 Detailed Description

A struct of read write mutex locks.

5.21.2 Constructor & Destructor Documentation

5.21.2.1 ReadWriteMutexLock() [1/2]

```
mage::ReadWriteMutexLock::ReadWriteMutexLock (
    ReadWriteMutex & mutex,
    ReadWriteMutexLockType lock_type )
```

Constructs a read write mutex lock for the given read write mutex and lock type.

Parameters

in	<i>mutex</i>	A reference to a read write mutex.
in	<i>lock_type</i>	The lock type.

5.21.2.2 ~ReadWriteMutexLock()

```
mage::ReadWriteMutexLock::~~ReadWriteMutexLock ( )
```

Destructs this read write mutex lock.

5.21.2.3 ReadWriteMutexLock() [2/2]

```
mage::ReadWriteMutexLock::ReadWriteMutexLock (
    const ReadWriteMutexLock & mutex_lock ) [private]
```

Constructs a read write mutex lock from the given read write mutex lock.

Parameters

in	<i>mutex_lock</i>	A reference to a read write mutex lock.
----	-------------------	---

5.21.3 Member Function Documentation

5.21.3.1 DowngradeToRead()

```
void mage::ReadWriteMutexLock::DowngradeToRead ( )
```

Downgrades this read write lock to read.

5.21.3.2 operator=()

```
ReadWriteMutexLock& mage::ReadWriteMutexLock::operator= (
    const ReadWriteMutexLock & mutex_lock ) [private]
```

Copies the given read write mutex lock to this read write mutex lock.

Parameters

in	<i>mutex_lock</i>	A reference to a read write mutex lock.
----	-------------------	---

Returns

A reference to the copy of *mutex_lock*.

5.21.3.3 UpgradeToWrite()

```
void mage::ReadWriteMutexLock::UpgradeToWrite ( )
```

Upgrades this read write lock to write.

5.21.4 Member Data Documentation

5.21.4.1 m_mutex

```
ReadWriteMutex& mage::ReadWriteMutexLock::m_mutex [private]
```

The read write mutex of this read write mutex lock.

5.21.4.2 m_type

```
ReadWriteMutexLockType mage::ReadWriteMutexLock::m_type [private]
```

The lock type of this read write mutex lock.

5.22 mage::Reference< T > Class Template Reference

```
#include <reference.hpp>
```

Public Member Functions

- [Reference](#) (T *ptr=NULL)
- [Reference](#) (const [Reference](#)< T > &reference)
- virtual [~Reference](#) ()
- [Reference](#) & [operator=](#) (T *ptr)
- [Reference](#) & [operator=](#) (const [Reference](#)< T > &reference)
- T * [operator->](#) ()
- const T * [operator->](#) () const
- const T * [GetPtr](#) () const
- [operator bool](#) () const

Private Attributes

- T * `m_ptr`

5.22.1 Detailed Description

```
template<typename T>
class mage::Reference< T >
```

A class of references.

Template Parameters

<i>T</i>	The type of reference.
----------	------------------------

5.22.2 Constructor & Destructor Documentation

5.22.2.1 Reference() [1/2]

```
template<typename T>
mage::Reference< T >::Reference (
    T * ptr = NULL )
```

Constructs a reference for the given pointer.

Parameters

in	<i>ptr</i>	The pointer.
----	------------	--------------

5.22.2.2 Reference() [2/2]

```
template<typename T>
mage::Reference< T >::Reference (
    const Reference< T > & reference )
```

Constructs a reference from the given reference.

Parameters

in	<i>reference</i>	The reference.
----	------------------	----------------

5.22.2.3 ~Reference()

```
template<typename T>
virtual mage::Reference< T >::~~Reference ( ) [virtual]
```

Destructs this reference.

5.22.3 Member Function Documentation

5.22.3.1 GetPtr()

```
template<typename T>
const T* mage::Reference< T >::GetPtr ( ) const
```

Returns the pointer of this reference.

Returns

The pointer of this reference.

5.22.3.2 operator bool()

```
template<typename T>
mage::Reference< T >::operator bool ( ) const
```

Checks whether the pointer of this reference does not point to `NULL`.

Returns

`true` if the pointer of this reference does not point to `NULL`. `false` otherwise.

5.22.3.3 operator->() [1/2]

```
template<typename T>
T* mage::Reference< T >::operator-> ( )
```

Dereferences this reference.

Returns

The pointer of this reference.

5.22.3.4 operator->() [2/2]

```
template<typename T>
const T* mage::Reference< T >::operator-> ( ) const
```

Dereferences this reference.

Returns

The pointer of this reference.

5.22.3.5 operator=() [1/2]

```
template<typename T>
Reference& mage::Reference< T >::operator= (
    T * ptr )
```

Copies the given pointer into a reference.

Parameters

in	<i>ptr</i>	The pointer.
----	------------	--------------

Returns

A reference for *ptr*.

5.22.3.6 operator=() [2/2]

```
template<typename T>
Reference& mage::Reference< T >::operator= (
    const Reference< T > & reference )
```

Copies the given reference into a reference.

Parameters

in	<i>reference</i>	The reference.
----	------------------	----------------

Returns

A reference for *reference*.

5.22.4 Member Data Documentation

5.22.4.1 m_ptr

```
template<typename T>
T* mage::Reference< T >::m_ptr [private]
```

The pointer of this reference.

5.23 mage::ReferenceCounted Class Reference

```
#include <reference.hpp>
```

Public Member Functions

- uint32_t [IncrementReferenceCount](#) ()
- uint32_t [DecrementReferenceCount](#) ()

Protected Member Functions

- [ReferenceCounted](#) ()

Private Attributes

- AtomicInt32 [m_reference_count](#)

5.23.1 Detailed Description

A class of reference counted objects.

5.23.2 Constructor & Destructor Documentation

5.23.2.1 ReferenceCounted()

```
mage::ReferenceCounted::ReferenceCounted ( ) [protected]
```

Constructs a reference counted object.

5.23.3 Member Function Documentation

5.23.3.1 DecrementReferenceCount()

```
uint32_t mage::ReferenceCounted::DecrementReferenceCount ( )
```

Decrements the reference count of this reference counted object.

Returns

The final reference count of this reference counted object.

5.23.3.2 IncrementReferenceCount()

```
uint32_t mage::ReferenceCounted::IncrementReferenceCount ( )
```

Increments the reference count of this reference counted object.

Returns

The final reference count of this reference counted object.

5.23.4 Member Data Documentation

5.23.4.1 m_reference_count


```
AtomicInt32 mage::ReferenceCounted::m_reference_count [private]
```

The reference count of this reference counted object.

5.24 mage::Renderer Class Reference

```
#include <renderer.hpp>
```

Inheritance diagram for mage::Renderer:



Public Member Functions

- void [SwitchMode](#) ()
- bool [IsWindowed](#) () const
- bool [IsFullScreen](#) () const

Protected Member Functions

- [Renderer](#) (HWND hwnd)
- virtual [~Renderer](#) ()
- HRESULT [InitializeDevice](#) ()
- HRESULT [UnitalizeDevice](#) ()
- void [Render](#) (double elapsed_time)

Protected Attributes

- HWND [m_hwindow](#)
- bool [m_windowed](#)
- D3D_DRIVER_TYPE [m_driver_type](#)
- D3D_FEATURE_LEVEL [m_feature_level](#)
- ID3D11Device2 * [m_device2](#)
- ID3D11DeviceContext2 * [m_device_context2](#)
- IDXGISwapChain2 * [m_swap_chain2](#)
- ID3D11RenderTargetView * [m_render_target_view](#)
- ID3D11Texture2D * [m_depth_stencil](#)
- ID3D11DepthStencilView * [m_depth_stencil_view](#)

Friends

- class [Engine](#)

Additional Inherited Members

5.24.1 Detailed Description

A class of renderers.

5.24.2 Constructor & Destructor Documentation

5.24.2.1 `Renderer()`

```
mage::Renderer::Renderer (
    HWND hwindow ) [protected]
```

Constructs a renderer.

Parameters

in	<i>hwindow</i>	The main window handle.
----	----------------	-------------------------

5.24.2.2 ~Renderer()

```
mage::Renderer::~~Renderer ( ) [protected], [virtual]
```

Destructs this renderer.

5.24.3 Member Function Documentation

5.24.3.1 InitializeDevice()

```
HRESULT mage::Renderer::InitializeDevice ( ) [protected]
```

Initializes the D3D11 device of this renderer.

Returns

A success/error value.

5.24.3.2 IsFullScreen()

```
bool mage::Renderer::IsFullScreen ( ) const
```

Check whether this renderer renders in full screen mode.

Returns

`true` if this renderer renders in full screen mode. `false` otherwise.

5.24.3.3 IsWindowed()

```
bool mage::Renderer::IsWindowed ( ) const
```

Check whether this renderer renders in windowed mode.

Returns

`true` if this renderer renders in windowed mode. `false` otherwise.

5.24.3.4 Render()

```
void mage::Renderer::Render (
    double elapsed_time ) [protected]
```

Renders the current frame.

Parameters

in	<i>elapsed_time</i>	The elapsed time since the previous frame.
----	---------------------	--

5.24.3.5 SwitchMode()

```
void mage::Renderer::SwitchMode ( )
```

Switches the mode of this renderer. Windowed mode is switched to full screen mode and vice versa.

5.24.3.6 UnitalizeDevice()

```
HRESULT mage::Renderer::UnitalizeDevice ( ) [protected]
```

Uninitializes the D3D11 device of this renderer.

Returns

A success/error value.

5.24.4 Friends And Related Function Documentation**5.24.4.1 Engine**

```
friend class Engine [friend]
```

5.24.5 Member Data Documentation**5.24.5.1 m_depth_stencil**

```
ID3D11Texture2D* mage::Renderer::m_depth_stencil [protected]
```

5.24.5.2 m_depth_stencil_view

```
ID3D11DepthStencilView* mage::Renderer::m_depth_stencil_view [protected]
```

5.24.5.3 m_device2

```
ID3D11Device2* mage::Renderer::m_device2 [protected]
```

5.24.5.4 m_device_context2

```
ID3D11DeviceContext2* mage::Renderer::m_device_context2 [protected]
```

5.24.5.5 m_driver_type

D3D_DRIVER_TYPE mage::Renderer::m_driver_type [protected]

5.24.5.6 m_feature_level

D3D_FEATURE_LEVEL mage::Renderer::m_feature_level [protected]

5.24.5.7 m_hwindow

HWND mage::Renderer::m_hwindow [protected]

Main window handle of this renderer.

5.24.5.8 m_render_target_view

ID3D11RenderTargetView* mage::Renderer::m_render_target_view [protected]

5.24.5.9 m_swap_chain2

IDXGISwapChain2* mage::Renderer::m_swap_chain2 [protected]

5.24.5.10 m_windowed


bool mage::Renderer::m_windowed [protected]

Flag indicating whether this renderer uses full screen (`false`) or windowed mode (`true`).

5.25 mage::Resource Class Reference

```
#include <resource.hpp>
```

Inheritance diagram for mage::Resource:



Public Member Functions

- [Resource](#) (const string &name, const string &path=".")
- virtual [~Resource](#) ()
- const string & [GetName](#) () const
- const string & [GetPath](#) () const
- const string [GetFilename](#) () const

Private Member Functions

- uint32_t [IncrementResourceReferenceCount](#) ()
- uint32_t [DecrementResourceReferenceCount](#) ()

Private Attributes

- AtomicInt32 [m_resource_reference_count](#)
- const string [m_name](#)
- const string [m_path](#)

Friends

- template<typename T >
class [ResourceManager](#)

5.25.1 Detailed Description

A class of resources.

5.25.2 Constructor & Destructor Documentation

5.25.2.1 Resource()

```
mage::Resource::Resource (
    const string & name,
    const string & path = "." )
```

Constructs a resource with a given name and path.

Parameters

in	<i>name</i>	A reference to the name.
in	<i>path</i>	A reference to the path.

5.25.2.2 ~Resource()

```
virtual mage::Resource::~~Resource ( ) [virtual]
```

Destructs this resource.

5.25.3 Member Function Documentation

5.25.3.1 DecrementResourceReferenceCount()

```
uint32_t mage::Resource::DecrementResourceReferenceCount ( ) [private]
```

Decrements the resource reference count of this reference counted object.

Returns

The final resource reference count of this reference counted object.

5.25.3.2 GetFilename()

```
const string mage::Resource::GetFilename ( ) const
```

Returns the filename of this resource.

Returns

The filename of this resource.

5.25.3.3 GetName()

```
const string& mage::Resource::GetName ( ) const
```

Returns the name of this resource.

Returns

A reference to the name of this resource.

5.25.3.4 GetPath()

```
const string& mage::Resource::GetPath ( ) const
```

Returns the path of this resource.

Returns

A reference to the path of this resource.

5.25.3.5 IncrementResourceReferenceCount()

```
uint32_t mage::Resource::IncrementResourceReferenceCount ( ) [private]
```

Increments the resource reference count of this reference counted object.

Returns

The final resource reference count of this reference counted object.

5.25.4 Friends And Related Function Documentation

5.25.4.1 ResourceManager

```
template<typename T >
friend class ResourceManager [friend]
```

5.25.5 Member Data Documentation

5.25.5.1 m_name

```
const string mage::Resource::m_name [private]
```

The name of this resource.

5.25.5.2 m_path

```
const string mage::Resource::m_path [private]
```

The path of this resource.

5.25.5.3 m_resource_reference_count

```
AtomicInt32 mage::Resource::m_resource_reference_count [private]
```

The resource reference count of this resource.

5.26 mage::ResourceManager< T > Class Template Reference

```
#include <resource_manager.hpp>
```

Public Member Functions

- [ResourceManager](#) (void(*CreateResourceFunction)(T **resource, const string &name, const string &path)=NULL)
- virtual [~ResourceManager](#) ()
- T * [AddResource](#) (const string &name, const string &path=".")
- void [RemoveResource](#) (T *resource)
- void [ClearResources](#) ()
- T * [GetResource](#) (const string &name, const string &path=".") const

Protected Attributes

- list< T *> [m_resources](#)
- void(* [CreateResource](#))(T **resource, const string &name, const string &path)

5.26.1 Detailed Description

```
template<typename T>
class mage::ResourceManager< T >
```

A class of resource managers.

Template Parameters

<i>T</i>	The type of resources.
----------	------------------------

5.26.2 Constructor & Destructor Documentation

5.26.2.1 ResourceManager()

```
template<typename T>
mage::ResourceManager< T >::ResourceManager (
    void(*) (T **resource, const string &name, const string &path) CreateResource↵
Function = NULL )
```

Constructs a resource manager.

Parameters

in	<i>CreateResourceFunction</i>	The application specific resource creation function.
----	-------------------------------	--

5.26.2.2 ~ResourceManager()

```
template<typename T>
virtual mage::ResourceManager< T >::~~ResourceManager ( ) [virtual]
```

Destructs this resource manager.

5.26.3 Member Function Documentation

5.26.3.1 AddResource()

```
template<typename T>
T* mage::ResourceManager< T >::AddResource (
    const string & name,
    const string & path = "." )
```

Adds a new resource to this resource manager.

Parameters

in	<i>name</i>	A reference to the name of the new resource.
in	<i>path</i>	A reference to the path of the new resource.

Returns

A pointer to the resource.

5.26.3.2 ClearResources()

```
template<typename T>
void mage::ResourceManager< T >::ClearResources ( )
```

Removes and destructs all the resources from this resource manager, and leaving the resource manager with no resources.

5.26.3.3 GetResource()

```
template<typename T>
T* mage::ResourceManager< T >::GetResource (
    const string & name,
    const string & path = "/" ) const
```

Returns a resource of this resource manager by its filename (given name and path).

Parameters

in	<i>name</i>	A reference to the name of the new resource.
in	<i>path</i>	A reference to the path of the new resource.

Returns

NULL if the resource is not present.
A pointer to the resource.

5.26.3.4 RemoveResource()

```
template<typename T>
void mage::ResourceManager< T >::RemoveResource (
    T * resource )
```

Removes the given resource from this resource manager.

Parameters

in, out	<i>resource</i>	A pointer to the resource.
---------	-----------------	----------------------------

5.26.4 Member Data Documentation

5.26.4.1 CreateResource

```
template<typename T>
void(* mage::ResourceManager< T >::CreateResource) (T **resource, const string &name, const
string &path) [protected]
```

The application specific resource creation function for the resources of this resource manager.

5.26.4.2 m_resources

```
template<typename T>
list< T * > mage::ResourceManager< T >::m_resources [protected]
```

The linked list containing the resources of this resource manager.

5.27 mage::Semaphore Class Reference

```
#include <lock.hpp>
```

Public Member Functions

- Semaphore ()
- ~Semaphore ()
- void Post (uint32_t count=1)
- void Wait ()
- bool TryWait ()

Private Attributes

- HANDLE m_handle

5.27.1 Detailed Description

A class of semaphores.

5.27.2 Constructor & Destructor Documentation

5.27.2.1 Semaphore()

```
mage::Semaphore::Semaphore ( )
```

Constructs a semaphore.

5.27.2.2 ~Semaphore()

```
mage::Semaphore::~~Semaphore ( )
```

Destructs this semaphore.

5.27.3 Member Function Documentation

5.27.3.1 Post()

```
void mage::Semaphore::Post (
    uint32_t count = 1 )
```

Increments the value of this semaphore variable by the given value.

The process executing wait is blocked until the value of the semaphore is greater or equal to 1.

Parameters

<code>in</code>	<code>count</code>	The increment value.
-----------------	--------------------	----------------------

5.27.3.2 TryWait()

```
bool mage::Semaphore::TryWait ( )
```

Checks whether waiting for this semaphore would be necessary.

Returns

`true` if waiting for this semaphore would be necessary. `false` otherwise.

5.27.3.3 Wait()

```
void mage::Semaphore::Wait ( )
```

Decrements the value of this semaphore variable by one.

If the initial value of the semaphore is negative, the waiting queue is not empty and thus one blocked process can be transferred to the ready queue.

5.27.4 Member Data Documentation**5.27.4.1 m_handle**

```
HANDLE mage::Semaphore::m_handle [private]
```

The handle of this semaphore.

5.28 mage::Sphere Struct Reference

```
#include <geometry.hpp>
```

Public Member Functions

- [Sphere](#) ()
- [Sphere](#) (XMFLOAT3 [p](#), float [r](#))
- bool [Encloses](#) (const list< XMFLOAT4 > &planes)
- bool [Collides](#) (const [Sphere](#) &sphere, const XMFLOAT3 velocity_sum, float *collision_distance)

Public Attributes

- XMFLOAT3 [p](#)
- float [r](#)

5.28.1 Detailed Description

A struct of spheres.

5.28.2 Constructor & Destructor Documentation

5.28.2.1 Sphere() [1/2]

```
mage::Sphere::Sphere ( )
```

Constructs a sphere.

5.28.2.2 Sphere() [2/2]

```
mage::Sphere::Sphere (
    XMFLOAT3 p,
    float r )
```

Constructs a sphere.

Parameters

in	<i>p</i>	The position
in	<i>r</i>	The radius.

5.28.3 Member Function Documentation

5.28.3.1 Collides()

```
bool mage::Sphere::Collides (
    const Sphere & sphere,
    const XMFLOAT3 velocity_sum,
    float * collision_distance )
```

Checks whether this sphere collides with a given sphere.

Parameters

in	<i>sphere</i>	The sphere.
in	<i>velocity_sum</i>	The sum of the velocities of both spheres.
out	<i>collision_distance</i>	The collision distance (in case of collision).

Returns

`true` if this sphere collides with *sphere*. `false` otherwise.

5.28.3.2 Encloses()

```
bool mage::Sphere::Encloses (
    const list< XMFLOAT4 > & planes )
```

Checks whether this sphere completely encloses the given (closed) volume.

Parameters

in	<i>planes</i>	A reference to a linked list containing the planes of the volume (each plane's coefficients are represented as a XMFLOAT4).
----	---------------	---

Returns

`true` if this sphere completely encloses *planes*. `false` otherwise.

5.28.4 Member Data Documentation

5.28.4.1 p

```
XMFLOAT3 mage::Sphere::p
```

The position of this sphere.

5.28.4.2 r

```
float mage::Sphere::r
```

The radius of this sphere.

5.29 mage::State Class Reference

```
#include <state.hpp>
```

Public Member Functions

- [State](#) (uint64_t id=0)
- uint64_t [GetId](#) () const
- virtual void [RequestViewSetup](#) ([ViewerSetup](#) *viewer_setup)

Protected Member Functions

- virtual void [Load](#) ()
- virtual void [Close](#) ()
- virtual void [Update](#) (double elapsed_time)
- virtual void [Render](#) ()

Private Attributes

- const uint64_t [m_id](#)

Friends

- class [StateManager](#)

5.29.1 Detailed Description

A class of states

5.29.2 Constructor & Destructor Documentation

5.29.2.1 State()

```
mage::State::State (
    uint64_t id = 0 )
```

Constructs a state with given id.

Parameters

in	<i>id</i>	The id.
----	-----------	---------

5.29.3 Member Function Documentation

5.29.3.1 Close()

```
virtual void mage::State::Close ( ) [protected], [virtual]
```

Closes this state. Allows this state to preform any post-processing destruction.

5.29.3.2 GetId()

```
uint64_t mage::State::GetId ( ) const
```

Returns the id of this state.

Returns

The id of this state.

5.29.3.3 Load()

```
virtual void mage::State::Load ( ) [protected], [virtual]
```

Loads this state. Allows this state to preform any pre-processing construction.

5.29.3.4 Render()

```
virtual void mage::State::Render ( ) [protected], [virtual]
```

Render this state.

5.29.3.5 RequestViewSetup()

```
virtual void mage::State::RequestViewSetup (
    ViewerSetup * viewer_setup ) [virtual]
```

Requests the view setup details for the given frame.

Precondition

viewer_setup is not NULL.

Parameters

in, out	<i>viewer_setup</i>	A pointer to a viewer setup.
---------	---------------------	------------------------------

5.29.3.6 Update()

```
virtual void mage::State::Update (
    double elapsed_time ) [protected], [virtual]
```

Updates this state.

Parameters

in	<i>elapsed_time</i>	The elapsed time since the previous update.
----	---------------------	---

5.29.4 Friends And Related Function Documentation

5.29.4.1 StateManager

```
friend class StateManager [friend]
```

5.29.5 Member Data Documentation

5.29.5.1 m_id

```
const uint64_t mage::State::m_id [private]
```

Application defined identifier (must be unique for state switching) of this state.

5.30 mage::StateManager Class Reference

```
#include <state_manager.hpp>
```

Public Member Functions

- void [AddState](#) ([State](#) *state, bool change=true)
- void [RemoveState](#) ([State](#) *state)
- void [ChangeState](#) (uint64_t id)
- [State](#) * [GetCurrentState](#) () const
- bool [IsStateChanged](#) () const

Protected Member Functions

- [StateManager](#) ()
- virtual [~StateManager](#) ()
- bool [Update](#) (double elapsed_time)
- void [ChangeState](#) ([State](#) *state)

Protected Attributes

- list< [State](#) *> [m_states](#)
- [State](#) * [m_current_state](#)
- bool [m_state_changed](#)

Friends

- class [Engine](#)

5.30.1 Detailed Description

A class of state managers.

5.30.2 Constructor & Destructor Documentation

5.30.2.1 StateManager()

```
mage::StateManager::StateManager ( ) [protected]
```

Constructs a state manager.

5.30.2.2 ~StateManager()

```
virtual mage::StateManager::~~StateManager ( ) [protected], [virtual]
```

Destructs this state manager.

5.30.3 Member Function Documentation

5.30.3.1 AddState()

```
void mage::StateManager::AddState (
    State * state,
    bool change = true )
```

Adds the given state from the states of this state manager.

Parameters

in	<i>state</i>	A pointer to the state.
in	<i>change</i>	Flag indicating whether the current state of this engine need to be changed to <i>state</i> .

5.30.3.2 ChangeState() [1/2]

```
void mage::StateManager::ChangeState (
    uint64_t id )
```

Changes the state of this state manager to the state with the given id.

Parameters

in	<i>id</i>	The id of the state to change to.
----	-----------	-----------------------------------

5.30.3.3 ChangeState() [2/2]

```
void mage::StateManager::ChangeState (
    State * state ) [protected]
```

Changes the state of this state manager to the given state.

Precondition

state is not NULL.

Parameters

in	<i>state</i>	A pointer to the new state.
----	--------------	-----------------------------

5.30.3.4 GetCurrentState()

```
State* mage::StateManager::GetCurrentState ( ) const
```

Returns the current state of this state manager.

Returns

A pointer to the current state of this state manager.

5.30.3.5 IsStateChanged()

```
bool mage::StateManager::IsStateChanged ( ) const
```

Checks whether the state of this state manager is changed.

Returns

true if the state is changed. false otherwise.

5.30.3.6 RemoveState()

```
void mage::StateManager::RemoveState (
    State * state )
```

Removes (and destructs) the given state from the states of this state manager.

Parameters

in	<i>state</i>	A pointer to the state.
----	--------------	-------------------------

5.30.3.7 Update()

```
bool mage::StateManager::Update (
    double elapsed_time ) [protected]
```

Updates this state manager and its current state.

Parameters

in	<i>elapsed_time</i>	The elapsed time since the previous frame.
----	---------------------	--

Returns

`true` if the state is changed in the current frame. `false` otherwise.

5.30.4 Friends And Related Function Documentation**5.30.4.1 Engine**

```
friend class Engine [friend]
```

5.30.5 Member Data Documentation**5.30.5.1 m_current_state**

```
State* mage::StateManager::m_current_state [protected]
```

A pointer to the current state of this state manager.

5.30.5.2 m_state_changed

```
bool mage::StateManager::m_state_changed [protected]
```

Flag indicating if the state changed in the current frame.

5.30.5.3 m_states

```
list< State * > mage::StateManager::m_states [protected]
```

The states of this state manager.

5.31 mage::Task Class Reference

```
#include <task.hpp>
```

Public Member Functions

- virtual `~Task()`
- virtual void `Run()`=0

5.31.1 Detailed Description

A class of tasks.

5.31.2 Constructor & Destructor Documentation

5.31.2.1 ~Task()

```
virtual mage::Task::~~Task ( ) [virtual]
```

Destructs this task.

5.31.3 Member Function Documentation

5.31.3.1 Run()

```
virtual void mage::Task::Run ( ) [pure virtual]
```

5.32 mage::Timer Class Reference

```
#include <timer.hpp>
```

Public Member Functions

- [Timer](#) ()
- virtual [~Timer](#) ()
- void [Start](#) ()
- void [Stop](#) ()
- void [Reset](#) ()
- void [Restart](#) ()
- double [Time](#) ()

Protected Member Functions

- double [time](#) ()

Protected Attributes

- double [m_time0](#)
- double [m_elapsed](#)
- bool [m_running](#)
- LARGE_INTEGER [m_performance_counter](#)
- LARGE_INTEGER [m_performance_frequency](#)
- double [m_performance_period](#)

5.32.1 Detailed Description

A class of (high precision) timers.

5.32.2 Constructor & Destructor Documentation

5.32.2.1 Timer()

```
mage::Timer::Timer ( )
```

Constructs a timer.

5.32.2.2 ~Timer()

```
virtual mage::Timer::~~Timer ( ) [virtual]
```

Destructs this timer.

5.32.3 Member Function Documentation

5.32.3.1 Reset()

```
void mage::Timer::Reset ( )
```

Resets this timer.

5.32.3.2 Restart()

```
void mage::Timer::Restart ( )
```

Restarts this timer.

5.32.3.3 Start()

```
void mage::Timer::Start ( )
```

Starts this timer.

5.32.3.4 Stop()

```
void mage::Timer::Stop ( )
```

Stops this timer.

5.32.3.5 `Time()`

```
double mage::Timer::Time ( )
```

Returns the elapsed time of this timer.

Returns

The elapsed time of this timer.

5.32.3.6 `time()`

```
double mage::Timer::time ( ) [protected]
```

Returns the time of this timer.

Returns

The time of this timer.

Note

This member method encapsulates the performance of the underlying counter/frequency processing.

5.32.4 Member Data Documentation

5.32.4.1 `m_elapsed`

```
double mage::Timer::m_elapsed [protected]
```

The elapsed time of this timer.

5.32.4.2 `m_performance_counter`

```
LARGE_INTEGER mage::Timer::m_performance_counter [protected]
```

The counter of this timer.

5.32.4.3 `m_performance_frequency`

```
LARGE_INTEGER mage::Timer::m_performance_frequency [protected]
```

The frequency of this timer.

5.32.4.4 `m_performance_period`

```
double mage::Timer::m_performance_period [protected]
```

The period of this timer.

5.32.4.5 m_running

```
bool mage::Timer::m_running [protected]
```

Flag indicating whether this timer is running.

5.32.4.6 m_time0

```
double mage::Timer::m_time0 [protected]
```

The initial time stamp of this timer.

5.33 mage::TLVertex Struct Reference

```
#include <geometry.hpp>
```

Public Member Functions

- [TLVertex](#) ()
- [TLVertex](#) (XMFLOAT4 [p](#), XMFLOAT4 [diffuse](#), XMFLOAT2 [tex](#))

Public Attributes

- XMFLOAT4 [p](#)
- XMFLOAT4 [diffuse](#)
- XMFLOAT2 [tex](#)

5.33.1 Detailed Description

A struct of transformed and lit vertices.

5.33.2 Constructor & Destructor Documentation

5.33.2.1 TLVertex() [1/2]

```
mage::TLVertex::TLVertex ( )
```

Constructs a transformed and lit vertex.

5.33.2.2 TLVertex() [2/2]

```
mage::TLVertex::TLVertex (
    XMFLOAT4 p,
    XMFLOAT4 diffuse,
    XMFLOAT2 tex )
```

Constructs a transformed and lit vertex.

Parameters

in	<i>p</i>	The position of the transformed and lit vertex (in projection space).
in	<i>diffuse</i>	The diffuse colour of the transformed and lit vertex.
in	<i>tex</i>	The texture coordinates of the transformed and lit vertex.

5.33.3 Member Data Documentation

5.33.3.1 diffuse

XMFLOAT4 mage::TLVertex::diffuse

The diffuse colour of this transformed and lit vertex.

5.33.3.2 p

XMFLOAT4 mage::TLVertex::p

The position of this transformed and lit vertex (in projection space).


5.33.3.3 tex

XMFLOAT2 mage::TLVertex::tex

The texture coordinates of this transformed and lit vertex.

5.34 mage::Variable::Value< T > Struct Template Reference

Inheritance diagram for mage::Variable::Value< T >:



Public Member Functions

- [Value](#) (const T *value)
- virtual [~Value](#) ()
- virtual const void * [GetValue](#) () const

Private Attributes

- const T * [m_value](#)

5.34.1 Detailed Description

```
template<typename T>
struct mage::Variable::Value< T >
```

A struct of values.

Template Parameters

<i>T</i>	The type of the value.
----------	------------------------

5.34.2 Constructor & Destructor Documentation

5.34.2.1 Value()

```
template<typename T >
mage::Variable::Value< T >::Value (
    const T * value )
```

Constructs a value.

Parameters

in	<i>value</i>	A pointer to the value.
----	--------------	-------------------------

5.34.2.2 ~Value()

```
template<typename T >
virtual mage::Variable::Value< T >::~~Value ( ) [virtual]
```

Destructs this value.

5.34.3 Member Function Documentation

5.34.3.1 GetValue()

```
template<typename T >
virtual const void* mage::Variable::Value< T >::GetValue ( ) const [virtual]
```

Returns the value of this value.

Returns

A pointer to the value of this value.

Implements [mage::Variable::AbstractValue](#).

5.34.4 Member Data Documentation

5.34.4.1 m_value

```
template<typename T >
const T* mage::Variable::Value< T >::m_value [private]
```

A pointer to the value of this value.

5.35 mage::Variable Struct Reference

```
#include <variable.hpp>
```

Classes

- struct [AbstractValue](#)
- struct [Value](#)

Public Member Functions

- template<typename T >
 [Variable](#) (const string &name, [VariableType](#) type, const T *value)
- [~Variable](#) ()
- bool [operator==](#) (const [Variable](#) &variable) const
- bool [operator!=](#) (const [Variable](#) &variable) const
- const string & [GetName](#) () const
- const [VariableType](#) & [GetType](#) () const
- const void * [GetValue](#) () const

Private Attributes

- const string [m_name](#)
- const [VariableType](#) [m_type](#)
- const [AbstractValue](#) * [m_value](#)

5.35.1 Detailed Description

A struct of (immutable) variables.

5.35.2 Constructor & Destructor Documentation

5.35.2.1 Variable()

```
template<typename T >
mage::Variable::Variable (
    const string & name,
    VariableType type,
    const T * value )
```

Constructs a variable.

Template Parameters

<i>T</i>	The (storage) type of the value.
----------	----------------------------------

Parameters

in	<i>name</i>	The name.
in	<i>type</i>	The (scripting) type of the value.
in	<i>value</i>	A pointer to the value.

5.35.2.2 ~Variable()

```
mage::Variable::~~Variable ( )
```

Destructs this variable.

5.35.3 Member Function Documentation**5.35.3.1 GetName()**

```
const string& mage::Variable::GetName ( ) const
```

Returns the name of this variable.

Returns

A reference to the name of this variable.

5.35.3.2 GetType()

```
const VariableType& mage::Variable::GetType ( ) const
```

Returns the type of this value.

Returns

The type of this value.

5.35.3.3 GetValue()

```
const void* mage::Variable::GetValue ( ) const
```

Returns the value of this variable.

Returns

A pointer to the value of this variable.

5.35.3.4 operator!=()

```
bool mage::Variable::operator!= (
    const Variable & variable ) const
```

Checks whether the given variable is not equal to this variable.

Parameters

in	<i>variable</i>	A reference to the variable to compare with.
----	-----------------	--

Returns

`true` if and only if this variable and *variable* have not the same name. `false` otherwise.

5.35.3.5 operator==()

```
bool mage::Variable::operator== (
    const Variable & variable ) const
```

Checks whether the given variable is equal to this variable.

Parameters

in	<i>variable</i>	A reference to the variable to compare with.
----	-----------------	--

Returns

`true` if and only if this variable and *variable* have the same name. `false` otherwise.

5.35.4 Member Data Documentation

5.35.4.1 m_name

```
const string mage::Variable::m_name [private]
```

The name of this variable.

5.35.4.2 m_type

```
const VariableType mage::Variable::m_type [private]
```

The type of this value.

Note

It is not possible to use `typeid(T).name()` since this assumes a bijection between the scripting types and the storage types, which is not the case. Thus the type needs to be stored explicitly.

5.35.4.3 m_value


```
const AbstractValue* mage::Variable::m_value [private]
```

A pointer to the value of this variable.

5.36 mage::VariableScript Class Reference

```
#include <variable_script.hpp>
```

Inheritance diagram for mage::VariableScript:



Public Member Functions

- [VariableScript](#) (const string &name, const string &path="./")
- virtual [~VariableScript](#) ()
- void [ExportScript](#) (const string &filename="")
- template<typename T >
void [AddVariable](#) (const string &name, [VariableType](#) type, const T *value)
- void [RemoveVariable](#) (const string &name)
- template<typename T >
const T * [GetValueOfVariable](#) (const string &name) const
- template<typename T >
void [SetValueOfVariable](#) (const string &name, const T *value)

Protected Member Functions

- void [ImportScript](#) ()
- void [ImportVariable](#) (const string &name, FILE *file)
- void [ExportVariable](#) (const [Variable](#) *variable, FILE *file)

Protected Attributes

- list< const [Variable](#) *> [m_variables](#)

5.36.1 Detailed Description

A class of variable scripts.

5.36.2 Constructor & Destructor Documentation

5.36.2.1 VariableScript()

```

mage::VariableScript::VariableScript (
    const string & name,
    const string & path = "./" )
  
```

Constructs a variable script.

Parameters

in	<i>name</i>	A reference to the name of the variable script.
in	<i>path</i>	A reference to the path of the variable script.

5.36.2.2 ~VariableScript()

```
virtual mage::VariableScript::~~VariableScript ( ) [virtual]
```

Destruct this variable script.

5.36.3 Member Function Documentation

5.36.3.1 AddVariable()

```
template<typename T >
void mage::VariableScript::AddVariable (
    const string & name,
    VariableType type,
    const T * value )
```

Adds the given variable to this variable script.

Precondition

No variable with the name *name* exists in this variable script.

Template Parameters

<i>T</i>	The type of the value.
----------	------------------------

Parameters

in	<i>name</i>	The name of the variable.
in	<i>type</i>	The type of the variable.
in	<i>value</i>	A pointer to the value of the variable.

5.36.3.2 ExportScript()

```
void mage::VariableScript::ExportScript (
    const string & filename = "" )
```

Exports this variable script to the file with the given filename.

Parameters

in	<i>filename</i>	A reference to the filename.
----	-----------------	------------------------------

5.36.3.3 ExportVariable()

```
void mage::VariableScript::ExportVariable (
    const Variable * variable,
    FILE * file ) [protected]
```

Export the given variable from this variable script to the given file.

Parameters

in	<i>variable</i>	A pointer to the variable variable.
in	<i>file</i>	A pointer to a file used for exporting.

5.36.3.4 GetValueOfVariable()

```
template<typename T >
const T* mage::VariableScript::GetValueOfVariable (
    const string & name ) const
```

Returns the value of the given variable in this variable script.

Template Parameters

<i>T</i>	The type of the value.
----------	------------------------

Parameters

in	<i>name</i>	The name of the variable.
----	-------------	---------------------------

Returns

NULL if no variable with the name *name* exists in this variable script.
A pointer to the value of the variable.

5.36.3.5 ImportScript()

```
void mage::VariableScript::ImportScript ( ) [protected]
```

Imports this variable script from its associated file.

5.36.3.6 ImportVariable()

```
void mage::VariableScript::ImportVariable (
    const string & name,
    FILE * file ) [protected]
```

Import the given variable from the given file to this variable script.

Precondition

No variable with the name *name* exists in this variable script.

Parameters

in	<i>name</i>	The name of the variable.
in	<i>file</i>	A pointer to a file used for importing.

5.36.3.7 RemoveVariable()

```
void mage::VariableScript::RemoveVariable (
    const string & name )
```

Removes the given variable from this variable script.

Parameters

in	<i>name</i>	The name of the variable.
----	-------------	---------------------------

5.36.3.8 SetValueOfVariable()

```
template<typename T >
void mage::VariableScript::SetValueOfVariable (
    const string & name,
    const T * value )
```

Sets the value of the given variable in this variable script.

Template Parameters

<i>T</i>	The type of the value.
----------	------------------------

Parameters

in	<i>name</i>	The name of the variable.
in	<i>value</i>	A pointer to the value of the variable.

Note

Nothing happens if no variable with the name *name* exists in this variable script.

5.36.4 Member Data Documentation

5.36.4.1 m_variables

```
list< const Variable * > mage::VariableScript::m_variables [protected]
```

Linked list containing the variables in this variable script.

5.37 mage::Vertex Struct Reference

```
#include <geometry.hpp>
```

Public Member Functions

- [Vertex](#) ()
- [Vertex](#) (XMFLOAT3 [p](#), XMFLOAT3 [n](#), XMFLOAT2 [tex](#))

Public Attributes

- XMFLOAT3 [p](#)
- XMFLOAT3 [n](#)
- XMFLOAT2 [tex](#)

5.37.1 Detailed Description

A struct of vertices.

5.37.2 Constructor & Destructor Documentation

5.37.2.1 [Vertex\(\)](#) [1/2]

```
mage::Vertex::Vertex ( )
```

Constructs a vertex.

5.37.2.2 [Vertex\(\)](#) [2/2]

```
mage::Vertex::Vertex (
    XMFLOAT3 p,
    XMFLOAT3 n,
    XMFLOAT2 tex )
```

Constructs a vertex.

Precondition

The length (L2-norm) of the normal must be equal to one (i.e. the normal vector is normalized).

Parameters

in	<i>p</i>	The position of the vertex (in object space).
in	<i>n</i>	The normal of the vertex.
in	<i>tex</i>	The texture coordinates of the vertex.

5.37.3 Member Data Documentation

5.37.3.1 `n`

`XMFLOAT3 mage::Vertex::n`

The normal of this vertex.

5.37.3.2 `p`

`XMFLOAT3 mage::Vertex::p`

The position of this vertex (in object space).

5.37.3.3 `tex`

`XMFLOAT2 mage::Vertex::tex`

The texture coordinates of this vertex.

5.38 `mage::ViewerSetup` Struct Reference

```
#include <state.hpp>
```

Public Member Functions

- [ViewerSetup\(\)](#)

Public Attributes

- `uint64_t` [m_view_clear_flags](#)

5.38.1 Detailed Description

A struct of viewer setups.

5.38.2 Constructor & Destructor Documentation

5.38.2.1 `ViewerSetup()`

`mage::ViewerSetup::ViewerSetup ()`

Constructs a viewer setup.

5.38.3 Member Data Documentation

5.38.3.1 `m_view_clear_flags`

`uint64_t mage::ViewerSetup::m_view_clear_flags`

Flags used for clearing the view.

