


# CSE110A: Compilers

## Topics: Algorithms for Parsing

- *Syntactic Analysis continued*
  - *Top down parsing*
    - *Oracle parser*
    - *Rewriting to avoid left recursion*



# New topic: Algorithms for parsing

One goal:

- Given a string  $s$  and a CFG  $G$ , determine if  $G$  can derive  $s$
- We will do that by implicitly attempting to derive a parse tree for  $s$
- Two different approaches, each with different trade-offs:
  - Top down
  - Bottom up

# Top-down parsing

input: 2+3+4


expr

Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM

# Top-down parsing

input: 2+3+4


Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM



# Top-down parsing

input: 2+3+4


Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM



# Top-down parsing

input: 2+3+4

Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM



# Top-down parsing

## Pros:

- Algorithm is simpler
- Faster than bottom-up
- Easier recovery

## Cons:

- Not efficient on arbitrary grammars
- Many grammars need to be re-written

# Bottom-up parsing

input: 2+3+4

Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM

<NUM, 2>   <PLUS>   <NUM, 3>   <PLUS>   <NUM,4>



# Bottom-up parsing

input: 2+3+4


Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM

expr  
|  
<NUM, 2>   <PLUS>   <NUM, 3>   <PLUS>   <NUM,4>

# Bottom-up parsing

input: 2+3+4


Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM



# Bottom-up parsing

input: 2+3+4

Operator	Name	Productions
+	expr	: expr PLUS NUM   NUM



# Bottom up

## Pros:

- can handle grammars expressed more naturally
- can encode precedence and associativity even if grammar is ambiguous

## Cons:

- algorithm is complicated
- in many cases slower than top down

Let's start with top down

```
root = start symbol;
focus = root;
push(None);
to_match = s.token();

while (true):
    if (focus is a nonterminal)
        pick next rule (A ::= B1,B2,B3...BN);
        push(BN... B3, B2);
        focus = B1

    else if (focus == to_match)
        to_match = s.token()
        focus = pop()

    else if (to_match == None and focus == None)
        Accept
```

```
1: Expr ::= Expr Op Unit
2:      |   Unit
3: Unit ::= '(' Expr ')'
4:      |   ID
5: Op  ::= '+'
6:      |   '*'
```

*Can we derive the string (a+b) \*c*

Expanded Rule	Sentential Form
start	Expr

Variable	Value
focus	
to_match	
s.istring	
stack	

```
root = start symbol;
focus = root;
push(None);
to_match = s.token();

while (true):
    if (focus is a nonterminal)
        pick next rule (A ::= B1,B2,B3...BN);
        push(BN... B3, B2);
        focus = B1

    else if (focus == to_match)
        to_match = s.token()
        focus = pop()

    else if (to_match == None and focus == None)
        Accept
```

*Currently we assume this is magic and picks the right rule every time*

- 1: Expr ::= Expr Op Unit
- 2: | Unit
- 3: Unit ::= '(' Expr ')'
- 4: | ID
- 5: Op ::= '+'
- 6: | '\*'

*Can we derive the string (a+b) \*c*

Expanded Rule	Sentential Form
start	Expr

Variable	Value
focus	
to_match	
s.istring	
stack	

```
root = start symbol;
focus = root;
push(None);
to_match = s.token();

while (true):
    if (focus is a nonterminal)
        pick next rule (A ::= B1,B2,B3...BN);
        push(BN... B3, B2);
        focus = B1

    else if (focus == to_match)
        to_match = s.token()
        focus = pop()

    else if (to_match == None and focus == None)
        Accept
```

*Currently we assume this is magic and picks the right rule every time*

- 1: Expr ::= Expr Op Unit
- 2: | Unit
- 3: Unit ::= '(' Expr ')'
- 4: | ID
- 5: Op ::= '+'
- 6: | '\*'

*Can we derive the string (a+b) \*c*

Expanded Rule	Sentential Form
start	Expr
1	Expr Op Unit
2	Unit Op Unit
3	'(' Expr ')' Op Unit
1	'(' Expr Op Unit ')' Op Unit
2	'(' Unit Op Unit ')' Op Unit
4	'(' ID Op Unit ')' Op Unit

And so on...

Variable	Value
focus	Op
to_match	'+'
s.istring	b) *c
stack	Unit ')' Op, Expr, None



```
root = start symbol;
focus = root;
push(None);
to_match = s.token();
```

```
while (true):
    if (focus is a nonterminal)
        pick next rule (A ::= B1,B2,B3...BN);
        push(BN... B3, B2);
        focus = B1
```

```
    else if (focus == to_match)
        to_match = s.token()
        focus = pop()

    else if (to_match == None and focus == None)
        Accept
```

*What can go wrong if we don't have a magic choice*

```
1: Expr ::= Expr Op Unit
2:      |   Unit
3: Unit ::= '(' Expr ')'
4:      |   ID
5: Op  ::= '+'
6:      |   '*'
```

*Can we derive the string (a+b) \*c*

Expanded Rule	Sentential Form
start	Expr

Variable	Value
focus	
to_match	
s.istring	
stack	

```
root = start symbol;
focus = root;
push(None);
to_match = s.token();
```

*What can go wrong*

```
while (true):
    if (focus is a nonterminal)
        pick next rule (A ::= B1,B2,B3...BN);
        push(BN... B3, B2);
        focus = B1

    else if (focus == to_match)
        to_match = s.token()
        focus = pop()

    else if (to_match == None and focus == None)
        Accept
```

Variable	Value
focus	
to_match	
s.istring	
stack	

```
1: Expr ::= Expr Op Unit
2:      | Unit
3: Unit ::= '(' Expr ')'
4:      | ID
5: Op  ::= '+'
6:      | '*'
```

*Can we derive the string (a+b) \*c*

Expanded Rule	Sentential Form
start	Expr
2	Expr Op Unit
2	Expr Op Unit Op Unit
2	Expr Op Unit Op Unit Op Unit
2	Expr Op Unit ....

*Infinite recursion!*

# Top down parsing does not handle left recursion

```
1: Expr ::= Expr Op Unit
2:       | Unit
3: Unit  ::= '(' Expr ') '
4:       | ID
5: Op    ::= '+'
6:       | '*'
```

direct left recursion

```
1: Expr_base ::= Unit
2:          | Expr_op
3: Expr_op   ::= Expr_base Op Unit
4: Unit      ::= '(' Expr_base ') '
5:          | ID
6: Op        ::= '+'
7:          | '*'
```

indirect left recursion

*Top down parsing cannot handle either*

# Top down parsing does not handle left recursion

- In general, any CFG can be re-written without left recursion

# Eliminating direct left recursion

```
Fee ::= Fee "a"  
      |   "b"
```

*What does this grammar describe?*

# Eliminating direct left recursion

*The grammar can be rewritten as*

$$\begin{array}{l} \text{Fee} ::= \text{Fee } \text{"a"} \\ \quad | \quad \text{"b"} \end{array}$$
$$\text{Fee} ::= \text{"b"} \text{Fee2}$$
$$\begin{array}{l} \text{Fee2} ::= \text{"a"} \text{Fee2} \\ \quad | \quad \text{"\""} \end{array}$$

# Eliminating direct left recursion

*In general, A and B can be any sequence of non-terminals and terminals*

$$\begin{array}{l} \text{Fee} ::= \text{Fee } A \\ \quad | \quad B \end{array}$$
$$\text{Fee} ::= B \text{ Fee2}$$
$$\begin{array}{l} \text{Fee2} ::= A \text{ Fee2} \\ \quad | \quad \text{"\""} \end{array}$$

# Eliminating direct left recursion

```
1: Expr ::= Expr Op Unit
2:      | Unit
3: Unit  ::= '(' Expr ')'
4:      | ID
5: Op    ::= '+'
6:      | '*'
```

*Lets do this one as an example:*

Fee	::=	Fee	A
			B



Fee	::=	B	Fee2
Fee2	::=	A	Fee2
			""



# Eliminating direct left recursion

A = ?  
B = ?

```
1: Expr ::= Expr Op Unit
2:      | Unit
3: Unit  ::= '(' Expr ')'
4:      | ID
5: Op    ::= '+'
6:      | '*'
```

```
1: Expr  ::= ?
2: Expr2 ::= ?
3:      | ?
4: Unit  ::= '(' Expr ')'
5:      | ID
6: Op    ::= '+'
7:      | '*'
```

*Lets do this one as an example:*

```
Fee ::= Fee A
     | B
```



```
Fee  ::= B Fee2
Fee2 ::= A Fee2
     | ""
```

# Eliminating direct left recursion

A = Op Unit  
B = Unit

```
1: Expr ::= Expr Op Unit
2:      | Unit
3: Unit  ::= '(' Expr ')'
4:      | ID
5: Op    ::= '+'
6:      | '*'
```

```
1: Expr  ::= Unit Expr2
2: Expr2 ::= Op Unit Expr2
3:      | ""
4: Unit  ::= '(' Expr ')'
5:      | ID
6: Op    ::= '+'
7:      | '*'
```

*Lets do this one as an example:*

```
Fee ::= Fee A
     | B
```



```
Fee  ::= B Fee2
Fee2 ::= A Fee2
     | ""
```

```
while (true):
    if (focus is a nonterminal)
        pick next rule ( $A ::= B_1, B_2, B_3 \dots B_N$ );
        push( $B_N \dots B_3, B_2$ );
        focus =  $B_1$ 

    else if (focus == to_match)
        to_match = s.token()
        focus = pop()

    else if (to_match == None and focus == None)
        Accept
```

focus	
to_match	
s.istring	
stack	

```

1: Expr    ::= Unit Expr2
2: Expr2   ::= Op Unit Expr2
3:         |  ""
4: Unit    ::= '(' Expr ')'
5:         |  ID
6: Op      ::= '+'
7:         |  '*'

```

[illegible]

```
root = start symbol;
focus = root;
push(None);
to match = s.token();
```

```
while (true):  
    if (focus is a nonterminal)  
        pick next rule ( $A ::= B_1, B_2, B_3 \dots B_N$ );  
        push( $B_N \dots B_3, B_2$ );  
        focus =  $B_1$ 
```

```
else if (focus == to_match)
    to_match = s.token()
    focus = pop()
```

```
else if (to_match == None and focus == None)
    Accept
```

Variable	Value
----------	-------

focus	
to_match	
s.istring	
stack	

*How to handle  
this case?*

```

1: Expr ::= Unit Expr2
2: Expr2 ::= Op Unit Expr2
3:      | ""
4: Unit ::= '(' Expr ')'
5:      | ID
6: Op ::= '+'
7:      | '*'

```

[illegible]

```
while (true):
    if (focus is a nonterminal)
        pick next rule (A ::= B1,B2,B3...BN);
        if A == "": focus=pop(); continue;
        push(BN... B3, B2);
        focus = B1

    else if (focus == to_match)
        to_match = s.token()
        focus = pop()

    else if (to_match == None and focus == None)
        Accept
```

```

1: Expr ::= Unit Expr2
2: Expr2 ::= Op Unit Expr2
3:      |  ""
4: Unit  ::= '(' Expr ')'
5:      |  ID
6: Op    ::= '+'
7:      |  '*'

```

[illegible]

# How about indirect left recursion?

```
1: Expr ::= Expr Op Unit
2:      | Unit
3: Unit  ::= '(' Expr ')'
4:      | ID
5: Op    ::= '+'
6:      | '*'
```

direct left recursion

```
1: Expr_base ::= Unit
2:          | Expr_op
3: Expr_op  ::= Expr_base Op Unit
4: Unit     ::= '(' Expr_base ')'
5:          | ID
6: Op       ::= '+'
7:          | '*'
```

indirect left recursion

*Top down parsing cannot handle either*

# How about indirect left recursion?

```
1: Expr_base ::= Unit
2:           | Expr_op
3: Expr_op   ::= Expr_base Op Unit
4: Unit      ::= '(' Expr_base ')'
5:           | ID
6: Op        ::= '+'
7:           | '*'
```

*Identify indirect left left recursion*

$$\text{Expr\_base} \rightarrow_{lhs} \text{Expr\_op} \rightarrow_{lhs} \text{Expr\_base}$$

# How about indirect left recursion?

```
1: Expr_base ::= Unit
2:           | Expr_op
3: Expr_op   ::= Expr_base Op Unit
4: Unit      ::= '(' Expr_base ')'
5:           | ID
6: Op        ::= '+'
7:           | '*'
```

*Identify indirect left left recursion*

$$\text{Expr\_base} \rightarrow_{lhs} \text{Expr\_op} \rightarrow_{lhs} \text{Expr\_base}$$

*Substitute indirect non-terminal closer to initial non-terminal*



# How about indirect left recursion?

```
1: Expr_base ::= Unit
2:           | Expr_op
3: Expr_op   ::= Expr_base Op Unit
4: Unit      ::= '(' Expr_base ')'
5:           | ID
6: Op        ::= '+'
7:           | '*'
```

```
1: Expr_base ::= Unit
2:           | Expr_base Op Unit
3: Expr_op   ::= Expr_base Op Unit
4: Unit      ::= '(' Expr_base ')'
5:           | ID
6: Op        ::= '+'
7:           | '*'
```

*Identify indirect left left recursion*

What to do with production rule 3?

$Expr\_base \rightarrow_{lhs} Expr\_op \rightarrow_{lhs} Expr\_base$

*Substitute indirect non-terminal closer to initial non-terminal*

# How about indirect left recursion?

```
1: Expr_base ::= Unit
2:           | Expr_op
3: Expr_op   ::= Expr_base Op Unit
4: Unit      ::= '(' Expr_base ')'
5:           | ID
6: Op        ::= '+'
7:           | '*'
```

```
1: Expr_base ::= Unit
2:           | Expr_base Op Unit
3: Expr_op   ::= Expr_base Op Unit
4: Unit      ::= '(' Expr_base ')'
5:           | ID
6: Op        ::= '+'
7:           | '*'
```

*Identify indirect left left recursion*

What to do with production rule 3?

It may need to stay if another production rule references it!

$Expr\_base \rightarrow_{lhs} Expr\_op \rightarrow_{lhs} Expr\_base$

*Substitute indirect non-terminal closer to initial non-terminal*

# Next time: algorithms for syntactic analysis

- Continue with our top down parser.
  - Backtracking
  - Lookahead sets