Norwalk Zoning Regulations Bulk Height Schedule 7.9.25

Note: Schedule is meant to provide the basic information regarding zone standards. Full listing of applicable criteria is available in the Zoning Regulations

Zone	Min. Lot Area	Frontage Build Out	Densisty (unit/lot area)	Lot width	Principal Building Height	Building Coverage\Max. Impervious Surface Coverage	Principal Building Setbacks		
							Front	Side	Rear
CD-1L	43,560	N/R	1 unit/ 43,560	150 ft. min.	2.5 stories max. 35 ft. to midpoint max. 40 ft. to peak max.	See Below[1]	40 ft. min.	30 ft. min.	30 ft. min.
CD-1M	12,500	N/R	1 unit/ 12,500	100 ft. min.	2.5 stories max. 35 ft. to midpoint max. 40 ft. to peak max.	See Below[1]	30 ft. min.	10 ft. min.	20 ft. min.
CD-1S	6,250	N/R	1 unit/ 6,250	50 ft. min.	2.5 stories max. 32 ft. to midpoint max. 40 ft. to peak max.	See Below[1]	Principal - 30 ft. min. Secondary - 20 ft. min.	6 ft. min.	15 ft. min.
CD-2	5,000	N/R	2 unit/ 5,000	50 ft. min.	2.5 stories max. 32 ft. to midpoint max. 40 ft. to peak max.	See Below[1]	[2]Principal - 30 ft. min. Secondary - 20 ft. min.	5 ft. min.	15 ft. min.
CD-3	N/R	Min. 60%	1 unit/ 1,650[3]	50 ft. min.; 100 ft. max.; 18 ft. min. for Townhouse	3.5 stories max. see allowed ceiling heights	80% Total Impervious Sfc. Cvg.[6]	6 ft. min., 12 ft. max.	0 ft.	3 ft. min.; or 15 ft. min. from center line of Rear Alley
CD-3W	N/R	Min. 60%	1 unit/ 1,650	50 ft. min.; 100 ft. max.; 18 ft. min. for Townhouse	2.5 stories max. see allowed ceiling heights	80% Total Impervious Sfc. Cvg.	6 ft. min., 12 ft. max.	0 ft. min.	15 ft. min.
CD-3C	N/R	Min. 60%	1 unit/ 1,650	50 ft. min.; 100 ft. max.; 18 ft. min. for Townhouse; 300 ft. max. for Large Scale Commercial	2 stories min., 4 stories max. see allowed ceiling heights	80%. IMP SFC. May inc. to 90% for Dev. of 30 or more Units, if 10% of Area isPub. Realm & 10% of Area Landscaping.	6 ft. min., 12 ft. max.	0 ft.	3 ft. min.; or 15 ft. min. from center line of Rear Alley
CD-4	N/R	Min. 80%	1 unit/ 500	300 ft. max.	2 stories min., 6.5 max., see additional limitations regulated by location. Also see allowed ceiling heights	80%. IMP SFC. May inc. to 90% for Dev. of 30 or more Units, if 10% of Area isPub. Realm & 10% of Area Landscaping.	0 ft. min., Principal - 12 ft. max. (Note: can be measured from Pub. Imp.)	0 ft. min.	3 ft. min.
CD-4W	N/R	Min. 80%	1 unit/ 500	300 ft. max.	2 stories min., 4.5 stories max. see allowed ceiling heights	90% Total Impervious Sfc. Cvg.	0 ft. min., 5 ft. max.	0 ft. min.	3 ft. min. [4]
SD-H	15 Acres	N/R	NP	300 ft. min.	See map within SD-H zone	75%	See map within SD-H zone		
SD-IC	2 Acres	N/R	1 unit/ 1,650	N/R	2.5 stories max.	25%	25 ft. min.	25 ft. min.	25 ft. min.
SD-LI	5,000	N/R	1 unit/ 1,650[5]	50 ft. min.	4 stories with limitations	50% for Buildings; 90% for Buildings and Parking	10 ft. min.	None, except 10 ft. min. if Abutting Res Zone	None, except 10 ft. min. if Abutting Residential Zone
SD-HI	5,000	N/R	N/P	50 ft. min.	4 stories with limitations	50% for Buildings; 90% for Buildings and Parking	10 ft. min.	0 ft. min., except 10 ft. min. Abutting Res Zone	0 ft. min., except 10 ft. min. if Abutting Residential Zone
SD-MC	N/R	N/R	1 unit/ 2,000	100 ft. min.	4.5 stories max.	80%; 90% if use LID practices and provide a vegetative buffer	5 ft. min.	5 ft. min.	25 ft. from CGL with limitations

NP - Not Permitted NR- Not Regulated

1) For Lot or Building Site Area ≤ 6,250 SF, Building Coverage 35%, Impervious Surface Coverage 50%

1A) Areas of 6,251 square feet to 12,499 square feet: Bld CVG 2,186 SF + 20% every additional SF of Lot area > 6,251 SF up to 12,499 SF. IMP SFC 50% of Area - 1% for every additional 400 SF Area up to 12,499 SF

1B) Areas of 12,500 SF or more, Building Coverage, 25% and 35% Impervious Surface Coverage

1C) IMP SFC can be inc. to 60% for Area < 12,500 SF, provided that all site runoff is retained on-site and if Lot abuts inland or tidal Watercourse or Wetland, a minimum 15' foot vegetated buffer, consisting of climate tolerant, native plant is installed

2) See Table 4.3.1-D for allowance for 2-family dwellings front setbacks

3) See EVTZ Village District for additional density bonuses

Norwalk Zoning Regulations Bulk Height Schedule 7.9.25

Note: Schedule is meant to provide the basic information regarding zone standards. Full listing of applicable criteria is available in the Zoning Regulations

4) See section 4.3.3.H

5) Permitted w/limitations

6) 60% maximum in the EAVD