Every page, reviewed and cross-checked

Eleven expert reviewers each audited one page through UI/UX, frontend, backend, accessibility and debugging lenses and compared it with Google Maps, Yelp, Beli, Burpple and GrabFood. A second, independent agent then re-read the code behind every finding, removed wrong claims, fixed severities and added what the first reviewer missed. Only cross-checked findings appear here. Scores are out of 10, measured against leading apps.

409
verified findings

14
critical

122
high

3.9/10
average page score

39
added by cross-checkers

80
claims removed or corrected

Scorecard

Merchant mode — 3/10

1 critical · 19 high · 17 medium · 9 low

Merchant mode is a wide prototype.

Profile (own & others) — 3.5/10

4 critical · 10 high · 19 medium · 6 low

The Profile surface looks finished, but much of what it shows is invented or broken.

Lists, wheel & extras — 3.5/10

2 critical · 10 high · 16 medium · 6 low

This is the weakest area of the app.

Home feed, stories & messages — 4/10

1 critical · 8 high · 18 medium · 3 low

The production Home feed looks like Instagram, but several things underneath it are broken.

Discover & map — 4/10

14 high · 17 medium · 6 low

Discover looks rich, but much of it is invented: the rail labels ('< 15 MIN', 'CURATED', 'MUST ORDER',

Search & filters — 4/10

7 high · 26 medium · 7 low

Production builds set EXPO_PUBLIC_CATALOG_READ_V2=1.

'Trending', 'Late Night') are not backed by data.

Stall & dish detail 4/10

1 critical 16 high 16 medium 14 low

The detail pages have solid foundations: race-safe async loads, a clean no-photo hero on dish detail, 44px accessible docks, and owner replies inline.

Reviews & posting 4/10

2 critical 13 high 16 medium 4 low

The backend pipeline has improved: submits are idempotent, the Recommend value persists, the feed uses one paginated query and prototype media is gated out of production.

Settings & account 4/10

2 critical 8 high 15 medium 8 low

The Settings page looks complete, but 12 of its 15 saved switches do nothing outside the Settings screen, including both privacy switches.

Login & sign-up 4.5/10

9 high 16 medium 11 low

The foundations are good.

Onboarding 4.5/10

1 critical 8 high 16 medium 7 low

Onboarding looks much better than in the 2026-10-18 audit: no login wall, no fake loader, one cuisine/dish screen, and a result screen ranked by taste.

Fix first: critical issues

Problems where a core action silently fails or users see wrong data.

Onboarding

Finishing the quiz in onboarding overwrites the taste answers with the neutral vector

Don't call setTasteVector from the dietary phase, or seed values from profile.tasteVector, or pass a draft through route params or a store. Add a regression test.

Home feed, stories & messages

Block never takes effect on the server

Pass authorId and write the UUID. Filter by authorId on the client. Clean up the name-based rows. Add a smoke SQL test: block a user, then confirm the feed RPC excludes them.

Stall & dish detail

Menu tiles show other dishes' photos, names, prices and tap targets

One tile = one dish: static AccessibleImage with a NoDishPhoto fallback (as in DishCard.tsx:72-83). Cycle only the dish's own gallery if motion is wanted.

Reviews & posting

Per-keystroke sanitizer prevents typing spaces, newlines and common words

Store raw text and sanitize once at submit (strip HTML, trim, cap). Remove SQL_META_REGEX from free-text paths. Enforce length on the server. Add a test that setText('a ') preserves the space.

Reviews & posting

Blocked/reported authors remain in the Review feed

Block by user_id. Filter blocked and moderated content on the server for the feed and dish reviews. Remove the item locally once the block or report succeeds.

Profile (own & others)

Following a user always fails RLS in Supabase mode and silently reverts

Add a SECURITY DEFINER follow_user(target) RPC that writes pending or approved based on the target's privacy setting. Use a plain insert, show a toast when the follow reverts, and add a smoke SQL test.

Profile (own & others)

Own follower/following counts are invented from feed and comment authors

Show only server counts from an RPC or counter column. Delete mergeFollowerNames, localFollowerCount and the local add-ons, and show a skeleton while loading.

Profile (own & others)

Followers list shows every community user; Following list shows the viewer's follows on anyone's profile

Build lists only from listFollowers/listFollowing(target) with pagination. Use local state only for the Follow button on each row, and write empty-state copy for the profile being viewed.

Profile (own & others)

Other users' follower and following stats are hard-coded

Add a get_public_profile RPC that returns real counts and respects privacy.

Settings & account

12 of 15 saved Settings switches have no effect

Hide the switches that have no consumer. Connect allowSearchHistory to search history recording and clear the history when it is turned off. Build hideReviewedDishesFromFeed on the server or remove it. Add a contract test that every visible switch has a consumer outside Settings.

Settings & account

Settings & account

'Change Password' always fails for Supabase users

Add a ChangePassword screen that re-authenticates and then calls auth.updateUser({password}) with no code exchange. Hide the row for users who signed in with a non-email provider.

Merchant mode

No in-app way into Merchant mode, and 'Switch to Customer Mode' is a one-way door

Load getMerchantAccount() in session bootstrap. Keep 'is merchant' separate from a mode flag, and have the switch toggle only the mode. Add a persistent Business entry or account switcher.

Lists, wheel & extras

Wheel never picks a winner: the seed is a 0–1 float

Pick winnerEntryId (integer index/id) in triggerSpin, store it, and derive the angle from that index. Unit-test n in {2,3,7}.

Lists, wheel & extras

No path to the result screen and no way out of the spin screen

In solo mode, resolve on the client (set status 'resolved' and winnerEntryId, then navigate). Reset spinSeed/status on Spin again. Add a close control and a Maestro smoke test.

All findings by page

All | Critical | High | Medium | Low | All lenses | Search findings or files

Login & sign-up 4.5/10

The foundations are good. Guests can use the app, OAuth uses PKCE with state checks, the return route survives sign-in, and account-scoped stores are cleared when the user changes. The screens on top are unfinished. In production the main "I Verified My Email" button always fails, changing your password from Edit Profile cannot succeed, the reset-success screen has fake buttons, and autofill, loading states and keyboard handling are missing. Next to Google Maps, Yelp, Beli or GrabFood it feels like a prototype with good bones.

▶ How it compares with other apps

▶ What it does well (10)

▶ Issues from the 18 Oct audit: 4 still present, 7 fixed

▶ Cross-check notes: 29 confirmed, 1 removed, 7 corrected, 7 added

▼ Findings (36)

high bug

'I Verified My Email' always fails in production

Because enable_confirmations is true, signUp returns no session. The button calls auth.refreshSession(), which throws AuthSessionMissingError when there is no session, so the user always sees 'Could not confirm verification yet'. hungry://auth/confirm maps to Login and drops the PKCE code, so the user has to sign in again by hand. OnboardingAuth also sends users to this screen. The only workaround is to find Login yourself.

Fix: Exchange ?code on auth/confirm and route from there. Better, use the 8-digit OTP that is already configured (config.toml:34) with verifyOtp({type:'signup'}). Replace the button with 'Open mail app' plus OTP entry.

`EmailVerificationScreen.tsx:139-194; supabaseService.ts:2994-2999; supabase/config.toml:33; linking.ts:116-117; client.ts:65-66`

---

high bug

Change password from Edit Profile can never succeed

EditProfile passes code 'profile-settings'. exchangeRecoveryCodeIfPresent either swallows the URL TypeError and calls exchangeCodeForSession('profile-settings'), which throws, or rejects it as an untrusted URL. updateUser never runs, so every signed-in user sees 'Password reset failed'.

Fix: Add a dedicated change-password path that calls updateUser({password}), with current-password re-auth or secure_password_change. Only exchange a code that came in through the deep link.

`EditProfileScreen.tsx:103-108; supabaseService.ts:1838-1868, 2981-2986`

---

high bug

Reset-password deep link is likely kicked off the screen mid-update (inferred race)

exchangeCodeForSession emits a session event, so applyAuthStateFromSession sets isAuthenticated to true. The RootNavigator effect sees AuthStack on top and calls navigateHome(), or resets to OnboardingWelcome on a device that hasn't onboarded, while updateUser is still in flight. The success navigation then targets an unmounted screen, and any error toast lands on Home.

Fix: Exchange the code on mount, and set a passwordRecoveryInProgress flag (or key off PASSWORD_RECOVERY) that the auth effect respects until updateUser resolves.

`useAppBootstrap.ts:309-323; RootNavigator.tsx:579-591; supabaseService.ts:2981-2986; ResetPasswordScreen.tsx:34-44`

---

high backend-data

sign_up_completed almost never fires, so the acquisition funnel is blind

The only emitter is the dead 'I Verified' handler, which is also the only place share attribution is consumed. Auto-confirm, OAuth sign-up and OnboardingAuth send no sign-up event. New accounts are instead logged as sign_in_completed with method 'email' through SIGNED_IN. Nothing tracks auth views, failures, guest continue, reset requests or OAuth cancels.

Fix: Fire it from one place: the first SIGNED_IN for a newly created user, or the confirm exchange. Attach share attribution there and add the missing funnel events.

`analytics.ts:464; EmailVerificationScreen.tsx:164-170; supabaseService.ts:2994-2999; useAppBootstrap.ts:309-323; OnboardingAuthScreen.tsx:1-2`

`rg sign_up_completed src -> only EmailVerificationScreen.tsx:164; SignUpScreen.tsx:71-75, 158-162; OnboardingAuthScreen.tsx:116,125,148,152,171`

---

high product **ResetPasswordSuccess has fake buttons and backwards copy**

The screen appears after the password has changed, but says 'Check your inbox'. 'Open email client' only shows a toast. 'Resend link' shows a success toast without calling any API. The resend Pressable has no role or label.

Fix: Split it into a 'Check your inbox' screen after ForgotPassword (with a real mail intent and a real resend with cooldown) and a 'Password updated' screen after reset, with a single Continue button.

`ResetPasswordSuccessScreen.tsx:19-20, 24, 48-57`

---

high ui-ux **Production shows disabled 'Google unavailable' / 'Apple unavailable' buttons**

oauthProvidersEnabled is off in production, but both buttons still render at 0.6 opacity. On SignUp they are the first thing on the screen. They look broken and lower contrast.

Fix: Enable Apple and Google in production. Until then, hide the buttons and the divider.

`featureFlags.ts:35; LoginScreen.tsx:290-307; SignUpScreen.tsx:244-261; AuthProviderButton.tsx:30-32, 61`

---

high ui-ux **Password-manager and Keychain autofill are disabled**

Input defaults autoComplete to 'off' on secure fields, and no auth screen sets textContentType or autoComplete. iOS won't offer saved or strong passwords, and Android Autofill won't fill.

Fix: Set email/username, current-password and new-password with passwordRules, plus name. Drop the forced 'off' default.

`Input.tsx:61; rg textContentType|autoComplete= src/app/screens/auth -> none`

---

high bug **No submitting state, so a double tap sends duplicate auth requests**

Button supports loading, which also disables it, but no auth screen uses it or isSubmitting. A second signUp or reset send hits the 60s rate limit and shows an error after a success. OAuth gives no in-flight feedback.

Fix: Bind formState.isSubmitting (and local OAuth state) to loading, and disable the sibling buttons while a request runs.

`Button.tsx:24,60; LoginScreen.tsx:268-273; SignUpScreen.tsx:365; ForgotPasswordScreen.tsx:114; ResetPasswordScreen.tsx:182; EmailVerificationScreen.tsx:139`

---

high ui-ux **Keyboard covers fields and buttons, and the first tap only dismisses it**

Screen has no KeyboardAvoidingView or keyboardShouldPersistTaps. Login and ResetPassword use scroll={false} plus a 64px offset, so the submit button can sit under the keyboard on small phones. On scrolling screens the first tap only dismisses the keyboard. There is no returnKeyType or onSubmitEditing chaining.

Fix: Use KeyboardAwareScrollView, always scroll, set keyboardShouldPersistTaps='handled', chain fields, and remove the offset.

Screen.tsx:57-105; LoginScreen.tsx:150-152; ResetPasswordScreen.tsx:54; ForgotPasswordScreen.tsx:52

---

medium bug

Emails are sent untrimmed

Validation trims only for the regex test. A trailing space from QuickType reaches the auth calls, and the user sees 'Incorrect email or password'.

Fix: Normalise with trim().toLowerCase() inside supabaseService.auth.

`validation.ts:15-25; LoginScreen.tsx:57; SignUpScreen.tsx:50-54; ForgotPasswordScreen.tsx:31; EmailVerificationScreen.tsx:46`

---

medium bug

Resend countdown (54s) is shorter than the server limit (60s)

The first 'Resend now' hits over_email_send_rate_limit and shows a generic error.

Fix: Use a shared 60s+ constant, map the rate-limit code to a message, and base the countdown on an end timestamp.

`EmailVerificationScreen.tsx:28, 52, 59; config.toml:35`

---

medium frontend

Mock email 'james.cook@chef.com' is the default on the verify screen

Without params, the screen shows this address and Resend sends to it.

Fix: Without an email param, redirect to SignUp.

`EmailVerificationScreen.tsx:26`

---

medium bug

OAuth outcome depends on the starting screen, and navigators race after auth

OAuth from Login forces onboarding complete; OAuth from SignUp forces it incomplete. SIGNED_IN reaches RootNavigator (reset to OnboardingWelcome) before the screen's own reset. Email login from Welcome on a device that hasn't onboarded flashes Welcome, then goes Home.

Fix: Decide from the server profile, let only RootNavigator route after auth, and use one 'Continue with Google' button.

`LoginScreen.tsx:73,135; SignUpScreen.tsx:158-172; RootNavigator.tsx:579-591; useAppBootstrap.ts:309-323`

---

medium backend-data

sign_in_completed is mislabelled, and sign-ups are counted as sign-ins

SIGNED_IN usually runs first and hardcodes method 'email'. It also ignores the caller's trackSignInEvent:false, so every new account is logged as a sign-in.

Fix: Derive the provider and whether the user is new from session.user in applyAuthStateFromSession, or have a single caller log the event.

`useSessionStore.ts:155-168, 220-226, 324-335; useAppBootstrap.ts:316-319`

---

medium ui-ux

Login is a dead end after a reset, and 'Continue without an account' throws away context

There is no close or back control. After resetRoot, Android back exits the app. When Login is pushed over a dish, 'Continue' resets to Home and leaves a stale returnRoute behind.

Fix: Present Login as a modal with an X. 'Not now' should goBack() and clear returnRoute.

`LoginScreen.tsx:47-52; RootNavigator.tsx:631-635; ProfileHomeScreen.tsx:259`

---

medium product

No context on the sign-in gate, and the action isn't replayed

Every gate shows a generic 'Welcome back' with a large logo, and only the route is restored, not the action.

Fix: Pass a reason, use a bottom-sheet gate, and replay the pending action.

`authCopy.ts:8; DishDetailScreenV2.tsx:443-448; RootNavigator.tsx:495-536`

---

medium ui-ux

Password rules are inconsistent, and the checklist is fake

The client requires 12+ characters with four character classes (against NIST guidance); the server sets no policy. The ResetPassword checklist is static.

Fix: Use an 8-10 character minimum plus an HIBP leaked-password check, mirror it in config.toml, and make the checklist update live.

`validation.ts:28-56; authCopy.ts:33-34; config.toml [auth]; ResetPasswordScreen.tsx:162-179`

---

medium backend-data

Vercel preview wildcards are on the auth redirect allow-list

Any matching preview deploy can receive auth codes, and the Supabase project is shared across environments.

Fix: Remove them from production and use a separate staging project.

`supabase/config.toml:25-28`

---

medium accessibility

Small tap targets and missing roles on secondary actions

'Forgot password?' is micro text with no hitSlop. The Terms and Privacy links are nested Text with no link role. 'Back to sign up' and 'Resend link' have no role. The shell title has no header role.

Fix: Give each a 44pt minimum, use the link or button role, split the legal links, and give the title the header role.

`LoginScreen.tsx:251-261,165-175; SignUpScreen.tsx:199-217,222-238; EmailVerificationScreen.tsx:80-93; ResetPasswordSuccessScreen.tsx:24; AuthScreenShell.tsx:43-45`

---

medium accessibility

Server errors appear only as toasts, and SignUp errors aren't tied to their fields

SignUp draws its own error text instead of passing error and errorText, so there is no red border and no live region. ResetPassword uses SHOUTED labels and '••••••••' placeholders.

Fix: Show an inline error banner, pass the error props, and use sentence-case labels.

`SignUpScreen.tsx:281-292,301-313,351-359; LoginScreen.tsx:79-85; ResetPasswordScreen.tsx:83-85,119-121`

---

medium product

Two auth UIs with diverging logic

OnboardingAuth reimplements sign-in and sign-up. It does call applySignedInProfile (through applySessionProfile), but without profileReady, and it maps every sign-in failure to the sign-up message with no invalid_credentials or email_not_confirmed handling.

Fix: Delete it and route to a shared auth sheet or stack with an entry-point param.

`OnboardingAuthScreen.tsx:76-87, 140-156; LoginScreen.tsx:57-85`

---

medium backend-data

(Added) Guest 'merge' overwrites a returning user's saved taste and dietary profile

Any guest taste or dietary signal on the device replaces the account's server tasteVector, tasteProfile and dietaryPreferences, and is written back to the server. A returning user who browses briefly as a guest on a new phone loses their real profile.

Fix: Merge only into an empty or neutral server profile, or ask the user before replacing.

`applySignedInProfile.ts:44-57`

---

medium bug

(Added) Confirm and reset links only work on the phone that requested them

PKCE stores the code_verifier on the device, and the redirects use the hungry:// custom scheme with no universal link. Opening the email on a laptop or another device fails.

Fix: Use OTP codes, or an https universal-link landing page with a fallback.

`client.ts:65-66; links.ts:24-27; config.toml redirect list`

---

medium ui-ux

(Added) Expired reset links and unconfirmed logins are dead ends

An expired or reused recovery code shows 'Password reset failed. Please try again.', but retrying can never work. Login's email_not_confirmed toast offers no resend.

Fix: Detect otp_expired or a bad code and offer 'Send a new link'. Add an inline 'Resend verification email' on email_not_confirmed.

`ResetPasswordScreen.tsx:37-43; LoginScreen.tsx:79-80`

---

medium ui-ux

(Added) Apple sign-in uses a web OAuth sheet, not native Sign in with Apple

Both providers go through WebBrowser.openAuthSessionAsync, so iOS users get a browser Apple ID login instead of the one-tap Face ID sheet. That is worse for conversion and a review risk once OAuth ships.

Fix: Use expo-apple-authentication with signInWithIdToken and the official AppleAuthenticationButton.

`supabaseService.ts:2580-2600; no expo-apple-authentication in src or package.json`

---

low ui-ux

ForgotPassword has no confirmation state

It shows a toast and goes straight back to Login. There is no 'check your inbox', resend or spam hint.

Fix: Route to a real 'Check your inbox' screen.

`ForgotPasswordScreen.tsx:30-34`

ForgotPasswordScreen.tsx:30-34

---

low bug **Splash can hang if the persisted session JSON is corrupt (inferred)**

safeAsyncStorage already swallows storage I/O errors, but a JSON.parse failure still calls onRehydrateStorage with state undefined. markHydrated never runs, isAuthReady stays false, and there is no timeout.

Fix: Call markHydrated() whether or not there was an error, and add a 5s Splash fallback.

`useSessionStore.ts:377-379; persistStorage.ts:193; useAppBootstrap.ts:244-247; SplashScreen.tsx:94-97`

---

low bug **A MainTabs return route is pushed twice**

HomeFeed saves {name:'MainTabs'}, and navigateHome resets to [MainTabs, MainTabs].

Fix: Treat a MainTabs returnRoute as a tab switch.

`HomeFeedScreen.tsx:321; RootNavigator.tsx:48, 524-532`

---

low bug **Session expiry overwrites the return route with 'Home'**

The user loses their place in a dish or the composer.

Fix: Capture the active route, as RootNavigator.tsx:616-630 does.

`RootNavigator.tsx:548-554`

---

low frontend **Login forces hasSkippedTasteQuiz=true for every returning user**

This overwrites the real quiz state.

Fix: Leave it undefined, or derive it from the server profile.

`LoginScreen.tsx:73,135; useSessionStore.ts:208`

---

low ui-ux **Internal backend wording reaches users**

Users can see 'not enabled in Supabase Auth', raw callback and state messages, and the 'security services' text in the error boundary.

Fix: Show friendly copy and log the raw error to Sentry.

`authCopy.ts:86-88; LoginScreen.tsx:100-108; SignUpScreen.tsx:119-127; AuthStack.tsx:19-20`

---

low ui-ux **Visual hierarchy and consistency problems**

Login and SignUp order OAuth and email differently. The divider reads 'OR REGISTER WITH EMAIL'. Provider labels use h3. The Apple button isn't HIG-styled. The title hardcodes 24pt. ResetPassword has no title. EmailVerification has duplicate back actions.

Fix: Use one layout (Apple, Google, then email), token typography, a 'Set a new password' title, and a single back action.

`LoginScreen.tsx:268-307; SignUpScreen.tsx:244-269; AuthProviderButton.tsx:75; AuthScreenShell.tsx:43; ResetPasswordScreen.tsx:52; EmailVerificationScreen.tsx:79-93,197-208`

A JS splash plays after the native

low performance

splash and ignores reduced motion

There is no expo-splash-screen coordination, so users see two splashes and a minimum of 600ms. The spring animations ignore reduced motion. Styles are rebuilt every render. A version stamp is shown to consumers.

Fix: Hold the native splash until auth is ready, respect reduced motion, and memoise styles.

`SplashScreen.tsx:34,44-91,99,162-173; tokens.ts:389; no preventAutoHideAsync in the repo`

---

low backend-data

Mock-only UX branches ship in the screens

The mock sign-up shows a warning toast and then a success toast. Mock resend resets the timer.

Fix: Move mock behaviour into the mock service.

`SignUpScreen.tsx:78-90; EmailVerificationScreen.tsx:45-54; ForgotPasswordScreen.tsx:36-37`

---

low accessibility

(Added) Field errors aren't announced on iOS and use 12pt text

accessibilityLiveRegion works only on Android, so VoiceOver users get no announcement on validation failure. The error text is micro, 12pt.

Fix: Call AccessibilityInfo.announceForAccessibility on error and use bodySmall or larger.

`Input.tsx:142-149`

---

low backend-data

(Added) TOTP MFA is enabled in config, but the app has no enrol or challenge flow

[auth.mfa.totp] has enroll and verify set to true, but there is no mfa or aal2 handling in src. The config is dead, and merchants have no second factor.

Fix: Add an optional MFA enrol flow for merchants and an aal2 challenge on Login, or turn the setting off.

`supabase/config.toml auth.mfa.totp; rg 'mfa\.|aal2' src -> none`

Onboarding 4.5/10

Onboarding looks much better than in the 2026-10-18 audit: no login wall, no fake loader, one cuisine/dish screen, and a result screen ranked by taste. The data underneath is still broken. In onboarding mode the separate DietaryPreferences instance overwrites the six taste answers with the neutral vector, cuisine picks are discarded, and result cards show stock photos (chicken rice for any dish outside the 14 seed IDs). The flow is still about 11 screens, and the auth screen has dead OAuth buttons, no keyboard handling and the wrong sign-in error copy.

▶ How it compares with other apps

▶ What it does well (10)

▶ Issues from the 18 Oct audit: 5 still present, 11 fixed

▶ Cross-check notes: 29 confirmed, 0 removed, 5 corrected, 2 added

▼ Findings (32)

critical bug

Finishing the quiz in onboarding overwrites the taste answers with the neutral vector

The last taste question navigates to a separate DietaryPreferences route, which mounts a fresh TasteQuizScreen whose values start at NEUTRAL_TASTE_VECTOR. Its handleFinish calls setTasteVector(values) and recordQuizResponse(values), so the Result ranking, Home personalisation and the server vector all become neutral.

Fix: Don't call setTasteVector from the dietary phase, or seed values from profile.tasteVector, or pass a draft through route params or a store. Add a regression test.

`TasteQuizScreen.tsx:37, :146 useState(INITIAL), :692-695 navigate('DietaryPreferences'), :226-233 handleFinish; OnboardingStack.tsx:23; useProfileStore.ts:557-603`

---

high backend-data

setTasteVector runs on every swipe and fires taste_quiz_completed, confidence bumps and server writes

Every answer change tracks 'taste_quiz_completed', adds 0.05 to confidence, increments signalCount and, for authenticated users, calls updateTasteVector. One quiz produces many 'completed' events and inflates confidence.

Fix: Keep a local draft, commit it once at finish, and emit a separate per-step event if needed.

`TasteQuizScreen.tsx:272-280, :523-531; useProfileStore.ts:563-567, :578-583, :593-603`

---

high bug

Retaking the quiz from Profile writes on every swipe, starts from neutral and can't be cancelled

In profile mode each swipe is saved and synced. Untouched dimensions reset to 5, and backing out does not roll anything back.

Fix: Start from profile.tasteVector, keep a draft, and discard it on back.

`EditProfileScreen.tsx:229-234; TasteQuizScreen.tsx:146, :272-275, :724-726`

---

high backend-data

Cuisine selections are required and then thrown away

At least one cuisine is required to continue, but `selected` is never saved. Only dish IDs are stored, so the strongest cold-start signal is lost.

Fix: Save cuisine IDs to the profile and the server, and use them in ranking (SearchFilters.cuisineTags, domain.ts:405) and in recordQuizResponse.

`CuisineSelectionScreen.tsx:214, :250-260, :391`

---

high ui-ux

Result cards show onboarding stock images, and chicken rice for any unknown dish

and chicken rice for any unknown dish

The screen ignores dish.imageUrl and uses a 14-seed-ID map that falls back to the chicken-rice asset. Any real catalog dish shows a chicken-rice photo labelled 'Photo of <dish>'.

Fix: Use dish.imageUrl with the shared no-photo fallback.

`TasteProfileResultScreen.tsx:102-107; onboardingFoodImages.ts:227-246; DishSummary.imageUrl in domain.ts`

---

high bug

Settings > Location > Continue does nothing and fires onboarding_completed again

handleSubmit saves the area and calls completeOnboarding but never navigates. The RootNavigator effect doesn't re-run because hasCompletedOnboarding is already true. The back button is labelled 'Back to location permission' in the Settings context.

Fix: If already onboarded, save, goBack() and show a toast. Only call completeOnboarding on first run.

`SettingsScreen.tsx:372-373; ManualLocationPickerScreen.tsx:117-121, :133-135; useSessionStore.ts:231-239; RootNavigator.tsx:593-603`

---

high ui-ux

OnboardingAuth shows two disabled OAuth buttons at the top in production

'Google unavailable' and 'Apple unavailable' sit above an 'or' divider. The provider error copy mentions Supabase Auth.

Fix: Hide the buttons when the flag is off, ship Apple/Google sign-in, and rewrite the copy for users.

`featureFlags.ts:35; OnboardingAuthScreen.tsx:258-271; authCopy.ts:82-88`

---

high frontend

OnboardingAuth has no keyboard avoidance, no scroll and no submit loading state

The form is a fixed View. The submit buttons have no loading state, so double taps can fire duplicate signUp calls. There are no autofill or content-type props, and autoCorrect is on for email.

Fix: Use KeyboardAvoidingView with a ScrollView, set loading={formState.isSubmitting}, and add textContentType/autoComplete.

`OnboardingAuthScreen.tsx:191-201, :385-390, :451-456; Button.tsx:24,60`

---

high product

The flow is still about 11 screens with inconsistent progress indicators

Welcome > Cuisine > 6 questions > Dietary > Result > Location. Only the quiz shows progress.

Fix: Collapse the quiz into a few 'this or that' taps, ask for location earlier, and use one progress bar across all steps.

`WelcomeScreen.tsx:51; CuisineSelectionScreen.tsx:259; TasteQuizScreen.tsx:48, :165, :330; TasteProfileResultScreen.tsx:164`

---

medium backend-data

Onboarding dish picks partly use IDs that exist in no catalog, and are stored only on the device

The dish-* picks match the 14 dev seed IDs, but about 8 onboarding-* IDs exist nowhere, and real production catalog IDs probably won't match. The picks are saved only locally.

Fix: Map picks to taste and cuisine tags, or resolve them to canonical dishes on the server, and save them to the profile.

`onboardingFoodImages.ts ids; supabase/seed.sql has only 14 dish-* IDs and no onboarding-* IDs; feed.ts:88; useProfileStore.ts:859-865`

---

medium product

Skipping the quiz also skips diet and allergy collection

Skip goes straight to LocationPermission, so a halal or allergic user is never asked about diet.

Fix: Make Skip go to the dietary step, or add diet chips to the cuisine screen.

`TasteQuizScreen.tsx:728-730; OnboardingIntroTemplate.tsx:313-316`

---

medium ui-ux

The dietary step mixes budget into a 'restrictions' screen and lists 30 flat flags

Budget comes first under 'Any dietary restrictions?'. The list includes EU allergens and implies a guarantee about allergens. The empty-search copy is wrong, and budget is stored only on the device.

Fix: Group the options, show the top SG diets first, add an allergen disclaimer and fix the empty-state copy.

`TasteQuizScreen.tsx:312, :367, :251, :64-126, :443; useProfileStore.ts:117`

---

medium bug

Sign-up with email verification skips the location step

The screen resets to EmailVerification with completedOnboarding:true, and verification then completes onboarding without a location.

Fix: After verification, return to LocationPermission if no location has been set.

`OnboardingAuthScreen.tsx:99-113; EmailVerificationScreen.tsx:27, :174-181`

---

medium product

The Result heart forces sign-in and then loses the save

After auth the user goes to LocationPermission and the dish is never saved. There is no visible 'Not now' control.

Fix: Store the pending dish and save it after auth, and add a 'Not now' button.

`TasteProfileResultScreen.tsx:131-141; OnboardingAuthScreen.tsx:72-74`

---

medium bug

Signing in to an existing account during onboarding overwrites its server taste profile

Any quiz swipe makes signalCount greater than 0, so the guest vector wins the merge and is uploaded over the returning user's trained vector.

Fix: Merge only on sign-up, or ask the user on sign-in.

`OnboardingAuthScreen.tsx:141-150; applySignedInProfile.ts:24-33, :50-68`

---

medium backend-data

Guest quiz responses are never recorded, and quiz_version is never set

recordQuizResponse returns early when there is no user, and nothing replays it after sign-up. The insert relies on the default 'v1'. Orphaned rows are not an issue: the 0040 deletion RPC removes them.

Fix: Queue the response and flush it after sign-up, and send an explicit quiz_version.

`supabaseService.ts:3555-3565; 0027_taste_recommendation_events.sql:54-61; 0040:184`

---

medium backend-data

No onboarding funnel analytics, and sign-ups from onboarding are not attributed

No onboarding screen calls trackAnalyticsEvent. OnboardingAuth always passes trackSignInEvent:false and never emits sign_up_completed, and the SIGNED_IN listener hardcodes method 'email'.

Fix: Add onboarding_step_viewed, onboarding_skipped and sign_up_completed events with surface 'onboarding'.

`rg trackAnalyticsEvent in src/app/screens/onboarding -> none; OnboardingAuthScreen.tsx:116,125,148,152,171; useSessionStore.ts:328-333`

---

medium ui-ux

Location step: the CTA fires the OS prompt without warning, denial copy is wrong, and there is no route to Settings

'Continue' fires the OS prompt. A denial shows 'We couldn't find your location'. getCurrentPositionAsync has no timeout, and the feature copy overclaims stall-level directions while floorplans are off. An 'Enter Manually' secondary button does exist.

Fix: Rename the CTA 'Allow location', rewrite the denial copy, offer openSettings when the prompt can't be shown again, add a timeout, and fix the feature copy.

`LocationPermissionScreen.tsx:199-204, :75-81, :83-94, :26-50; useLocationStore.ts:107-115; featureFlags.ts:36`

---

medium frontend

The quiz layout wastes vertical space and can clip on small screens

Empty header placeholder Views, minHeight:44 spacers under every footer, a fixed 298pt card and overflow hidden.

Fix: Remove the dead views and size the card from the available height.

`TasteQuizScreen.tsx:297-308, :667, :700, :742, :168`

---

medium frontend

The Result screen has no loading or error state and ignores the bottom safe area

The grid starts empty and cards pop in. Errors are swallowed. The footer has no insets.bottom, and the cards can't be tapped.

Fix: Add a skeleton, a retry, paddingBottom of insets.bottom, and tappable cards.

`TasteProfileResultScreen.tsx:43-66, :80-84, :159`

---

medium product

No taste-profile reveal on the Result screen

The screen says 'Your taste profile is ready' but never shows the profile.

Fix: Show a compact taste summary or archetype plus a 'because you…' reason on each card.

`TasteProfileResultScreen.tsx:78-85`

---

medium accessibility

Animations ignore Reduce Motion, and the Welcome CTA stays hidden for about 1.4s

Welcome runs a ~1.38s sequence with the CTA at opacity 0 until it ends. No onboarding file checks Reduce Motion.

Fix: Use a reduced-motion hook and show the CTA immediately.

`WelcomeScreen.tsx:35-47, :198-210; CuisineSelectionScreen.tsx:231-238; TasteQuizScreen.tsx:189-224`

---

medium product

The cuisine list is thin and mixes diet with cuisine

Only 9 cuisines, with 'Muslim-friendly' listed as a cuisine. Satay and briyani IDs repeat across sections.

Fix: Drive the list from catalog tags, move Halal to the diet step, and add Thai, Peranakan, desserts and cafes.

`onboardingFoodImages.ts:42-52, :157-210`

---

medium ui-ux

Optional dish picks appear below the fold

'Any favourites?' renders under a tall 9-card grid, so users rarely see it.

Fix: Expand the picks inline under the cuisine card, or auto-scroll with a hint.

`CuisineSelectionScreen.tsx:24-25, :297-357`

---

medium bug

(Added) A failed sign-in on OnboardingAuth shows sign-up error copy, and there is no Forgot password

handleLogin's catch shows AUTH_COPY.signUp.genericErrorToast ('Could not continue sign-up') for wrong passwords and every other sign-in error. The sign-in tab has no reset link. Returning, already-onboarded users are also pushed through LocationPermission again.

Fix: Use the signIn copy with an invalid-credentials case, add a Forgot password link, and skip Location for accounts that are already onboarded.

`OnboardingAuthScreen.tsx:141-155 (catch uses signUp copy), :72-74; authCopy.ts:21 (signIn copy) vs :50 (signUp copy)`

---

low frontend

Orphaned Intro template, Intro1 and OnboardingScreenShell

Intro1 is reachable only from SignUp and the dev launcher, so first runs differ by entry point. OnboardingScreenShell is not imported anywhere.

Fix: Delete them, or point SignUp at CuisineSelection.

`SignUpScreen.tsx:169; DeveloperLauncherScreen.tsx:904; OnboardingIntroTemplate.tsx`

---

low accessibility

Accessibility labels and semantics need polish

Quiz option labels read the answer before the question, Select/Deselect labels repeat the selected state, emojis are read aloud, and 'Selected: X' is a disabled Button.

Fix: Fix the labels, mark decorative content, and use a chip for 'Selected'.

`TasteQuizScreen.tsx:548; CuisineSelectionScreen.tsx:44,129; WelcomeScreen.tsx:178; ManualLocationPickerScreen.tsx:129-166`

---

low accessibility **(Added) The Result heart button's touch target is under 44pt**

A 15px icon with 4pt padding and 8pt hitSlop gives about 39pt.

Fix: Use a minimum 44x44 Pressable.

`TasteProfileResultScreen.tsx:122-147`

---

low ui-ux **Hard-coded fonts, sizes and colours bypass the style system**

Literal Fraunces/Nunito sizes, #FFFFFF and rgba scrims; fixed lineHeights may clip at large text sizes.

Fix: Add a display typography variant and use tokens.

`WelcomeScreen.tsx:97-150; CuisineSelectionScreen.tsx:77,147,179,196-198,283; OnboardingAuthScreen.tsx:204-213`

---

low bug **Finishing from Location can trigger two navigations (returnRoute race)**

finish() resets the root, and the RootNavigator effect also calls navigateHome.

Fix: Let RootNavigator own the transition.

`LocationPermissionScreen.tsx:64-73; RootNavigator.tsx:593-595`

---

low performance **Minor render and perf issues in the quiz and cuisine screens**

Inline separator, interpolations created per render, 'as any', uncleared timers, an unused answeredKeys, and Dimensions read at module load.

Fix: Hoist and memoise, clear timers on unmount, and use useWindowDimensions.

`TasteQuizScreen.tsx:482, :535-543, :461, :203-222; CuisineSelectionScreen.tsx:21-25; WelcomeScreen.tsx:17`

---

low ui-ux **Taste-question content is unconvincing**

Questions use 'tonight' moods but are stored as permanent preferences. The 'sour' options aren't sour, and fish soup appears twice.

Fix: Phrase questions as stable preferences and choose clearer example dishes.

`TasteQuizScreen.tsx:39-46; onboardingFoodImages.ts:259-268`

Home feed, stories & messages 4/10

The production Home feed looks like Instagram, but several things underneath it are broken. Block never matches on the server. Like, save and follow state are never loaded from the server, so a tap can delete a like that already exists. Every like the user gives adds an alert about themselves to their

own inbox. The Updates inbox shows raw ISO timestamps and UUIDs. A consumer has no way to get from a post to the dish or stall. DMs, comments and stories sit behind flags and are further from shippable than the prior audit said.

▶ How it compares with other apps

▶ What it does well (8)

▶ Issues from the 18 Oct audit: 3 still present, 5 fixed

▶ Cross-check notes: 25 confirmed, 0 removed, 6 corrected, 2 added

▼ Findings (30)

critical backend-data **Block never takes effect on the server**

blockAuthor writes blocked_user_key as the author's display name, lowercased and hyphenated. The server checks compare blocked_user_key with the user's UUID as text, so they never match and blocked users' content still arrives. The client hides them only through an in-memory Set that is lost on restart, and that Set matches by name, so every author with the same display name is hidden too. App Store guideline 1.2 needs a working block.

Fix: Pass authorId and write the UUID. Filter by authorId on the client. Clean up the name-based rows. Add a smoke SQL test: block a user, then confirm the feed RPC excludes them.

`src/lib/security/communitySafety.ts:25-27, ~72-91 (blockAuthor); supabaseService.ts:4365-4374; 0041_full_audit_social_safety.sql:62,66; 0040:173`

---

high bug **Like and save state never loads from the server; a tap can delete an existing like**

initializeInteractions sets liked:false and saved:false for unseen posts, and the RPC returns no viewer state. reactToBite reads first, then deletes or inserts, so it toggles whatever the server has. After a reinstall, the heart shows empty, a tap turns it red, and the server deletes the like. The whole store is persisted with no partialize. Two fast taps race the read-then-write. Counts never refresh after a post is first seen.

Fix: Add viewer_has_liked and viewer_has_saved to the RPC as EXISTS subqueries and load them on every fetch. Make the like call idempotent: setReaction(postId, liked).

`useSocialStore.ts:146-162, 216-233, 557-561; supabaseService.ts:3770-3794; 0033 returns no viewer columns`

---

high bug **Every like puts a notification about yourself in your own inbox**

toggleLike, addComment and addReply call addActivityUpdate with the current user as actor and no recipientUserId. Liking someone else's post adds '<you> liked your post' (with the post UUID as target) to your Updates and raises the bell badge.

Fix: Remove the local addActivityUpdate calls and create notifications for other users on the server with

triggers.

`useSocialStore.ts:195-206, ~450, ~517; HomeFeedScreen.tsx:292-306; ActivityInboxScreen.tsx:111-113`

---

high bug

Updates tab shows raw ISO timestamps and UUIDs

time is set to createdAt and target to targetId. Because target is always set, it overrides the friendly label, and that label is the author's name in any case. The UUID is also read aloud by the accessibility label. new_follower is mapped to the share icon with an empty postId, so tapping it does nothing, and new_reply rows target a comment id and go nowhere.

Fix: Format times with formatTimeAgo and resolve targets to dish names. Add a follow kind that opens UserProfile. Resolve reply targets to their post on the server. Show avatars.

`useActivityStore.ts:83-108; ActivityInboxScreen.tsx:66-78, 386-440`

---

high product

In production a feed post leads nowhere

For consumers (canAccessMap false), the dish overlay, venue line and caption are plain text and comments are off. Nothing takes the user to the dish or stall.

Fix: Make the dish and venue overlay open DishDetail or StallDetail, add a 'View dish' chip, and make a caption tap open post detail.

`HomeFeedScreen.tsx:313, 1478-1497, 1682-1702`

---

high product

'Copy link' copies no link, and share sends no URL

Copy puts dish and venue text on the clipboard with no URL and no toast. Share.share sends text only. Shares are counted even when the user cancels. webShareUrl already exists.

Fix: Use webShareUrl('post', id), toast 'Link copied', and count a share only on Share.sharedAction.

`HomeFeedScreen.tsx:708-723; ActivityPostDetailScreen.tsx:280`

---

high performance

The whole feed re-renders on every carousel scroll frame, like and heart animation

renderFeedCard depends on interactions, carouselIndexByPostId and heartBurst. The carousel onScroll writes a fractional index to state on every event, so every mounted card rebuilds on each frame.

Fix: Extract a memoized FeedPostCard with a per-post selector, and keep the carousel index local to the card.

`HomeFeedScreen.tsx:1168-1998, 1353-1374, 2084`

---

high backend-data

No feed pagination; unbounded loads of posts and media

The RPC is always called with p_limit 40 and null cursors, and there is no onEndReached. The feed also merges a repository load of every published post, all post_media and all stall_posts with select * and no limit. The repository path ignores hidden_posts, so a hidden post comes back after restart.

Fix: Use the RPC as the only source for the feed, paginate with cursors, and stop hydrating posts and media in the catalog.

`supabaseService.ts:1274-1287; sharedStallPosts.ts:47-49;`

supabaseRepository.ts:648-656

---

high product **Shared post links require login and often show 'no longer available'**

post/:postId is a protected route, so a friend without an account is sent to Login. Signed-in users get a lookup against local caches only, so a post that has not been hydrated shows 'This post is no longer available.' The title is 'Activity post', Hide passes no onHidden, like and save labels are static, and production code looks up mock ACTIVITY_UPDATES.

Fix: Add a public get_post_by_id RPC fetched async with a skeleton and a not-found state, title the screen with the dish name, and prompt sign-in on like or save.

`linking.ts:217; RootNavigator.tsx:100; ActivityPostDetailScreen.tsx:43-45, 84-90, 116-124, 158, 232-238, 292, 329`

---

medium backend-data **listConversations downloads every message (DMs flag only)**

It fetches all messages of all conversations with no limit to get the last message and unread count. markConversationRead reads every message and writes a receipt per message, and runs on every realtime message. Off in production.

Fix: Add a list_conversations RPC (lateral join, unread count in SQL) and mark messages read in a single SQL statement.

`supabaseService.ts:2785-2800, 2847-2856, 4100-4126, 4232-4255; ChatDetailScreen.tsx:89,103`

---

medium bug **Follow state is never loaded and not gated by auth**

followedUserIds starts empty and is only flipped locally. On a new device, people you already follow show 'Follow', and followed authors lose their place at the top of the feed. A guest's tap flips the button, the server fails, and it silently flips back.

Fix: Load the follow list (listFollowing) after sign-in and gate Follow behind the auth prompt.

`useSocialStore.ts:114, 299-317; HomeFeedScreen.tsx:1291-1296; feed.ts:99-104`

---

medium bug **' more' on captions does nothing in production**

With comments off, ' more' is not pressable. With comments on, it opens comments instead of expanding. Overflow detection under numberOfLines may not fire on Android (inferred).

Fix: Make the caption a Pressable that expands in place.

`HomeFeedScreen.tsx:1654-1702, 247-253, 820-830`

---

medium bug **Offline or backend failure shows 'No posts yet – Share a dish'**

Service errors are swallowed into [], so the error state cannot be reached.

Fix: Let network errors throw. Show the error state or a cached feed with an offline banner.

`sharedStallPosts.ts:29-45; supabaseService.ts:1141, 1288-1291; HomeFeedScreen.tsx:2036-2061`

---

medium bug **Saving a post toggles the dish favourite**

If the dish was already a favourite, saving the post removes it, and an 'unsaved' taste signal is

logged.

Fix: Set the favourite idempotently on save and leave favourites alone on unsave.

`HomeFeedScreen.tsx:806-818; useProfileStore.ts:443-449`

---

medium bug

Pull-to-refresh moves the newest posts down the feed

The feed groups are rotated by refreshSeed. The taste ranking is computed and then thrown away when the feed is re-sorted by recency.

Fix: Remove the rotation and blend recency with taste on purpose.

`feed.ts:106-130, 132-160`

---

medium bug

Feed posts silently disappear when their venue is not hydrated (inferred)

buildHomeFeedItems drops posts whose venue is not in the local repository, even though the RPC rows carry the venue fields.

Fix: Build the venue from the RPC venue fields when the repository has no match.

`feed.ts:139-156 (if (!venue) return null)`

---

medium performance

Media URLs are re-signed one at a time on every fetch

One createSignedUrl call per path, with a new URL on every refetch. The image cache treats each as a new image, so images re-download and flicker, and the URLs expire after 1 hour.

Fix: Sign in batches, key the image cache by storage path, and skip refetching while data is fresh.

`supabaseService.ts:1015-1027, 1215-1219, 1300-1302`

---

medium frontend

Videos autoplay offscreen, show a permanent play icon, and ignore double-tap like

Videos play as soon as they mount, with no viewability check. A static PlayCircle covers every video. onPress is dropped for video, so double-tap like does not work. The mute button is 36pt.

Fix: Play only the most-visible video, show the icon only while paused, forward taps, and make the mute target 44pt.

`ZoomableVideo.tsx:25-29, 196-204; ZoomableMedia.tsx:32-54; HomeFeedScreen.tsx:1453-1459`

---

medium ui-ux

Social loading state is a bare spinner that hides the header

The skeleton belongs only to the dead review mode, so the bell, Weekly Picks and stories are all hidden while loading.

Fix: Render the list header plus post-shaped skeletons.

`HomeFeedScreen.tsx:2000-2034, 127-148`

---

medium bug

Comments sheet mixes in dish reviews, has no auth gate, and fails silently (comments flag only)

Dish reviews are inserted with createdAt = now. Replies can target review ids. There is no auth gate on posting, and failures only console.error. Post and Reply have no role or label. The sheet

duplicates ReviewCommentsSheet.

Fix: Reuse ReviewCommentsSheet, separate reviews from comments, gate posting behind auth, and add a failed state with retry.

`HomeFeedScreen.tsx:832-898, 2257-2280, 2377-2393; useSocialStore.ts:484-486, 552-554`

---

medium product

Stories are a facade (flag only, merchant and dev only)

Content is an in-memory seed. 'Gallery' is canned assets. Videos are rendered as images. Tapping your own ring always opens AddStory. 'Send message' builds a fake chat id. Stories are grouped by display name.

Fix: Keep the flag off until there is a real stories table, uploads, receipts and grouping by author id.

`supabaseService.ts:756-830, 3794-3816; AddStoryScreen.tsx:31-36, 98; StoryViewerScreen.tsx:83-89, 175-177, 513-539; CircleStoryCarousel.tsx:49`

---

medium bug

Sharing to a DM sends plain text the recipient cannot open

The message has no id or URL. The rich card is stored only locally for the sender. Promise.all reports a partial failure as one generic error.

Fix: Add a post attachment or URL, render a post card in chat, and use Promise.allSettled.

`useActivityStore.ts:117-138; ChatDetailScreen.tsx:246-277; HomeFeedScreen.tsx:677-701`

---

medium ui-ux

ChatDetail falls short of basic messenger behaviour

ScrollView with no scroll-to-end or pagination. A realtime error shows the load-error message. Single-line composer. No pending or failed bubbles. No profile link, block or report. KeyboardAvoidingView is undefined on Android.

Fix: Use an inverted FlatList, show realtime errors in a banner, and add a nonce per draft, a multiline composer, a profile link, and block and report.

`ChatDetailScreen.tsx:124-133, 185-215, 213-278, 292-301`

---

medium ui-ux

Activity inbox: double fetch, a scan per row, and one tab in production

useEffect and useFocusEffect both load on mount. Each row scans the repository. Production shows a single-pill segmented control. There is no refresh, mark-all-read, grouping or avatars, and markConversationRead is not caught.

Fix: Remove the mount effect, reuse postById, hide the control when there is one tab, and add refresh, sections, avatars and mark-all-read.

`ActivityInboxScreen.tsx:145-156, 386-397, 174-214, 304`

---

medium accessibility

Brand orange fails WCAG AA for small text

#E8531E on white is 3.69:1. It is used for Follow, ' more', Post, badges and prices. An accessible token (orangeText/orangeControl #B43B12) already exists.

Fix: Use orangeText or orangeControl for small text and for backgrounds behind white micro text.

`tokens.ts:19-23; HomeFeedScreen.tsx:1301-1313, 1674-1678, 2277; ActivityInboxScreen.tsx:205-208, 334-337`

---

medium accessibility **Touch targets under 44pt and unlabelled controls**

More is 32pt, Follow is 32pt high, mute is 36pt, back buttons are 28pt, and cancel-reply is 14px. Avatar, Reply and Post are unlabelled. Story like has no state.

Fix: Enforce a 44pt minimum in the Pressable primitive, label every Pressable, and add selected state to story like.

`HomeFeedScreen.tsx:2239-2246, 2617-2632; DirectMessagesScreen.tsx:68-74; ChatDetailScreen.tsx:176-183; StoryViewerScreen.tsx:678-688`

---

medium product **No product analytics on the social surface**

There are no events for feed view, impression, like, save, share, comment, follow or chat send.

Fix: Add typed events in the store actions, and impressions from viewability.

`rg trackAnalyticsEvent src/app/screens/home returns nothing`

---

low frontend **About 1,000 dead lines; HomeFeedScreen has grown to 2,765 lines**

Dead social components, review mode, unused styles, an unreachable DirectMessagesScreen, and a ts-ignored estimatedItemSize.

Fix: Delete the dead code and split the screen.

`HomeFeedScreen.tsx:70, 1735-1955, 2085-2086; DirectMessagesScreen.tsx:80-83`

---

low bug **Bell badge count differs from the inbox**

Home does not filter updates by recipientUserId; the inbox does.

Fix: Use one shared unread selector in both places.

`HomeFeedScreen.tsx:292-306; ActivityInboxScreen.tsx:111-113`

---

low backend-data **Author names come from the snapshot taken at publish**

Renamed users show stale names, and name-keyed follow and block depend on this value.

Fix: Prefer the live profile fields and key social state by authorId.

`supabaseService.ts:1319-1321, 3659-3662`

Discover & map

4/10

Discover looks rich, but much of it is invented: the rail labels ('< 15 MIN', 'CURATED', 'MUST ORDER', 'Trending', 'Late Night') are not backed by data. The location model can quietly return an empty feed, or assert 'YOU ARE AT' for a place the app never located. The map is hidden from consumers, and on the default legacy path its pins and filters do nothing. Decide-for-me is now the strongest part of the page, but it re-picks a different dish from the one Discover chose and logged, and it ignores a manually chosen location.

▶ How it compares with other apps

▶ What it does well (7)

▶ Issues from the 18 Oct audit: 9 still present, 7 fixed

▶ Cross-check notes: 35 confirmed, 1 removed, 5 corrected, 1 added

▼ Findings (37)

high product

Consumers cannot reach any map (deliberate merchant/dev-only gate)

Every map entry point, including the stall rows that open MapZoomedIn, renders only when !isUserMode. A normal production user has no map on a page called 'Discover & map'. With the map bugs below, the gate is defensible for now, but a core competitor capability is missing.

Fix: Fix the HomeMap bugs, then expose the map to all users, or stop promising a map. At minimum, add a list/map toggle on 'Stalls in {area}'.

`DiscoverHomeScreen.tsx:1253, 2270-2286, 3298-3309, 3321-3341; HomeFeedScreen.tsx:313`

---

high backend-data

Manual or unknown area labels return an empty Discover feed

The client always sends areaName. When the name is not in the areas table, area_requested is true and area_found is false. The two area branches need area_found and the radius branch needs NOT area_requested, so the RPC returns 0 rows. The empty array is truthy, so the client fallback never runs. 'Tiong Bahru' is a client anchor but is not seeded in areas, and manual labels such as 'Maxwell Food Centre' also miss.

Fix: Fall back to the radius branch when the area is not found, send areaName only for known planning areas, and add a SQL smoke test for an unknown area name.

`DiscoverHomeScreen.tsx:1349-1350, 1377-1383; 20261018133000_discovery_feed_all_venues.sql:37-52, 89-93, 125-129, 161-171; singaporeBuildings.ts:51; 20260606120000...sql:208-238; supabaseService.ts:3158-3162`

---

high product

Rail badges and section labels are fabricated

'< 15 MIN' covers every dish; there is no prep-time data. 'CURATED' and 'MUST ORDER' on every card are just rating >= 4.4, and in Supabase mode the rail falls back to Trending. 'Trending' sorts by cravingCount, which is reviewCount. 'Late Night' is a name or dinner-flag heuristic that ignores opening hours.

Fix: Rename the rails to what they are ('Top rated near you', 'Most reviewed', 'Under S$8') or back them with real fields. Show 'MUST ORDER' only when a real flag is set.

`bites.ts:354-376; DiscoverHomeScreen.tsx:264, 1783-1789, 2702-2717, 2950-2952, 3006-3020`

---

high bug

'YOU ARE AT' asserts a location the app never got

With permission denied and no manual pick, currentLocation stays at the hard-coded Maxwell coordinate, and the header asserts Chinatown. The OS permission prompt fires on mount with no priming, and again on every mount while permission is not granted.

Fix: Show 'Choose your area' with a picker when there is neither a fix nor a manual pick. Ask for permission only from a user action.

`useLocationStore.ts:29; DiscoverHomeScreen.tsx:1255-1259, 1343-1350, 2249`

---

high bug

Decide-for-me ignores the manual location (added)

The Discover feed uses manualCoordinate ?? currentLocation, but both Decide pickers use GPS currentLocation only. A user who set an area by hand, or whose permission was denied, gets 'nearby' picks around the default Maxwell coordinate.

Fix: Use one effectiveLocation helper (manualCoordinate ?? currentLocation) everywhere, and flag it as approximate when it is the default.

`DiscoverHomeScreen.tsx:1343-1344 vs 2000-2006; DecideForMeResultScreen.tsx:250, 268-276`

---

high bug

Decide-for-me throws away the pick Discover made

Discover picks a dish (searchDishes is called without lat/lng), records a taste interaction for it and stores it. The result screen builds its own candidate list with location and budget and replaces the stored pick if it is not in that list. The user sees a different dish from the one that was logged.

Fix: Use a single selection function. Discover only navigates, and the result screen picks and logs.

`DiscoverHomeScreen.tsx:2000-2046; DecideForMeResultScreen.tsx:268-311`

---

high bug

Crave swipe gestures save the wrong dish (stale PanResponder closure)

The responder is created once in useRef, so the release handler calls the first render's swipeRight, which captures dishes[0] and the first-render isAuthenticated. Every right swipe toggles dish 0. The screen never calls recordTasteInteraction, despite promising a sharper taste profile. Downgraded from critical because the flag is off in production.

Fix: Read the index and auth state from refs, or rebuild the responder in useMemo. Use an idempotent save, and record like and pass.

`CraveScreen.tsx:53, 56-76, 78-99, 156; featureFlags.ts:37-38`

---

high bug

The map opens on Maxwell, and 'Recenter' goes to Maxwell

On the legacy path the camera centres on the selected building or hc-maxwell. The LocateFixed button is labelled 'Recenter map to default building'. HomeMap never passes currentLocation to MapSurface, so there is no user dot.

Fix: Centre on the effective user location, make the locate button recentre on the user, and pass currentLocation.

`HomeMapScreen.tsx:59, 151-156, 409, 573-593, 407-437; MapSurface.tsx:401-405, 543`

high bug

On the legacy path, map pins and filters do nothing and the sheet gesture is frozen

onMarkerPress is set only when catalogReadV2 is on, and that flag is env-driven and off by default. The filter chips are read only by the V2 fetch. The bottom-sheet PanResponder in useRef freezes displayMode at 'carousel', and FULL_HEIGHT is never reached.

Fix: Wire marker presses on both paths, apply the filters to legacy data or hide the chips, and rebuild the responder (or use @gorhom/bottom-sheet).

`HomeMapScreen.tsx:130-131, 433, 197-251, 297-318, 186-188; featureFlags.ts:28`

---

high backend-data

Ranking uses a static dishes.distance_meters column, and every call rescans all dishes

The proximity term reads top_dish.distance_meters (default 0), so every venue gets the maximum bonus. priced_menu_venues is a materialized DISTINCT scan over every priced dish on each call. The 500-row cap is ordered only by has_menu, not by distance.

Fix: Use the computed st_distance in the rank, replace the scan with an EXISTS check on each candidate, and order the cap by distance.

`0002_core_schema.sql:73; 20261018133000...sql:53-62, 173-174, 211`

---

high ui-ux

Mapbox attribution and logo are disabled, and a developer env-var notice can reach users

attributionEnabled and logoEnabled are both false, which conflicts with Mapbox's attribution terms. Without a token, users see 'Set `EXPO_PUBLIC_MAPBOX_ACCESS_TOKEN`...' over fake roads.

Fix: Re-enable the logo and attribution. Gate the notice behind __DEV__ and show 'Map unavailable' in release builds.

`MapSurface.tsx:451-465, 480-482`

---

high backend-data

Collections are local-only, unreachable, and hang when loading fails

Save only flips an in-memory Set; persistence is a TODO. Nothing navigates to CollectionList. CollectionDetail's load has no try/catch, so a rejected load leaves the skeleton up forever. collection_saved fires twice, from trackCollectionSaved and from the store. The flag is off in production.

Fix: Persist saves with RLS, add an entry point, use try/finally with an error state, and track the save once.

`useCollectionStore.ts:80-106; CollectionDetailScreen.tsx:60-73, 136-139; gamificationEvents.ts:67-69`

---

high bug

Preloading screens on press-in runs their effects (inferred)

Preloading DecideForMeResult without params would send decide_for_me_triggered (surface 'direct'), result_shown and recordImpression on a mere touch. Preloading MapZoomedIn runs its mount effect setSelectedBuilding, which fires map_pin_tapped and floor_switched. Preloading

mount effect setSelectedBuilding, which fires map_pin_tapped and floor_switched. Preloading QuickBites runs a search RPC.

Fix: Don't preload screens with analytics effects, or gate those effects on useIsFocused(). Pass the same params on preload as on navigate.

`DiscoverHomeScreen.tsx:2137, 2169, 2399, 3328; DecideForMeResultScreen.tsx:256-264, 332-346; MapZoomedInScreen.tsx:49-52; prefetch.ts:192-214 (relies on React Navigation 7 preload semantics; node_modules was not available to confirm)`

---

high bug

Header count shows a skeleton forever or disagrees with the list

When both count paths fail, the count stays null and null renders a skeleton indefinitely. When it loads, the count uses planning_area ILIKE label while the list uses the areas table and a radius, so the header can show '0 places' above a non-empty list, or a large count above a short one.

Fix: Return the count from the feed RPC, and hide the line when the count fails.

`supabaseService.ts:3010-3019; supabaseRepository.ts:793-803; DiscoverHomeScreen.tsx:1387, 1983, 2262-2268`

---

medium bug

The Dietary Needs and Halal chips show dishes that don't qualify

'Dietary' passes a dish that matches any one flag (some), and falls back to halal, vegetarian and pork_free when the profile has none. 'Halal' also matches the substring 'halal' anywhere in the text, including 'non-halal'.

Fix: Require every flag, and use only structured flags for halal.

`DiscoverHomeScreen.tsx:110, 1710-1722`

---

medium ui-ux

The 'More from {area}' showcase pads with repeats and traps scrolling

It makes one card per dish and loops the array up to 30, with the header showing '30 cards'. It is a nested vertical ScrollView with custom scroll locking and snapping.

Fix: Use one card per venue with no repeats, inside a normal grid or rail.

`DiscoverHomeScreen.tsx:159-209, 849, 797-831, 1523-1575, 2217`

---

medium performance

Discover is one 3,445-line component that re-renders everything and runs dead work

Gesture state uses setState, re-rendering the whole screen, and 3 interpolations per showcase card are rebuilt on each render (about 90). The idle timer resets on every scroll event and loops pulseAnim, which is not bound to any view. ?? [] creates a new array each render, which breaks the memos.

Fix: Split into memoised sections, delete the pulse, keep gesture state in refs or shared values, and use stable empty constants.

`DiscoverHomeScreen.tsx:893-921, 1449-1519, 1556-1564, 1315-1316`

---

medium backend-data

Every GPS refresh blanks Discover and fires two RPCs

The effect is keyed on raw lat/lng and clears the feed to null. Promise.all throws away a good feed when the count call fails.

Fix: Key the effect on a rounded geocell, keep stale content during a refresh, and use Promise.allSettled.

`DiscoverHomeScreen.tsx:1356-1411; useAppBootstrap.ts:144-158`

---

medium bug

Discover's error state almost never shows

rpcRows returns undefined on error, and the service falls back silently to the partial cache with a neutral taste vector. The catch block runs only on an exception.

Fix: Return an explicit fallback status and show a 'Showing saved results' banner.

`supabaseService.ts:686-726, 3158-3162; DiscoverHomeScreen.tsx:1392-1399`

---

medium accessibility

Small tap targets and unlabelled icon controls

SEE ALL and VIEW MAP are 12px text with no hitSlop. Several icon Pressables have no role or label: the HomeMap legend toggle, the MapZoomedIn back button and stall rows, the Decide back button (40x40), Crave back, pass and like, QuickBites tiles, and the SearchResultsView tabs and Taste Filters button.

Fix: Add hitSlop so targets reach 44x44, and give each control a role and a label.

`DiscoverHomeScreen.tsx:2719-2728 etc.; HomeMapScreen.tsx:552-570; MapZoomedInScreen.tsx:126-144, 187-208; DecideForMeResultScreen.tsx:524-529; CraveScreen.tsx:176-186; QuickBitesScreen.tsx:173-176; SearchResultsView.tsx:339-376`

---

medium accessibility

Badge text fails contrast

White 12px text sits on #4ADE80 in dark mode (about 1.7:1) and on orange (#E8531E in light mode, about 3.7:1; #F97316 in dark mode, about 2.8:1).

Fix: Use dark text on light fills, or darker fills, and add these pairs to the contrast tests.

`DiscoverHomeScreen.tsx:2704-2716, 2944-2952, 3011-3019; tokens.ts:15, 19, 91, 95, 105`

---

medium accessibility

No reduce-motion support on the page

The parallax, CyclingGridImage auto-cycling, the match counter and the Crave rotation all ignore Reduce Motion. useReduceMotion exists but this page never uses it.

Fix: Respect useReduceMotion.

`src/hooks/useReduceMotion.ts; no import in discover screens, components/discover or components/map`

---

medium ui-ux

Map cards round prices, and 'Live map status' sits on static data

Prices show as S${Math.round(price)}. 'Live map status' appears whenever the provider is Supabase, and high crowding is labelled 'Trending' in a hard-coded 10px font.

Fix: Use toFixed(2), drop 'Live', label high crowding 'Busy', and use typography tokens.

`HomeMapScreen.tsx:80-115, 700, 835-843; dataTrustDisclosure.ts:14, 26-28`

---

medium ui-ux

Placeholder and debug content in consumer-facing screens

One hard-coded Unsplash photo is used for trending pins. Copy reads 'Raw catalog record' and 'Approved source'. Decide shows an invented description when the dish has none. Stalls are

placed on a fake 7x7 grid.

Fix: Remove the placeholders, and plot stalls only when real coordinates exist.

`MapSurface.tsx:136-141; HomeMapScreen.tsx:657-660, 786-789, 366-375; MapZoomedInScreen.tsx:64-78; DecideForMeResultScreen.tsx:626-627`

---

medium bug

The left-edge back-gesture strip swallows taps on the map

A full-height strip at least 28px wide with pointerEvents='box-only' never claims the responder on touch start, so taps on it are swallowed. That covers the map, the legend button and the left edge of the cards. The native stack already sets gestureEnabled.

Fix: Remove the strip, or limit it to the area outside the sheet.

`HomeMapScreen.tsx:320-333, 440-450, 861-866; RootNavigator.tsx:682-686`

---

medium bug

QuickBites 'See all' uses a different dataset and fake distances

It re-queries from GPS rather than the Discover area. Distance comes from the partial cache, so it falls back to 0m. The heart count is really the review count. The footer duplicates the grid. Errors show 'Try changing your filters'.

Fix: Pass the area as a route param, use the server distance, label counts honestly, and add a separate error state.

`QuickBitesScreen.tsx:233, 255, 288, 354-383; bites.ts:292-297`

---

medium performance

QuickBites animates height on the JS thread and re-renders every cell

Height is animated with useNativeDriver: false. renderItem depends on the visible-id Set, so every cell re-renders on each viewability change. Each cell also polls measureInWindow.

Fix: Animate transforms on the native driver, and pass extraData instead of rebuilding renderItem.

`QuickBitesScreen.tsx:301, 434-441, 574; CyclingGridImage.tsx:15, 99`

---

medium backend-data

HomeMap V2 refetches on every camera move

There is no debounce, the two calls run one after the other, and failures silently clear the map.

Fix: Debounce, run the calls in parallel, and show loading and error chips.

`HomeMapScreen.tsx:197-251, 422-432`

---

medium product

Three overlapping 'choose for me' entry points

Decide and Wheel sit side by side on Discover. The unused DecideForMeCard describes Decide as 'the Hungry wheel'. Home has its own Decide button.

Fix: Keep one primary action.

`DiscoverHomeScreen.tsx:2395-2513; components/discover/DecideForMeCard.tsx:62, 103`

---

medium backend-data

The count query's ILIKE on planning_area likely can't use the indexes (inferred)

ilike(planning_area, name) with an exact count runs against btree indexes, so it is likely a

.ilike('planning_area', name) with an exact count runs against btree indexes, so it is likely a sequential scan.

Fix: Compare the normalised expression with = in an RPC, or reuse the feed count.

`supabaseRepository.ts:795-799`

---

medium bug

map_pin_tapped is fired by code, not by user taps

setSelectedBuilding always sends the event, and it is called from the MapZoomedIn mount effect, from Home before navigating, and from a press-in preload. highlightedStallVenueId is never cleared.

Fix: Send the event from the marker handler only, and clear the highlight after use.

`useDiscoveryStore.ts:65-73; MapZoomedInScreen.tsx:49-52; HomeFeedScreen.tsx:780-787; HomeMapScreen.tsx:178; DiscoverHomeScreen.tsx:2169, 3328`

---

low product

Analytics gaps across the page

Discover tracks only the Decide trigger. Map, QuickBites and Crave track nothing.

Fix: Add rail impression and tap, chip, see-all and map viewport events.

`DiscoverHomeScreen.tsx:64, 1987`

---

low ui-ux

'Stalls in {area}' rows lack the details people choose by

Rows show only the opening time, with no open state, rating, distance or price.

Fix: Add 'Open · closes 9pm', distance and rating.

`DiscoverHomeScreen.tsx:3357-3388`

---

low frontend

Dead or orphaned components and data

discover/DecideForMeCard, ClusterPin and MapBottomSheet are unused. The floorplan viewers are off but still come in through the barrel import. INTENT_CHIPS categories are wrong. popularNearby is refreshed but never read. The SearchResultsView tabs only change styling.

Fix: Delete or wire them up.

`components/map/index.ts; HomeMapScreen.tsx:30; DiscoverHomeScreen.tsx:99-108, 1292-1297; SearchResultsView.tsx:138, 337`

---

low ui-ux

Collection screens have layout bugs

CollectionList wraps the fixed-width CollectionCard in a second Pressable and a bordered View, so borders double. CollectionDetail uses edges=['top'] and also adds insets.top padding, so the inset is applied twice.

Fix: Add a full-width card variant, and use one inset strategy.

`CollectionListScreen.tsx:46-63; CollectionDetailScreen.tsx:115, 121`

---

low ui-ux

The MapZoomedIn sheet is a dead end when stalls are closed

It lists at most 3 open stalls. With none open it shows only 'Closed now'.

Fix: List all stalls with their status, and add Directions.

`MapZoomedInScreen.tsx:92-96, 179-210`

low bug **Late-night chip ordering is frozen at mount**

The chip order computes the hour once in useMemo([]), while the rail recomputes it on every render.

Fix: Use one hour value, refreshed on focus.

`DiscoverHomeScreen.tsx:1435-1446 vs 1644-1645`

Search & filters 4/10

Production builds set EXPO_PUBLIC_CATALOG_READ_V2=1. In that mode the Search landing page is mostly empty: a disabled suggestion card, an empty 'Stalls worth checking' section, and a Taste filter that changes nothing. Guests hit a sign-in wall with no button. The production results grid itself works: it has a persistent query field, server pagination and a retry state. Staging and dev run a different legacy search with its own serious bugs, so QA never sees the search users actually get.

▶ How it compares with other apps

▶ What it does well (7)

▶ Issues from the 18 Oct audit: 7 still present, 4 fixed

▶ Cross-check notes: 35 confirmed, 0 removed, 6 corrected, 2 added

▼ Findings (40)

high product **The production SearchHome is a hollow shell**

Under v2, collections=[], so suggestedDish is undefined and inline results are off. Users see a disabled hero card with an empty image and the false claim 'Best match within 2km', plus a 'Stalls worth checking' heading with zero items.

Fix: Hide sections that have no data in v2, or feed them from catalog_raw_dishes_page (sort=nearby, limit 4). Add v2 inline results. Remove or compute the 2km copy.

`eas.json:49; DishSearchScreen.tsx:57-63, 73-75, 230-296, 298-358; search.ts:123-188 (no 2km filter)`

high product **Guests hit a sign-in wall with no CTA and no back button**

SearchResults and Browse* are not protected routes. In v2 a guest gets an EmptyState with no CTA and no header, so the only way out is the system back gesture.

Fix: Allow anonymous search over a limited projection, or add a back button and a Sign in CTA that returns the guest to the same page.

`SearchResultsScreen.tsx:461-470; RootNavigator.tsx:94-114; DiscoverHomeScreen.tsx:2053, 2527, 2583; catalog/index.ts:315`

high bug

The Taste filter and most category chips do nothing

rawCatalogRequest never sends taste values. Of the SearchHome categories, only noodles and rice survive, and only the first one selected. The legacy RPC sends neither categories nor taste, and rank_score has no taste term.

Fix: Remove the dead controls from production, or add p_taste_vector and p_categories to the RPCs and use them in ranking.

`SearchResultsScreen.tsx:263-282, 1260-1263; TasteFilterScreen.tsx:46-51, 75; supabaseRepository.ts:833-852; dish_food_types.sql:325-333`

---

high backend-data

Legacy text search is filtered by a meaningless stored distance column

radius defaults to 1000 and lat/lng are never set, so the RPC applies d.distance_meters <= 1000 to a stored column that is not the distance from the user.

Fix: Pass the user's location, send a null radius for text queries, and never filter on d.distance_meters.

`useSearchStore.ts:41-47; supabaseRepository.ts:841, 1084-1085; dish_food_types.sql:308-323`

---

high product

Staging and dev QA a different search from production

Only the production EAS profile sets the v2 flag, so bugs in one path are invisible to whoever tests the other.

Fix: Set the flag in preview, run smoke tests against it, then delete the legacy path.

`eas.json:41-49; SearchResultsScreen.tsx:564-576, 1264-1277; DishSearchScreen.tsx:57-58`

---

high bug

An unmatched dietary or cuisine chip silently shows everything (legacy browse)

filtered.length || query ? filtered : feedItems, so a selected Halal chip with no matches shows non-halal food. Matching is a substring search over free text.

Fix: Always return the filtered list with an empty state, and match against structured dietary and cuisine fields.

`SearchResultsScreen.tsx:843-872 (line 871)`

---

high ui-ux

Raw backend error text is shown to users

The v2 grid passes error.message as the EmptyState body, which bypasses the showDebugErrorDetails guard.

Fix: Show friendly copy, pass the raw text via errorMessage, and report it to Sentry.

`SearchResultsScreen.tsx:433-436, 540-546; catalog/index.ts:320-324; EmptyState.tsx:77-83`

---

medium bug

Load-more failures are invisible and retry silently

Errors render only when the list is empty, and the footer shows only a spinner. The next

onEndReached retries silently.

Fix: Add an inline 'Couldn't load more. Retry' footer and stop auto-retrying.

`SearchResultsScreen.tsx:433-437, 519-521, 537-557`

---

medium bug

A location refresh wipes the results list and scroll position

loadPage depends on the currentLocation object. A GPS re-read (once the fix is older than 10 min) or a manual location change resets the list to page 1.

Fix: Depend on rounded coordinates, or snapshot the location per query and offer 'Search this area'.

`SearchResultsScreen.tsx:392, 410-459; useLocationStore.ts:31, 138-150`

---

medium backend-data

Legacy search has no pagination and discards scores

p_limit is 20 with a null cursor, the score is dropped, and the best_match sort is a no-op.

Fix: Paginate, or retire the legacy path.

`supabaseRepository.ts:843-845; search.ts:34-62; SearchResultsScreen.tsx:1288`

---

medium ui-ux

Legacy results flash a false 'No matches found'

isLoading is never passed, and results fall back to a synchronous scan of a possibly cold cache.

Fix: Pass isLoading while serviceResults is null, and skip the synchronous fallback in supabase mode.

`SearchResultsView.tsx:132, 384-386; SearchResultsScreen.tsx:1292-1317`

---

medium backend-data

RPC failure or offline shows as 'no results'

rpcRows returns undefined on any error, the code falls back to the cache, and the user sees an empty list with no error.

Fix: Return a typed error and show an offline or error state with Retry.

`supabaseRepository.ts:756-768; SearchResultsScreen.tsx:1302-1308`

---

medium ui-ux

The 'All' and 'Dishes' tabs do nothing

activeTab only drives styling, and the tabs have no tab role or selected state.

Fix: Remove the tabs, or implement real segments with tablist semantics.

`SearchResultsView.tsx:138, 162, 336-360`

---

medium ui-ux

Legacy results hide the query behind an icon, and it collapses on blur

The search field is a 56px icon that collapses on blur. While it is expanded, the header and its back control are hidden. The v2 grid is not affected: its field is persistent.

Fix: Use a persistent search bar.

`SearchResultsView.tsx:232, 250-262, 293-310; SearchResultsScreen.tsx:1140-1156`

---

medium bug

A stale persisted query and categories leak into new searches

filters persist across launches. SearchHome's input starts empty, but results use the stored query, and v2 falls back to storedQuery.

Fix: Don't persist the query. Pass it as the initialQuery route param, and show active categories as removable chips.

`useSearchStore.ts:162-169; DishSearchScreen.tsx:56, 221-229; SearchResultsScreen.tsx:1259-1263, 1272`

---

medium backend-data

Recent searches are never shown, and the 'Allow search history' toggle is ignored

recentSearches is stored but never rendered. allowSearchHistory is read only by Settings, so queries are still persisted and sent as search_query taste interactions when it is off.

Fix: Render recents on SearchHome, and gate rememberSearch, addHistoryEntry and recordTasteInteraction('search_query') on the toggle.

`useSearchStore.ts:113-132, 162-169; useUIStore.ts:63, 122; SettingsScreen.tsx:72, 536`

---

medium bug

Results need two taps while the keyboard is open

Screen's ScrollView and the search FlashLists don't set keyboardShouldPersistTaps, so the first tap only dismisses the keyboard.

Fix: Set keyboardShouldPersistTaps='handled' and keyboardDismissMode='on-drag'.

`Screen.tsx:57-84; DishSearchScreen.tsx:171-207; SearchResultsView.tsx:387; SearchResultsScreen.tsx:513`

---

medium ui-ux

SearchHome doesn't autofocus and has no 'search' return key

The Input sets neither autoFocus nor returnKeyType. The v2 grid TextInput also lacks returnKeyType and a clear button.

Fix: Add autoFocus, returnKeyType='search' and a clear button.

`DishSearchScreen.tsx:143-159; SearchResultsScreen.tsx:486-505`

---

medium backend-data

A slider drag floods analytics

setTasteValues fires taste_filter_applied on every slider step. Apply only calls goBack, and changes apply live with no Cancel.

Fix: Keep slider values in local state, commit on Apply, and fire one event.

`TasteFilterScreen.tsx:46-51, 75; useSearchStore.ts:89-100`

---

medium backend-data

The production search grid has no analytics

RawCatalogBrowseGrid records no query, zero-result, filter or click events.

Fix: Add search_query, search_zero_results, filter_changed, result_opened and load_more events.

`SearchResultsScreen.tsx:380-562; contrast 1369-1384, 1419-1433`

---

medium accessibility

Taste sliders have no accessible name or value

No Slider has an accessibilityLabel or accessibilityValue.

Fix: Set the label to dimension.label and add accessibilityValue {min, max, now, text}.

`TasteFilterScreen.tsx:38-52`

medium accessibility

Results-page controls are unlabelled or under 44pt

The TASTE FILTERS pill has no role or label and is about 24-28pt tall. The clear X is 20px with no hitSlop. The v2 back button is a bare 24px icon. Tabs have no role.

Fix: Use the IconButton and Button primitives with touch-target sizing and hitSlop.

`SearchResultsView.tsx:314-320, 339-348, 364-381; SearchResultsScreen.tsx:479-485`

---

medium accessibility

Browse cards auto-cycle with no reduce-motion support

Dish cards cycle through other stalls' dishes, so the tap target and label change under the finger. Card text is 10px. CyclingGridImage doesn't use the existing useReduceMotion hook.

Fix: Show only the item's own photos, honour reduce motion, and use 12px or larger text.

`SearchResultsScreen.tsx:93-100, 180, 199, 208, 994-1010;`
`src/hooks/useReduceMotion.ts exists but is unused here`

---

medium ui-ux

Distances are unformatted and may be measured from a fake point

Distances show as raw meters. With location denied, the default point (1.2813, 103.8458) is used silently. Legacy card distances show the stored dish.distanceMeters.

Fix: Format distances as m/km and show a 'using default location' banner.

`SearchResultsScreen.tsx:201, 364-366; useLocationStore.ts:29, 91`

---

medium performance

SearchHome recomputes a full-catalog stall ranking on every render (non-v2)

getDiscoverStallCollections isn't memoized and is O(V×P + V×D) per keystroke.

Fix: Memoize it and precompute per-venue maps, or move it to the server.

`DishSearchScreen.tsx:61-63; search.ts:126-163`

---

medium bug

The browse index can be cached empty for the whole session

It is built from the synchronous caches after a 350ms idle timeout and never invalidated outside tests.

Fix: Invalidate it when the repository refreshes, or wait for hydration.

`browseIndex.ts:40-48; SearchResultsScreen.tsx:606-633`

---

medium performance

Every browse cell re-renders on each viewability change

renderBrowseItem depends on a new Set each time, and every cell rescans the list for slides.

Fix: Precompute slides, memoize BrowseGridCard, and use extraData.

`SearchResultsScreen.tsx:874-884, 994-1010, 93-100`

---

medium performance

The legacy results page fires an un-debounced search RPC on every keystroke

onQueryChange=updateQuery changes filters, which re-runs the getSearchResultsAsync effect

immediately on every character. Each keystroke also writes the persisted store.

Fix: Debounce by about 250ms, and keep the in-progress query in local state until it is committed.

`SearchResultsScreen.tsx:1293-1313, 1406-1407; useSearchStore.ts:50-56, 162-169`

---

medium backend-data

Search predicates likely defeat the indexes (inferred)

Leading-wildcard ILIKE runs on food_type and on arrays. The trigram index on catalog_raw_dish_cards exists only on name, while venue_name and food_type are also searched. This was not checked with EXPLAIN.

Fix: Add trigram indexes or a combined search_text column, then run EXPLAIN ANALYZE.

`dish_food_types.sql:15, 170-176, 442; 20260713120000_versioned_raw_catalog_reads.sql:117`

---

medium backend-data

Dietary filters mean 'any of' on the server but 'all of' on the client

The server uses && and ORs the dish and venue tags. The client requires every flag.

Fix: Use @> for dietary flags on the server.

`dish_food_types.sql:292-307, 440; supabaseRepository.ts:1110-1112`

---

medium product

Text search ignores proximity

With a query, v2 drops the radius and sorts by trigram similarity only.

Fix: Blend a distance decay into relevance and add a Sort control.

`SearchResultsScreen.tsx:272-277; dish_food_types.sql:440-445`

---

medium product

No Open now, price or rating filters in production

'Local', the only chip mapped to openOnly, is excluded from the raw chips, although the RPC already supports p_open_only and p_max_price.

Fix: Add Open now, price and 4★+ chips.

`SearchResultsScreen.tsx:219-223, 280`

---

medium product

Mood (AI) search is practically unreachable

It runs only from the legacy results bar on submit, never in v2, never for guests, and shows no loading state.

Fix: Trigger it on zero results for multi-word queries, and add it to v2.

`SearchResultsScreen.tsx:1331-1384, 1409; DishSearchScreen.tsx:152-158`

---

low frontend

Dead code: sort modes, the initialFilter param and the searchRow style

sortMode is fixed to best_match. The initialFilter route param is never read. browseStyles.searchRow is unused.

Fix: Wire them up or delete them.

`search.ts:16, 42-62; SearchResultsScreen.tsx:1227, 1288; navigationTypes.ts:107`

---

low bug **Route params seed state only once (inferred)**

initialSearchQuery and initialFoodTypeTag are passed only to useState.

Fix: Sync from params in an effect.

`SearchResultsScreen.tsx:394-398, 590`

---

low ui-ux **Fake author attribution on browse cards**

With no post, the author falls back to the venue name and the dish photo.

Fix: Hide the badge when there is no post.

`SearchResultsScreen.tsx:735-736`

---

low ui-ux **An 'Unverified' pill on most catalog cards**

Every non-approved card gets a muted 'Unverified' pill.

Fix: Badge positive verification instead.

`SearchResultsScreen.tsx:337-353`

---

low ui-ux **The entry animation runs on the JS thread and ignores reduce motion**

useNativeDriver:false is set for opacity and transform.

Fix: Use the native driver and useReduceMotion.

`DishSearchScreen.tsx:93-108`

---

low bug **The v2 back button has no fallback**

goBack() is called without canGoBack(). SearchHome has a fallback to Discover, but the v2 grid does not, so a cold-start or deep-link entry leaves a dead back button.

Fix: Mirror SearchHome's fallback to MainTabs → Discover.

`SearchResultsScreen.tsx:479-483 vs DishSearchScreen.tsx:129-135`

---

low product **No shareable search links**

linking.ts has no Search or Browse route.

Fix: Add search?q=&filter=.

`src/app/navigation/linking.ts`

Stall & dish detail 4/10

The detail pages have solid foundations: race-safe async loads, a clean no-photo hero on dish detail, 44px accessible docks, and owner replies inline. But both pages show invented or wrong data as fact. Menu tiles show other dishes' photos under a dish's name, reviewers get stock Unsplash faces, and untagged dishes get a "5/10 Sweet" score, a meaningless "% match" and a "Live" wait estimate from a static column. Distances are a seeded column, and dish reviews vanish on a warm cache. Against Google Maps, Yelp, GrabFood and Burpple, the stall page also lacks a rating summary at the top, a Directions/Call/Order row, a real menu, and even a Write a review button.

top, a Directions/Call/Order row, a real menu, and even a Write-a-review button.

▶ How it compares with other apps

▶ What it does well (10)

▶ Issues from the 18 Oct audit: 7 still present, 8 fixed

▶ Cross-check notes: 42 confirmed, 4 removed, 10 corrected, 7 added

▼ Findings (47)

critical bug **Menu tiles show other dishes' photos, names, prices and tap targets**

Each tile cycles [this dish + first 3 other dishes] and sets its name, price, a11y label and onPress from slides[activeIndex]. CyclingGridImage drops slides with no image and reports an index into safeImages, so the photo and the label come from different dishes. In a stall where one dish has a photo, every tile shows that photo. A mid-cycle tap opens the wrong dish. A tile with no images renders an empty View.

Fix: One tile = one dish: static AccessibleImage with a NoDishPhoto fallback (as in DishCard.tsx:72-83). Cycle only the dish's own gallery if motion is wanted.

`StallDetailScreen.tsx:193-195, 211-213, 227-229, 245-255, 1149; CyclingGridImage.tsx:47-53, 59-70, 239-243`

---

high product **Reviewers without an avatar get random stock-photo faces**

When authorAvatarUrl is missing, an Unsplash portrait of a stranger is picked by name hash and labelled 'Avatar of {name}', which undermines trust in the reviews. reviewRoleFromRating also invents 'Verified Foodie' from a star rating (unused).

Fix: Use the Avatar primitive with initials (PopularVisitorsSection.tsx:126). Delete AVATAR_POOL and reviewRoleFromRating.

`detailTransforms.ts:16-21, 32-40, 51, 61; StallDetailScreen.tsx:1209-1217`

---

high backend-data **Dish detail says 'No reviews yet' while the header counts reviews (warm cache)**

The cached dish mapper sets reviews: []. DishDetail prefers cachedDish and skips get_dish_detail, the only source of reviews, so the page shows '4.6 (12 listed reviews)' above 'No reviews yet'. Even when reviews load, it shows only 3, with no date, avatar, owner reply or See all.

Fix: Always fetch paginated dish reviews, add 'See all N reviews', and keep the empty state for reviewCount===0 only.

`supabaseRepository.ts:252, 1064-1067; DishDetailScreenV2.tsx:204-207, 268, 663-668, 930-969`

---

high performance **Up to 3 queries per dish (N+1) plus serial photo signing on stall open, for photos never shown**

getReviewsForDish runs for every dish (up to 50): an unpaginated reviews select, then review_photos and public_profiles selects when reviews exist, with each photo URL signed inside a loop. That is about 50-150 round trips to show 6 reviews, and the stall page never renders review photos. Errors become [], so a failure looks the same as an empty list.

Fix: Add a list_venue_reviews(p_venue_id, p_limit, p_cursor) RPC joining profiles. Batch-sign photos only when shown. Add an error state with retry.

`StallDetailScreen.tsx:479-505; supabaseService.ts:3191-3204, 902-950 (await at 930); detailTransforms.ts:3-14, 66`

---

high bug

'Recent Reviews' are neither recent nor stall-wide, and don't name the dish

Reviews are flatMapped in dish order and the first 6 kept, unsorted, so one dish can fill the section. dishName is computed but never rendered.

Fix: Sort by createdAt desc (or use the server RPC). Render 'on {dishName}' linked to DishDetail.

`detailTransforms.ts:47-66; StallDetailScreen.tsx:1191-1246`

---

high product

Dish attribute cards show invented values as facts

Untagged dishes get a neutral vector of 5s, so they show 'Taste Intensity 5/10 · Sweet'. Texture falls back to 'Signature'/'House style'. The cosine '% match' is high for any two positive vectors and is put in the share text. In Supabase mode the wait card says 'Live wait estimate' for a static live_crowd column.

Fix: Hide the grid when untagged or low-confidence. Show the match only with real signals, and remove it from share text. Don't label static data as Live.

`DishDetailScreenV2.tsx:172-187, 209, 375-402, 425; supabaseRepository.ts:237-244; catalog_display_provenance_guardrails.sql:613; dataTrustDisclosure.ts:15`

---

high bug

Dish 'Tried' toggles the whole stall, so a second dish un-marks it

isDishTried is per dish, but markTried flips stall isTried. Tapping Tried on an unchecked Dish B, after Dish A was marked, un-marks the stall. The '+5 Food Cred' toast uses a client-side pointsAwarded=5 whatever the server awarded, and it shows in production although gamification is off there. The '-5' branch can never run.

Fix: Model dish-tried separately, and never clear the stall from a dish page. Take points from the RPC, and gate Food Cred copy on the flag.

`DishDetailScreenV2.tsx:486-537; useStallInteractionStore.ts:125-173; featureFlags.ts:39`

---

high backend-data

award_food_cred accepts a client-supplied p_points amount (cross-page)

resolved_points := coalesce(p_points, default), and authenticated users can execute it through the wrapper, so a direct RPC call can mint any amount. The daily cap limits count, not amount. No later migration redefines it (live DB not checked).

Fix: Ignore p_points unless the caller is service_role, and add per-entity daily dedupe.

supabase/migrations/0042_full_audit_gamification.sql:213-240, 470-472;
20260522142004_advisor_private_rpc_wrappers.sql:25

---

high bug

Stall heart 'saves the stall' by favouriting dishes[0] and shifts the taste vector

Its label and toast say stall, but it calls toggleFavourite(leadDish), adding the first menu dish to Want to try and pulling the taste vector toward it. It does nothing until the menu hydrates. This duplicates StallInteractionBar's real stall Save.

Fix: Remove the heart or wire it to useStallInteractionStore.toggleSaved. Keep one Save concept per page.

`StallDetailScreen.tsx:310-313, 827-866; useProfileStore.ts:435-460; StallInteractionBar.tsx:51-64, 101-108`

---

high product

Distance is a stored DB column, not the distance from the user

'120m away' comes from dishes.distance_meters, and the detail RPCs take no lat/lng. The repository acknowledges this and has getDistanceMetersFromBuildingId, which the detail screens don't use. A stored 0 shows as '0m away'.

Fix: Compute from useLocationStore and building coordinates (reuse the helper), and hide distance when location is unknown.

`supabaseRepository.ts:231, 1088-1106; catalog_display_provenance_guardrails.sql:605; StallDetailScreen.tsx:601-605; DishCard.tsx:114`

---

high ui-ux

Stall hero and menu tiles are blank for most stalls

The hero (75% of width) uses leadDish?.imageUrl with no fallback, and the dish list is empty until it hydrates. Most stalls open with a large empty block labelled 'hero dish photo'.

Fix: Fall back to merchant cover, then a gallery image, then a short branded header. Use NoDishPhoto in tiles.

`StallDetailScreen.tsx:887-900; CyclingGridImage.tsx:241-243`

---

high frontend

Supabase mode briefly shows 'No menu available' and 'Add a menu photo' while loading, and the same on errors

dishes is EMPTY_DISHES until listDishesByVenue resolves, and the menu has no loading state. A fetch error sets [], which looks identical to an empty menu, with no retry.

Fix: Track menu status (loading/error/ready): skeleton while loading, Retry on error, and the empty CTA only when ready and empty.

`StallDetailScreen.tsx:309-311, 396-403, 1118-1186`

---

high frontend

Forced 800ms skeleton on every stall open

isLoading starts true and a timer clears it after 800ms, even for cached data.

Fix: Remove the timer. Show the skeleton only while venue detail is genuinely loading.

`StallDetailScreen.tsx:267, 273-276, 568-570`

---

high product

Delivery links are fetched but never shown; DeliveryPlatformButton is dead code

get_venue_detail returns delivery_links and mapRpcVenue maps them, but nothing renders them, which drops the 'Order online' action.

Fix: Render venue.deliveryLinks as DeliveryPlatformButtons in the stall action row and on dish detail.

`20260628063500_venue_logo_detail_reads.sql:27, 71-73; supabaseRepository.ts:304-318; src/components/dish/DeliveryPlatformButton.tsx (no consumers)`

---

high ui-ux

No rating summary, price level or action row at the top of the stall page

The header shows only logo, name and address, with a decorative ChevronRight in a card that can't be tapped. There is no rating or count, price band, open badge, or Directions/Call/Share row. Status is buried in an hours card, and directions only work through the Address card.

Fix: Header: name, rating (count), price, 'Open · closes 9pm', then chips for Directions, Call, Order, Save and Share.

`StallDetailScreen.tsx:911-935 (chevron 934), 963-981, 1053-1077`

---

high ui-ux

Stall page has no 'Write a review' button anywhere

The reviews empty state says 'Write your first review for this stall.' but has no CTA. The only route to reviewing is the hidden 'Mark Visited' gate for signed-in users, so the core contribution loop is missing from the stall page.

Fix: Add a 'Write a review' button in the reviews header and empty state that opens ReviewMain with venueId and sends guests through requireAuthForProtectedAction.

`StallDetailScreen.tsx:1360-1364 (EmptyState without ctaLabel), 621-661, 938-946`

---

high bug

Back is a dead end on cold-start shared links

createState builds a single-route state for /dish and /venue links, and both detail headers call goBack() without canGoBack(). Dish not-found says 'Try searching' but offers only Go back.

Fix: Put MainTabs(Home) under detail routes or use a goBackOrHome helper. Add a Search CTA.

`linking.ts:86-88, 123-130; DishDetailScreenV2.tsx:363-364, 1096-1099; StallDetailScreen.tsx:818-824`

---

medium backend-data

Stall menu capped at 50 items, ordered by search rank

get_venue_detail lists dishes through search_dishes(p_limit => 50). Larger menus are silently truncated, and 'Showing X of Y' counts only the truncated set.

Fix: Add a paginated menu RPC ordered by merchant section, and show the true total.

`20260628063500_venue_logo_detail_reads.sql:76-82; supabaseRepository.ts:981-985; StallDetailScreen.tsx:1112-1115`

---

medium performance

Venue detail RPC called twice on a cold cache

getVenue and listDishesByVenue both call get_venue_detail (with 50 dishes) when there is no cached venue.

Fix: Return { venue, dishes } from one call, and key effects on venue?.id.

`supabaseService.ts:3055-3057, 3148-3151; supabaseRepository.ts:907-910, 981-985`

---

medium bug

Open/closed status is wrong in common cases

Day of the week is ignored. Any 'closed' text means always closed. Empty or unparseable hours mean 'Open now' when DB isOpen is true. A single range is repeated for all 7 days. Dish detail uses device-local 'today' while the util uses SGT.

Fix: Use one structured per-day parser in SGT, return 'unknown' and show 'Hours not listed', and show Opens at / Closes in.

`stallStatus.ts:91-112; stallLocation.ts:36-52; StallDetailScreen.tsx:606-613; DishDetailScreenV2.tsx:149-153`

---

medium bug

Dish hours parser drops segments and misreads days

Splits on commas, silently drops unmatched segments after the first match, defaults unknown day tokens to Mon, and shows rows[0] when today has no row.

Fix: Share one tested parser, and show 'Closed today' when today has no row.

`DishDetailScreenV2.tsx:58-86, 100-147, 155-162`

---

medium bug

Menu category regexes have no word boundaries

Without a merchant section, Steak and Steamed egg land in Drinks (tea), Watercress soup in Drinks (water), Inside-out roll in Sides, and Oatmeal in Sets.

Fix: Use \b boundaries, prefer the server food types, and fall back to a single 'Menu' group.

`StallDetailScreen.tsx:163-175`

---

medium frontend

Dish-to-dish navigation reuses the screen and keeps stale state

navigate('DishDetail') from DishDetail updates params instead of pushing (inferred from RN7, no getId), so back skips the previous dish and scroll and open sections carry over. The first Signature tile is the current dish, and with a cold cache the list shows only the current dish.

Fix: Use push, exclude the current dish, fetch venue dishes when the cache is empty, and rename the section 'More from {stall}'.

`DishDetailScreenV2.tsx:193-199, 253-260, 852-857; RootNavigator.tsx:694`

---

medium bug

A venue fetch failure turns a valid dish into 'We can't find this dish'

The page needs both dish and venue. getVenue falls back to the cache, but if both miss, a dish that loaded fine shows the removed state with no retry. The stall error boundary copy says 'this dish'.

Fix: Degrade venue sections instead, separate errors from not-found with Retry, and fix the copy.

`DishDetailScreenV2.tsx:300-309, 353-368; supabaseService.ts:3055-3057; StallDetailScreen.tsx:576, 801`

---

medium ui-ux

'Add a menu photo' opens the review composer

It navigates to ReviewMain with only venueId, and that route has no menu-photo mode.

Fix: Open the menu-photo submission flow directly.

Fix: Open the menu-photo submission flow directly.

`StallDetailScreen.tsx:1174-1183; navigationTypes.ts:53`

---

medium ui-ux

Mark Visited: double toasts, a stale comment and an inconsistent gate

The bar's warning toast is immediately replaced by StallDetail's toast. The comment says tried can't be un-tried, but the code toggles. Dish 'Tried' writes reviewedDishIds and bypasses the review gate.

Fix: Show one toast, apply one rule on both pages, and fix the comment.

`StallInteractionBar.tsx:5, 70-84; StallDetailScreen.tsx:652-656; DishDetailScreenV2.tsx:506`

---

medium accessibility

Star ratings unreadable to screen readers; amber stars and the Review CTA fail contrast

Star rows have no label, and on stall reviews the stars are the only rating cue. Amber #F5A623 on white is 2.03:1. White 'Review' text is 3.69:1 on #E8531E (light) and 2.80:1 on #F97316 (dark).

Fix: Label the rows 'Rated n out of 5', use the Button primitive (dark on orange), and a darker amber on light surfaces.

`StallDetailScreen.tsx:1226-1233; DishDetailScreenV2.tsx:655-662, 952, 1062-1081; tokens.ts:11, 19, 26, 95`

---

medium accessibility

Small tap targets on secondary actions

The help icon (18px), Reply text, contact rows, claim-explainer X (18px) and catalog back arrow (24px) are under 44px. The dish hours toggle has no expanded state.

Fix: Use minHeight 44 or hitSlop, and accessibilityState.expanded.

`StallDetailScreen.tsx:1009-1047, 1276-1288, 1378-1384; MerchantClaimExplainerScreen.tsx:53-59; CatalogRawDetailScreen.tsx:101-107; DishDetailScreenV2.tsx:772-776`

---

medium product

Share sheet says 'Share review'; share analytics are wrong or missing

The sheet is titled 'Share review'. With postId '', onShared never fires. WhatsApp and Telegram send dish_shared with review_id 'stall-...'. The merchant share event fires when the sheet opens. In non-prod, in-app chat sends a post card with an empty postId.

Fix: Pass a kind (dish/stall/review) for the title and event, track every channel, and record the merchant share on completion.

`StallDetailScreen.tsx:361-371, 723-738; DishDetailScreenV2.tsx:418-440; ReviewShareSheet.tsx:90-158, 168, 211`

---

medium backend-data

get_dish_detail returns unbounded reviews with raw photo URLs and a snapshot author name

jsonb_agg over all reviews with no limit, raw rp.url, r.author_name, and no merchant_reply, so owner replies never show on dish detail.

Fix: Return only aggregates, and use a shared paginated, URL-signed review RPC that includes the reply.

`20260610120000_catalog_display_provenance_guardrails.sql:652-670`

---

medium product

'Add this dish to a list' silently saves with an invented score of 8

ListPlus (live in production) adds to the first owned portfolio or creates one, with no picker and score: 8.

Fix: Open a list picker, leave the score empty, and add a visible label.

`DishDetailScreenV2.tsx:991-1007; DetailSaveActions.tsx:142-198 (184-185); featureFlags.ts:42`

---

medium product

No product-analytics funnel for stall pages

There is no stall_viewed or menu-open event. trackStallMarkedTried hard-codes sourceScreen 'StallDetail' even when called from dish detail.

Fix: Add stall_viewed, stall_menu_dish_opened and review_started events, and pass the source through.

`StallDetailScreen.tsx:414-422, 665; useStallInteractionStore.ts (trackStallMarkedTried call)`

---

medium backend-data

Unpriced dishes show 'S$0.00'

mapDish sets price via toNumber(row.price), which falls back to 0, and dish detail and Signature tiles always render formatBasePrice. Any catalog dish with a null price shows as free (how often depends on catalog data, inferred).

Fix: Keep price nullable, and show 'Price not listed' or priceRange when it is missing.

`supabaseRepository.ts:73-78, 234; DishDetailScreenV2.tsx:189-191, 651, 919`

---

low performance

Per-tile timer and measureInWindow every 4s

Only runs when a tile has 2 or more valid images and is gated on visibility, so the cost is limited today. Goes away with the critical tile fix.

Fix: Use static tiles, or one screen-level visibility-aware timer.

`CyclingGridImage.tsx:113-168; StallDetailScreen.tsx:233-243`

---

low frontend

Linear catalog scans in render; cache not reactive

getVenueById and getDishById run .find over the whole catalog on each parent render, and the cache doesn't notify the screen when it changes. Carousel ticks re-render only the card.

Fix: Index the cache by id and subscribe through a selector.

`StallDetailScreen.tsx:268; DishDetailScreenV2.tsx:204; supabaseRepository.ts:1059-1072`

---

low product

Dish page shows no open/closed status or directions

isVenueOpen only feeds the wait helper. There is no Open/Closed badge, distance or Directions on dish detail, and the venue pill only links to the stall.

Fix: Add an open badge and a Directions chip beside the venue pill.

`DishDetailScreenV2.tsx:374, 396-398, 596-625`

---

low ui-ux

A dish with no reviews shows '0.0 (0 listed reviews)' and five empty stars

There is no special case for reviewCount === 0.

Fix: Show 'No ratings yet'.

`DishDetailScreenV2.tsx:654-669`

---

low accessibility

Stall hero labelled as a photo when there is none

AccessibleImage always gets '{name} hero dish photo', even with an undefined uri.

Fix: Mark it decorative or use a placeholder when there is no image.

`StallDetailScreen.tsx:894-899`

---

low ui-ux

Header subtitle crams the full address into one truncated line

Full address, unit and distance are joined with numberOfLines=1, then repeated in the Address card. Empty units leave 'Name - ' and a trailing ' · '.

Fix: Use '{Centre} · #{unit} · {distance}' and filter out empty parts.

`StallDetailScreen.tsx:358-366, 924-932; stallLocation.ts:11-34; DishDetailScreenV2.tsx:422, 621-623`

---

low ui-ux

Menu grid width ignores the container padding

Width uses spacing[5]*2 while the padding is spacing[3], giving uneven gutters.

Fix: Use (screenWidth - spacing[3]*3)/2.

`StallDetailScreen.tsx:906, 1151`

---

low ui-ux

V1 stall versus V2 dish visual mismatch

Headers, hero ratios, section names and save metaphors (heart vs bookmark) all differ.

Fix: Share DetailHeader, HoursCard and ReviewList components.

`StallDetailScreen.tsx:818-876, 966-972, 1191; DishDetailScreenV2.tsx:552-586, 785-787, 929, 1021`

---

low product

Auto-generated description and internal 'listed' wording

Italic filler is shown like editorial copy, and 'listed reviews' / 'Listed hours:' are internal terms.

Fix: Hide the description when missing, and use plain wording.

`DishDetailScreenV2.tsx:667, 678-687; StallCard.tsx:52; OperatingHours.tsx:20`

---

low frontend

Unused dish/stall components (one uses Skia)

StallCard, StallHeader, OperatingHours, ImageCarousel, MustOrderBadge, TasteRadar, TasteRadarChart, ProfileRadarChart, DeliveryPlatformButton and the DeliveryButton shim have no consumers. (DecideForMeCard is used.)

Fix: Delete them, or wire up DeliveryPlatformButton and MustOrderBadge.

`grep outside src/components/{stall,dish}: src/components/dish/index.ts`

grep outside src/components/{stall,dish}; src/components/dish/index.ts

---

low bug **Claim-pending state is per profile and in-memory (non-prod)**

After one claim, every stall shows Claim Pending, and the state is lost on restart. Gated off in production.

Fix: Read the claim status per venue from the server.

`submitClaimFromStall.ts:24; StallDetailScreen.tsx:333, 1386-1398; featureFlags.ts:20`

---

low ui-ux **Catalog raw detail: dead source link, raw errors, 'Sign in' message for signed-in users**

The source URL is not pressable, loadError.message is shown verbatim, and auth and mode problems share one message.

Fix: Use a trusted link, friendly error copy, and separate messages.

`CatalogRawDetailScreen.tsx:33-49, 183-190`

---

low ui-ux **PopularVisitors opens a profile by name only**

No authorId is passed, although the route accepts one.

Fix: Pass the user id.

`PopularVisitorsSection.tsx:74-84; navigationTypes.ts:133-139`

---

low ui-ux **Follow hidden from guests; fallback toasts have no settings action**

Guests never see Follow, and the toasts point to Settings with no link.

Fix: Show Follow to guests behind the auth gate, and add a toast action that opens settings.

`StallDetailScreen.tsx:947-949; FollowStallButton.tsx:61-73`

Reviews & posting 4/10

The backend pipeline has improved: submits are idempotent, the Recommend value persists, the feed uses one paginated query and prototype media is gated out of production. The writing experience is broken, though, because a per-keystroke sanitizer trims spaces, collapses newlines and deletes common words. Production also ships safety and integrity gaps: blocking does not hide content, review shares increment an unrelated post's share count, the V1 composer guesses the dish, and a review can go live without its photos while the user is told publishing failed.

▶ How it compares with other apps

▶ What it does well (8)

▶ Issues from the 18 Oct audit: 6 still present, 9 fixed

▶ Cross-check notes: 31 confirmed, 0 removed, 6 corrected, 4 added

▼ Findings (35)

critical bug

Per-keystroke sanitizer prevents typing spaces, newlines and common words

setText and the post caption call sanitizeFreeText on each keystroke. It trims whitespace and strips SQL keywords (select/update/delete…) and ';' '--'. The input is controlled, so 'great food' becomes 'greatfood' and multiline text collapses. Stripping SQL keywords protects nothing, because Supabase queries are parameterised.

Fix: Store raw text and sanitize once at submit (strip HTML, trim, cap). Remove SQL_META_REGEX from free-text paths. Enforce length on the server. Add a test that setText('a ') preserves the space.

`src/lib/security/inputSanitization.ts:3-8,22-25; src/store/useReviewDraftStore.ts:96-102; ReviewScreen.tsx:321-329; PostComposerScreen.tsx:376`

---

critical backend-data

Blocked/reported authors remain in the Review feed

A block adds a display-name key to an in-memory set. ReviewFeedScreen never calls isContentHiddenForSession, and listRecentReviews has no block or moderation filter. Blocks are keyed by name, so blocking 'Hungry User' hides every user without a name, and renaming escapes a block. This is an App Store 1.2 rejection risk.

Fix: Block by user_id. Filter blocked and moderated content on the server for the feed and dish reviews. Remove the item locally once the block or report succeeds.

`communitySafety.ts:23-50,214-236; no isContentHiddenForSession in ReviewFeedScreen.tsx; supabaseService.ts:3301-3312,964-967; 0017_store_policy_safety_controls.sql:61-66`

---

high backend-data

Review share increments an unrelated post's share count

openShareReview borrows a stall post id that matches the dish or venue. onShared then calls incrementShare, which calls shareBite on that post. WhatsApp and Telegram shares are logged as 'system_share', a system share counts even when cancelled, and the review's own share count is forced to 0.

Fix: Record shares against review_id with the real channel. Count a share only when Share.share returns sharedAction.

`ReviewFeedScreen.tsx:714-735,785-800,949-955; ReviewShareSheet.tsx:132-158; useSocialStore.ts:378-410`

---

high bug

Photo upload failure leaves a published, photo-less review while the UI says it failed

submitReview inserts the publicly readable review first and uploads photos after. If an upload fails, the user sees 'Could not publish review' while the review is already live and counted in the dish average. Users who give up never learn it was posted.

Fix: Upload photos first, or add a pending/published status and publish once photos attach. Tell the user

only the photos failed.

`supabaseService.ts:3216-3271; 0008_phase7_auth_scaffold.sql:76-78 (select using true); ReviewScreen.tsx:197-201`

---

high bug **Post composer V1 attaches venue-only posts to the stall's first dish**

With only venueId, the dish memo returns listDishesByVenue[0] and passes it as routeDishId, which gets past publishing.ts's guard. The /order deep link takes this path, and the screen has no Change control.

Fix: Remove the fallback, show a dish picker and add a Change button. Reconsider routing /order to the composer.

`PostComposerScreen.tsx:106-114,211-215; linking.ts:135,218`

---

high ui-ux **Dish picker is an absoluteFill overlay inside a ScrollView**

The overlay fills the scroll content, not the viewport, and uses a hard-coded paddingTop of 60, so it can open off-screen. The nested FlatLists lose virtualization, Android back exits the screen, and an empty stall search shows nothing.

Fix: Use a route or bottom sheet/modal with back handling, safe-area insets and empty states.

`ReviewScreen.tsx:210,379-485; components/ui/Screen.tsx:57-83`

---

high product **Recommend defaults to 'Skip', so reviews are saved as not recommended**

The draft starts with recommend:false and 'Skip' shows as selected, so untouched reviews store would_recommend=false. The feed then hides the 'Would recommend' line. publishing.ts omits the field, so the server default of true applies there.

Fix: Make the field tri-state with Yes/No options, or derive it from the rating. Send the same value from both paths and backfill affected rows.

`features/review/reviewDraft.ts:9; ReviewScreen.tsx:172,350-366; supabaseService.ts:3233; ReviewFeedScreen.tsx:314-341`

---

high performance **Feed signs photo URLs serially (up to 250 sequential requests)**

createSignedUrl is awaited in a loop for each photo across 50 reviews x 5 photos. The one-hour signed URLs defeat the image cache and break shared links.

Fix: Use one createSignedUrls batch per page, or public/CDN media, with a stable cacheKey.

`supabaseService.ts:921-934,1015-1027; ReviewFeedScreen.tsx:65`

---

high product **Success modal shows client-computed points in production while gamification is off**

reviewScore is computed on the client and the +N points badge renders unconditionally. A toast also fires alongside the modal.

Fix: Gate the badge on gamificationEnabled and take the value from the server. Show one confirmation.

`ReviewScreen.tsx:151-161,193-194; ReviewSuccessModal.tsx:92; featureFlags.ts:39`

---

high ui-ux **Photo filters are applied in the preview only; uploads are unfiltered**

The editor auto-opens after each pick and toasts 'Filter applied!', but only a single global filterId is stored and the original files upload.

Fix: Bake the filter into the file before upload, or remove filters from production. Make the editor opt-in.

`MediaPicker.tsx:76-77,192-203; MediaEditor.tsx:93-103; ReviewScreen.tsx:165-175`

---

high accessibility **Media edit/remove buttons unlabelled and 28x28; add tiles unlabelled**

There are no role or label props, and the tiny remove target sits next to edit. The header says 'Photos & Reels' in production and the counter hard-codes /5.

Fix: Add roles and labels, 44pt targets and an Undo on remove. Use maxPhotos in the counter and fix the title.

`MediaPicker.tsx:83-86,110-121,125-140,155-188,242-248`

---

high accessibility **StarRating is 'adjustable' with no actions and the wrong range**

There is no onAccessibilityAction. The range has min:1 while now can be 0, the label omits the current value, the child stars duplicate focus, and the feed StarRow has no label.

Fix: Add increment/decrement actions and min:0, use the label 'Rating, n of 5', hide the children from accessibility and label StarRow.

`StarRating.tsx:24-60; ReviewFeedScreen.tsx:76-90,228`

---

high ui-ux **Form order backwards; Publish disabled without explanation**

The order is Photos, Place, 'Caption', Rating, Recommend. Publish stays disabled until a dish and rating are chosen with no helper text. There is no counter and no sticky CTA.

Fix: Reorder to Dish, Stars, Text with counter, Photos, Recommend. Use a sticky Publish button with helper text.

`ReviewScreen.tsx:216-374`

---

high bug **Stale persisted draft overrides a venue-only entry**

selectedDishId = draft.selectedDishId || routeDishId, and the picker opens only when no draft dish exists, so a review started from stall Y can show an old draft for stall X. When both route params are present, selectDish silently wipes the old draft.

Fix: Treat route params as authoritative and prompt 'Continue review of A / Start new'.

`ReviewScreen.tsx:72-74,95-101,119-123; useReviewDraftStore.ts:49-72; StallDetailScreen.tsx:657,1175-1181`

---

high ui-ux **'Add a menu photo' is a dead end**

It opens the review editor for a stall with no dishes, which shows 'No dishes listed' and nothing else. The menu-photo code is __DEV__-only inside the unreachable QuickReviewSheet.

Fix: Build a submitMenuPhoto flow or remove the button. Allow venue-level or free-text dish reviews.

`StallDetailScreen.tsx:1175-1181; ReviewScreen.tsx:412-417; QuickReviewSheet.tsx:102-118`

medium bug

Feed does not refresh after the user posts

The service feed loads only on mount, refresh and retry, with no focus refetch or optimistic insert, so a new review is missing until the user pulls to refresh.

Fix: Prepend the submitted review optimistically, or refetch on focus after submit.

`ReviewFeedScreen.tsx:604-613; no useFocusEffect or focus listener in the file`

---

medium ui-ux

Single-photo picking; duplicate URIs break removal; no cap in store

allowsEditing is on and there is no multi-select, so five photos take five picker-and-editor trips. Tiles are keyed by URI and removePhoto filters by URI, so a duplicate pick collides and one tap removes both. addPhoto does not enforce the 5-photo cap.

Fix: Use multi-select with a selection limit, give photos IDs and enforce the cap in the store.

`MediaPicker.tsx:58-66,143-145; useReviewDraftStore.ts:103-110`

---

medium product

Feed filters are just sorts; search covers only loaded rows

'By Dish' and 'By Location' sort alphabetically, 'Top Rated' sorts only the loaded page, and client-side search can show 'No reviews found' while matches exist on the server.

Fix: Run filters and search on the server, add near-me and following filters, and rename the chips.

`ReviewFeedScreen.tsx:67-72,654-672,685-695`

---

medium backend-data

No index for the global recent query; created_at cursor skips ties

The only created_at index is (dish_id, created_at, id), which this query cannot use, and lt('created_at') drops rows with equal timestamps.

Fix: Add an index on reviews(created_at desc, id desc) and use a keyset cursor.

`supabaseService.ts:3301-3315; 0029_server_side_discovery_reads.sql:14-15`

---

medium backend-data

Review table accepts rating 0, unbounded text, duplicates and an unchecked venue

The insert policy checks only uid. The rating check allows 0, and there is no text cap, no per-(user, dish) limit, no venue/dish consistency check and no block on merchant self-review. author_name is client-writable.

Fix: Add CHECK constraints, a trigger that sets venue_id/author_name, a uniqueness or rate limit and a self-review block.

`0008_phase7_auth_scaffold.sql:82-85; 0002_core_schema.sql:157-168; supabaseService.ts:964-967`

---

medium frontend

renderItem depends on whole store maps; O(replies) count per row

Any social-store change re-renders every card, each row reduces over all replies, and ReviewCard is not memoised.

Fix: Memoise cards, use per-card selectors and precompute counts.

Fix: Remove cards, use per-card selectors and precompute counts.

`ReviewFeedScreen.tsx:137,781-843,801-810`

---

medium accessibility

Tiny adjacent Report/Block links; unlabelled dish chip; dates without year

The links have no hitSlop and appear on the user's own reviews. The chip has no role. Dates show month and day only. Avatars show an initial despite authorAvatarUrl.

Fix: Use an overflow menu hidden on own reviews, 44pt targets, a chip role, relative dates and avatars.

`ReviewFeedScreen.tsx:162-165,205-254,363-391`

---

medium product

No production reactions; merchant replies never reach the feed

Likes work only in mock mode. listRecentReviews does not select merchant_reply_text even though the mapper reads it.

Fix: Add a backed Helpful reaction, and select and render merchant replies.

`ReviewFeedScreen.tsx:512; supabaseService.ts:3307,973`

---

medium product

Taste tags shown only to merchants and developers

The chip group renders only when !isUserMode.

Fix: Show 6 to 8 tags to all reviewers and block self-reviews.

`ReviewScreen.tsx:43-45,339-348; ReviewSuccessModal.tsx:19-21,88-90`

---

medium bug

Quick Review mounted but unreachable; its submit is fake

Nothing calls showQuickReview. Its submit waits 800ms, awards points and calls no API.

Fix: Delete it, or rebuild it on submitReview.

`RootNavigator.tsx:424-433,784; useUIStore.ts:48,107; QuickReviewSheet.tsx:99-129`

---

medium frontend

Dead review components; MusicSelection route registered in production

PhotoPicker, MusicPicker, TasteTagSelector, ReviewScreenShell and ReviewStars are unused. The MusicSelection route is registered without a flag and Select only calls goBack.

Fix: Delete the unused files and gate the route behind prototypeRoutesEnabled.

`components/review/index.ts; MusicSelectionScreen.tsx:36-117,471-475; RootNavigator.tsx:722`

---

medium ui-ux

Post composer V1: tap-to-delete thumbnails, Replace wipes media, no exit guard

There is no visual cue that a tap removes media, Replace discards earlier picks, nothing is persisted or confirmed on exit, and dish search caps at 12 results.

Fix: Add an X badge, append instead of replacing, add a beforeRemove confirmation and show progress.

`PostComposerScreen.tsx:94,174,221,308-366`

Composer V1 passes data via a global

medium frontend

store and an ImagePicker type shim

The store is shared with V2, so composer data can leak between them. The shim hides MediaTypeOptions deprecation from the type checker (inferred).

Fix: Pass an explicit payload, import the picker normally and use a mediaTypes array.

`PostComposerScreen.tsx:30-55,156,206-215; MediaPicker.tsx:58-62`

---

medium performance

Serial full-size photo uploads with no progress and a generic error

Uploads run in a sequential loop with no resize, and the catch discards the server's message.

Fix: Resize, upload in parallel with a limit, show progress and surface errors.

`supabaseService.ts:870-900; MediaPicker.tsx:63-64; ReviewScreen.tsx:197-201`

---

medium backend-data

Persisted draft not cleared on session-store sign-out

clearAccountScopedStores omits the review draft, so the next account inherits the draft and its clientReviewId. Cache URIs may be purged (inferred).

Fix: Reset the draft in clearAccountScopedStores, key it by user, and copy media to the document directory.

`useReviewDraftStore.ts:145-153; useSessionStore.ts:97-113; SettingsScreen.tsx:165,262,280`

---

medium product

No analytics for post flow, feed or drop-off

Only review_started, review_submitted and the messaging dish_shared events exist.

Fix: Track failures, abandonment, post publishing, filter and search use, and every share channel.

`useReviewDraftStore.ts:58; ReviewScreen.tsx:185; ReviewShareSheet.tsx:153`

---

low bug

popToTop on a single-screen stack after submit

The action bubbles to the parent navigator (inferred), so the user does not return to the dish they reviewed. The auth redirect uses getParent()?.getParent(), which can be undefined.

Fix: Call getParent()?.goBack() or replace the screen with DishDetail.

`ReviewStack.tsx:9-14; ReviewScreen.tsx:42,125-130,196; src/app/screens/profile/ProfileStack.tsx:87`

---

low performance

Venue list re-walks every building on each render

venues is computed without memoisation on every keystroke in the editor.

Fix: Memoise on [repository, query] or use a server search.

`ReviewScreen.tsx:87-92`

---

low ui-ux

PostComposerV2 (prototype) fakes drafts, scheduling and AI

Save Draft wipes the post, schedules are ignored and the AI features return canned output.

Fix: Remove these or label them clearly as prototype.

`PostComposerScreenV2.tsx:253-262; useComposerStore.ts:228-270; ComposerBottomBar.tsx`

low frontend

Feed leftovers: setTimeout skeleton, no-op search submit, no tab scroll-to-top, text-based interaction key

The skeleton is driven by setTimeout(0), search submit does nothing, tapping the active tab does not scroll to the top, and the interaction key embeds the review text.

Fix: Derive loading from the fetch, implement scroll-to-top and key interactions by review id.

`ReviewFeedScreen.tsx:544-547,566-571,712,866`

Profile (own & others) 3.5/10

The Profile surface looks finished, but much of what it shows is invented or broken. Follower and following counts and lists are filled in from anyone who posted or commented, and other users' follower stats are hard-coded to 0 or 1. Following a user can never succeed in Supabase because the client writes status 'approved' while RLS only allows inserting 'pending'. Post grids only show posts that happen to be in the newest 40 posts app-wide. The visual layout and the Passport and Missions components are decent, but the social graph is not real.

▶ How it compares with other apps

▶ What it does well (7)

▶ Issues from the 18 Oct audit: 4 still present, 2 fixed

▶ Cross-check notes: 37 confirmed, 0 removed, 3 corrected, 2 added

▼ Findings (39)

critical backend-data

Following a user always fails RLS in Supabase mode and silently reverts

followUser upserts status 'approved'. The only follows insert policy requires status='pending' and approved_at null, and only the followee may UPDATE. No later migration changes this. toggleFollow flips the button to 'Following', then on error only calls console.error and flips back with no message. No follow can be written from the app.

Fix: Add a SECURITY DEFINER follow_user(target) RPC that writes pending or approved based on the target's privacy setting. Use a plain insert, show a toast when the follow reverts, and add a smoke SQL test.

`supabaseService.ts:3942-3953; 0023_integration_posts_privacy_chat.sql:367-379; useSocialStore.ts:299-317`

critical bug

Own follower/following counts are

invented from feed and comment authors

localFollowerCount counts every distinct author in cached comments, replies and repository.listStallPosts(), then takes Math.max with the server count. Following adds the local followed maps on top of the server count, so every follow is counted twice.

Fix: Show only server counts from an RPC or counter column. Delete mergeFollowerNames, localFollowerCount and the local add-ons, and show a skeleton while loading.

`ProfileHomeScreen.tsx:357-392, 394-439`

---

critical bug

Followers list shows every community user; Following list shows the viewer's follows on anyone's profile

Followers is serviceFollowers plus every community user (posts, comments, replies, DM participants), minus only the target's name. Following always merges the viewer's local followedUserIds and followedAuthors, whoever's profile is open. Empty-state copy is always written as 'You'.

Fix: Build lists only from listFollowers/listFollowing(target) with pagination. Use local state only for the Follow button on each row, and write empty-state copy for the profile being viewed.

`ProfileConnectionsScreen.tsx:169-223, 225-276, 278-303, 316-320`

---

critical bug

Other users' follower and following stats are hard-coded

Followers shows isFollowingAuthor ? 1 : 0 and Following always shows 0.

Fix: Add a get_public_profile RPC that returns real counts and respects privacy.

`UserProfileContent.tsx:351-362`

---

high backend-data

Profile post grids only cover the newest 40 posts app-wide

listUserPosts fetches the newest 40 published posts from everyone and filters by author on the client. The own profile filters the home feed the same way. Older posts never appear, so the grid can say 'No posts yet' for a user who has posted.

Fix: Filter on the server with .eq('author_id') and a pagination cursor, add an index on (author_id, published_at), and render with FlashList.

`supabaseService.ts:1132-1140, 3636-3640; sharedStallPosts.ts:29-57; ProfileHomeScreen.tsx:301-310; UserProfileContent.tsx:164-192`

---

high bug

Matching by display name shows other people's posts as yours

The own grid includes any post whose authorName equals your displayName. Other-user avatar, review and post lookups also fall back to name matching.

Fix: Match only on authorId. When there is no id, show a 'profile unavailable' state.

`ProfileHomeScreen.tsx:305-309; UserProfileContent.tsx:89-94, 180-184, 194-267`

---

high bug

'Reviews' on other profiles are actually cached comments

userReviewItems is built only from comments and replies already cached on this device, matched by author name.

Fix: Fetch real reviews for that user (paginated), or rename the tab.

`UserProfileContent.tsx:229-267, 365-370`

---

high frontend

'Stalls' stat on another user's profile is a dead button, and would show your stalls anyway

VisitedStalls is registered only in the Profile tab stack, but UserProfile is a root route. VisitedStallsScreen reads the viewer's own reviewedDishIds.

Fix: Add a userId param and register the route on the root stack, or remove onPress for other users.

`UserProfileContent.tsx:371-376; RootNavigator.tsx:693; ProfileStack.tsx:82; VisitedStallsScreen.tsx:26-53`

---

high frontend

Followers/Following from another user's profile switches tabs and breaks Back

Navigation falls back to MainTabs > Profile > Followers, so Back lands on your own ProfileHome. Profile is a protected tab, so a guest is sent to login. With no authorId (for example from PopularVisitorsSection, which passes none), the stat buttons do nothing.

Fix: Register the connection lists on the root stack, and hide the stat buttons when there is no id.

`UserProfileContent.tsx:96-118; RootNavigator.tsx:93; PopularVisitorsSection.tsx:78-83`

---

high backend-data

RLS blocks reading other users' follower lists; errors look like empty lists

follows_select_participant only allows rows where you are the follower or followee. The service turns errors into [], so the screen cannot tell 'forbidden' from 'empty'.

Fix: Add a privacy-aware SECURITY DEFINER list RPC, and throw on error so the screen can show an error state.

`0023_integration_posts_privacy_chat.sql:362-365; supabaseService.ts:3967-4001`

---

high bug

Follow state is never loaded from the server

followedUserIds is only persisted locally ('hungry-social-v1'). On a new device everyone shows 'Follow'. isFollowing() is never called.

Fix: Load followedUserIds from listFollowing(self) on sign-in, and call isFollowing when a profile mounts.

`useSocialStore.ts:77,114,299-317,559; supabaseService.ts:4003-4010`

---

high bug

Passport celebration never finishes and re-fires analytics

Setting celebratingStampId re-runs the effect. Its cleanup clears the timeout and the new run returns early, so markStampCelebrated never runs. The store is not persisted, so stamps re-celebrate every launch, and every cold start re-emits passport_stamp_earned.

Fix: Mark the stamp celebrated at the start and keep the visual flag in a ref or local state. Persist celebrated ids per user, and seed the previous earned set before emitting analytics.

`PassportScreen.tsx:121-141; usePassportStore.ts:165, 192-214`

---

high performance

Viewing another profile runs all of your own profile's fetches

UserProfileScreen renders ProfileHomeScreen, whose hooks and effects (stories, submissions, the full feed, own followers/following) all run before it returns UserProfileContent.

Fix: Render UserProfileContent directly from UserProfileScreen.

`UserProfileScreen.tsx:8-18; ProfileHomeScreen.tsx:263-439 vs 510-519`

---

high accessibility

Unlabeled buttons on other-user and post screens

UserProfileContent: StatBlock, the Posts/Reviews toggles and review cards have no role, label or selected state. SocialPostDetail: the share, save, comment and like icon buttons have no labels. Connections and VisitedStalls rows have no role or label.

Fix: Reuse ProfileHome's StatBlock and segmented-control pattern, and add labels such as 'Like, 12 likes, liked'.

`UserProfileContent.tsx:393-428, 466-475, 525-551; SocialPostDetailScreen.tsx:286-380; ProfileConnectionsScreen.tsx:345-363; VisitedStallsScreen.tsx:63-75`

---

medium bug

Your own posts open your profile as a stranger's, with a 'Follow' button on yourself

HomeFeed openUserProfile and the Connections rows navigate to UserProfile even when the author is you. UserProfileContent never compares the author with profile.id, so it shows Follow for yourself, the hard-coded 0/1 stats and cached-comment 'Reviews'. Tapping Follow writes a self-follow that the follower_id <> followee_id check rejects, and the button bounces back. HomeFeed hides its own inline Follow for self (isOwnAuthor), but the profile screen does not.

Fix: When authorId === profile.id, navigate to the Profile tab or render self mode, and never show Follow for yourself.

`HomeFeedScreen.tsx:725-737, 1190, 1236-1258; UserProfileContent.tsx:281-347; 0023_integration_posts_privacy_chat.sql:21`

---

medium bug

ProfileHome load effect re-runs every load whenever tried stalls change

triedStallIds is a dependency, so any markTried re-runs loadStories and loadStallSubmissions (which has no guard). With gamification on, loadStallInteractions triggers the effect itself and .then reads a stale triedStallIds. The promises have no .catch.

Fix: Split into a mount-only load effect (each call with .catch) and a separate effect that computes progress.

`ProfileHomeScreen.tsx:172-178, 263-291; useStallSubmissionStore.ts:20-23`

---

medium backend-data

Gamification and submission stores leak between accounts

clearAccountScopedStores does not reset the FoodCred, Mission, Passport or StallSubmission stores. loadCredProfile and loadMissions return early when isLoaded is set, whichever user is signed in. Mostly affects non-production, because gamification is off in prod.

Fix: Call each store's _reset() on sign-out, and key isLoaded by userId.

`useSessionStore.ts:97-113; useFoodCredStore.ts:89-90; usePassportStore.ts:245-`

medium accessibility

Tap targets below 44pt

Avatar edit badge 28pt, Follow buttons 30/32pt, Favourites heart 32pt, AddStall controls 28pt, and the Taste 'SHARE' link about 16pt with no hitSlop.

Fix: Make every hit area at least 44x44 with hitSlop or minHeight.

`ProfileHomeScreen.tsx:724-736, 836-847; UserProfileContent.tsx:326; ProfileConnectionsScreen.tsx:436; FavouritesScreen.tsx:94-95; AddStallScreen.tsx:630-631, 689-691`

---

medium bug

'Reviews' stat and tab count dishes marked as tried

addReviewedDish (the tried action) feeds reviewedDishIds, which the Reviews stat, Reviews tab and VisitedStalls all read.

Fix: Keep tried dishes separate from reviewed dishes, and render real review cards.

`useProfileStore.ts:699-718; ProfileHomeScreen.tsx:333-355, 781-790`

---

medium backend-data

Stall count and Visited list come from different sources

The stat reads stats.stallsVisited, which nothing keeps up to date. The list is built from reviewedDishIds through the local catalog. The screen title says 'Visited stores' while the stat says 'Stalls'.

Fix: Derive both from user_stall_interactions, and use one noun everywhere.

`ProfileHomeScreen.tsx:791-797; VisitedStallsScreen.tsx:32-58`

---

medium ui-ux

No loading or error states; empty states flash

Grids and review lists start empty and show 'No posts yet' until loaded. Errors become []. SocialGrid's spinner never stops for a signed-out user. No pull-to-refresh.

Fix: Track loading/ready/error per query. Add skeletons, a Retry button and RefreshControl.

`ProfileHomeScreen.tsx:189, 953-997; UserProfileContent.tsx:85, 497-503; ReviewHistoryScreen.tsx:41-73; SocialGridScreen.tsx:45, 53-74`

---

medium product

No block, report, share or message on another user's profile

The only action is Follow. There is no overflow menu, no deep link to a profile, and no Message button.

Fix: Add a '...' menu (Share profile, Block, Report) that reuses communitySafety, and add a user/:userId link.

`UserProfileContent.tsx:281-347; linking.ts`

---

medium ui-ux

Own-profile header is thin and the edit action is mislabeled

Only avatar and name are shown. The only way into the full editor is a 28pt badge labeled 'Edit profile photo'. The 'Guest User' branches are dead code. Heart and send icons are used for Followers and Following.

Fix: Add an Edit profile button, a bio and a FoodCredBadge. Remove the dead guest branches.

`ProfileHomeScreen.tsx:676-779`

---

medium ui-ux

Hamburger menu dismisses poorly and signs out without confirming

The click-catcher sits inside the scroll content, and the menu is not modal for screen readers. Sign Out runs immediately.

Fix: Use a BottomSheet or ActionSheet, and confirm sign-out with an Alert.

`ProfileHomeScreen.tsx:531-674`

---

medium ui-ux

Taste Fingerprint has an icon-only header row and bars screen readers cannot read

No summary line and no accessibilityValue. 'Copy link' copies text with no link and gives no feedback. Uses the deprecated RN core Clipboard.

Fix: Add a persona summary and accessibilityValue. Use expo-clipboard with a toast.

`ProfileHomeScreen.tsx:2, 448-459, 863-882, 1210-1259`

---

medium ui-ux

AddStall submits made-up opening hours by default

The form starts with 'Mon 10:00 AM - 10:00 PM', which is submitted even if the user skips the section. Postal code and URL are not validated, and there is no unsaved-changes prompt.

Fix: Start with zero hour slots. Validate a 6-digit postal code and the URL, and add a beforeRemove prompt.

`AddStallScreen.tsx:228-235, 489-492, 781-787, 1086-1093`

---

medium frontend

AddStall drag handle is rebuilt every render and cannot be used with a screen reader

PanResponder.create runs inline in render, and the handle has no accessibilityActions. Uses the deprecated MediaTypeOptions.

Fix: Use gesture-handler or move-left/right accessibility actions, and use mediaTypes: ['images'].

`AddStallScreen.tsx:298, 621-679`

---

medium backend-data

AddStall calls gamification backends even when gamification is off

awardFoodCred, incrementMission and recordPassportContribution run with no flag check, and Promise.allSettled hides any failures.

Fix: Check FEATURE_FLAGS.gamificationEnabled first, or award on the server.

`AddStallScreen.tsx:498-503; featureFlags.ts:39`

---

medium bug

ReviewHistory shows the dish's average as the user's rating and repeats the CTA on every card

rating falls back to dish.rating. Every card has its own 'Write another review' button, cards cannot be tapped, and the key falls back to a constant.

Fix: Hide unknown ratings, use one header CTA, and make cards pressable with stable keys.

`ReviewHistoryScreen.tsx:101, 106, 114`

---

medium ui-ux

'Saved' naming and icons are inconsistent

The stat uses a bookmark and opens 'Saved dishes', where removing is a heart labeled 'favourites'. Saved stalls and lists are not shown.

Fix: Use one verb and one icon, and add tabs for Dishes / Stalls / Lists.

`ProfileHomeScreen.tsx:798-806; FavouritesScreen.tsx:30, 86-103`

---

medium frontend

Vertical ScrollViews nested inside the Screen ScrollView

ProfileScreenShell always passes scroll, and Connections, VisitedStalls, FollowedStalls and Passport each nest their own ScrollView. Nothing is virtualized.

Fix: Use scroll={false} with FlashList.

`ProfileScreenShell.tsx:26-34; ProfileConnectionsScreen.tsx:337; VisitedStallsScreen.tsx:60; FollowedStallsScreen.tsx:37; PassportScreen.tsx:166`

---

medium performance

Grids and SocialPostDetail render everything at once

Grids map every post into a flex-wrap View. SocialPostDetail renders every post as a full card. SocialGrid computes its width from Dimensions once at load.

Fix: Use FlashList and useWindowDimensions.

`ProfileHomeScreen.tsx:955-990; UserProfileContent.tsx:433-461; SocialPostDetailScreen.tsx:398; SocialGridScreen.tsx:27-29`

---

medium ui-ux

SocialPostDetail shows a '1 / N' badge but only the first photo

Only mediaUrls[0] is rendered. Share does nothing without a primaryDish, and the author row cannot be tapped.

Fix: Add a horizontal pager, a share fallback and a link to the author's profile.

`SocialPostDetailScreen.tsx:166-213, 256-266, 286-289`

---

low ui-ux

Other-profile content heading always says 'Posts' and Unfollow has no confirmation

An h2 'Posts' sits above the Posts/Reviews toggle, even when Reviews is selected. Tapping 'Following' unfollows at once with no confirmation, so a mis-tap drops the follow (Instagram asks first).

Fix: Remove the static heading or bind it to the active tab, and confirm unfollow with an ActionSheet.

`UserProfileContent.tsx:301-304, 381`

---

low bug

CredEarnedToast never dismisses itself and drops repeat awards

visible depends on a ref that does not trigger a re-render. Two awards of the same amount show only once, and the toast is not announced to screen readers.

Fix: Drive the toast from an event id plus a timeout, and announce it for accessibility.

`CredEarnedToast.tsx:29, 39-60, 66`

low bug **PassportStampCard shows another category's 'to next stamp' count**

Locked cards use the global nextStamp.remainingCount, and only 4 stamp artworks cover 11 categories.

Fix: Compute the remaining count per category.

`PassportStampCard.tsx:43-44, 116; passportAssets.ts`

---

low ui-ux **MissionBanner has no press feedback and a crowded header**

Pressed and unpressed backgrounds are identical in the all-done state, and the disclosure text is squeezed inline.

Fix: Add a pressed tint, move the disclosure to its own line, and list active missions first.

`MissionBanner.tsx:57, 108-113; MissionsScreen.tsx:52-65`

---

low product **Dead or unwired pieces**

FoodCredBadge is unused, trackPassportViewed is never called, ProfilePremium duplicates ProfileHome, and FollowedStalls can only be reached from Settings.

Fix: Wire these up or remove them, and add profile analytics events.

`ProfileStack.tsx:77; gamificationEvents.ts; SettingsScreen.tsx:462-469`

---

low frontend **Connections list dedupes by name and can show raw UUIDs**

Rows are keyed by name, and unresolved users fall back to showing their userId as the name. The search filters on location, which is never shown, and rows have a double border.

Fix: Dedupe by userId and hide unresolved users.

`ProfileConnectionsScreen.tsx:228-237, 261-269, 280-289, 306-313, 355-364`

Settings & account 4/10

The Settings page looks complete, but 12 of its 15 saved switches do nothing outside the Settings screen, including both privacy switches. "Change Password" always fails with a real (Supabase) account, and editing your email changes only an unverified profile column. The server side of account deletion is mature. Around it, the export misses most posts and is shared as plain text, "Clear local cache" deletes saved session data, and accessibility is weak.

▶ How it compares with other apps

▶ What it does well (8)

▶ Issues from the 18 Oct audit: 5 still present, 5 fixed

▶ Cross-check notes: 31 confirmed, 1 removed, 7 corrected, 1 added

▼ Findings (33)

critical product **12 of 15 saved Settings switches have no effect**

showLocationBadge, allowSearchHistory, openToExternalApps, dietaryFiltersEnabled, activityFeedEnabled, hideReviewedDishesFromFeed and showOnlyFavoriteDishes are visible in production. Push, mission, cred, passport and badges are behind feature flags. None of them is read anywhere except useUIStore, SettingsScreen and a source-contract test. Two of them are privacy controls that do nothing, which is a PDPA trust problem.

Fix: Hide the switches that have no consumer. Connect allowSearchHistory to search history recording and clear the history when it is turned off. Build hideReviewedDishesFromFeed on the server or remove it. Add a contract test that every visible switch has a consumer outside Settings.

`useUIStore.ts:120-145,150-166; the only other references are in mvp-source-of-truth-contracts.test.ts:61+; useSearchStore.ts:113,133 record history unconditionally; SettingsScreen.tsx:338-345,386-393,403-434,514-521,532-539`

---

critical bug **'Change Password' always fails for Supabase users**

EditProfile passes code 'profile-settings', and resetPassword calls exchangeCodeForSession on it, which errors. In mock mode the user lands on a false 'Check your inbox' screen whose 'Resend link' only shows a toast. The row is also shown to users who signed in with Google or Apple and have no password.

Fix: Add a ChangePassword screen that re-authenticates and then calls auth.updateUser({password}) with no code exchange. Hide the row for users who signed in with a non-email provider.

`EditProfileScreen.tsx:103-109; ResetPasswordScreen.tsx:34-43; supabaseService.ts:2981-2985,1838-1868; ResetPasswordSuccessScreen.tsx:20,25`

---

high backend-data **Email edit changes a profile column only, not the sign-in email, with no verification**

updateProfile upserts user_profiles.email and never calls auth.updateUser({email}). fetchUserProfile prefers row.email, so Settings shows the unverified address. There is no format validation, and every save re-sends the email even when it hasn't changed.

Fix: Make email read-only. Add a 'Change email' flow that uses auth.updateUser and shows a confirm-in-inbox state. Sync the column from auth.users.

`EditProfileScreen.tsx:178-184,206-211; supabaseService.ts:3392,641-642; SettingsScreen.tsx:307-313`

---

high backend-data **The PDPA export silently omits most posts and saved posts**

listUserPosts and getSavedBites filter the 40 newest posts across the whole platform. Errors return [] so the section is marked ok:true. Many categories are missing entirely.

Fix: Add a server-side export_my_data() RPC scoped to auth.uid() that throws on errors and includes a manifest of the categories covered.

`supabaseService.ts:1132-1140,3636-3640,3912-3924,3206-3217; exportMyData.ts:27-34`

high frontend **The export is shared as one large text message, not a file**

Share.share puts the raw JSON into chat apps. A large payload may hit Android's Binder limit (inferred). There is no machine-readable file.

Fix: Write a .json file and open it with Sharing.shareAsync, or email a signed download link.

`SettingsScreen.tsx:129-133; package.json has no expo-sharing or expo-file-system`

---

high bug **'Clear local cache' deletes the saved session, profile and location**

The handler reuses the account purge. Supabase never restores completedOnboarding, so a signed-in user can be sent back to onboarding on a cold start if nothing writes the session again first (inferred, depends on timing). Local taste events are lost. The copy is misleading, and the row and dialog titles don't match.

Fix: Remove only search-v1, review-draft-v1 and the image cache. Use one name for the row and the dialog.

`SettingsScreen.tsx:114-123,254-269,541-545; useSessionStore.ts:303-305,369-376; RootNavigator.tsx:580-585`

---

high accessibility **SettingsRow exposes no role, state or label**

Switches aren't announced with their state. The inner Switch has no label. Rows that only show a value still highlight when pressed. The busy export row doesn't set busy state.

Fix: Toggle rows: role switch with a checked state, and hide the inner Switch from accessibility. Navigation rows: role button with an accessibilityValue. Render value rows as a View.

`SettingsRow.tsx:44-58,52,112-119; SettingsScreen.tsx:546-551,585`

---

high ui-ux **Changing location from Settings never returns, and logs onboarding as completed again**

The picker calls completeOnboarding (which tracks onboarding_completed) and never navigates away. setManualSelection forces permission to 'denied', so the permission switch turns off.

Fix: Add a mode:'settings' parameter. In that mode, go back and skip completeOnboarding. Keep the OS permission separate from the manual location.

`SettingsScreen.tsx:369-377; ManualLocationPickerScreen.tsx:117-121; useSessionStore.ts:231-238; RootNavigator.tsx:593-603; useLocationStore.ts:192-199`

---

high bug **'Reset selected location' also resets GPS**

It sets permission to 'unknown' and moves the location to the CBD default. Nothing fetches a fresh GPS fix.

Fix: Add clearManualLocation() and then refresh location with force when permission is granted.

`SettingsScreen.tsx:237-252; useLocationStore.ts:29,207-215`

---

high ui-ux **The Location permission switch doesn't match the OS permission**

Turning it off sets the local state to 'denied', clears manualCoordinate and opens system Settings. The app never re-reads the permission when it returns to the foreground.

Fix: Show a read-only status row and re-check the permission when the app becomes active.

`SettingsScreen.tsx:217-235,378-385; useLocationStore.ts:179-185`

---

medium bug

(Added) Saving Edit Profile resets Left-handed mode

applyProfile replaces the whole profile with the server copy, which has no leftHandedMode field (only mock data sets it). Tapping Save silently turns left-handed mode off.

Fix: Merge the local-only fields in applyProfile, or move left-handed mode into useUIStore.

`EditProfileScreen.tsx:212; useProfileStore.ts:368-375,852-857; no leftHandedMode in supabaseService.ts`

---

medium backend-data

Account deletion leaves the avatar and media in storage

The anonymise function doesn't null avatar_url. user_profiles.id has no foreign key to auth.users, so the row remains. The worker never touches storage. Each avatar change uploads a new file and never deletes the old one.

Fix: Remove the avatars/{uid}/* and media prefixes, null avatar_url, and delete the previous avatar after an upload.

`0040:285-303; 0002_core_schema.sql:117-118; process-account-deletions/index.ts:109; supabaseService.ts:984-1003`

---

medium ui-ux

Delete account: no re-authentication, lands on Sign Up, and leaves the old screen stack

Deletion takes a single Alert. Afterwards the app navigates to SignUp instead of resetting, so the old stack stays underneath. No scheduled date is shown.

Fix: Ask for the password or an OTP, then reset to a 'Deletion scheduled for <date>' screen.

`SettingsScreen.tsx:145-180 (navigate :167) vs :281 reset`

---

medium ui-ux

'Profile photo updated' appears before saving, and there is no unsaved-changes guard

The toast fires when the photo is picked. Leaving the screen discards edits silently. Save is always enabled, and an empty name is accepted.

Fix: Change the toast copy, track unsaved changes, add a beforeRemove confirm and validate the name.

`EditProfileScreen.tsx:99-100,177,199-225`

---

medium frontend

The avatar picker asks for full photo-library access it doesn't need, and the pre-prompt can hang

The pre-prompt appears on every tap even though the system picker needs no permission. The Alert is cancelable with no onDismiss, so dismissing it on Android leaves the promise pending. MediaTypeOptions is deprecated.

Fix: Call launchImageLibraryAsync directly, or add onDismiss that resolves false.

`EditProfileScreen.tsx:58-93; gallery.ts:20-41`

Alerts switches show defaults

medium backend-data

before loading and after a failed load

The switches render the defaults, and errors are swallowed. They stay enabled while a save is running.

Fix: Add loading and error states, and disable the switches until loaded and while saving.

`StallAlertsSettings.tsx:29,32-43,49`

---

medium ui-ux

Denying notification permission leads to a toast with no action

There is no Open Settings action.

Fix: Use an Alert that offers Linking.openSettings.

`StallAlertsSettings.tsx:49-54; SettingsScreen.tsx:206-215`

---

medium bug

A failed profile visibility change is silent

The value reverts and the error is only logged with console.error.

Fix: Return a promise, then show a pending state and an error toast with Retry.

`useProfileStore.ts:535-555; SettingsScreen.tsx:189-204`

---

medium ui-ux

Information architecture is cluttered and inconsistent

The display name appears twice. A raw Profile ID is shown. There are two discovery sections. Left-handed mode sits under Feed. 'Help Center' opens /contact. 'Data controls' duplicates in-app deletion. Casing is mixed. Sign out is buried in a section.

Fix: Regroup into standard sections and put Sign out on its own at the bottom.

`SettingsScreen.tsx:293-320,368,402,419-426,553-557,566-591; links.ts:8,11`

---

medium accessibility

Off-state switch track contrast is about 1.2:1 in both themes

Light: #E2E8F0 on #FFFFFF. Dark: #2D3748 on #242F40. Both fail WCAG 1.4.11.

Fix: Use an off-track token with at least 3:1 contrast.

`SettingsRow.tsx:114-118; tokens.ts:6,18,82,94`

---

medium accessibility

Section titles aren't headers, and the text is uppercased in code

There is no header role, and the title goes through toUpperCase().

Fix: Add accessibilityRole header and use textTransform.

`SettingsSection.tsx:22-24`

---

medium accessibility

Edit Profile controls have no role or label

The avatar Pressable and the Change Password row have no role or label.

Fix: Add a button role and labels.

`EditProfileScreen.tsx:114-119,185-196`

---

medium product

The Haptic feedback switch is ignored almost everywhere

Only useSocialStore checks it, while 30 files import expo-haptics.

Fix: Use a single wrapper that checks the setting, and lint-ban direct imports.

`useSocialStore.ts:38`

---

medium bug

Signing out from the Profile menu skips confirmation and keeps search history

The menu calls signOut without confirming, and signOut doesn't clear search or drafts.

Fix: Clear search and drafts inside signOut, and add a confirm.

`ProfileHomeScreen.tsx:643-655; useSessionStore.ts:97-113`

---

medium backend-data

Exported follower and following lists have no names

The embedded user_profiles join is blocked by the owner-only RLS policy (inferred).

Fix: Read names from public_profiles.

`supabaseService.ts:3967-3998; 0038:350-354`

---

low backend-data

A client can insert a deletion request with any scheduled_for, status or legal_hold

There is a table-wide INSERT grant, and RLS checks only user_id. A duplicate request shows a generic error.

Fix: Revoke INSERT and add a SECURITY DEFINER request function.

`0017:21-24; 0040:32; supabaseService.ts:2935-2939`

---

low ui-ux

The Theme row cycles on each tap

The choices are never shown.

Fix: Use a three-option picker.

`SettingsScreen.tsx:182-187,475-487`

---

low product

No analytics on Settings or Edit Profile actions

Deletion, export and privacy changes are not measured.

Fix: Add events.

`SettingsScreen.tsx:1-45; EditProfileScreen.tsx:1-14`

---

low ui-ux

Icons don't match their meaning

Bell is used for a privacy switch, Globe for favourites, and HandMetal for both left-handed mode and haptics.

Fix: Choose icons by meaning.

`SettingsScreen.tsx:340,358,405,421,429,498,566-581`

---

low performance

Settings uses about 45 store selectors, and rows aren't memoized

Any change re-renders the whole tree.

Fix: Use useShallow per section and React.memo.

`SettingsScreen.tsx:52-99`

---

low product **Support is a Gmail address, and the Terms page uses a different domain**

This weakens trust for a PDPA contact.

Fix: Use a support@usehungry.com address and a DPO contact.

`links.ts:5; terms/page.tsx:35 vs privacy/page.tsx:29`

---

low frontend **The grace-period length is set in both TypeScript and SQL**

The copy can drift from the real schedule.

Fix: Show the scheduled_for date returned by the server.

`types.ts:561; 20261017120000:6`

---

low ui-ux **Left-handed mode is device-local and is wiped when you sign out**

clearProfile resets it.

Fix: Move it to useUIStore or sync it.

`useProfileStore.ts:852-857,866-874`

Merchant mode 3/10

Merchant mode is a wide prototype. It has 16 screens, and PRs #74 and #76 added real server-side write guards and live menu sync. Too much of what it promises is fake or broken end to end. A real merchant has no in-app way in, scheduled promotions never go live, and audience targeting, location privacy, AI, team invites and weekly emails do nothing. The cross-check also found three more serious problems. Anonymous callers can read every live outlet's raw row, including email and unit or floor. Delete Dish is unreachable on Android. Profile edits to name, hours and unit are reported as live but never reach diners. It is rightly off in production and not pilot-ready.

▶ How it compares with other apps

▶ What it does well (7)

▶ Issues from the 18 Oct audit: 5 still present, 2 fixed

▶ Cross-check notes: 41 confirmed, 2 removed, 7 corrected, 5 added

▼ Findings (46)

No in-app way into Merchant mode, and

critical product

'Switch to Customer Mode' is a one-way door

The Profile menu entry needs the merchant store to already hold an account, and only MerchantTabs and the verification screens load it. A fresh sign-in never shows the entry, so the only way in is the /merchant deep link or the dev launcher. Switching mode or signing out clears the account, which hides the entry again.

Fix: Load getMerchantAccount() in session bootstrap. Keep 'is merchant' separate from a mode flag, and have the switch toggle only the mode. Add a persistent Business entry or account switcher.

`ProfileHomeScreen.tsx:570. setAccount only at MerchantTabs.tsx:47,350,379, VerificationCentreScreen.tsx:123 and HomeBasedVerificationScreen.tsx:126. clearMerchant at MerchantProfileScreen.tsx:140, MerchantSettingsScreen.tsx:154 and useSessionStore.ts:98. linking.ts:139-141, 222-235.`

---

high backend-data

Anonymous users can read every live outlet's full row, including contact email, unit, floor and building

The anon RLS policy on merchant_outlets is only is_live = true, with no column grants. Any anon-key caller can select every column of every live outlet, verified or not, including contact_email, contact_phone, unit_number, floor, building_id, location_privacy and merchant_account_id. This bypasses #76's 'owner card only for verified outlets' rule and makes home-based 'hidden' privacy impossible.

Fix: Drop the anon table policy and serve public outlet data only through the security-definer RPC with privacy applied. Restrict non-member authenticated reads the same way. Add an RLS smoke test.

`20260623161000_rls_performance_advisor_cleanup.sql:99-101 (merchant_outlets_anon_live_select using is_live = true). No later policy and no revoke or column grant on merchant_outlets in any migration.`

---

high bug

Delete Dish (and Cancel) is missing on Android

'Dish Options' is a 5-button Alert. React Native's Android Alert shows only the first three buttons (Edit, Mark Sold Out, Feature), so Delete and Cancel are dropped. There is no other delete affordance anywhere in merchant mode.

Fix: Use an ActionSheet or BottomSheet or a swipe action, and add Delete inside DishEditor.

`MerchantMenuScreen.tsx:229-247. The only deleteDish call is :219. RN Alert.js on Android slices buttons to three (inferred from library source; node_modules not installed).`

---

high bug

Profile editor says 'Your changes are live' but name, hours, unit and floor never reach diners

The outlet-to-venue sync copies only closure, phone, website, cuisine and logo. The public owner card adds description, email, socials and photos. Stall name, operating hours, unit and floor stay in merchant_outlets, and diners keep seeing the old venue values.

Fix: Sync these fields (with review for name changes), or change the copy to say which fields go live.

`BusinessProfileEditorScreen.tsx:214-222. 20261018171000_merchant_live_sync_hardening.sql:106-163 (synced fields), 169-205 (owner card). No other trigger updates venues.name, operating_hours, unit_number or floor.`

high bug

Editors stay mounted as hidden tabs, so 'Add dish' and 'New promotion' open pre-filled and saving duplicates

With no id param, the load function returns early without resetting state. The old fields remain, and Save calls addDish or createPromotion, which creates a duplicate that is live for verified outlets.

Fix: Move the editors into a native stack wrapping the tabs, or key on params or reset when the screen gains focus.

`MerchantTabs.tsx:472-491. DishEditorScreen.tsx:110 with state at 83-95. PromotionBuilderScreen.tsx:85 with state at 48-67. Save at DishEditorScreen.tsx:183-187 and PromotionBuilderScreen.tsx:181-185.`

---

high frontend

Detail screens are hidden tabs, so Back goes to Dashboard

There are 12 hidden-tab routes with no backBehavior (the default is firstRoute). goBack after saving lands on Dashboard. There is no push animation or swipe-back, and unverified merchants land on a verification wall.

Fix: Use a native stack for the detail routes, with backBehavior='history' as a stopgap.

`MerchantTabs.tsx:437-506. goBack at DishEditorScreen.tsx:195, PromotionBuilderScreen.tsx:188, BusinessProfileEditorScreen.tsx:223, HomeBasedVerificationScreen.tsx:129.`

---

high bug

First profile save silently changes location privacy from 'approximate' to 'hidden'

The DB default is 'approximate'. The switch's ON means 'exact' and OFF writes 'hidden', so an approximate outlet saves as hidden. The label is inverted.

Fix: Use a 3-option segmented control, hide Exact for home_based, and relabel it.

`BusinessProfileEditorScreen.tsx:146 (|| 'exact' fallback), 527-537. 0018:50. supabaseService.ts:2004-2005.`

---

high backend-data

Home-based location privacy is never enforced, and the HBB flow never marks the outlet home-based

No consumer path reads location_privacy. The HBB screen sends only name and privacy, never businessType 'home_based', so 'Exact Address' passes validation and the outlet stays a hawker_stall.

Fix: Set business_type on HBB submit, apply privacy in the public RPCs and projection, and add a smoke test.

`HomeBasedVerificationScreen.tsx:112-115, 186-204. location_privacy is referenced only at 0018:50-51 and supabaseService.ts:2005 and 5130. profileValidation.ts:98-100.`

---

high bug

Profile dietary labels, taste tags and gallery are never saved

The fields are collected, but updateBusinessProfile doesn't map them and toMerchantOutlet returns empty arrays.

Fix: Pass the fields and add them to the mapping in the approved Picture Flow.

Fix: Remove the fields, or add columns and map them both ways using the canonical DietaryFlag chips.

`BusinessProfileEditorScreen.tsx:186-202 (as any). supabaseService.ts:5123-5175, 2012, 2017, 2018.`

---

high backend-data

Scheduled promotions never go live while the merchant list shows 'Active'

A future start date stores status 'scheduled'. The diner RPC requires 'active' and nothing promotes scheduled rows. The list recomputes status from dates on the client.

Fix: Have the RPC accept active or scheduled within the time window, or store only published plus the window.

`PromotionBuilderScreen.tsx:157-163. merchantReadiness.ts:120-131. 20260607120000_customer_active_promotions.sql:51. PromotionListScreen.tsx:107-111.`

---

high product

A published promotion is invisible until 'Show on Hungry' is on (default off)

The RPC requires is_live, which defaults to false, and nothing warns the merchant.

Fix: Block publishing or offer a one-tap Go live, and show a 'Not visible to diners' chip.

`20260607120000:50. 0018:54. BusinessProfileEditorScreen.tsx:135. PromotionBuilderScreen.tsx:187.`

---

high bug

Promotion dates are UTC, so in SGT a promotion runs 08:00 to 07:59 the next day

Boundaries use a Z suffix, and the default start date comes from toISOString, so before 8am SGT it is yesterday. There is no time-of-day window, despite what the placeholder suggests.

Fix: Build boundaries in Asia/Singapore, use date pickers, and add daily windows.

`PromotionBuilderScreen.tsx:58-61, 159-160, 169-170, 242-243, 334. promotionValidation.ts:35-39.`

---

high product

Promotion audience targeting is decorative

target_audience is stored but never filtered on, and publishing works with zero audiences.

Fix: Remove or relabel it, or enforce it server-side.

`PromotionBuilderScreen.tsx:452-477. 20260607120000:47-62. PromotionListScreen.tsx:223-228.`

---

high product

Every AI feature is a template, and the AI Assistant can never show an insight

The outputs are fixed strings. The allergen check is substring matching: noodle flags Gluten and eggplant flags Eggs, and 'no allergens' gives false reassurance. Insights hold only the weekly_summary, which the screen filters out. The summary card reports topDishes.length as the menu item count.

Fix: Use a real edge function or remove the AI labels and entry. Add a merchant-declared disclaimer on allergens.

supabaseService.ts:5954-6012 (6001). AIAssistantScreen.tsx:46. DishEditorScreen.tsx:250-269, 384-392, 443-451. CustomerInboxScreen.tsx:387-395.

---

high bug

Menu scan: 'Edit before adding' publishes first, drops data, and there is no scan entry

acceptOCRDraft inserts before the editor opens. Accept drops description, tags and dietary data. The id is deterministic, so a double tap fails. Raw OCR text is shown as the description. Nothing calls ingest-menu-photo. Accept All ends with Success even after errors.

Fix: Pre-fill the editor and accept on save, add a Scan menu capture, use an idempotent RPC, and report partial failures.

OCRDraftScreen.tsx:74-121, 224-275. supabaseService.ts:5371, 5383-5412. MerchantMenuScreen.tsx:462-472.

---

high backend-data

Team management does nothing

Invites have user_id null and an outbox that nothing drains, and there is no accept flow. The role is hard-coded to owner. Staff is excluded from merchant_can_manage_venue.

Fix: Hide Team until it works, then build invite tokens, an accept RPC, a real role read and an email sender.

supabaseService.ts:6062-6108, 2076. supabase/functions has no outbox consumer. 0020:6-22. MerchantSettingsScreen.tsx:30-36, 283-325.

---

high product

'Immediate' low-rating alerts and weekly emails don't exist

Alerts are created on the client only when a screen opens, with no push. Emails are never sent. The manual send claims every team member was notified.

Fix: Use a trigger on review insert with push through send-notifications, plus an inbox with a badge. Fix the copy.

MerchantSettingsScreen.tsx:231-247, 373-386, 414-428. MerchantDashboardScreen.tsx:273-277. supabaseService.ts:5840-5952.

---

high ui-ux

Reply composer scrolls with the content, and the keyboard covers Send

An absoluteFill View inside Screen's ScrollView, with autoFocus, no KeyboardAvoidingView and no modal semantics.

Fix: Use BottomSheet or a Modal with KeyboardAvoidingView, and say the reply is public.

CustomerInboxScreen.tsx:160-170, 410-428, 474-481. Screen.tsx:57-84.

---

high backend-data

Inbox Comments and Mentions are always empty, and 'View original' shows a UUID

getInbox reads only reviews. The empty state prints the raw enum. View original shows an Alert with the source id.

Fix: Remove those chips, navigate to the source, and map enums to labels.

supabaseService.ts:5422-5462. CustomerInboxScreen.tsx:31-37, 75-81, 142-144.

---

high ui-ux

Dashboard metric cards always show a green trending-up arrow with no comparison

The arrow is hard-coded green with no delta, which contradicts the Analytics tab's real deltas.

Fix: Show the real delta with an icon and text, or remove the arrow.

`MerchantDashboardScreen.tsx:135, 148-151, 323-338.`
`MerchantAnalyticsScreen.tsx:20-30, 153-156.`

---

medium bug

Dashboard and Performance show different average ratings, and 'N new reviews' counts all-time reviews

Dashboard swaps in all-time inbox figures.

Fix: Use the range-scoped RPC values.

`merchantReadiness.ts:101-118. MerchantDashboardScreen.tsx:265-272, 340-349.`
`MerchantAnalyticsScreen.tsx:177-192.`

---

medium bug

Peak hours are in UTC, and midnight shows as '0 AM'

extract(hour) has no time zone (session TZ is UTC; inferred), and the formatter has no hour-0 case.

Fix: Use at time zone 'Asia/Singapore' and Intl formatting.

`20260525120301_merchant_analytics_foundation.sql:1133-1135.`
`MerchantAnalyticsScreen.tsx:477.`

---

medium frontend

Performance tab blanks on range change, its title flickers, there is no stale guard, and See More is an Alert

Full skeletons on every range change. The title switches between Analytics and Performance. Out-of-order responses can render. Funnel steps are shown as shares of one total.

Fix: Keep data while refetching, drop stale responses, use one title, add drill-downs and charts.

`MerchantAnalyticsScreen.tsx:47-70, 89-131, 158-163, 255-262.`
`MerchantDashboardScreen.tsx:253-288.`

---

medium ui-ux

Unverified merchants are trapped with no exit

Every tab, Profile and Settings is verified-only, and those are where the exits sit. Several unverified branches are dead code, including Profile's 'Verification pending' label.

Fix: Allow menu and profile preparation, gate only publishing, and add an always-available exit.

`merchantGuards.ts:89-104. MerchantTabs.tsx:85-99.`
`MerchantDashboardScreen.tsx:445-455. MerchantMenuScreen.tsx:288-290.`
`MerchantProfileScreen.tsx:42-43.`

---

medium ui-ux

Verification submits on one pick, has no camera or rejection reason, and has no video limits

One gallery pick submits immediately. The rejected state ignores the stored rejection_reason.

Fix: Use a checklist with review before submit, camera capture, the rejection reason with resubmit, and a video cap.

`VerificationCentreScreen.tsx:65-129, 133-204. supabaseService.ts:5096-5108.`

---

medium bug

Home-based verification fails silently and can submit partially

Errors are only logged. The per-photo loop can leave partial evidence. The stated photo minimum isn't enforced. The checkbox and radio options have no semantics.

Fix: Show an inline error, use one transaction, enforce the minimum, and use Checkbox and RadioGroup primitives.

`HomeBasedVerificationScreen.tsx:107-134, 263, 294-306, 347-366.`

---

medium performance

Sold-out is read-modify-write, and saves rebuild the venue catalog many times

The flags write is non-atomic. Row-level triggers on three tables each rebuild all venue cards, and the client also does a full cache refresh.

Fix: Use an atomic array update, statement-level triggers or a once-per-transaction queue, and drop the client refresh.

`supabaseService.ts:5309-5330, 5242-5245, 5285-5288.`
`20261018150000_merchant_live_sync.sql:433-443, 585-602.`

---

medium ui-ux

Sold-out is buried in an Alert, and the 'optimistic' update isn't optimistic

Toggling takes three taps, the state updates only after the network call, and there is no 'until tomorrow'.

Fix: Add an inline Switch with rollback, sold_out_until, and Mark all available.

`MerchantMenuScreen.tsx:164-184, 229-247, 360-365, 437-441.`

---

medium backend-data

Dish create and edit are non-atomic, with client clock ids

Separate insert, images, flags and vector calls. The id is merchant-dish-${Date.now()}.

Fix: Use a single transactional upsert RPC with a UUID or idempotency key.

`supabaseService.ts:5229-5295.`

---

medium performance

Inbox and low-rating sync read every review, and reviews(venue_id) has no index

No limit, filters run on the client, and everything is reread on every Dashboard or Settings open.

Fix: Add an index on (venue_id, created_at desc), paginate, filter in SQL, and use a trigger for detection.

`supabaseService.ts:5422-5462, 5840-5879. 0002_core_schema.sql:170-171. 0029:14-15.`

---

medium performance

Redundant fetches, and prefetch warms the wrong range

The full menu and inbox are loaded just for chips. The outlet is re-resolved per call, verification is fetched N+1, prefetch warms '7d' while Dashboard defaults to 'Today', and there is no query cache (inferred).

Fix: Add a counts RPC, a query cache, and the aligned prefetch range.

`MerchantDashboardScreen.tsx:265-272. supabaseService.ts:2021, 2056-2110. prefetch.ts:290-292.`

---

medium ui-ux

Promotion builder has typed dates and three price fields that must agree, with no end, delete or duplicate

Dates are typed as strings and the price fields must agree. There are no lifecycle actions. The preview differs from the diner card, which shows 'No price change set' or an ASCII arrow label.

Fix: Use pickers, compute the third price, preview with CustomerPromotionCard, add End/Delete/Duplicate, and hide an empty price row.

`PromotionBuilderScreen.tsx:235-316, 381-450. promotionValidation.ts:124-133. merchantReadiness.ts:146-160. CustomerPromotionCard.tsx:37-52.`

---

medium accessibility

Custom touch targets lack role, state or label, and several are tiny

The range segments have no role or selected state and use white on orange. Pressables have no roles. Micro-text links have no hitSlop. VerifiedBadge is unlabeled. Trend is shown by colour only.

Fix: Use the shared primitives, add roles and states, give targets at least 44pt, and pair colour with text.

`MerchantDashboardScreen.tsx:67-87. MerchantProfileScreen.tsx:54-77. MerchantAnalyticsScreen.tsx:232-243. DishEditorScreen.tsx:384-392, 443-451. VerifiedBadge.tsx:36-45.`

---

medium ui-ux

Profile tab is thin, and merchants can't set a real address

All three rows open the same editor and there are no settings links. The editor collects only unit and floor, and a floor alone counts as location set. Components are defined inside render, there is a nested ScrollView, and signOut is not awaited.

Fix: Turn Profile into a settings index, add a postal-code lookup and map pin, and hoist the components.

`MerchantProfileScreen.tsx:45-77, 95-160. BusinessProfileEditorScreen.tsx:457-493. merchantReadiness.ts:40-42.`

---

medium product

Free-text hours, so 'Open' status is wrong

Status shows Open whenever the outlet is live with no closure.

Fix: Use structured weekly hours, compute open-now in SGT, and support special hours.

`BusinessProfileEditorScreen.tsx:495-509. merchantReadiness.ts:53-57.`

---

medium bug

Profile form resets when the outlet object changes, and no editor guards unsaved changes

The effect overwrites every field when activeOutlet's identity changes, which the idle sync triggers. There is no beforeRemove guard.

Fix: Seed the form once per outlet.id, skip when dirty, and add a Discard prompt.

`BusinessProfileEditorScreen.tsx:139-161. MerchantTabs.tsx:348-366. useMerchantStore.ts:68-79.`

---

medium product

No product analytics in merchant mode

There is no event instrumentation, so activation and drop-off can't be measured.

Fix: Instrument key events with outlet_id and no PII.

`rg for track/analytics calls in the merchant screens, components and MerchantTabs.tsx finds none.`

---

low frontend **Dashboard, Performance and Profile never refetch on focus**

Only Menu and PromotionList listen for focus, so counts go stale after replies or edits.

Fix: Use useFocusEffect, or a query cache with invalidation.

`MerchantMenuScreen.tsx:83. PromotionListScreen.tsx:85. MerchantDashboardScreen.tsx:253-290 refetches only on mount or range change.`

---

low backend-data **Merchant notification deep links point at routes that don't exist**

Links use 'MerchantTabs/MerchantAnalytics' (the route is Analytics) and 'MerchantTabs/CustomerInbox' (not in the linking config).

Fix: Use valid hungry://merchant paths and add CustomerInbox to the linking config.

`supabaseService.ts:5859, 5901, 6088. linking.ts:224-234.`

---

low ui-ux **Dish editor asks for taste scores and saves ingredients as taste tags**

0-10 numeric fields. Ingredients are saved as diner-facing tags. The loading state is plain text.

Fix: Remove the manual vector, split ingredients from tags, and use a skeleton.

`DishEditorScreen.tsx:170, 234-248, 284, 354-372.`

---

low bug **&& renders around price and rating, and '$' is used instead of 'S$'**

A value of 0 would render a bare '0' outside Text. In practice this is mostly mock-only, since the Supabase mapper drops price 0 and ratings are 1-5.

Fix: Use ternaries and a shared formatPrice.

`OCRDraftScreen.tsx:202-206. CustomerInboxScreen.tsx:307.`

---

low ui-ux **Settings polish: duplicated heading, destructive-styled mode switch, dev-style send, stale rollback**

Team Management appears twice. The mode switch has a red LogOut icon. Rollback reverts the whole captured object. Two preferences have no toggles.

Fix: Remove the duplicate header, use a neutral icon, remove the manual send, and use functional setState.

`MerchantSettingsScreen.tsx:130-143, 266-281, 414-420, 449-455.`

---

low product **In-App Ordering mock is promoted from the Dashboard**

Fake QR, disabled buttons, and a static unticked verification step on a verified-only screen.

Fix: Remove it, or replace it with Notify me.

`OrdersComingSoonScreen.tsx:297-311. MerchantDashboardScreen.tsx:618-625.`

---

low frontend **AI dismissals don't persist, and Featured Visitors refetches both lists per tap**

Dismiss only changes local state.

Fix: Persist dismissals and update from the mutation result.

`AIAssistantScreen.tsx:78-80. FeaturedVisitorsScreen.tsx:52-83.`

---

low frontend **Image picker copy and API are dated**

The rationale always says 'profile image', it is gallery only, and it uses the deprecated MediaTypeOptions.

Fix: Use a contextual rationale, add camera capture, and migrate to mediaTypes arrays.

`MerchantImageField.tsx:41-63. VerificationCentreScreen.tsx:89-97.`

---

low frontend **Duplicated gate logic and an inconsistent dev bypass**

The per-screen gate ignores developerMerchantMode, and the access screen is duplicated.

Fix: Use one access hook and one access screen.

`MerchantTabs.tsx:39 vs 318-320, 43-83 vs 376-432.`

Lists, wheel & extras 3.5/10

This is the weakest area of the app. The Wheel ships in production from Discover's hero button and can never produce a result. The seed is a 0–1 float, so the winner index is fractional, the completion handler returns early, and the user is stuck on a disabled "SPINNING..." screen with no exit control. Portfolios has a sound Supabase schema and a good public share page, but the screens are rough: UUID-paste collaborators, stale or 0 counts, endless "Loading...", a render loop in the detail screens, and "private" notes that any viewer of a public list can read.

▶ **How it compares with other apps**

▶ **What it does well (7)**

▶ **Issues from the 18 Oct audit: 7 still present, 2 fixed**

▶ **Cross-check notes: 28 confirmed, 0 removed, 9 corrected, 6 added**

▼ **Findings (34)**

critical bug **Wheel never picks a winner: the seed is a 0–1 float**

triggerSpin sets seed = Math.random(). winnerIndex = ((seed % n)+n)%n stays fractional, so the pointer always lands in slice 0, activeEntries[0.43] is undefined, and the completion handler returns early. The user stays on the spin screen with status 'spinning'. This is the production solo

flow from Discover's hero button.

Fix: Pick winnerEntryId (integer index/id) in triggerSpin, store it, and derive the angle from that index. Unit-test n in {2,3,7}.

`src/store/useWheelStore.ts:273; src/app/screens/wheel/WheelSpinScreen.tsx:95-98, 117-118; DiscoverHomeScreen.tsx:2463-2464`

---

critical bug

No path to the result screen and no way out of the spin screen

WheelResult needs party.winnerEntryId, which only a never-broadcast 'party_resolved' event sets. Today the user is stuck on a disabled 'SPINNING...' button (canSpin requires !spinning); headerShown is false and there is no back control. Fixing only the seed sends every spin to the elimination branch: replace to Lobby, then 'Spin Wheel' replays the stale seed immediately and loops.

Fix: In solo mode, resolve on the client (set status 'resolved' and winnerEntryId, then navigate). Reset spinSeed/status on Spin again. Add a close control and a Maestro smoke test.

`WheelSpinScreen.tsx:121-133, 147-148, 290-322; useWheelStore.ts:284-293, 330-339; WheelStack.tsx:14`

---

high backend-data

'Private' portfolio notes are readable by any viewer of the list

The copy says 'Only for you and collaborators', but the portfolio_items SELECT policy exposes every column to anyone who can view the portfolio (public lists, approved followers on followers_only lists). authenticated has a table SELECT grant and the client selects '*'. The UI gate is cosmetic and also hides the notes from collaborators. Other users' notes are persisted to device storage.

Fix: Move private notes to an owner/collaborator-only table, or revoke column SELECT and serve them via a definer RPC. Select explicit columns.

`PortfolioItemPickerScreen.tsx:164-169; migration 20260527103000:78, 299-324; 20260527104500_checklist_portfolio_passport_grant_fix.sql:8; supabaseService.ts:6726-6735; PortfolioItemRow.tsx:84`

---

high backend-data

Checklist and portfolio stores survive sign-out

Both are zustand-persisted, including items, collaborators and notes. clearAccountScopedStores never calls their _reset. On a shared device the next user sees the previous user's lists via the cache fallback, and quick-save can fall back to stale checklists[0].

Fix: Call both _reset() in clearAccountScopedStores and key persisted state by user id.

`useChecklistStore.ts:224-230; usePortfolioStore.ts:202-214, 530-550; useSessionStore.ts:98-115`

---

high bug

Detail screens re-render in a loop until items load

items[id] ?? [] creates a new array each render. It is the label effect's dependency, and setLabels({}) creates a new object, which re-renders and runs the effect again. It loops on empty or offline lists. When items exist, every store change re-fetches all labels (N+1).

Fix: Use a stable EMPTY constant or useMemo, key the effect on a joined id string, and skip unchanged setLabels.

ChecklistDetailScreen.tsx:38, 53-78; PortfolioDetailScreen.tsx:54, 72-97

---

high bug

Load failures leave 'Loading...' up forever and cause unhandled rejections

loadChecklists and loadPortfolios rethrow with no cache. The screens don't catch, isLoaded stays false, and there is no retry or error state.

Fix: Add a loadError state, an error view with Retry, and pull-to-refresh.

useChecklistStore.ts:63-75; ChecklistsHomeScreen.tsx:24-28, 54-64; usePortfolioStore.ts:202-216; PortfoliosHomeScreen.tsx:31-33, 118-123

---

high bug

Several mutations fail silently

Checklist picker add (duplicate throw), markItemTried and deleteItem have no catch