WT Node Configuration Guide

1 Node1 Configuration

1. Set multi-user target as your default target. Then, reboot.
2. Configure your Host Name, IP Address, Gateway and DNS:
   - IP Address: `172.24.40.40/24`
   - Gateway: `172.24.40.1`
   - DNS: `172.24.40.1`
   - Hostname: `node1.tekup.com`
3. Configure repos AppStream and BaseOS:
   - AppStream link:
     `http://centos.anexia.at/centos-stream/9-stream/AppStream/x86_64/os/`
   - BaseOS Link:
     `https://centos.anexia.at/centos-stream/9-stream/BaseOS/x86_64/os/`
4. Find the lines that contain the string "wild" from the file `/usr/share/dict/words`. Save the result to `/root/result`.
5. Find files that belong to `user1`. Copy files to `/root/output`.
6. Compress:
   - `/usr/tmp` to `/root/compress1.tar.gz`
   - `/usr/include` to `/root/compress2.tar.bz2`
7. Configure the following job: `logger -p local3.info "wt redhat"`. This job runs every two minutes.
8. Configure `154.70.152.179` as your chrony server.
9. Create a user named `anna` on the two machines with uid 5003. Her home directory on the server is named `/node1/anna`. It will be mounted on `/node2/anna` with autofs when anna connects.
10. Host a web server on your machine which will be used to display the content of three pages `file1`, `file2` and `file3` using port 82.
11. Create the following users:
    - `Susan`, (shell=`/bin/sh`, uid=1500; secondary group: linux)
    - `antoine`, (non interactive shell)
    - `julien`, (base directory: `/dir`)

12. All files that will be created by `julien` should have permissions `rw- -r-- ---` and all directories should have permissions `-rwxr-x---`.

13. Create a collaborative directory `/common/share` with the following characteristics:

    - Owner: `root`
    - Group: `sysadms`
    - The directory should be readable, writable and accessible by root and group sysadms but not to any other user.
    - Files that will be created in `/common/share` should belong to sysadms group.

14. Create a user `dbuser1` and build the image named `pdfconvert` using the following:

    - Dockerfile:
      `https://raw.githubusercontent.com/sachinyadav3496/Text-ToPDF/master/Dockerfile`
    - Application:
      `https://raw.githubusercontent.com/sachinyadav3496/Text-ToPDF/master/pdf_converter.p`

15. Create a container using the image `pdfconvert`. The container is named `pdfconvertor`. Attach volumes `/data/input` and `/data/output` (in container) to `/action/incoming` and `/action/outcoming` (in your machine) respectively.

16. Create a service `container-pdfconvertor.service` from the container `pdfconvertor`.

2 Node2 Configuration

1. Define `alberate` as the root password.

2. Configure your Host Name, IP Address, Gateway and DNS:

    - IP Address: `172.24.40.41/24`
    - Gateway: `172.24.40.1`
    - DNS: `172.24.40.1`
    - Hostname: `node1.tekup.com`

3. Configure repos AppStream and BaseOS:

    - AppStream link:
      `http://centos.anexia.at/centos-stream/9-stream/AppStream/x86_64/os/`
    - BaseOS Link:
      `https://centos.anexia.at/centos-stream/9-stream/BaseOS/x86_64/os/`

4. Create a logical Volume and mount it permanently. Create the logical volume with the name “data” by using 81 PE’s from the volume group “storage”.

    - Consider each PE size of the volume group as “16 MB”.
    - Mount it on `/data` with file system xfs.

5. Extend data. The new size should be between 1300M and 1316M.

6. Add a swap partition with a size of 512MB and mount it permanently.

7. Set recommended profile as your tuned profile.