

HTML and CSS Fresher Interview Questions and Answers

Preparation guide

Source and accuracy note: This is a general HTML and CSS fresher-level preparation guide based on standard web-development concepts and commonly asked entry-level questions. It is not a Wipro internal document, leaked question paper, or verified list of current Wipro questions. Actual questions may vary by role, interviewer, and assessment.

HTML Questions

1. What is HTML?

HTML, or HyperText Markup Language, defines the structure and meaning of content on web pages.

2. What is an HTML element?

An element usually consists of an opening tag, content, and a closing tag. Some elements, such as `img` and `input`, are void elements and do not have closing tags.

```
<p>This is a paragraph.</p>
```

3. What is the difference between a tag and an attribute?

A tag identifies an element. An attribute provides additional information or configuration for that element.

```

```

4. What is HTML5?

HTML5 is the modern HTML standard that introduced semantic elements, native audio and video, improved forms, and browser APIs.

5. What are semantic elements?

Semantic elements communicate the role of content to browsers, developers, search engines, and assistive technology. Examples include `header`, `nav`, `main`, `section`, `article`, `aside`, and `footer`.

6. Difference between div and span?

div is a generic block-level container. span is a generic inline container. Neither conveys specific meaning by itself.

7. Difference between block and inline elements?

A block element normally starts on a new line and can occupy available width. An inline element normally flows within surrounding text. CSS can change their display behavior.

8. What is the purpose of DOCTYPE?

<!DOCTYPE html> tells the browser to use standards mode when interpreting the document.

9. What are head and body?

head contains metadata, the title, linked resources, and scripts. body contains the page content displayed in the browser.

10. What is the purpose of the title element?

title sets the document title shown in the browser tab and used by bookmarks and search systems.

11. What is the meta viewport tag?

It helps pages scale correctly on mobile devices.

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

12. Why is the alt attribute important?

alt provides alternative text for images when they cannot be seen and supports screen-reader users. Decorative images can use an empty alt attribute.

13. Difference between id and class?

An id should identify one unique element in a document. A class can be shared by multiple elements and is commonly used for styling or scripting.

14. What is a hyperlink?

```
<a href="https://example.com">Visit site</a>
```

The anchor element creates links to pages, sections, files, or other resources.

15. Difference between ordered and unordered lists?

ol represents an ordered list, usually numbered. ul represents an unordered list, usually shown with bullets. Both use li for items.

```
<ul>
  <li>HTML</li>
  <li>CSS</li>
</ul>
```

16. How are tables structured?

table contains the table, tr contains a row, th contains a header cell, and td contains a data cell. caption can provide a table title.

17. What is a form?

A form collects user input and can submit it to a server.

```
<form action="/submit" method="post">
  <label for="email">Email</label>
  <input id="email" name="email" type="email" required>
  <button type="submit">Send</button>
</form>
```

18. Why should label be associated with input?

It improves accessibility and allows users to focus the input by selecting its label. Use matching for and id values.

19. What are common input types?

Common types include text, email, password, number, date, checkbox, radio, file, submit, and button. The type can provide validation and an appropriate mobile keyboard.

20. Difference between GET and POST in forms?

GET places form data in the URL and is commonly used for retrieval. POST sends data in the request body and is commonly used when submitting or changing data. HTTPS is needed for protecting sensitive data.

21. What are required, placeholder, and value?

required requests validation before submission. placeholder shows a temporary hint and is not a label. value specifies the current or initial value.

22. What is an iframe?

iframe embeds another browsing context inside a page. It should be used carefully and configured with suitable security and permissions.

23. How do audio and video work in HTML5?

```
<video controls>
```

```
  <source src="movie.mp4" type="video/mp4">
```

```
</video>
```

The controls attribute provides browser controls. Providing suitable formats and fallback text improves compatibility.

24. What is accessibility in HTML?

Accessibility means making content usable by people with different abilities. Use semantic elements, labels, alt text, keyboard-friendly controls, logical heading order, and sufficient contrast.

25. What is the difference between localStorage, sessionStorage, and cookies?

localStorage persists in the browser until cleared. sessionStorage lasts for a browser tab session. Cookies are small values sent with matching HTTP requests and can have expiration and security attributes.

CSS Questions

26. What is CSS?

CSS, or Cascading Style Sheets, controls the presentation and layout of HTML content.

27. What are the ways to add CSS?

Inline CSS uses a style attribute, internal CSS uses a style element, and external CSS uses a linked stylesheet. External stylesheets are generally easier to maintain.

```
<link rel="stylesheet" href="styles.css">
```

28. What is a CSS selector?

A selector identifies the elements to which declarations apply.

```
p { color: navy; }
```

```
.notice { padding: 1rem; }
```

```
#main-title { font-size: 2rem; }
```

29. Difference between class and id selectors?

Class selectors use a dot and are reusable. ID selectors use a hash and have higher specificity, so they should be reserved for unique elements.

30. What is the CSS box model?

Each element is laid out as content, padding, border, and margin from inside to outside.

```
box-sizing: border-box;
```

31. Difference between margin and padding?

Padding is space inside the border around content. Margin is space outside the border between elements.

32. What does box-sizing do?

content-box makes declared width apply to content only. border-box includes padding and border within the declared width and height.

33. What is specificity?

Specificity determines which competing selector wins. In general, inline styles are stronger than IDs, IDs are stronger than classes and attributes, and those are stronger than element selectors. Source order also matters when specificity ties.

34. What is the cascade?

The cascade combines origin, importance, specificity, and source order to determine the final style.

35. Difference between display none and visibility hidden?

display: none removes the element from layout. visibility: hidden hides it while usually preserving its layout space.

36. What are common position values?

static is the normal position. relative offsets an element from its normal position. absolute positions it relative to a positioned ancestor. fixed attaches it to the viewport. sticky switches between normal and fixed-like behavior within a scroll area.

37. What is z-index?

z-index controls stacking order for elements in relevant stacking contexts. A higher value does not always win if elements belong to different stacking contexts.

38. What is Flexbox?

Flexbox is a one-dimensional layout system for arranging items along a row or column.

```
.toolbar {  
  display: flex;  
  justify-content: space-between;  
  align-items: center;  
  gap: 1rem;  
}
```

39. What is CSS Grid?

Grid is a two-dimensional layout system for rows and columns.

```
.layout {  
  display: grid;  
  grid-template-columns: 1fr 2fr;  
  gap: 1rem;  
}
```

40. Difference between Flexbox and Grid?

Flexbox is primarily for one-dimensional alignment. Grid is designed for two-dimensional layouts. They are often used together.

41. What are media queries?

Media queries apply styles conditionally based on viewport or device characteristics, enabling responsive design.

```
@media (max-width: 700px) {  
  .layout { grid-template-columns: 1fr; }  
}
```

42. What are responsive units?

%, em, rem, vw, and vh can adapt to context or viewport. px is a fixed CSS pixel unit. rem is relative to the root font size, while em is relative to the current context.

43. Difference between pseudo-class and pseudo-element?

A pseudo-class describes a state, such as `:hover` or `:focus`. A pseudo-element targets a conceptual part, such as `::before` or `::first-letter`.

```
a:hover { color: red; }  
.card::before { content: ''; }
```

44. What are CSS variables?

Custom properties store reusable values and can be changed at runtime.

```
:root { --brand-color: #225b87; }  
.button { background: var(--brand-color); }
```

45. Difference between transition and animation?

A transition animates a change between states, commonly caused by hover or focus. An animation uses keyframes and can run independently or repeat.

46. What is overflow?

overflow controls content that exceeds an element's box. Common values are visible, hidden, scroll, and auto.

47. What is the difference between opacity and rgba transparency?

opacity affects the entire element, including its children. An rgba or modern color with alpha changes only that color's transparency.

48. What is inheritance in CSS?

Some properties, such as color and font-family, inherit from a parent by default. Layout properties such as margin generally do not.

49. What does !important do?

It increases a declaration's priority. It should be used sparingly because it makes styles harder to override and maintain.

50. How can a CSS page be made accessible?

Use readable contrast, visible keyboard focus, scalable text, logical layouts, reduced-motion support where appropriate, and do not communicate important information through color alone.

Small Practice Task

Create a responsive profile card using semantic HTML, a labeled form control, an image with meaningful alt text, CSS variables, Flexbox or Grid, and a media query. Test it with keyboard navigation and at both narrow and wide viewport sizes.

Final Preparation Checklist

Revise semantic HTML, forms, accessibility, selectors, the box model, specificity, positioning, Flexbox, Grid, responsive design, pseudo-classes, variables, and basic browser debugging with developer tools.