Your Brand POS

Technical requirements

What a shop needs to run the system. Everything runs locally on the shop's network; the internet is needed only for card payments, updates and off-site backups.

Optional Planned

SERVER (IN THE SHOP)

Computer	Mini PC, Raspberry Pi 4/5 (4 GB) or any Linux/macOS computer, left on during trading
Software	Python 3.9 or newer, OpenSSL. No other packages or database server
Storage	1 GB free is ample; all data in one SQLite file
Network	Wired or Wi-Fi on the shop network, with a fixed IP address (DHCP reservation)
Power	UPS recommended Optional

REGISTER AND PHONES

Register	Laptop, PC or tablet with a current Chrome, Edge, Safari or Firefox; 10" screen or larger
Phones	iPhone or Android with a current browser and rear camera, for scanning, receiving and stocktake
NFC writing	Android phone with NFC, Chrome browser Planned
Install	Nothing to install; pages can be added to the home screen

SCANNING HARDWARE

Bench scanner	2D (QR-capable) presentation scanner, USB or Bluetooth, keyboard (HID) mode with Enter suffix
Handheld	Cordless 2D scanner, keyboard mode, for large items Optional
Overhead camera	1080p autofocus USB webcam on an arm, even LED lighting Optional
NFC pad	13.56 MHz ISO 14443A reader, NTAG21x, USB keyboard mode (UID output) Planned
NFC writer	PC/SC USB reader/writer (ACR122U class) as an alternative to Android Planned

AUSTRALIAN COMPLIANCE

GST	10%, prices GST-inclusive; GST-free items supported
Receipts	Tax invoice format once the shop's ABN is entered
Reporting	GST collected per period to support BAS
Time zones	All Australian states and territories

NETWORK AND SECURITY

Protocol	HTTPS only, TLS 1.2+, on port 443 (or 8443)
Certificate	Self-signed for trial; trusted certificate via own domain and reverse proxy (e.g. Caddy) for production
Wi-Fi	Covering counter and stock areas; phones join the same network
Logins	Owner and cashier roles, PIN login, 12-hour sessions, lockout after repeated wrong PINs
Remote access	Secure tunnel (e.g. Tailscale) Optional

PAYMENTS

Cash	Built in, with Australian 5c rounding and change calculation
Card	Shop's own Square account and reader, used alongside the register
Card data	Never entered into or stored by the POS
Integrated reader	Stripe Terminal or Square Terminal Planned

PRINTING AND LABELS

Label printer	Desktop direct thermal, 2"–4" (e.g. TSC DA/TE series), taking third-party rolls; OS driver installed
Tag sizes	50×25, 50×30, 40×30, 57×32, 62×29 mm presets, any custom size, or A4 21-up sheets
Tag content	QR code: **SKU | VENDOR | PRICE**, or a link to the stocktake screen
NFC labels	Direct thermal paper labels with NTAG213 inlay, matching printer core size Planned
Receipts	58, 62 or 80 mm thermal printer, or on screen Optional

DATA AND BACKUP

Storage	Single SQLite database file on the shop's computer
Backup	One-click download from Settings; automatic off-site backup Planned
Audit	Refunds, price changes, stock adjustments and settings changes logged with user and time
Capacity	Sized for a single shop: hundreds of products, multiple registers and phones

Minimum to start trading: one computer on the shop network, one register device with a browser, a QR-capable scanner or phone camera, a direct thermal label printer, and a card reader from the shop's own provider.

Items marked Planned are on the roadmap and not yet available.