

GenTex_OS - LEFT manual

Version: 2026-09-18. TS uses one shared gated texture engine. The pads blend pitch and add fold, delay and filter gestures. P1-P3 influence texture pitch, P4 feedback, P5 texture and P6 the delay/resonance relationship. MIDI Note On opens the shared gate and changes timbre and energy; Note Off closes the gate.

GenTexOS is a nonlinear texture generator for diceFriend. It is built for feedback, folding, filtering, micro-delay, smearing, bit reduction, and self-moving stereo textures.

GenTexOS has two main performance modes: **RS mode** and **Touch mode**. RS mode is a self-running texture loop. Touch mode turns the three pads into struck resonant texture voices.

Main Operation

- **SHIFT** changes the function layer of the six knobs.
- **Short DICE** randomizes both control layers at once.
- **Hold DICE** switches between RS mode and Touch mode.
- **Touch pads T1, T2, T3** behave differently in RS mode and Touch mode.

CV and MIDI

- **CV1** works as a continuous modulation source for fold and chaos.
- **CV2** works as a trigger/clock detector when pulses are present.
- CV2 triggers create macro movements inside the texture: feedback spike, fold sweep, delay scatter, and filter dip.
- GenTexOS can send MIDI notes from CV2-triggered texture events.
- MIDI aftertouch follows the current audio energy.
- MIDI pitch bend follows the CV modulation.
- Incoming MIDI is passed through.

LEDs

- The SHIFT and non-SHIFT LEDs show the active control layer.
- In RS mode, the lower LEDs follow CV activity and audio movement.
- In Touch mode, the lower LEDs show active pads for a few seconds after touch or knob movement.
- A DICE action briefly flashes the lower LEDs.

RS Mode

RS mode is the main GenTex texture engine. It uses a self-referencing feedback path with wavefolding, filtering, micro-delay, delay smear, and output saturation.

The sound can move from quiet electrical movement to rough folded noise, resonant delay chatter, unstable stereo feedback, and bit-crushed texture beds.

RS Controls

Normal layer:

- **Knob 1:** Feedback amount.
- **Knob 2:** Fold amount.
- **Knob 3:** Delay time.
- **Knob 4:** Chaos injection.
- **Knob 5:** Filter cutoff.
- **Knob 6:** Filter resonance.

SHIFT layer:

- **Knob 1:** Pre-gain.

- **Knob 2:** Fold asymmetry.
- **Knob 3:** Delay smear.
- **Knob 4:** Bit depth.
- **Knob 5:** Filter mode.
- **Knob 6:** Output saturation.

RS Touch Pad Behavior

In RS mode, the pads directly alter the texture loop.

- **T1:** Freeze. Holds the current delay/feedback texture.
- **T2:** Smear. Adds animated delay smear and stereo blur.
- **T3:** Spike. Pushes the feedback into a stronger burst.

Releasing a pad cleans up the loop so the texture can move again without becoming stuck.

Touch Mode

Touch mode uses a separate three-voice texture instrument. The pads trigger individual voices while the same six knobs define their pitch, decay, resonance, brightness, and nonlinear character.

Normal layer:

- **Knob 1:** T1 pitch.
- **Knob 2:** T2 pitch.
- **Knob 3:** T3 pitch.
- **Knob 4:** T1 decay.
- **Knob 5:** T2 decay.
- **Knob 6:** T3 decay.

SHIFT layer:

- **Knob 1:** Resonance / Q.
- **Knob 2:** Stereo spread.
- **Knob 3:** Brightness.
- **Knob 4:** Character.
- **Knob 5:** Fine tune.
- **Knob 6:** Fold drive.

Touch mode is more playable and more percussive than RS mode. It is useful for struck textures, resonant clicks, folding pings, and noisy pitched gestures.

DICE Randomization

Short DICE randomizes the full texture setup. The randomizer is designed to make audible changes, so DICE should not feel like a tiny or hidden variation.

Randomization affects feedback, fold, delay, chaos, filter, pre-gain, smear, bit depth, filter mode, and saturation.

Performance Notes

- GenTexOS is intentionally sensitive to feedback. Small changes can produce large shifts.
- Use T1 Freeze to capture a texture, T2 Smear to blur it, and T3 Spike to push it into a burst.
- CV2 triggers are useful for rhythmic texture events.
- Touch mode is the safer place for pitched, pad-based performance.
- RS mode is best for evolving texture, noise beds, and unstable stereo feedback.