

**| bars make cores**

**|\_** spec alas (map term tome)  
 produces a door (a core with sample)  
**|%** (unit term) (map term tome)  
 produces a core (battery and payload)  
**|@** (unit term) (map term tome)  
 produces a wet core (battery and payload)  
**|.** hoon  
 produces a trap (a core with one arm)  
**|:** [hoon hoon]  
 produces a gate with a custom sample  
**|-** hoon  
 produces a trap (a core with one arm) and evaluates it  
**|^** hoon (map term tome)  
 produces a core whose battery includes a \$ arm and computes the latter  
**|~** [spec value]  
 produces an iron gate  
**|\*** [spec value]  
 produces a wet gate (a one-armed core with sample)  
**|=** [spec value]  
 produces a dry gate (a one-armed core with sample)  
**|?** hoon  
 produces a lead trap  
**|\$** (lest term) spec  
 produces a mold

---

**\$ bucs form molds**

**\$@** [spec spec]  
 structure that normalizes a union tagged by head atom  
**\$:** (list spec)  
 forms a cell type (tuple) [a=foo b=bar c=baz]  
**\$\_** hoon  
 structure that normalizes to an example \_foo  
**\$%** (list spec)  
 structure that recognizes a union tagged by head atom  
**\$\*** hoon  
 bunt (take default value of mold) \*foo  
**\$^** hoon  
 structure that normalizes a union tagged by head depth (cell)  
**\$~** [hoon spec]  
 defines a custom type default value  
**\$-** [spec spec]  
 structure that normalizes to an example gate  
**\$=** [skin spec]  
 structure that wraps a face around another structure foo=bar  
**\$?** (list spec)  
 forms a type from a union of other types ?(\$foo \$bar \$baz)  
**\$>** [spec spec]  
 structure from filter (requiring)  
**\$<** [spec spec]  
 structure from filter (excluding)  
**\$\$** [spec (map term spec)]  
 structure from recursion

<b>\$ </b>	[spec hoon] structure with verification	
<b>\$.</b>	[spec (map term spec)] structure as read-write core	
<b>\$+</b>	[stud spec] standard structure	
<b>\$;</b>	hoon manual structure	
<b>\$/</b>	[spec (map term spec)] structure as write-only core	
<b>\$`</b>	[spec (map term spec)] structure as read-only core	
<b>\$&amp;</b>	[spec hoon] repaired structure	
<b>\$!</b>	[spec (map term spec)] structure as opaque core	
<hr/>		
<b>%</b>	<b>cens put the fun in function</b>	
<b>%_</b>	[wing (list (pair wing hoon))] resolves a wing with changes, preserving type	
<b>%.</b>	[hoon hoon] calls a gate, inverted	
<b>%^</b>	[hoon hoon hoon hoon] calls a gate with triple sample	
<b>%+</b>	[hoon hoon hoon] calls a gate with a cell sample	
<b>%-</b>	[hoon hoon] calls a gate	(fun arg)
<b>:%</b>	[hoon (list hoon)] calls a gate with many arguments	
<b>%~</b>	[wing hoon hoon] evaluates an arm in a door	~(arm core arg)
<b>:%*</b>	[wing hoon (list (pair winghoon))] evaluates an expression, then resolves a wing with changes	
<b>%=</b>	[wing (list (pair wing hoon))] resolves a wing with changes	foo(x 1, y 2, z 3)
<hr/>		
<b>:</b>	<b>cols make cells</b>	
<b>:_</b>	[hoon hoon] constructs a cell, inverted	
<b>:^</b>	[hoon hoon hoon hoon] constructs a cell, 4-tuple	[a b c d]
<b>:+</b>	[hoon hoon hoon] constructs a cell, 3-tuple	[a b c]
<b>:-</b>	[hoon hoon] constructs a cell, 2-tuple	[a b], a^b (a^b^c)
<b>:~</b>	(list hoon) constructs a null-terminated list	~[a b c]
<b>:*</b>	(list hoon) constructs an n-tuple	[a b c d e ...]
<b>::</b>	marks a comment (digraph, not rune)	
<hr/>		
<b>.</b>	<b>dotsnock</b>	
<b>+.atom</b>	increments an atom using Nock 4	+(42)

<b>.*</b>	[hoon hoon]	evaluates using Nock 2	
<b>.=</b>	[hoon hoon]	tests for equality using Nock 5	=(a b)
<b>.?</b>	hoon	tests for cell or atom using Nock 3	
<b>.^</b>	[spec hoon]	loads from namespace using Nock 12	
<hr/>			
<b>^</b>	<b>kets cast</b>		
<b>^ </b>	hoon	converts a gold core to an iron core (invariant)	
<b>^.</b>	[hoon hoon]	typecasts on value	
<b>^-</b>	[spec hoon]	typecasts by explicit type label	`foo`bar
<b>^+</b>	[hoon hoon]	typecasts by inferred type (a fence)	
<b>^&amp;</b>	hoon	converts a core to a zinc core (covariant)	
<b>^~</b>	hoon	folds constant at compile time	
<b>^=</b>	[skin hoon]	binds name to a value	foo=bar
<b>^?</b>	hoon	converts a core to a lead core (bivariant)	
<b>^*</b>	spec	produces example type value	
<b>^:</b>	spec	produces a 'factory' gate for a type (switch from regular parsing to spec/type parsing)	,foo
<hr/>			
<b>~</b>	<b>sigs hint</b>		
<b>~ </b>	[hoon hoon]	prints in stack trace if failure	
<b>~\$</b>	[term hoon]	profiler hit counter	
<b>~-</b>	[hoon hoon]	prints in stack trace, user-formatted	
<b>~%</b>	[chum hoon tyre hoon]	registers jet	
<b>~/</b>	[chum hoon]	registers jet with registered context	
<b>~&lt;</b>	[\$@(term [term hoon]) hoon]	raw hint, applied to product ("backward")	
<b>~&gt;</b>	[\$@(term [term hoon]) hoon]	raw hint, applied to computation ("forward")	
<b>~+</b>	[@ hoon]	caches a computation	
<b>~&amp;</b>	[@ud hoon hoon]	prints (used for debugging)	
<b>~?</b>	[@ud hoon hoon hoon]	prints conditionally (used for debugging)	
<b>~=</b>	[hoon hoon]	detects duplicate	

---

```

~!  [hoon hoon]
    prints type if compilation failure

```

---

```

;  mics make
;:  [hoon (list hoon)]
    calls a binary function as an $n$-ary function           :($fun a b c d)
;<  [spec hoon hoon hoon]
    glues a pipeline together (monadic bind)
;~  [hoon (list hoon)]
    glues a pipeline together with a product-sample adapter (monadic bind)
;;  [spec hoon]
    normalizes with a mold, asserting fixpoint
;+
    (Sail) makes a single XML node
;*
    (Sail) makes a list of XML nodes from Hoon expression
;=  marl:hoot
    (Sail) makes a list of XML nodes
;/  hoon
    (Sail) yields tape as XML element

```

---

```

=  tises alter
=|  [spec hoon]
    combines default type value with the subject
=.  [wing hoon hoon]
    changes one leg in the subject
=?  [wing hoon hoon hoon]
    changes one leg in the subject conditionally
=^  [skin wing hoon hoon]
    pins the head of a pair; changes a leg with the tail
=:  [(list (pair wing hoon)) hoon]
    changes multiple legs in the subject
=/  [skin hoon hoon]
    combines a named noun with the subject
=;  [skin hoon hoon]
    combines a named noun with the subject, inverted
=<  [hoon hoon]
    composes two expressions, inverted                       foo:bar
=>  [hoon hoon]
    composes two expressions
=-  [hoon hoon]
    combines a new noun with the subject
=*  [(pair term (unit spec)) hoon hoon]
    defines an alias
=,  [hoon hoon]
    exposes namespace (defines a bridge)
=+  [hoon hoon]
    combines a new noun with the subject
=~  (list hoon)
    composes many expressions

```

---

```

-/= terminators terminate
--  terminates core expression (digraph, not rune)
==  terminates running series of Hoon expressions (digraph, not rune)

```

**? wuts test**

<b>? </b>	(list hoon) logical OR (loobean)	(foo bar baz)
<b>?:</b>	[hoon hoon hoon] branches on a boolean test	
<b>?.</b>	[hoon hoon hoon] branches on a boolean test, inverted	
<b>?&lt;</b>	[hoon hoon] negative assertion	
<b>?&gt;</b>	[hoon hoon] positive assertion	
<b>?-</b>	[wing (list (pair spec hoon))] switches against a union, no default	
<b>?^</b>	[wing hoon hoon] branches on whether a wing of the subject is a cell	
<b>?=</b>	[spec wing] tests pattern match	
<b>?#</b>	[skin wing] tests pattern match	
<b>?+</b>	[wing hoon (list (pair spec hoon))] switches against a union, with default	
<b>?&amp;</b>	(list hoon) logical AND (loobean)	& (foo bar baz)
<b>?@</b>	[wing hoon hoon] branches on whether a wing of the subject is an atom	
<b>?~</b>	[wing hoon hoon] branches on whether a wing of the subject is null	
<b>?!</b>	hoon logical NOT (loobean)	!foo

**! zaps run wild**

<b>!:</b>	turns on stack trace
<b>!.</b>	turns off stack trace
<b>!,</b>	[*hoon hoon] emits AST of expression (use as !, *hoon expression)
<b>!;</b>	[hoon hoon] emits the type for an expression using the type of type
<b>!&gt;</b>	hoon wraps a noun in its type
<b>!=</b>	hoon makes the Nock formula for a Hoon expression
<b>!?</b>	[\$@(@ { @ @}) hoon] restricts Hoon version
<b>!!</b>	~ crashes
<b>!&lt;</b>	hoon lift dynamic value into static context

**/ fases file (+ford arm of %cLay)**

<b>/?</b>	foo pin a version number
-----------	-----------------------------

```

/-  foo, *bar, baz=qux
    imports a file from the sur directory (* pinned with no face, = with specified face)
/+  foo, *bar, baz=qux
    imports a file from the lib directory (* pinned with no face, = with specified face)
/=  clay-raw /sys/vane/clay
    imports results of user-specified path wrapped in face
/*  myfile %hoon /gen/myfile/hoon
    imports the contents of a file in the desk converted to a mark (build-time static data)

+  luses arm cores
+|
    labels a chapter (produces no arm)
+$  [term spec]
    produces a structure arm (type definition)
++  [term hoon]
    produces a (normal) arm
+*  [term term spec]
    produces a type constructor arm
+-  [term spec]
    produces a

```



### syntax

```

+1:[%a [%b %c]] [%a [%b %c]]
+2:[%a [%b %c]] %a
+3:[%a [%b %c]] [%b %c]
+4:[%a [%b %c]] %ride failed
+6:[%a [%b %c]] %b
+7:[%a [%b %c]] %c

```

$[%a [%b %c]]$



&n nth element

|n tail after nth element

<[1 2 3]> renders list as a tape  
>[1 2 3]< renders list as a tank

. current subject

+ +:.

- -:.

+> +>:.

a.b.c limb search path

%y ~ 0 (nil)  
& yes/true  
%n | no/false  
%a constant  
\$ empty term (@tas)

'urbit' cord, atom @t  
"urbit" tape or list of characters  
=wire shadow type name (in defn)  
/path path name

```

.:[%a [%b %c]] [%a [%b %c]]
-:[%a [%b %c]] %a
+:[%a [%b %c]] [%b %c]
-<:[%a [%b %c]] %ride failed
+<:[%a [%b %c]] %b
+>:[%a [%b %c]] %c

```

### lark syntax equivalents

+1	+5 ->
+2 -	+6 +<
+3 +	+7 +>
+4 -<	+8 -<-

^face face in outer core (^face)

..arm core in which ++arm is defined

, ,. strip the face

-:!> type spear, use as -:!>(.3.14)

eny entropy  
now current time  
our ship

`a [~ a]  
~[a b c] [a b c ~]  
[a b c]~ [[a b c] ~]  
a/b [%a b]

### elementary molds

\* noun  
@ atom (atom)  
^ cell  
? loobean

~ null

**@p notation**

@	Empty aura	
@c	Unicode codepoint	~~~45fed.
@d	Date	
@da	Date, absolute	~2020.12.25..7.15.0..1ef5
@dr	Date, relative	~d71.h19.m26.s24..9d55
@f	Loobean (for compiler, not castable)	&
@i	Internet address	
@if	IPv4 address	.195.198.143.90
@is	IPv6 address	.0.0.0.0.0.1c.c3c6.8f5a
@n	Nil (for compiler, not castable)	~
@p	Phonemic base	~laszod-dozser-fosrum-fanbyr
@q	Phonemic base, unscrambled (used with Urbit HD wallet)	~laszod-dozser-dalteb-hilsyn
@r	IEEE-754 floating-point number	
@rh	Floating-point number, half-precision, 16-bit	.~~3.14
@rs	Floating-point number, single-precision, 32-bit	.3.141592653589793
@rd	Floating-point number, double-precision, 64-bit	.~3.141592653589793
@rq	Floating-point number, quadruple-precision, 128-bit	.~~~3.141592653589793
@s	Integer, signed (sign bit low)	
@sb	Signed binary	--0b10.0000
@sd	Signed decimal	--1.000
@sv	Signed base-32	--0v201.4gvm1.245kc
@sw	Signed base-64	--0w2.04AfS.G8xqc
@sx	Signed hexadecimal	--0x2004.90fd
@t	UTF-8 text (cord)	'urbit'
@ta	ASCII text (knot)	~.urbit
@tas	ASCII text symbol (term)	%urbit
@u	Integer, unsigned	
@ub	Unsigned binary	0b10.1011
@uc	Bitcoin address	0c1A1zP1eP5QGefi2DMPTfTL5SLmv7DivfNa
@ud	Unsigned decimal	8.675.309
@uv	Unsigned base-32	0v88nvd
@uw	Unsigned base-64	0wx5~J
@ux	Unsigned hexadecimal	0x84.5fed

Capital letters at the end of auras indicate the bitwidth in binary powers of two, starting from A.

- @ubD signed single-byte (8-bit) decimal
- @tD 8-bit ASCII text
- @rhE half-precision (16-bit) floating-point number
- @uxG unsigned 64-bit hexadecimal
- @uvJ unsigned 512-bit integer (frequently used for entropy)

Auras are non-coercive, but conversions may have to go via the empty aura: ^-(@ud ^-(@ 'foo')).

**Nock 4K**

A noun is an atom or a cell. An atom is a natural number. A cell is an ordered pair of nouns.

Reduce by the first matching pattern; variables match any noun.

nock(a)	*a	
[a b c]	[a [b c]]	
[a b]	0	
a	1	
[a b]	[a b]	
a	1 + a	
[a a]	0	
[a b]	1	
[1 a]	a	
[2 a b]	a	
[3 a b]	b	
[(a + a) b]	/[2 [a b]]	
[(a + a + 1) b]	/[3 [a b]]	
a	/a	
[1 a b]	a	
[(a + a) b c]	#[a [b [a b] c] c]	
[(a + a + 1) b c]	#[a [a b] c] c]	
a	#a	
[a [b c] d]	[*[a b c] *[a d]]	
[a 0 b]	/[b a]	slot operator (noun at tree address)
[a 1 b]	b	constant
[a 2 b c]	*[a b] *[a c]	evaluate
[a 3 b]	?*[a b]	test for atom
[a 4 b]	+*[a b]	increment
[a 5 b c]	=*[a b] *[a c]	distribution
[a 6 b c d]	*[a *[c d] 0 *[2 3] 0 *[a 4 4 b]]]	if-then-else
[a 7 b c]	*[a b] c]	compose
[a 8 b c]	*[a b] a] c]	extend
[a 9 b c]	*[a c] 2 [0 1] 0 b]	invoke
[a 10 [b c] d]	#[b *[a c] *[a d]]	edit noun
[a 11 [b c] d]	*[a c] *[a d]] 0 3]	hint
[a 11 b c]	*[a c]	
a	a	interpret