HTML Tags

03 March 2026 20:14

HTML tags are like keywords which defines that how web browser will format and display the content. With the help of tags, a web browser can distinguish between an HTML content and a simple content. HTML tags contain three main parts: opening tag, content and closing tag. But some HTML tags are unclosed tags.

When a web browser reads an HTML document, browser reads it from top to bottom and left to right. HTML tags are used to create HTML documents and render their properties. Each HTML tags have different properties.

- All HTML tags must enclosed within <> these brackets.
- Every tag in HTML performs different tasks.
- If you have an open tag <tag>, then you must use a close tag </tag> (except some tags)

Syntax:

<tag> content </tag>

HTML tags are always written in lowercase letters.

For example:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>SigmaPi Academy</title>
</head>
<body>
    <header>
        <h1>Welcome Students</h1>
    </header>
    <section>
        <p>
            Learning HTML5 is the first step to web development.
        </p>
    </section>
    <footer>
        <p>&copy SigmaPi Academy</p>
    </footer>
</body>
</html>
```

Unclosed HTML Tags

Some HTML tags are not closed. For example BR and HR.

 tag: BR stands for break line. It breaks the line of the code.
<hr> tag: HR stands for horizontal rule. This tag is used to put a line across the web page.

HTML Meta Tags

DOCTYPE, title, link, meta, and style

HTML Text Tags
<p>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, , , <abbr>, <acronym>, <address>, <bdo>, <blockquote>, <cite>, <q>, <code>, <ins>, <del>, <kbd>, <pre>, <samp>, <var> and

HTML Link Tags
<a> and <base>

HTML Image and Object tags
<img>, <area>, <map>, <param> and <object>

HTML List Tags
<ul>, <ol>, <li>, <dl>, <dt> and <dd>

HTML table tags
<table>, <tr>, <td>, <tbody>, <tfoot>, <col>, <colgroup> and <caption>

HTML Form tags
<form>, <input>, <textarea>, <select>, <option>, <optgroup>, <button>, <label>, <fieldset> and <legend>

HTML Scripting Tags
<script> and <noscript>

HTML Attributes

HTML attributes are keywords found in an opening element tag to give more details about that particular element. CSS is needed to manage how HTML elements behaves, look and function. Every attribute takes the form name="value" and should always put inside the start tag. Nearly every element can use attributes to let us style, link, add tool tips, or include images and videos.

Every attribute increases the accuracy of both the interpretation and presentation of the element by the browser. While the names and values and attributes can differ greatly based on case, it is recommended by W3C that you use a small letters. Several attributes can be put on one tag by inserting a space between them.

Syntax:
<element attribute_name="value">content</element>

For example:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>SigmaPi Academy</title>
</head>
<body>
    <header>
        <h1>Welcome Students</h1>
    </header>
```

Key : value pair, and each "key:value" pair is separated

```
        <header>
            <h1>Welcome Students</h1>
        </header>
        <section>
            <p style="height:50px; color:blue">
                Learning HTML5 is the first step to web development.
            </p>
            <p style="color: red;">It will change the color of content</p>
        </section>
        <footer>
            <p>&copy SigmaPi Academy</p>
        </footer>
    </body>
    </html>
```

attribute

Key : value pair, and each 'key:value' pair is separated by ';' semicolon and space. and they are written inside double quote.

The href Attribute

The HRF attribute is the main attribute of <a > anchor tag. This attribute gives the link address which is specified in that link. The HRF attribute provides the hyperlink and if you leave the link address blank the page will not be redirected.

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Useful links</title>
</head>
<body>
    <h1>Useful pages which I visit regularly</h1>
    <a href="https://sigmapi-academy.github.io/coding-robotics/">Sigmapi-academy</a> <br>
    <a href="https://www.google.com/">Google</a><br>
    <a href="https://chatgpt.com/">Chat GPT</a> <br>
    <a href="https://www.amazon.com/">Amazon</a><br>
    <a href="">This is a link</a>
    <img src="../images/holi1.jpg" height="400" width="600" alt="Image of Holi">
</body>
</html>
```

src, width, and height Attributes

The SRC attribute is one of the important and required attributes of the <img> element. It is the source for the image which is required to display on the browser. This attribute can. Contain images in the same directory or another directory. The image name or source should be correct else the browser will not display the image.
The size and alternate information of an image are given by width, height and alt.

The alt attribute

You use the alt attribute to give an image alternative text if it does not load correctly. A website needs to be easy to navigate for everyone and to be effective with SEO(Search Engine Optimizer).

Homework: