Page :
Date : / /

6.9.25 ST. XAVIER'S → IST SEM → BLOCK

SECTION-A

1) i) d → long

ii) a → code generated by Java compiler

iii) a → 9.0

iv) b → 8

v) c → Math.floor(-6.7)

vi) d → double

vii) a → integer

viii) c → 125.0

ix) b → 0.0

ix) c → break

xi) d → object

xii) a → Encapsulation

xiii) a → equal

xiv) a → expression

xv) b → implicit conversion

xvi) c → "x"

xvii) c → escape sequences

xviii) a → ●=

xix) c → Identifier

xx) a → Object

Page :
Date : / /

2] i) a- 10 12 12 13

b- 16

c- 1 4 7 10

22

ii) dis = (price >= 100) ? 10.0/100 * price : 15.0/100 * price ;

iii) z = (x * x * x) + (y * y * y) - Math.sqrt (x * x + y * y);

iv)

v) False

PTO

Page :
Date : / /

SECTION-B

3]
```
import java.util.*;
public class Geometry
{
 public static void main (String args[])
 {
  Scanner sc = new Scanner (System.in);
  System.out.print ("\If Press 1 for P of sqn, 2 for P of
                rect, and 3 for circumference of circle");
  System.out.print ("\n Enter your choice 1,2,3: ");
  int ch = sc.nextInt ();
 switch (ch)
{
  case 1 : {
        System.out.print ("\n Enter side:");
        int s = sc.nextInt ();
        System.out.print ("\n Perimeter = " + (4*s));
        break; }
case 2 : {
        System.out.print ("\n Enter length : ");
        int l = sc.nextInt ();
        System.out.print ("\n Enter breadth :");
        int b = sc.nextInt ();
        System.out.print ("\n Perimeter = "+(2*(l+b)));
        }
        break; }
```

Page :
Date : / /

```
case 3 : {
        System. out. print ("\n Enter radius: ");
        int r = sc. nextInt ();
        System. out. print ("\nCircumference =" (2*3*r));
        break; }
default :
        System. out. print ("\nWRONG CHOICE");
        break; }
    }
}
```

P.T.O

Page :
Date : / /

4] import java.util.*;
class Post_office
{
public static void main (String args[]),
{
Scanner sc = new Scanner (System.in);
System.out.print ("If Enter weight:");
~~double w = sc.nextDouble();~~
~~if (w>0.0 && w<=10.0)~~
double w = sc.nextDouble();
double r=0;
if (w>0.0 && w<=10.0)
{
r = 10 + 0.05;
System.out.print ("In Rate =" +r);
}
else if (w>10.0 && w<=30.0)
{
r = 30 + 0.05;
System.out.print ("In Rate = " +r);
}
else if (w>30.0 && w<=60.0)
{
r = 70+0.05;
System.out.print ("In Rate = " +r);}

```
else if ( w > 60.0)
    {
     r = 150 + 0.05 ;
     System.out.print( "\n Rate = " + r) ;
    }
else
   System.out.print ( "\n ERROR") ;
  }
}
```

P.T.O

Page :
Date : / /

6]

```
import java.util.Scanner;
public class Pronic
{
  public static void main (String args[])
  {
   Scanner sc=new Scanner;
   System.out.print("If Enter a no.:");
   int n= sc.nextInt();
   int product=1, t
  for( int i=0; n=t; i<=t; i++)
    {
      product= i*(i+1);
      if (product==t)
       System.out.println("PRONIC");
      else
        Continue;
      }
       if (product!=t)
        System.out.print("NOT PRONIC");
    }
}
```