

DATA UPDATION AND DELETION

31 August 2026 08:11

Updating and deletion of data are also part of SQL data manipulation language (DML).

Data Update

We may need to make changes in the value (S) of one or more columns of existing records in a table. For example, we may require some changes in address, phone number or spelling of a name Etc. The UPDATE statement is used to make such modification in existing data.

Syntax:

```
UPDATE table_name
SET attribute_name = value1, attribute2 = value2,...
WHERE condition;
```

For example, Update the bonus attribute of employee relation, the employees who are working in deptid D001 and D002.

```
mysql> UPDATE employee SET bonus = salary * 0.1
-> WHERE deptid IN('D001', 'D002');
Query OK, 8 rows affected (0.381 sec)
Rows matched: 8 Changed: 8 Warnings: 0

mysql> select * from employee;
+-----+-----+-----+-----+-----+
| EMPNO | ENAME  | SALARY | BONUS | DEPTID |
+-----+-----+-----+-----+-----+
| 1001 | Ravi   | 10000  | 1000  | D001   |
| 1002 | Mukesh | 12000  | 1200  | D001   |
| 1003 | Jack   | 15000  | 1500  | D001   |
| 1004 | Mark   | 16000  | 1600  | D002   |
| 1005 | Allen  | 20000  | NULL  | D003   |
| 1006 | Wiess  | 18000  | 1800  | D002   |
| 1007 | Robert | 21000  | NULL  | D005   |
| 1008 | Kritka | 18000  | NULL  | D005   |
| 1009 | Joseph | 14000  | 1400  | D001   |
| 1010 | Tanya  | 15000  | 1500  | D002   |
| 1011 | Rajesh | 10000  | 1000  | D001   |
+-----+-----+-----+-----+-----+
11 rows in set (0.027 sec)
```

Data Deletion

Delete statement is used to delete./ remove one or more records from a table.

Syntax:

```
DELETE FROM table_name
WHERE condition;
```

Suppose the employee 'Allen' has left the company. So his record must be deleted.

```
mysql> DELETE from employee
-> WHERE ename = 'Allen';
Query OK, 1 row affected (0.164 sec)
```

