
Strings in Java

29 October 2026 18:45

String name = "Priyaan";



first character is at '0' index

last character (name.length()-1)

number of characters in String.

charAt(index) → 0 >= index < string.length()

char data is written in single quotes.

char grade = 'A';

The char data type can compare by using relational operator ==, >=, <=, >, <

if (grade >= 'A' && grade <= 'F')

But this type of comparison is not possible in String objects. We have to use String class methods.

```
public class CharDemo
{
    public static void main (String args[]) {
        System.out.print("\f");
        String aloo = "This is his fish";
        int i;
        for (i = 0; i < aloo.length(); i++) {
            char C = aloo.charAt(i);
            System.out.print("\n" + C);
        }
    }
}
```

```java
package MyStrings;
import java.util.Scanner;

/**
 * Write a description of class AlphabetCheck here.
 *
 * @author (your name)
 * @version (a version number or a date)
 */
public class AlphabetCheck
{
    public static void main (String args[]) {
        Scanner sc = new Scanner(System.in);
        System.out.print("\fEnter any alphabet: ");
        char C = sc.next().charAt(0);
        if(C >= 'A' && C <= 'Z') {
            System.out.print("\nYou have entered an uppercase alphabet.");
        }
        else if(C >= 'a' && C <= 'z') {
            System.out.print("\nYou have entered a lowercase alphabet.");
        }
        else {
            System.err.print("\nWRONG INPUT IDIOT!!!");
        }
    }
}
```

String class methods used to compare string objects

compareTo()
compareToIgnoreCase()

} it compares the string, such that, first string is greater than the second string or not. It returns int value.

equals()
equalsIgroneCase()

} ← it is used for equality comparison, it returns true/false boolean value.

startsWith()
endsWith()

} Returns boolen value, if first string object starts with / ends with second string, then it return true otherwise false

Amit Preyash
Anit Priyaan

'e' - 'i' = (-ve) value → first string < second string
'i' - 'e' = +ve value → first string > secondstring.
'e' - 'e' = 0 → first string = secondstring.

firstString.methodName(secondString)

String s1 = "Preyash";
String s2 = "P";

s1.startsWith(s2); // true

s1 ↑ first string
s2 ↑ second string.