Variables and Datatypes in JS

05 April 2026 18:05

Variables in JavaScript

A variable is like a container that stores data.

```
> let name = "Deeptanarayan";
undefined
> name
'Deeptanarayan'
> let age = 19;
undefined
> age
19
```

- "name" stores a text value.
- "age" stores a number

Javascript provides three ways to declare variables:

A. var
B. let
C. const

A. var: is the old way of declaring variables.

```
> var city="Kolkata";
undefined
> console.log(city)
Kolkata
undefined
```

```
> if (true){
| var y = 100;
| }
undefined
> console.log(y)
100
undefined
> y
100
```

If we declare the variable by using var keyword. Then its access is available outside the block.

B. let: Is the modern way to declare variables.

```
> let fname = 'Harry';
undefined
> console.log
[Function: log]
> console.log(fname);
Harry
undefined
> let x = 100;
undefined
```

```
> if(true){
| let m = 100;
| }
undefined
> console.log(m)
Uncaught ReferenceError: m is not defined
```

```
> if(true){
| let m = 100;
| console.log(m);
| }
100
undefined
```

let

Vs

```
> if (true){
| var y = 100;
| }
undefined
> console.log(y)
100
undefined
> y
100
```

var

```
100
undefined
```

let

```
100
```

var

C. **const:** Is used when the value should not change.

```
> const country = 'India';
undefined
> country = 'USA';
Uncaught TypeError: Assignment to constant variable.
> const pi = 3.14;
undefined
> console.log(pi);
3.14
undefined
```

Data Types in JavaScript

Javascript data types are divided into two types:

1. Primitive type
2. Non-Primitive(Reference) Data Types

Primitive Data Types

Primitive types store a single value.

There are 7 Primitive types in Javascript:

1. String
2. Number
3. Boolean
4. Undefined
5. Null
6. BigInt
7. Symbol

1. **String**

```
> let studentName = "Deeptanarayan"
undefined
> let message = 'Hello world!'
undefined
> let greeting = `Welcome`
undefined
> console.log(greeting)
Welcome
undefined
```

Strings can use single quotes, double quotes or backticks.