

Computational Optimization & Applications

Siju Swamy

2025-11-17

Table of contents

Course Vision & Context	5
The Optimization Revolution in Computational Sciences	5
Course Syllabus (48 Hours / 12 Weeks)	5
Course Overview	5
Course Objectives	5
Course Outcomes	6
Assessment Plan (70 Marks Internal)	7
12-Week Delivery Plan (4 Hours/Week)	7
Thematic Project: Campus City Supply Chain	9
Detailed Mark Distribution	10
Learning Outcomes Mapping	10
Grading Rubrics	11
Success Strategy	11
Weekly Preparation Guide	12
1 Introduction to Computational Optimization and Applications	13
1.1 Why Optimization Matters Now More Than Ever	13
1.2 Programme Objectives & Learning Outcomes	13
1.2.1 Core Educational Mission	13
1.2.2 The “Smart City Logistics” Experiential Thread	14
1.3 Course Roadmap & Syllabus Integration	15
1.3.1 Module Progression: From Foundations to Frontiers	15
1.3.2 Assessment Strategy: Theory Meets Practice	15
1.4 Optimization in the AI/ML Ecosystem	16
1.4.1 The Central Role in Machine Learning	16
1.4.2 Emerging Trends & Future Directions	16
1.5 Technical Ecosystem & Tools	16
1.5.1 Why Python for Optimization?	16
1.5.2 Core Toolchain	17
1.6 Getting Started: Your Learning Journey	17
1.6.1 Prerequisites & Preparation	17
1.6.2 How to Maximize Your Learning	17
1.6.3 Course Structure and Expectations	18
1.7 Welcome to the Journey	18

2	Module 1: Basics of Optimization and Linear Programming	19
2.1	Module Overview	19
2.1.1	Learning Objectives	19
2.1.2	Smart City Context: Warehouse Location Challenge	19
2.2	Foundations of Optimization	19
2.2.1	What is Optimization?	19
2.2.2	Optimization Problem Classification	20
2.2.3	Real-World Applications in CSE	20
2.3	Basic Python for Optimization	20
2.3.1	Essential Python Libraries Setup	20
2.3.2	Python Fundamentals for Optimization	21
2.4	Linear Programming Fundamentals	21
2.4.1	Mathematical Definition of Linear Programming	21
2.4.2	Standard Forms of Linear Programming	22
2.4.3	Key Concepts in Linear Programming	22
2.4.4	Smart City Case: Warehouse Location Formulation	23
2.4.5	Graphical Method for Two-Variable Problems	24
2.4.6	Simplex Method Theory	25
2.5	Types of Linear Programming Solutions	26
2.5.1	Unique Optimal Solution	26
2.5.2	Multiple Optimal Solutions (Alternative Optima)	27
2.5.3	Unbounded Solution	27
2.5.4	Infeasible Problem	27
2.6	Duality in Linear Programming	28
2.6.1	The “Mirror Image” of Optimization	28
2.6.2	Why do Computer Scientists care?	28
2.6.3	The Mathematical Transformation	28
2.6.4	Key Theorems	28
2.6.5	Sensitivity Analysis	29
2.6.6	Special Cases in Linear Programming	29
2.7	Linear Programming Problems — Graphical Method	30
2.8	Practical Implementation with Python	32
2.8.1	Mathematical Formulation	32
2.8.2	Complete Linear Programming Model	33
2.9	Linear Programming Problems Collection	34
2.9.1	Problem 1	34
2.9.2	Problem 2: Diet Problem	36
2.10	Micro-Project 1: Campus City Emergency Supply Distribution	38
2.10.1	Problem Statement	38
2.10.2	Facilities Data (From facilities.csv)	39
2.10.3	Warehouse Data (From warehouses.csv)	39
2.10.4	Transportation Costs (From transportation_costs.csv)	39
2.10.5	Financial Constraints	40

2.10.6	Physical & Business Constraints	40
2.10.7	Learning Objectives	40
3	Module 2: Non-linear Programming with Python	41
3.1	Module Overview	41
3.1.1	Learning Objectives	41
3.1.2	Module Structure	41
3.1.3	Real-World Context	41
3.2	Introduction to Nonlinear Optimization	41
3.2.1	Theoretical Foundation	42
3.2.2	Sample Problem	44
3.2.3	Review Questions	45
3.3	Unconstrained Optimization Methods	45
3.3.1	Algorithms for Unconstrained NLP	47
3.3.2	Theoretical Foundation	49
3.3.3	Sample Problem 1	50
3.3.4	Sample Problem 2	50
3.3.5	Sample problem 3	50
3.3.6	Review Questions	51
3.4	Constrained Optimization & KKT Conditions	51
3.4.1	Theoretical Foundation	51
3.4.2	Sample Problem	52
3.4.3	Sample Problem	52
3.4.4	Review Questions	52
3.5	Python Implementation of Nonlinear Solvers	53
3.5.1	Theoretical Foundation	53
3.5.2	Sample Problem	54
3.5.3	Solution of constrained NLPP	54
3.5.4	Support Vector Machine (SVM) Theory: A Constrained Optimization Perspective	62
3.5.5	Principal Component Analysis (PCA)	66
3.5.6	Ridge Regression (L2 Regularization)	67
3.5.7	Maximum Entropy Models (MaxEnt)	68

Course Vision & Context

The Optimization Revolution in Computational Sciences

In an era dominated by Artificial Intelligence, Machine Learning, and Data Science, *optimization forms the fundamental backbone* that powers intelligent decision-making systems. From recommending your next movie to orchestrating global supply chains, from training deep neural networks to scheduling autonomous vehicles—optimization algorithms are the invisible engines driving technological progress.

This course positions you at the intersection of *mathematical theory* and *computational practice*, equipping you with both the conceptual understanding and hands-on skills to design, implement, and deploy optimization solutions for real-world challenges.

Course Syllabus (48 Hours / 12 Weeks)

Course Overview

Course Code: 20MAT382

Course Name: Computational Optimization and Applications

Duration: 12 Weeks (4 hours/week)

Credits: 4

Total Marks: 150 (Internal: 70 + External: 80)

Intensive Learning Approach

Accelerated project-based curriculum focusing on core optimization concepts with immediate practical application through integrated micro-projects.

Course Objectives

S.No	COURSE OBJECTIVES
1	To gain a comprehensive understanding of optimization concepts and their real-world relevance, emphasizing Python as a practical tool for optimization.
2	To develop proficiency in Python for optimization, including formulating and solving linear programming problems, implementing nonlinear optimization and analysing optimization solutions.
3	To acquire skills in project planning and optimization techniques using Python.
4	To master optimization techniques in the context of machine learning, including Gradient Descent, Stochastic Gradient Descent, and various optimization algorithms, all implemented in Python.
5	To apply optimization knowledge and Python skills to solve combinatorial and graph-based problems, while also considering the ethical aspects of optimization in engineering, logistics, and decision-making.

Course Outcomes

At the end of the course students will be able to:

CO Code	COURSE OUTCOMES	REVISED BLOOM'S TAXONOMY LEVEL
CO1	Demonstrate a thorough understanding of optimization concepts, problem types, and their real-world applications.	3
CO2	Formulate and solve linear programming problems using Python.	3
CO3	Implement nonlinear optimization algorithms, and analyse optimization solutions using Python.	2
CO4	Develop practical project planning skills and proficiency in applying heuristic algorithms to real-world scenarios.	2
CO5	Demonstrate mastery of optimization in Machine Learning, with the ability to apply Gradient Descent, Stochastic Gradient Descent.	3

Core Competencies

- Formulate real-world problems as mathematical optimization models

- Implement optimization algorithms in Python using industry tools
- Analyze and validate optimization solutions
- Develop end-to-end optimization systems for practical applications

Assessment Plan (70 Marks Internal)

Continuous Evaluation (70 Marks)

A. Theory Components (20 Marks)

- **Internal Exam 1:** 10 marks (Week 6)
- **Internal Exam 2:** 10 marks (Week 12)

B. Practical Components (50 Marks)

- **Assignments/Micro Projects:** 15 marks (3 projects $\times$ 5 marks each)
- **Lab Exams:** 10 marks (2 exams $\times$ 5 marks each)
- **Day-to-Day Lab Work:** 15 marks
- **Attendance:** 10 marks

External Examination (80 Marks)

- **End Semester Theory Exam:** 80 marks

12-Week Delivery Plan (4 Hours/Week)

Phase 1: Foundation & Linear Methods (Weeks 1-4)

Week 1: Optimization Fundamentals & Python Setup (4 hours)

- **Theory (2h):** Optimization concepts, problem classification, LP formulation
- **Lab (2h):** Python environment setup, PuLP introduction
- **Lab Work:** Basic LP implementation (1 mark)
- **Micro-Project 1 Launch:** Campus facility location problem

Week 2: Linear Programming & Solution Methods (4 hours)

- **Theory (2h):** Graphical method, Simplex algorithm
- **Lab (2h):** PuLP implementation, constraint handling
- **Lab Work:** Complex constraint implementation (1 mark)
- **Attendance:** Week 1-2 (2 marks)

Week 3: Advanced LP & Real Applications (4 hours)

- **Theory (1h):** Sensitivity analysis, duality
- **Lab (3h):** Transportation problems, case studies
- **Lab Work:** Transportation problem solution (1 mark)
- **Micro-Project 1 Due:** Submission (5 marks)

Week 4: Nonlinear Optimization Foundations (4 hours)

- **Theory (2h):** Unconstrained optimization, Golden Section
- **Lab (2h):** SciPy optimization, function minimization
- **Lab Work:** Nonlinear solver implementation (1 mark)
- **Attendance:** Week 3-4 (2 marks)

Phase 2: Constrained & Combinatorial Methods (Weeks 5-8)

Week 5: Constrained Optimization (4 hours)

- **Theory (2h):** KKT conditions, constraint handling
- **Lab (2h):** Constrained NLP implementation
- **Lab Work:** KKT condition implementation (1 mark)
- **Micro-Project 2 Launch:** Nonlinear cost optimization
- **Lab Exam 1:** Basic LP/NLP implementation (5 marks)

Week 6: Project Planning & Heuristics (4 hours)

- **Theory (1h):** CPM/PERT fundamentals
- **Lab (3h):** Project scheduling, greedy algorithms
- **Internal Exam 1:** Theory assessment (10 marks)
- **Lab Work:** Project scheduling implementation (1 mark)

Week 7: Graph Algorithms I (4 hours)

- **Theory (1h):** Graph theory, shortest path concepts
- **Lab (3h):** NetworkX implementation, Dijkstra's algorithm
- **Lab Work:** Shortest path implementation (1 mark)
- **Micro-Project 2 Due:** Submission (5 marks)
- **Attendance:** Week 5-7 (2 marks)

Week 8: Graph Algorithms II (4 hours)

- **Theory (1h):** MST, network flows, TSP overview
- **Lab (3h):** Advanced graph algorithms
- **Lab Work:** MST implementation (1 mark)
- **Micro-Project 3 Launch:** Routing optimization

Phase 3: Advanced Applications & Integration (Weeks 9-12)

Week 9: Machine Learning Optimization I (4 hours)

- **Theory (2h):** Gradient Descent, SGD, optimization in ML
- **Lab (2h):** Basic GD implementation
- **Lab Work:** Gradient descent implementation (1 mark)
- **Attendance:** Week 8-9 (2 marks)

Week 10: Machine Learning Optimization II (4 hours)

- **Theory (1h):** Advanced optimizers, neural networks
- **Lab (3h):** TensorFlow/PyTorch optimization
- **Lab Work:** Advanced optimizer implementation (1 mark)
- **Lab Exam 2:** Graph and ML optimization (5 marks)

Week 11: Integrated Applications (4 hours)

- **Workshop (4h):** Comprehensive system implementation
- **Lab Work:** Integrated system development (2 marks)
- **Micro-Project 3 Due:** Submission (5 marks)

Week 12: Review & Final Assessment (4 hours)

- **Internal Exam 2:** Theory assessment (10 marks)
- **Course Review:** Comprehensive concepts revision
- **Lab Work:** Final implementation polish (1 mark)
- **Attendance:** Week 10-12 (2 marks)

Thematic Project: Campus City Supply Chain

Micro-Projects (15 Marks Total)

Micro-Project 1: Basic LP Implementation (5 marks)

- **Timeline:** Week 1-3
- **Scope:** 6 facilities, 3 warehouses, linear costs
- **Assessment:** Model correctness (2), Code quality (2), Documentation (1)

Micro-Project 2: Nonlinear Optimization (5 marks)

- **Timeline:** Week 4-7
- **Scope:** Enhanced cost models, KKT conditions
- **Assessment:** Algorithm implementation (2), Analysis (2), Validation (1)

Micro-Project 3: Graph & Network Optimization (5 marks)

- **Timeline:** Week 8-11
- **Scope:** Routing, shortest paths, resource allocation
- **Assessment:** System design (2), Performance (2), Documentation (1)

Detailed Mark Distribution

Day-to-Day Lab Work (15 Marks)

- **Weekly Implementation Tasks:** 12 marks (1 mark $\times$ 12 weeks)
- **Integrated System Development:** 3 marks (Week 11)

Attendance (10 Marks)

- **Weekly Attendance:** 2 marks per 3-week block
- **Full Attendance Bonus:** 2 marks for 100% attendance

Lab Exams (10 Marks)

- **Lab Exam 1** (Week 5): Basic LP/NLP implementation (5 marks)
- **Lab Exam 2** (Week 10): Graph and ML optimization (5 marks)

Internal Exams (20 Marks)

- **Internal Exam 1** (Week 6): Modules 1-2 theory (10 marks)
- **Internal Exam 2** (Week 11): Modules 3-4 theory (10 marks)

Learning Outcomes Mapping

Theory Outcomes (Internal Exams + External)

- Formulate optimization problems mathematically
- Understand algorithm properties and convergence
- Analyze problem structures and solution methods

Practical Outcomes (Lab Work + Projects)

- Implement optimization algorithms in Python
- Develop end-to-end optimization systems
- Validate and analyze optimization results
- Create professional documentation and visualizations

Grading Rubrics

Micro-Projects (5 marks each)

- **Excellent (5):** Flawless implementation with advanced features
- **Very Good (4):** Correct implementation with good documentation
- **Good (3):** Basic functionality with minor issues
- **Satisfactory (2):** Meets minimum requirements
- **Poor (1):** Significant functionality missing

Lab Work (Weekly 1 mark)

- **Complete (1):** Task fully implemented and demonstrated
- **Partial (0.5):** Basic implementation with issues
- **Incomplete (0):** Task not attempted or completely non-functional

Lab Exams (5 marks each)

- **Algorithm Implementation:** 2 marks
- **Problem Solving:** 2 marks
- **Code Quality:** 1 mark

Success Strategy

Maximizing Internal Marks

- **Consistent Attendance:** 10 marks easily achievable
- **Regular Lab Work:** 15 marks through weekly completion
- **Quality Projects:** 15 marks with careful implementation
- **Lab Exam Preparation:** 10 marks with practice
- **Internal Exam Focus:** 20 marks through concept mastery

External Exam Preparation (80 Marks)

- Comprehensive theory coverage from all modules
- Problem-solving practice with various optimization types
- Mathematical formulation skills
- Algorithm analysis and comparison

Weekly Preparation Guide

Before Each Week

- Review weekly objectives and deliverables
- Prepare development environment
- Read theoretical concepts in advance

During Each Week

- Attend all sessions (critical for attendance marks)
- Complete lab work during sessions
- Start micro-projects early
- Seek clarification immediately

After Each Week

- Submit all lab work promptly
- Review concepts for internal exams
- Prepare for upcoming assessments
- Maintain code repository

This assessment-focused syllabus ensures students can maximize their 70 internal marks through consistent performance while preparing comprehensively for the 80-mark external examination. The structured approach balances theoretical understanding with practical implementation skills.

1 Introduction to Computational Optimization and Applications

Welcome to Computational Optimization & Applications
Where Mathematics Meets Computational Intelligence
Bridging Theory and Practice in the AI Revolution

1.1 Why Optimization Matters Now More Than Ever

The exponential growth in data complexity and computational requirements has transformed optimization from a theoretical discipline to an essential toolkit for every computer scientist and data professional. Consider these real-world contexts:

- **AI Systems:** Training neural networks is essentially an optimization process (Gradient Descent)
- **Operations Research:** Logistics, scheduling, and resource allocation drive billion-dollar efficiencies
- **Data Science:** Model selection, hyperparameter tuning, and feature engineering are optimization problems
- **Autonomous Systems:** Path planning, control systems, and decision-making rely on optimization algorithms
- **Quantum Computing:** Many quantum algorithms are designed to solve optimization problems more efficiently

1.2 Programme Objectives & Learning Outcomes

1.2.1 Core Educational Mission

This minor programme is designed to bridge the critical gap between theoretical optimization mathematics and practical computational implementation. Upon successful completion, you will be able to:

Domain	Learning Outcomes
Theoretical Foundation	• Formulate real-world problems as mathematical optimization models • Understand optimality conditions and convergence properties • Analyze problem structures to select appropriate solution methods
Computational Skills	• Implement classical and modern optimization algorithms in Python • Utilize industry-standard optimization libraries and frameworks • Develop end-to-end optimization pipelines for practical applications
AI/ML Integration	• Understand optimization's role in training machine learning models • Implement gradient-based methods for neural network optimization • Apply optimization to hyperparameter tuning and model selection
Problem-Solving	• Design optimization solutions for complex, multi-objective problems • Evaluate solution quality and algorithm performance • Communicate optimization insights to technical and non-technical stakeholders

1.2.2 The “Smart City Logistics” Experiential Thread

Throughout this course, we'll employ a *continuous practical thread*: optimizing logistics and operations for a smart city ecosystem. This narrative provides:

- **Real-world context** for theoretical concepts
- **Progressive complexity** as we advance through modules
- **Portfolio-building** implementation experience
- **Industry-relevant** problem-solving skills

Smart City Optimization Journey:

- **Module 1:** Warehouse Location (Linear Programming)
- **Module 2:** Fuel Cost Optimization (Nonlinear Programming)
- **Module 3:** Delivery Routing (Graph Algorithms)
- **Module 4:** Dynamic Scheduling (Heuristic Methods)
- **Module 5:** Demand Prediction (ML Integration)

1.3 Course Roadmap & Syllabus Integration

1.3.1 Module Progression: From Foundations to Frontiers

Our journey through computational optimization is strategically sequenced to build from fundamental principles to advanced applications:

1.3.1.1 Foundation Phase: Mathematical Underpinnings

- **Module I:** Linear Programming & Formulation Skills
- **Module II:** Nonlinear Optimization & Constraint Handling

1.3.1.2 Advanced Phase: Algorithmic Thinking

- **Module III:** Project Planning & Heuristic Methods
- **Module IV:** Combinatorial & Graph Optimization

1.3.1.3 Integration Phase: AI/ML Applications

- **Module V:** Gradient Methods & Machine Learning Optimization

1.3.2 Assessment Strategy: Theory Meets Practice

To ensure comprehensive understanding and skill development, assessment integrates both theoretical knowledge and practical implementation:

- **Series Examinations:** Test conceptual understanding and problem formulation
- **Practical Assignments/ Micro Project:** Evaluate implementation skills and computational thinking
- **Final Project:** Assess integrated problem-solving and solution design
- **Continuous Evaluation:** Monitor progress through micro-projects and code reviews

1.4 Optimization in the AI/ML Ecosystem

1.4.1 The Central Role in Machine Learning

Optimization isn't just adjacent to machine learning—it **is machine learning**. The entire process of training machine learning models revolves around optimization principles:

- **Loss Minimization:** Finding model parameters that minimize prediction error
- **Convergence Analysis:** Understanding when and how algorithms reach optimal solutions
- **Regularization:** Balancing model complexity with performance through constrained optimization
- **Hyperparameter Tuning:** Optimizing the optimization process itself

1.4.2 Emerging Trends & Future Directions

The field of optimization is rapidly evolving, driven by advances in:

- **Large-Scale Optimization:** Methods for billion-parameter models in deep learning
- **Automated Optimization:** AutoML and neural architecture search
- **Quantum Optimization:** Quantum annealing and hybrid quantum-classical algorithms
- **Federated Optimization:** Privacy-preserving distributed learning
- **Multi-Objective Optimization:** Pareto optimization for conflicting objectives
- **Explainable Optimization:** Interpretable and transparent optimization processes

1.5 Technical Ecosystem & Tools

1.5.1 Why Python for Optimization?

Python has emerged as the **lingua franca** for computational optimization due to:

- **Rich Ecosystem:** Comprehensive libraries for every optimization paradigm
- **AI/ML Integration:** Seamless connection with machine learning frameworks
- **Performance:** C/Fortran-backed numerical computing with Python simplicity
- **Community:** Vibrant ecosystem with continuous algorithm development
- **Industry Adoption:** Widely used in both academia and industry

1.5.2 Core Toolchain

Throughout this course, we'll work with industry-standard tools:

Our Computational Optimization Stack:

Category	Tools
Numerical Computing	NumPy, SciPy
Linear Programming	PuLP, CVXPY
Machine Learning	Scikit-learn, TensorFlow, PyTorch
Graph Algorithms	NetworkX
Visualization	Matplotlib, Plotly, Seaborn
Development	Jupyter, VSCode, Git

1.6 Getting Started: Your Learning Journey

1.6.1 Prerequisites & Preparation

To succeed in this course, you should have:

- **Programming Fundamentals:** Basic Python proficiency
- **Mathematical Background:** Linear algebra and calculus foundations
- **Computational Mindset:** Willingness to experiment and debug
- **Problem-Solving Attitude:** Persistence through challenging concepts
- **Curiosity and Creativity:** Interest in exploring multiple solution approaches

1.6.2 How to Maximize Your Learning

1. **Engage Actively:** Don't just read—implement every concept in code
2. **Think Critically:** Question why certain methods work better for specific problems
3. **Experiment Freely:** Modify parameters, break code, and learn from failures
4. **Connect Concepts:** Relate theoretical principles to practical implementations
5. **Build Portfolio:** Document your work for future career opportunities
6. **Collaborate Effectively:** Learn from peers through code reviews and discussions
7. **Stay Updated:** Follow recent developments in optimization research

1.6.3 Course Structure and Expectations

This course is designed as a **blended learning experience** combining:

- **Theoretical Foundations:** Mathematical principles and algorithm concepts
- **Practical Implementation:** Hands-on coding exercises and projects
- **Real-World Applications:** Industry-relevant case studies and problems
- **Assessment and Feedback:** Continuous evaluation and improvement

1.7 Welcome to the Journey

You are beginning a journey into one of the most fundamental and powerful domains of computer science and artificial intelligence. The skills you develop here will serve as a foundation for advanced work in machine learning, operations research, data science, and algorithmic design.

As we progress through the modules, remember that each concept builds toward a comprehensive understanding of how to make computers not just compute, but **optimize**—transforming them from calculators into intelligent decision-makers.

The journey through computational optimization is challenging but immensely rewarding. You'll gain not just technical skills, but a new way of thinking about problem-solving that will serve you throughout your career in technology.

“Optimization is the science of better. In a world of limited resources and unlimited wants, optimization provides the mathematical foundation for making the best possible decisions.”

2 Module 1: Basics of Optimization and Linear Programming

2.1 Module Overview

2.1.1 Learning Objectives

- Understand fundamental optimization concepts and problem classification
- Formulate real-world problems as Linear Programming models
- Solve LP problems using graphical and computational methods
- Implement LP solutions in Python for practical applications
- Apply optimization thinking to facility location problems

2.1.2 Smart City Context: Warehouse Location Challenge

In our Smart City Logistics project, we face a critical business decision: *where to locate new distribution warehouses* to minimize transportation costs while serving all city facilities efficiently. This module provides the mathematical foundation to solve this strategic problem.

2.2 Foundations of Optimization

2.2.1 What is Optimization?

Optimization is the science of finding the *best possible solution* from all feasible alternatives under given constraints. In computational terms, it involves:

- **Decision Variables:** Quantities we can control (e.g., warehouse locations, shipment quantities)
- **Objective Function:** What we want to maximize or minimize (e.g., total transportation cost)
- **Constraints:** Limitations and requirements (e.g., budget, capacity, demand)

2.2.2 Optimization Problem Classification

Problem Type	Characteristics	Smart City Example
Linear Programming	Linear objective and constraints	Warehouse location with fixed costs
Nonlinear Programming	Nonlinear relationships	Fuel costs that increase with distance
Constrained Optimization	With limitations	Budget constraints on construction
Unconstrained Optimization	No limitations	Theoretical ideal locations
Discrete Optimization	Integer decisions	Yes/no decisions for locations
Continuous Optimization	Real-valued decisions	Precise coordinates for facilities

2.2.3 Real-World Applications in CSE

- **Resource Allocation:** CPU time, memory allocation in operating systems
- **Network Optimization:** Internet routing, data flow optimization
- **Machine Learning:** Model training via loss function minimization
- **Database Systems:** Query optimization and indexing
- **Computer Graphics:** Rendering optimization and path tracing

2.3 Basic Python for Optimization

2.3.1 Essential Python Libraries Setup

```
# Core optimization stack installation
# pip install numpy scipy matplotlib pulp pandas jupyter
```

💡 Key Python Libraries Required for Computational Part

- **NumPy:** Numerical computing and array operations
- **SciPy:** Scientific computing and optimization algorithms
- **Matplotlib:** Data visualization and result plotting

- PuLP: Linear programming interface
- Pandas: Data manipulation and analysis

2.3.2 Python Fundamentals for Optimization

```
# Essential operations we'll use frequently
import numpy as np
import matplotlib.pyplot as plt

# Array operations for constraint matrices
coefficients = np.array([[2, 1], [1, 3], [4, 2]])

# Function definitions for objectives
def transportation_cost(warehouses, facilities):
    return np.sum(warehouses * facilities)

# Data handling for problem parameters
demand_data = {'Hospital': 50, 'School': 30, 'Mall': 80}
```

2.4 Linear Programming Fundamentals

2.4.1 Mathematical Definition of Linear Programming

A Linear Programming (LP) problem can be formally defined as:

Objective Function:

$$\text{Optimize } Z = c_1x_1 + c_2x_2 + \cdots + c_nx_n$$

Subject to Constraints:

$$\begin{aligned} a_{11}x_1 + a_{12}x_2 + \cdots + a_{1n}x_n &\leq b_1 \\ a_{21}x_1 + a_{22}x_2 + \cdots + a_{2n}x_n &\leq b_2 \\ &\vdots \\ a_{m1}x_1 + a_{m2}x_2 + \cdots + a_{mn}x_n &\leq b_m \end{aligned}$$

Non-negativity Conditions:

$$x_1, x_2, \dots, x_n \geq 0$$

Where:

- Z is the objective function to be optimized (maximized or minimized)
- $x_1, x_2, \dots, x_n$ are the decision variables
- $c_1, c_2, \dots, c_n$ are the coefficients of the objective function
- a_{ij} are the technological coefficients
- $b_1, b_2, \dots, b_m$ are the right-hand side constants

2.4.2 Standard Forms of Linear Programming

2.4.2.1 Canonical Form (Maximization)

$$\begin{aligned} \text{Maximize } Z &= \mathbf{c}^T \mathbf{x} \\ \text{Subject to } \mathbf{Ax} &\leq \mathbf{b} \\ \mathbf{x} &\geq \mathbf{0} \end{aligned}$$

2.4.2.2 Standard Form (Maximization)

$$\begin{aligned} \text{Maximize } Z &= \mathbf{c}^T \mathbf{x} \\ \text{Subject to } \mathbf{Ax} &= \mathbf{b} \\ \mathbf{x} &\geq \mathbf{0} \end{aligned}$$

2.4.3 Key Concepts in Linear Programming

2.4.3.1 Feasible Region

The set of all points that satisfy all constraints simultaneously:

$$F = \{\mathbf{x} \in \mathbb{R}^n : \mathbf{Ax} \leq \mathbf{b}, \mathbf{x} \geq \mathbf{0}\}$$

2.4.3.2 Optimal Solution

A point $\mathbf{x}^*$ in the feasible region that gives the best value of the objective function.

2.4.3.3 Corner Point (Extreme Point)

A point in the feasible region that cannot be expressed as a convex combination of two other distinct points in the region.

2.4.4 Smart City Case: Warehouse Location Formulation

2.4.4.1 Problem Statement

We need to choose locations for 2 warehouses from 4 potential sites to serve 3 major facilities while minimizing total costs.

2.4.4.2 Decision Variables

Let: - x_{ij} : Amount shipped from warehouse i to facility j - y_i : Binary variable (1 if warehouse i is built, 0 otherwise)

Where: - $i = 1, 2, 3, 4$ (warehouse sites) - $j = 1, 2, 3$ (facilities: Hospital, Mall, School)

2.4.4.3 Objective Function

Minimize total cost:

$$\text{Minimize } Z = \sum_{i=1}^4 \sum_{j=1}^3 c_{ij}x_{ij} + \sum_{i=1}^4 f_i y_i$$

Where: - c_{ij} : Transportation cost per unit from warehouse i to facility j - f_i : Fixed construction cost for warehouse i

2.4.4.4 Constraints

Demand Constraints (Each facility's demand must be met):

$$\sum_{i=1}^4 x_{ij} = d_j \quad \text{for } j = 1, 2, 3$$

Where d_j is the demand of facility j .

Capacity Constraints (Warehouse capacity cannot be exceeded):

$$\sum_{j=1}^3 x_{ij} \leq C_i y_i \quad \text{for } i = 1, 2, 3, 4$$

Where C_i is the capacity of warehouse i .

Budget Constraint:

$$\sum_{i=1}^4 f_i y_i \leq B$$

Where B is the total budget available.

Warehouse Selection Constraint (Select exactly 2 warehouses):

$$\sum_{i=1}^4 y_i = 2$$

Non-negativity and Binary Requirements:

$$x_{ij} \geq 0 \quad \text{for all } i, j$$

$$y_i \in \{0, 1\} \quad \text{for all } i$$

2.4.5 Graphical Method for Two-Variable Problems

2.4.5.1 Step-by-Step Procedure

1. **Plot Constraints:** Convert each inequality to equality and plot the line
2. **Identify Feasible Region:** Determine which side of each line satisfies the inequality
3. **Find Corner Points:** Identify intersection points of constraint boundaries
4. **Evaluate Objective Function:** Calculate objective value at each corner point
5. **Identify Optimal Solution:** Select the corner point with best objective value

2.4.5.2 Example: Simple Warehouse Problem

Consider a simplified version with 2 warehouses and 1 facility:

Problem:

$$\text{Maximize } Z = 40x_1 + 30x_2$$

$$\text{Subject to } 2x_1 + x_2 \leq 100$$

$$x_1 + 3x_2 \leq 90$$

$$x_1 \geq 0, x_2 \geq 0$$

Step 1: Plot Constraints - Constraint 1: $2x_1 + x_2 = 100 \rightarrow$ Line through (0,100) and (50,0)
- Constraint 2: $x_1 + 3x_2 = 90 \rightarrow$ Line through (0,30) and (90,0)

Step 2: Identify Corner Points - Intersection of axes: (0,0), (0,30), (50,0) - Intersection of constraints: Solve:

$$2x_1 + x_2 = 100$$

$$x_1 + 3x_2 = 90$$

Solution: $x_1 = 42, x_2 = 16$

Step 3: Evaluate Objective Function

- At (0,0): $Z = 0$
- At (0,30): $Z = 900$
- At (50,0): $Z = 2000$
- At (42,16): $Z = 40 \times 42 + 30 \times 16 = 2160$

Optimal Solution: $x_1 = 42, x_2 = 16$ with $Z = 2160$

2.4.6 Simplex Method Theory

2.4.6.1 Fundamental Theorem of Linear Programming

If an LP problem has an optimal solution, then there exists at least one corner point of the feasible region that is optimal.

2.4.6.2 Simplex Algorithm Steps

1. Convert to Standard Form

- Convert inequalities to equations using slack variables
- Ensure all variables are non-negative
- Convert minimization to maximization if needed

2. Initial Basic Feasible Solution

- Identify basic variables (variables with coefficient 1 in one equation and 0 in others)
- Set non-basic variables to zero

3. Optimality Test

- Calculate reduced costs for non-basic variables
- If all reduced costs ≤ 0 (for maximization), current solution is optimal

4. Pivot Column Selection

- Choose non-basic variable with most positive reduced cost (for maximization)

5. Pivot Row Selection

- Use minimum ratio test: $\min \left\{ \frac{b_i}{a_{ij}} : a_{ij} > 0 \right\}$

6. Pivot Operation

- Make pivot element equal to 1
- Make other elements in pivot column equal to 0

7. **Repeat** until optimality condition is satisfied

2.4.6.3 Simplex Tableau Format

The simplex method uses a tableau to organize calculations:

Basic Var	x_1	x_2	s_1	s_2	RHS
s_1	2	1	1	0	100
s_2	1	3	0	1	90
Z	-40	-30	0	0	0

Where s_1, s_2 are slack variables.

2.5 Types of Linear Programming Solutions

When we feed a problem into a solver (like the Simplex algorithm), we usually expect a single, perfect answer. But algorithms are strict logicians. If we ask for the impossible or the infinite, they will tell us exactly that. In Linear Programming, there are four distinct outcomes.

2.5.1 Unique Optimal Solution

The “Ideal” Scenario

This is the standard result. Geometrically, the feasible region is a polygon, and the Objective Function (the “slope” of profit or cost) cuts through the region such that it touches exactly **one** corner point (vertex) last.

- **Mathematical Context:** The slope of the objective function does *not* match the slope of any binding constraint.
- **Engineering Implication:** There is exactly one best way to allocate your resources. Any deviation from this plan results in lower profit or higher cost.

2.5.2 Multiple Optimal Solutions (Alternative Optima)

The “Flexibility” Scenario

Sometimes, you might get a result where the solver says: *“You can choose Point A ($x = 2, y = 5$) or Point B ($x = 4, y = 3$), and the profit is exactly the same.”*

- **Why this happens:** The slope of your Objective Function is **parallel** to one of the binding constraint lines. Instead of touching a single corner, the objective function lies flat against an entire edge of the feasible region.
- **Engineering Implication:** This is actually great news for a designer! It means you have **flexibility**. Mathematically, the cost is the same, but maybe Plan A is politically easier to implement than Plan B. You can choose based on secondary factors (like aesthetics or risk) without losing optimality.

2.5.3 Unbounded Solution

The “Too Good to Be True” Scenario

Imagine writing a program to maximize profit, and the output is **Infinity**. While exciting, this is invariably a **modeling error**.

- **Why this happens:** The feasible region is not closed (it extends infinitely in one direction), and you are trying to maximize in that direction. You have forgotten a constraint.
- **Real-world Example:** “Maximize production.” If you don’t add a constraint for “Available Raw Materials” or “Factory Capacity,” the math assumes you can produce infinite units.
- **Mathematical Check:** In the Simplex tableau, this occurs when a variable can enter the basis, but no variable leaves (no positive ratio in the pivot test).

2.5.4 Infeasible Problem

The “Impossible” Scenario

This is the most common frustration in real-world engineering. You hit “Run,” and the solver returns an error.

- **Why this happens:** The constraints are contradictory. There is no overlap in the shaded regions. The Feasible Region is empty ($F = \emptyset$).
- **Real-world Example:** “Build a warehouse that is within 5km of the city center ($x \leq 5$) AND at least 10km away from residential zones ($x \geq 10$).” It is mathematically impossible to satisfy both.
- **Debugging:** You must relax (loosen) one or more constraints to find a solution.

2.6 Duality in Linear Programming

2.6.1 The “Mirror Image” of Optimization

Every Linear Programming problem (which we call the **Primal**) has a ghostly twin brother called the **Dual**.

If the **Primal** problem asks: *“How do I mix these ingredients to make the most profit?”* The **Dual** problem asks: *“How much are these ingredients actually worth to me?”*

2.6.2 Why do Computer Scientists care?

1. **Computational Efficiency:** Sometimes the Primal problem has 100,000 constraints and is slow to solve. The Dual might have only 100 constraints and is much faster. Solving the Dual gives you the exact same optimal value (Z^*) as the Primal.
2. **Shadow Prices (Economic Interpretation):** The solution values of the Dual variables ($y_1, y_2, \dots$) tell you the **Shadow Price** of your resources.
 - *Insight:* If the shadow price of “Machine Hours” is \$50, it means acquiring **one extra hour** of machine time will increase your total profit by exactly \$50. This tells managers where to invest!

2.6.3 The Mathematical Transformation

We convert a Primal to a Dual by flipping the matrix: * **Maximization** becomes **Minimization**. * **Right-Hand Side** (b) constants of Primal become **Objective Coefficients** (c) of Dual. * **Constraint Matrix** (A) is transposed (A^T).

2.6.4 Key Theorems

- **Weak Duality Theorem:** The value of *any* feasible solution to the Maximization problem is always $\leq$ the value of *any* feasible solution to the Minimization problem. They bound each other.
- **Strong Duality Theorem:** If the Primal has an optimal solution, the Dual has an optimal solution, and **their Objective Values are equal** ($Z_{\text{primal}} = W_{\text{dual}}$).

Every LP problem (primal) has a corresponding dual problem:

Primal Problem:

$$\begin{aligned} &\text{Maximize } Z = \mathbf{c}^T \mathbf{x} \\ &\text{Subject to } \mathbf{Ax} \leq \mathbf{b} \\ &\mathbf{x} \geq \mathbf{0} \end{aligned}$$

Dual Problem:

$$\begin{aligned} &\text{Minimize } W = \mathbf{b}^T \mathbf{y} \\ &\text{Subject to } \mathbf{A}^T \mathbf{y} \geq \mathbf{c} \\ &\mathbf{y} \geq \mathbf{0} \end{aligned}$$

2.6.4.1 Duality Theorems

1. **Weak Duality Theorem:** For any feasible solution $\mathbf{x}$ of primal and $\mathbf{y}$ of dual:

$$\mathbf{c}^T \mathbf{x} \leq \mathbf{b}^T \mathbf{y}$$

2. **Strong Duality Theorem:** If either primal or dual has an optimal solution, then both have optimal solutions and:

$$\mathbf{c}^T \mathbf{x}^* = \mathbf{b}^T \mathbf{y}^*$$

2.6.5 Sensitivity Analysis

Sensitivity analysis examines how changes in parameters affect the optimal solution:

2.6.5.1 Changes in Objective Function Coefficients

- Range of optimality for each coefficient
- Effect on optimal solution when coefficients change

2.6.5.2 Changes in Right-Hand Side Constants

- Shadow prices (dual variables)
- Range of feasibility for each constraint

2.6.5.3 Changes in Constraint Coefficients

- Effect of adding new variables or constraints
- Impact of changing technological coefficients

2.6.6 Special Cases in Linear Programming

2.6.6.1 Transportation Problems

Special structure where sources supply destinations with minimum transportation cost.

2.6.6.2 Assignment Problems

Special case of transportation problem where each source is assigned to exactly one destination.

2.6.6.3 Network Flow Problems

Optimization problems defined on networks with flow conservation constraints.

2.7 Linear Programming Problems — Graphical Method

Below are **five LPP problems** designed to be solved using the **graphical method**. For each problem:

1. Draw each constraint as a straight line in the x_1 - x_2 plane.
2. Identify the feasible region (including $x_1, x_2 \geq 0$).
3. Find all corner (vertex) points of the feasible region.
4. Evaluate the objective Z at each corner to determine the optimum.
5. State the optimal solution and the optimal value Z^* .

Problem 1 — Simple maximization

Maximize

$$Z = 3x_1 + 2x_2$$

Subject to

$$x_1 + x_2 \leq 4,$$

$$x_1 \leq 3,$$

$$x_2 \leq 2,$$

$$x_1, x_2 \geq 0.$$

Problem 2 — Two binding inequalities

Maximize

$$Z = 5x_1 + 4x_2$$

Subject to

$$2x_1 + x_2 \leq 8,$$

$$x_1 + 2x_2 \leq 8,$$

$$x_1, x_2 \geq 0.$$

Problem 3 — Minimization with intersection corner

Minimize

$$Z = 4x_1 + 6x_2$$

Subject to

$$x_1 + x_2 \geq 4,$$

$$2x_1 + x_2 \geq 6,$$

$$x_1, x_2 \geq 0.$$

Problem 4 — Resource allocation (mix of $\leq$ and $\geq$)

A factory makes two products P_1 and P_2 with profits \$7 and \$5 respectively.

Maximize profit

$$Z = 7x_1 + 5x_2$$

Subject to resource limits

$$3x_1 + 2x_2 \leq 18 \quad (\text{machine-hours}),$$

$$x_1 + 2x_2 \geq 4 \quad (\text{minimum production constraint}),$$

$$x_1, x_2 \geq 0.$$

Problem 5 — Problem with a redundant constraint

Maximize

$$Z = 2x_1 + 3x_2$$

Subject to

$$x_1 + 4x_2 \leq 12,$$

$$2x_1 + 8x_2 \leq 24,$$

$$x_1 + x_2 \leq 5,$$

$$x_1, x_2 \geq 0.$$

2.8 Practical Implementation with Python

Problem Statement

A Smart City logistics company needs to determine the optimal distribution strategy between two warehouses (Warehouse A and Warehouse B) to minimize total operational costs. The company must decide how many units to ship from each warehouse while considering capacity constraints and transportation costs.

2.8.0.1 Problem Data:

- **Warehouse A:** Transportation cost = \$40 per unit
- **Warehouse B:** Transportation cost = \$30 per unit
- **Constraint 1:** Minimum demand exceeds 60
- **Constraint 2:** Warehouse A has a maximum capacity of 50
- **Constraint 3:** Warehouse B has a maximum capacity of 40
- **Constraint 4:** Total units from both warehouses cannot exceed 200 (2 units from A + 3 unit from B combination)
- Both warehouses have non-negative shipment quantities

2.8.1 Mathematical Formulation

2.8.1.1 Decision Variables

Let: - \$ x_1 \$: Number of units to ship from Warehouse A - \$ x_2 \$: Number of units to ship from Warehouse B

2.8.1.2 Objective Function

Minimize the total transportation cost:

$$\text{Minimize } Z = 40x_1 + 30x_2$$

2.8.2 Complete Linear Programming Model

$$\begin{aligned} \text{Minimize } Z &= 40x_1 + 30x_2 \\ \text{Subject to } x_1 + x_2 &\geq 60 \\ x_1 &\leq 50 \\ x_2 &\leq 40 \\ 2x_1 + 3x_2 &\leq 200 \\ x_1 &\geq 0 \\ x_2 &\geq 0 \end{aligned}$$

Using PuLP for LP Problems

PuLP provides a high-level interface for formulating and solving optimization problems:

```
import pulp

# Create optimization problem
model = pulp.LpProblem("Warehouse_Location", pulp.LpMinimize)

# Define decision variables
x1 = pulp.LpVariable('Warehouse_A', lowBound=0, cat='Continuous')
x2 = pulp.LpVariable('Warehouse_B', lowBound=0, cat='Continuous')

# Define objective function
model += 40*x1 + 30*x2, "Total_Cost"

# Add realistic constraints
model += x1 + x2 >= 60, "Minimum_Demand"
model += x1 <= 50, "Warehouse_A_Capacity" # Warehouse A max capacity
model += x2 <= 40, "Warehouse_B_Capacity" # Warehouse B max capacity
model += 2*x1 + 3*x2 <= 200, "Budget_Constraint" # Combined resource constraint

# Solve the problem
model.solve()

# Print results
print(f"Status: {pulp.LpStatus[model.status]}")
print(f"Optimal Cost: ${pulp.value(model.objective):.2f}")
print(f"Warehouse A: {x1.varValue} units")
print(f"Warehouse B: {x2.varValue} units")
```

Status: Optimal

Optimal Cost: \$2000.00
Warehouse A: 20.0 units
Warehouse B: 40.0 units

2.9 Linear Programming Problems Collection

2.9.1 Problem 1

A manufacturing company produces two products (A and B) using three machines (M1, M2, M3). The profit per unit is \$50 for product A and \$40 for product B. Machine time requirements and availability are given below. Determine the optimal production quantities to maximize profit.

Machine	Product A (hrs/unit)	Product B (hrs/unit)	Available Hours
M1	2	1	100
M2	1	2	80
M3	1	1	60

Mathematical Formulation

Decision Variables:

- x_1 : Units of Product A to produce
- x_2 : Units of Product B to produce

Objective Function:

$$\text{Maximize } Z = 50x_1 + 40x_2$$

Constraints:

$$2x_1 + x_2 \leq 100 \quad (\text{Machine M1})$$

$$x_1 + 2x_2 \leq 80 \quad (\text{Machine M2})$$

$$x_1 + x_2 \leq 60 \quad (\text{Machine M3})$$

$$x_1, x_2 \geq 0$$

Python Solution

```

import pulp

# Create the optimization problem
model = pulp.LpProblem("Product_Mix_Optimization", pulp.LpMaximize)

# Decision variables
x1 = pulp.LpVariable('Product_A', lowBound=0, cat='Continuous')
x2 = pulp.LpVariable('Product_B', lowBound=0, cat='Continuous')

# Objective function
model += 50*x1 + 40*x2, "Total_Profit"

# Constraints
model += 2*x1 + x2 <= 100, "Machine_M1"
model += x1 + 2*x2 <= 80, "Machine_M2"
model += x1 + x2 <= 60, "Machine_M3"

# Solve
model.solve()

# Results
print("=== PRODUCT MIX OPTIMIZATION ===")
print(f"Status: {pulp.LpStatus[model.status]}")
print(f"Optimal Profit: ${pulp.value(model.objective):.2f}")
print(f"Product A: {x1.varValue} units")
print(f"Product B: {x2.varValue} units")
print(f"Machine M1 usage: {2*x1.varValue + x2.varValue}/100 hours")
print(f"Machine M2 usage: {x1.varValue + 2*x2.varValue}/80 hours")
print(f"Machine M3 usage: {x1.varValue + x2.varValue}/60 hours")

```

```

=== PRODUCT MIX OPTIMIZATION ===
Status: Optimal
Optimal Profit: $2800.00
Product A: 40.0 units
Product B: 20.0 units
Machine M1 usage: 100.0/100 hours
Machine M2 usage: 80.0/80 hours
Machine M3 usage: 60.0/60 hours

```

2.9.2 Problem 2: Diet Problem

A nutritionist needs to design a minimum-cost diet that meets daily nutritional requirements. Two foods are available with different nutrient contents and costs. Determine the optimal food quantities.

Nutrient	Food 1 (units/kg)	Food 2 (units/kg)	Minimum Daily Requirement
Protein	2	1	8 units
Carbs	1	2	10 units
Fat	1	1	6 units
Cost (\$)	3	2	-

Mathematical Formulation

Decision Variables:

- x_1 : kg of Food 1 to include in daily diet
- x_2 : kg of Food 2 to include in daily diet

Objective Function:

Minimize the total daily cost:

$$\text{Minimize } Z = 3x_1 + 2x_2$$

Constraints:

Protein Requirement:

$$2x_1 + x_2 \geq 8$$

Carbohydrates Requirement:

$$x_1 + 2x_2 \geq 10$$

Fat Requirement:

$$x_1 + x_2 \geq 6$$

Non-negativity Constraints:

$$x_1 \geq 0, \quad x_2 \geq 0$$

Complete Linear Programming Model

$$\begin{aligned}
&\text{Minimize } Z = 3x_1 + 2x_2 \\
&\text{Subject to } 2x_1 + x_2 \geq 8 \\
&\quad x_1 + 2x_2 \geq 10 \\
&\quad x_1 + x_2 \geq 6 \\
&\quad x_1 \geq 0 \\
&\quad x_2 \geq 0
\end{aligned}$$

Python Implementation

```

import pulp

# Create the optimization problem
model = pulp.LpProblem("Diet_Problem", pulp.LpMinimize)

# Define decision variables
x1 = pulp.LpVariable('Food_1', lowBound=0, cat='Continuous')
x2 = pulp.LpVariable('Food_2', lowBound=0, cat='Continuous')

# Define objective function (minimize cost)
model += 3*x1 + 2*x2, "Total_Cost"

# Add nutritional constraints
model += 2*x1 + x2 >= 8, "Protein_Requirement"
model += x1 + 2*x2 >= 10, "Carbohydrates_Requirement"
model += x1 + x2 >= 6, "Fat_Requirement"

# Solve the problem
model.solve()

# Display results
print("=== DIET PROBLEM OPTIMIZATION ===")
print(f"Solution Status: {pulp.LpStatus[model.status]}")
print(f"Minimum Daily Cost: ${pulp.value(model.objective):.2f}")
print(f"Optimal Food Quantities:")
print(f"  Food 1: {x1.varValue:.2f} kg")
print(f"  Food 2: {x2.varValue:.2f} kg")

# Verify nutritional intake
print(f"\nNutritional Analysis:")
print(f"Protein Intake: {2*x1.varValue + x2.varValue:.1f} units (Minimum: 8 units)")
print(f"Carbohydrates Intake: {x1.varValue + 2*x2.varValue:.1f} units (Minimum: 10 units)")

```

```

print(f"Fat Intake: {x1.varValue + x2.varValue:.1f} units (Minimum: 6 units)")

# Cost breakdown
print(f"\nCost Breakdown:")
print(f"Food 1 Cost: ${3*x1.varValue:.2f}")
print(f"Food 2 Cost: ${2*x2.varValue:.2f}")
print(f"Total Cost: ${pulp.value(model.objective):.2f}")

```

=== DIET PROBLEM OPTIMIZATION ===

Solution Status: Optimal

Minimum Daily Cost: \$14.00

Optimal Food Quantities:

Food 1: 2.00 kg

Food 2: 4.00 kg

Nutritional Analysis:

Protein Intake: 8.0 units (Minimum: 8 units)

Carbohydrates Intake: 10.0 units (Minimum: 10 units)

Fat Intake: 6.0 units (Minimum: 6 units)

Cost Breakdown:

Food 1 Cost: \$6.00

Food 2 Cost: \$8.00

Total Cost: \$14.00

2.10 Micro-Project 1: Campus City Emergency Supply Distribution

As an optimization analyst at **Campus City Logistics**, you've been tasked with designing the optimal supply distribution network for essential resources across campus facilities. The current ad-hoc system is inefficient and costly.

2.10.1 Problem Statement

Determine the optimal warehouse locations and distribution plan that minimizes total annual costs while meeting all facility demands, respecting warehouse capacity constraints, and operating within the allocated budget.

2.10.2 Facilities Data (From facilities.csv)

Based on our dataset, we have 15 facilities with the following key attributes:

Critical Facilities Selected for Micro-Project 1:

Facility ID	Facility Name	Type	Daily Demand
MED_CENTER	Campus Medical Center	Hospital	80 units
ENG_BUILDING	Engineering Building	Academic	30 units
SCIENCE_HALL	Science Hall	Academic	35 units
DORM_A	North Dormitory	Residential	55 units
DORM_B	South Dormitory	Residential	45 units
LIBRARY	Main Library	Academic	25 units

Total Daily Demand: 270 units

2.10.3 Warehouse Data (From warehouses.csv)

Warehouse ID	Warehouse Name	Daily Capacity	Construction Cost	Operational Cost/Day
WH_NORTH	North Campus Warehouse	400 units	\$300,000	\$800
WH_SOUTH	South Campus Warehouse	350 units	\$280,000	\$700
WH_EAST	East Gate Warehouse	450 units	\$320,000	\$900

Total Available Capacity: 1,200 units

2.10.4 Transportation Costs (From transportation_costs.csv)

- **Data Source:** Pre-calculated matrix with actual distances
- **Cost Range:** \$3.68 - \$5.03 per unit between selected locations
- **Calculation:** Based on real geographic coordinates using Haversine formula

2.10.5 Financial Constraints

- **Annual Budget:** \$1,500,000
- **Operational Period:** 365 days (annual calculation)
- **Construction Cost:** Amortized over 10 years
- **All costs must be annualized**

2.10.6 Physical & Business Constraints

1. **Warehouse Selection:** Select exactly 2 warehouses for redundancy
2. **Demand Satisfaction:** Each facility must receive exactly its daily demand $\times 365$
3. **Capacity Limits:** Shipments from each warehouse $\leq$ capacity $\times 365$
4. **Budget Limit:** Total annual cost $\leq$ \$1,500,000
5. **Non-negativity:** All shipment quantities ≥ 0

2.10.7 Learning Objectives

Technical Skills

- Formulate Mixed-Integer Linear Programming (MILP) problem
- Implement optimization model using PuLP
- Handle real geographic and cost data
- Validate constraint satisfaction

Analytical Skills

- Interpret optimization results in business context
- Analyze cost breakdown and efficiency metrics
- Provide actionable recommendations

Project Deliverables

1. Deliverable 1: Mathematical Formulation (3 Marks)
2. Deliverable 2: Report in .pdf format (7 Marks)

3 Module 2: Non-linear Programming with Python

3.1 Module Overview

3.1.1 Learning Objectives

- Understand the limitations of linear models and need for nonlinear optimization
- Master unconstrained optimization techniques (Golden Section, Fibonacci)
- Formulate and solve constrained nonlinear problems using KKT conditions
- Implement nonlinear optimization algorithms in Python
- Apply nonlinear methods to realistic cost modeling problems

3.1.2 Module Structure

- **Section 2.1:** Introduction to Nonlinear Optimization
- **Section 2.2:** Unconstrained Optimization Methods
- **Section 2.3:** Constrained Optimization & KKT Conditions
- **Section 2.4:** Python Implementation of Nonlinear Solvers
- **Section 2.5:** Advanced Applications & Micro-Project 2

3.1.3 Real-World Context

Extend the Campus City supply chain model with realistic nonlinear cost functions, environmental constraints, and multi-period optimization challenges.

3.2 Introduction to Nonlinear Optimization

Nonlinear programming (NLP) is an optimization technique used to find the best outcome (maximum profit, lowest cost, etc.) in a mathematical model where at least one of the objective functions or constraints is nonlinear. This means the relationship between variables cannot be represented on a straight line. NLP addresses the complexity found in real-world scenarios,

such as modeling physical systems or financial markets, where linear assumptions are often inadequate for accurate prediction and decision-making . Key components of an NLP problem include decision variables, an objective function to be optimized, and constraints that limit the possible solutions.

The primary purpose of using NLP is to provide more accurate and realistic models for optimization problems across various fields, including engineering design, economics, finance, and operations research. For example, in portfolio optimization, investors use NLP to maximize returns while balancing risk, which inherently involves nonlinear relationships between different assets. In chemical engineering, NLP helps optimize process yields and efficiency where reaction kinetics are nonlinear. It is applied when linear models fail to capture the true nature of the relationships between the inputs and outputs of a system.

Solving NLP problems involves specialized algorithms, such as sequential quadratic programming (SQP), interior-point methods, or generalized reduced gradient methods. The “how much” refers to the computational resources and mathematical complexity required, which are often significantly greater than for linear programming. The complexity and effort vary widely based on the problem’s size and structure (e.g., convexity). While the general approach is similar (define variables, objective, constraints), the execution demands sophisticated software and potentially substantial processing power to find the global optimum efficiently.

3.2.1 Theoretical Foundation

The fundamental theoretical difference between Linear Programming Problems (LPP) and NLP lies in the *mathematical nature of their objective functions and constraints*, which dictates the complexity of their feasible regions, solution methods, and optimality guarantees.

Feature	Linear Programming (LPP)	Nonlinear Programming (NLP)
Function Types	Objective function and all constraints must be linear.	At least one function (objective or a constraint) is nonlinear.
Feasible Region	The feasible region is a convex polyhedron (a shape with flat faces).	The feasible region can be non-convex, curved, or disconnected.
Optimality	A locally optimal solution is always a globally optimal solution. The optimum lies at a corner point (vertex) of the feasible region.	Solutions often only guarantee a local optimum. The global optimum is difficult to find without additional assumptions (e.g., convexity of the entire problem).

Feature	Linear Programming (LPP)	Nonlinear Programming (NLP)
Solution Methods	Solved primarily by the Simplex Method or Interior Point Methods , which systematically explore the corner points.	Requires more complex iterative numerical methods such as Gradient Descent , Newton's Method , or Lagrangian heuristics , often relying on derivatives.
Computational Complexity	Generally easier and faster to solve, even with a vast number of variables.	Generally more computationally intensive and difficult to solve, especially for large-scale, non-convex problems.

Optimization Problems			
Linear Programming (LPP)		Nonlinear Programming (NLP)	
Linear objective & linear constraints		At least one objective or constraint is nonlinear	
Feasible region is convex		Region may be curved or nonconvex	
Optimal solution at a vertex		May have multiple local optima	
Solved via Simplex / IPM		Solved via numerical methods	

3.2.1.1 Why Nonlinear Optimization?

Linear programming assumes proportional relationships, but real-world problems often involve:

- **Economies of scale:** Decreasing marginal costs
- **Physical constraints:** Nonlinear relationships (distance vs fuel consumption)
- **Quality constraints:** Minimum/maximum thresholds with nonlinear effects
- **Environmental factors:** Quadratic cost functions for emissions

3.2.1.2 Mathematical Formulation

A general Nonlinear Programming (NLP) problem:

Objective Function:

$$\text{Minimize } f(\mathbf{x})$$

Subject to:

$$\begin{aligned} g_i(\mathbf{x}) &\leq 0, & i = 1, \dots, m \\ h_j(\mathbf{x}) &= 0, & j = 1, \dots, p \\ \mathbf{x} &\in \mathbb{R}^n \end{aligned}$$

Where:

- $f(\mathbf{x})$: Nonlinear objective function
- $g_i(\mathbf{x})$: Nonlinear inequality constraints
- $h_j(\mathbf{x})$: Nonlinear equality constraints

3.2.2 Sample Problem

Problem Statement: A delivery company has a cost function $C(d) = 500 + 2d + 0.1d^2$ where d is distance in km. Find the optimal delivery distance that minimizes cost per unit for a shipment of 100 units.

Mathematical Formulation:

$$\text{Minimize } \frac{C(d)}{100} = 5 + 0.02d + 0.001d^2$$

Solution:

1. Take derivative: $\frac{d}{dd} (5 + 0.02d + 0.001d^2) = 0.02 + 0.002d$
2. Set to zero: $0.02 + 0.002d = 0$
3. Solve: $d = -10 \text{ km} \rightarrow \text{Not feasible}$
4. Check boundaries: Minimum at $d = 0$ with cost \$5/unit

Interpretation: The cost function is convex and increasing, so minimum occurs at shortest distance.

3.2.3 Review Questions

1. What are three real-world scenarios where linear models fail and nonlinear optimization is required?
2. Explain the difference between convex and non-convex optimization problems. Why is this distinction important?
3. A manufacturing process has cost $C(x) = 1000 + 50x + 0.5x^2$ where x is production volume. Find the production level that minimizes average cost.
4. Why can't the Simplex method be directly applied to nonlinear optimization problems?
5. Describe a campus logistics scenario where nonlinear optimization would provide better results than linear programming.

i NLP Vs LPP

The linear nature of LPP guarantees a single, well-defined feasible region and objective function behavior, allowing for robust algorithms like the Simplex method to efficiently find the absolute best (global) solution. NLP, by contrast, accommodates the complex, often non-convex, relationships found in many real-world problems. This flexibility comes at a theoretical and computational cost: the presence of curves and non-linear interactions means there may be multiple “local” optimal points, and standard algorithms may get stuck at one that is not the overall best solution. The theoretical foundation of NLP thus focuses heavily on iterative improvement, convergence properties, and finding efficient ways to navigate these more challenging landscapes.

3.3 Unconstrained Optimization Methods

Unconstrained Nonlinear Programming deals with optimizing a nonlinear objective function without any constraints on the decision variables. The objective is to determine a point $x^* \in \mathbb{R}^n$ such that:

$$\min_{x \in \mathbb{R}^n} f(x)$$

(or equivalently $\max f(x)$ depending on the problem context).

Intuition Behind Unconstrained NLP

The central idea in solving unconstrained NLP problems is to understand how the objective function surface behaves and to iteratively move toward regions where the function value improves.

Downhill Movement Intuition

For minimization problems, the objective is to move step-by-step in a direction that decreases the function value, much like descending a slope.

Hiking Analogy

Consider attempting to reach the lowest valley point in a mountainous landscape while blind-folded. The only available information is the slope beneath your feet. The safest strategy is always stepping in the direction that slopes downward most strongly.

Key points

- This *direction of steepest descent* is mathematically represented by the gradient $\nabla f(x)$.
- Repeated movement in this direction leads to progressively lower function values until a flat region is encountered. ## Link with Calculus

In single-variable calculus, stationary (optimal) points are found by solving:

$$\frac{df}{dx} = 0$$

In multi-variable calculus, this concept generalizes to:

$$\nabla f(x^*) = 0$$

A point where the gradient is zero is called a **critical point**. It may represent:

Type of Critical Point	Interpretation
Local Minimum	Valley bottom
Local Maximum	Hilltop
Saddle Point	A flat ridge point

To classify these points, second-order information is required.

First-Order Necessary Condition (FONC)

For a differentiable function $f(x)$, a point x^* can be a local minimum only if:

$$\nabla f(x^*) = 0$$

This guarantees flatness but **does not guarantee** an actual minimum.

i Second-Order Sufficient Condition (SOSC)

Let $H(x)$ denote the **Hessian matrix** of second partial derivatives:

$$H(x) = \left[\frac{\partial^2 f}{\partial x_i \partial x_j} \right]$$

If x^* satisfies $\nabla f(x^*) = 0$ and

$H(x^*)$ is positive definite

then x^* is a **strict local minimum**.

Curvature Interpretation

Hessian Property	Interpretation
$H \succ 0$	Strict minimum (upward curvature)
$H \prec 0$	Maximum (downward curvature)
Indefinite	Saddle point (mixed curvature)

3.3.1 Algorithms for Unconstrained NLP

This module focuses specifically on *iteration-based direct search techniques*, which do not require gradient or Hessian calculations. Such algorithms are especially useful when:

- The derivative is difficult or impossible to compute
- The objective function is noisy or discontinuous
- Only function value evaluations are available

The algorithms covered in this module include:

3.3.1.1 Fibonacci Search Method

A bracketing method used for **one-dimensional** minimization.

This method iteratively narrows down an interval containing the minimum using Fibonacci numbers.

i Key Concept

The interval size decreases proportionally according to Fibonacci sequence ratios, ensuring efficient narrowing.

This method is applicable to Smooth 1-D unimodal functions.

3.3.1.2 Golden Section Search Method

A more efficient improvement over Fibonacci search, eliminating the need to precompute steps. The method divides the interval using the *Golden Ratio*:

$$\phi = \frac{\sqrt{5} + 1}{2} \approx 1.618$$

i Key Concept

The interval is repeatedly reduced while maintaining internal division based on ϕ , ensuring optimal reduction at each iteration.

3.3.1.3 Hooke and Jeeves Pattern Search Method

A *direct search* method used for *multidimensional* optimization without derivatives.

i Key Components

- **Exploratory search:** Tests moves along coordinate directions to find improvement.
- **Pattern move:** Accelerates search in the identified promising direction.

3.3.1.4 Advantages

- Does not require derivative information
- Suitable for complex, non-smooth landscapes

Unconstrained NLP is guided by theoretical optimality conditions and solved computationally using iterative search techniques. In this module, emphasis is placed on **direct search algorithms** useful when derivatives are unavailable.

$$\nabla f(x^*) = 0 \quad \text{and} \quad H(x^*) \succ 0$$

The practical tools studied—**Fibonacci Search, Golden Section Search, and Hooke & Jeeves**—offer systematic methods for approaching optimal points when classical derivative-based methods cannot be applied.

3.3.1.5 Review Questions

1. Why does the condition $\nabla f(x^*) = 0$ not guarantee a minimum?
2. What role does curvature play in distinguishing minima from maxima?
3. Why are direct search methods such as Fibonacci or Golden Section useful?
4. Compare Hooke & Jeeves with gradient-based methods.
5. Explain why Golden Section is more efficient than Fibonacci Search.

3.3.2 Theoretical Foundation

3.3.2.1 One-Dimensional Search Methods

When dealing with single-variable nonlinear functions, we use specialized search techniques:

Golden Section Search: - Divide interval using golden ratio $\phi = \frac{1+\sqrt{5}}{2} \approx 1.618$ - Progressively narrow search interval - Guaranteed convergence for unimodal functions

Fibonacci Search: - Uses Fibonacci sequence for interval reduction - Optimal in terms of function evaluations - Similar convergence properties to Golden Section

3.3.2.2 Mathematical Basis

For a unimodal function $f(x)$ on interval $[a, b]$:

Golden Section Points:

$$x_1 = b - \frac{b-a}{\phi}$$
$$x_2 = a + \frac{b-a}{\phi}$$

Where $\phi = 1.618$

i Alter:

Instead of choosing $\phi = 1.618$, we can select the other Golden section ratio (< 1). In that case the section points can be calculated as:

$$x_1 = b - \phi \cdot (b-a)$$
$$x_2 = a + \phi \cdot (b-a)$$

Iteration: Compare $f(x_1)$ and $f(x_2)$, eliminate portion of interval based on which is larger.

3.3.3 Sample Problem 1

Problem Statement: Use Golden Section search to minimize $f(x) = (x-3)^2 + 2$ on interval $[0, 5]$ with 4 iterations.

Solution: Iteration 1:

- $x_1 = 5 - \frac{5-0}{1.618} = 1.91, f(x_1) = 2.19$
- $x_2 = 0 + \frac{5-0}{1.618} = 3.09, f(x_2) = 2.01$
- Since $f(x_1) > f(x_2)$, new interval: $[1.91, 5]$

Iteration 2:

- $x_1 = 5 - \frac{5-1.91}{1.618} = 3.09$ (already computed)
- $x_2 = 1.91 + \frac{5-1.91}{1.618} = 3.82, f(x_2) = 2.67$
- Since $f(x_1) < f(x_2)$, new interval: $[1.91, 3.82]$

Continue for 4 iterations → Final interval: $[2.85, 3.15]$ containing true minimum at $x=3$

3.3.4 Sample Problem 2

Problem Statement: A warehouse has energy consumption $E(w) = 1000 + 50w + 0.2w^2$ kWh, where w is weekly shipments ($0 \leq w \leq 200$). Find optimal shipment volume that minimizes energy per shipment.

Solution: Energy per shipment: $f(w) = \frac{1000}{w} + 50 + 0.2w$

Using Golden Section on $[10, 200]$:

- **Iteration 1:** Compare $w=70.8$ and $w=139.2$
- **Iteration 2:** Compare $w=44.4$ and $w=70.8$
- **Iteration 3:** Compare $w=57.6$ and $w=70.8$
- **Optimal:** $w = 70.7$ shipments/week, energy/shipment = 78.3 kWh

3.3.5 Sample problem 3

Minimize

$$f(x) = -\frac{1}{(x-1)^2} \left(\ln(x) - 2 \left(\frac{x-1}{x+1} \right) \right)$$

such that x in $[1.5, 4.5]$ using the Golden Section Method.

3.3.6 Review Questions

1. Explain why Golden Section search is more efficient than exhaustive search for unimodal functions.
2. Compare Golden Section and Fibonacci search methods. When would you choose one over the other?
3. A transportation cost function is $C(d) = \frac{1000}{d} + 2d$ for $d > 0$. Use Golden Section to find the optimal distance in $[10, 100]$ with 3 iterations.
4. What is a unimodal function and why is this property important for one-dimensional search methods?
5. How would you modify Golden Section search if you suspected multiple local minima in your search interval?

3.4 Constrained Optimization & KKT Conditions

3.4.1 Theoretical Foundation

3.4.1.1 Karush-Kuhn-Tucker (KKT) Conditions

For constrained nonlinear optimization, KKT conditions provide necessary conditions for optimality:

Primal Problem:

$$\begin{aligned} & \text{Minimize } f(\mathbf{x}) \\ & \text{Subject to } g_i(\mathbf{x}) \leq 0, \quad i = 1, \dots, m \\ & \quad \quad h_j(\mathbf{x}) = 0, \quad j = 1, \dots, p \end{aligned}$$

KKT Conditions:

1. **Stationarity:** $\nabla f(\mathbf{x}) + \sum \lambda_i \nabla g_i(\mathbf{x}) + \sum \mu_j \nabla h_j(\mathbf{x}) = 0$
2. **Primal Feasibility:** $g_i(\mathbf{x}) \leq 0, \quad h_j(\mathbf{x}) = 0$
3. **Dual Feasibility:** $\lambda_i \geq 0$
4. **Complementary Slackness:** $\lambda_i g_i(\mathbf{x}) = 0$

3.4.1.2 Interpretation

- **Lagrange Multipliers (,):** Sensitivity of objective to constraint changes
- **Complementary Slackness:** Inactive constraints have zero multipliers
- **Stationarity:** Balance between objective improvement and constraint satisfaction

3.4.2 Sample Problem

Problem Statement:

Minimize $f(x, y) = x^2 + y^2$ subject to $x + y \geq 4$.

Solution:

1. **Rewrite constraint:** $g(x, y) = 4 - x - y \leq 0$
2. **Lagrangian:** $L(x, y, \lambda) = x^2 + y^2 + \lambda(4 - x - y)$
3. **KKT Conditions:**
 - $\frac{\partial L}{\partial x} = 2x - \lambda = 0$
 - $\frac{\partial L}{\partial y} = 2y - \lambda = 0$
 - $\lambda(4 - x - y) = 0$
 - $4 - x - y \leq 0, \lambda \geq 0$
4. **Case 1:** $\lambda = 0 \rightarrow x=0, y=0 \rightarrow$ violates constraint
5. **Case 2:** $4 - x - y = 0 \rightarrow$ from stationarity: $x=y= \lambda/2 \rightarrow 4 - \lambda/2 - \lambda/2 = 0 \rightarrow \lambda=4$
6. **Solution:** $x=2, y=2, \lambda=4, f=8$

3.4.3 Sample Problem

Problem Statement: Campus City wants to minimize transportation cost $C(d) = 2d + 0.1d^2$ while ensuring at least 80% of routes are under 3km. Formulate as KKT problem.

Solution:

Mathematical Formulation:

- Objective: Minimize $\sum 2d_i + 0.1d_i^2$
- Constraint: $\frac{\text{count}(d_i \leq 3)}{n} \geq 0.8$

KKT Interpretation:

- Lagrange multiplier indicates cost increase for relaxing the 80% constraint
- Helps decide if expanding the constraint is cost-effective

3.4.4 Review Questions

1. Explain the economic interpretation of Lagrange multipliers in constrained optimization.
2. What does complementary slackness tell us about active vs inactive constraints at the optimal solution?

3. Solve using KKT: Minimize $f(x) = x^2$ subject to $x \geq 2$.
4. How do KKT conditions extend the method of Lagrange multipliers for inequality constraints?
5. In a campus logistics context, what would a high Lagrange multiplier for an environmental constraint indicate?

3.5 Python Implementation of Nonlinear Solvers

3.5.1 Theoretical Foundation

3.5.1.1 Python Optimization Ecosystem

- **scipy.optimize**: Comprehensive optimization toolkit
- **minimize() function**: Unified interface for multiple algorithms
- **Algorithm choices**: SLSQP, trust-constr, COBYLA for constrained problems

3.5.1.2 Key Functions

```
from scipy.optimize import minimize

# For unconstrained problems
result = minimize(fun, x0, method='BFGS')

# For constrained problems
result = minimize(fun, x0, constraints=constraints, method='SLSQP')
```

Practical Considerations

- Initial guess (x_0): Critical for convergence
- Gradient provision: Can significantly improve performance
- Constraint formulation: Proper bounds and constraint objects

3.5.2 Sample Problem

Problem Statement: Implement Golden Section search in Python for $f(x) = (x - 4)^2 + 3$ on $[0, 10]$.

Solution:

```
import math

def golden_section_search(f, a, b, tol=1e-6, max_iter=100):
    phi = (1 + math.sqrt(5)) / 2
    for i in range(max_iter):
        x1 = b - (b - a) / phi
        x2 = a + (b - a) / phi

        if f(x1) > f(x2):
            a = x1
        else:
            b = x2

        if abs(b - a) < tol:
            return (a + b) / 2
    return (a + b) / 2

# Test the function
def objective(x):
    return (x - 4)**2 + 3

result = golden_section_search(objective, 0, 10)
print(f"Optimal x: {result:.4f}") # Output: Optimal x: 4.0000
```

Optimal x: 4.0000

3.5.3 Solution of constrained NLPP

To solve NLPP using KKT method, we will use `solve()` function from the `sympy` library. Key functions required for solution will be imported

```
from sympy import symbols, diff, solve
```

Example 1: Minimize $f(x, y) = x^2 + y^2$ subject to $x + y \geq 4$ (Standard form: $4 - x - y \leq 0$).

SymPy does not inherently “solve” inequality constraints in the same way a numerical solver (like SciPy) does. Instead, you must manually transform the inequality into an equation using the Complementary Slackness condition from the KKT framework. Here is the logic: An inequality constraint $g(x) \leq 0$ is handled by introducing a Lagrange multiplier λ and adding the equation $\lambda \cdot g(x) = 0$ to your system.

The 3-Step “Filter” Workflow Since SymPy’s solve function returns all mathematical solutions (stationary points), you must add a “Filter” step to check the inequalities manually. - *Formulate*: Convert inequalities to KKT equations (Stationarity + Complementary Slackness). - *Solve*: Use `solve()` to find all candidate points. - *Filter*: Discard solutions that violate Primal Feasibility ($g(x) \leq 0$) or Dual Feasibility ($\lambda \geq 0$).

Python code:

```
from sympy import symbols, diff, solve

# 1. Define Variables
x, y = symbols('x y', real=True)
lam = symbols('lambda', real=True) # Lagrange Multiplier

# 2. Define Functions
f = x**2 + y**2           # Objective
g = 4 - x - y             # Inequality constraint (g <= 0)

# 3. Formulate Lagrangian
# L = f + lambda * g
L = f + lam * g

# 4. Generate KKT Equations
# A. Stationarity: Gradient of L must be zero
eq1 = diff(L, x)
eq2 = diff(L, y)

# B. Complementary Slackness: lambda * constraint = 0
eq3 = lam * g

# 5. Solve the System of Equations
# We ask SymPy to find values for x, y, and lambda that satisfy these 3 equalities
solutions = solve([eq1, eq2, eq3], (x, y, lam), dict=True)

print(f"Candidate Solutions found: {len(solutions)}")

# 6. Filter Solutions (The Crucial Step for Inequalities)
```

```

print("\n--- Validation Step ---")
valid_solutions = []

for sol in solutions:
    x_val = sol[x]
    y_val = sol[y]
    lam_val = sol[lam]

    # Check Primal Feasibility:  $g(x) \leq 0$ 
    # (Using a small tolerance for floating point comparisons if needed)
    primal_check = (4 - x_val - y_val) <= 0

    # Check Dual Feasibility:  $\lambda \geq 0$ 
    dual_check = lam_val >= 0

    print(f"Testing Point ({x_val}, {y_val}) with lambda={lam_val}:")
    print(f"  Constraint  $g \leq 0$ ? {primal_check}")
    print(f"  Dual  $\lambda \geq 0$ ? {dual_check}")

    if primal_check and dual_check:
        print("  VALID Optimal Solution")
        valid_solutions.append(sol)
    else:
        print("  INVALID (Violates KKT conditions)")

# Output Final Result
if valid_solutions:
    opt = valid_solutions[0]
    print(f"\nOptimal Solution: x={opt[x]}, y={opt[y]}, cost={opt[x]**2 + opt[y]**2}")

```

Candidate Solutions found: 2

```

--- Validation Step ---
Testing Point (0, 0) with lambda=0:
  Constraint  $g \leq 0$ ? False
  Dual  $\lambda \geq 0$ ? True
  INVALID (Violates KKT conditions)
Testing Point (2, 2) with lambda=4:
  Constraint  $g \leq 0$ ? True
  Dual  $\lambda \geq 0$ ? True
  VALID Optimal Solution

```


Optimal Solution: $x=2$, $y=2$, $\text{cost}=8$

Example 2: Solve $f(x_1, x_2) = -x_1^2 - x_2^2$; $-x_1 - x_2 \leq -1$; $-2x_1 + 2x_2 \leq 1$; $x_1, x_2 \geq 0$.

```
import sympy as sp

# 1. Define Variables
x1, x2 = sp.symbols('x1 x2', real=True)
lam1, lam2 = sp.symbols('lambda1 lambda2', real=True)

# 2. Define Objective (Maximization)
f = -x1**2 - x2**2

# 3. Define Constraints in Standard Form (g(x) <= 0)
# Original: -x1 - x2 >= -1 -> x1 + x2 <= 1 -> x1 + x2 - 1 <= 0
g1 = x1 + x2 - 1

# Original: -2x1 + 2x2 <= 1 -> -2x1 + 2x2 - 1 <= 0
g2 = -2*x1 + 2*x2 - 1

# 4. Formulate Lagrangian for Maximization (L = f - lambda*g)
L = f - lam1 * g1 - lam2 * g2

# 5. KKT Equations
# A. Stationarity (Gradient of L w.r.t x must be 0)
stat_x1 = sp.diff(L, x1)
stat_x2 = sp.diff(L, x2)

# B. Complementary Slackness (lambda * g = 0)
slack_1 = lam1 * g1
slack_2 = lam2 * g2

# 6. Solve the System
print("Solving KKT system...")
# We assume non-negativity of x (x >= 0) is a boundary check rather than an explicit Lagrangian
# to keep the symbolic solver efficient for this demo.
solutions = sp.solve([stat_x1, stat_x2, slack_1, slack_2], (x1, x2, lam1, lam2), dict=True)

# 7. Validation & Filtering
print(f"\nFound {len(solutions)} candidate points. Filtering for optimality...")
print("-" * 75)
print(f"{'Point (x1, x2)':<20} | {'Multipliers':<20} | {'Objective':<10} | {'Status'}")
```

```

print("-" * 75)

best_f = -float('inf')
best_sol = None

for sol in solutions:
    # Extract numerical values
    x1_v = float(sol[x1])
    x2_v = float(sol[x2])
    l1_v = float(sol[lam1])
    l2_v = float(sol[lam2])

    status = "Valid"

    # Check 1: Non-negativity of variables ( $x \geq 0$ )
    if x1_v < -1e-7 or x2_v < -1e-7:
        status = "Invalid ( $x < 0$ )"

    # Check 2: Primal Feasibility ( $g \leq 0$ )
    elif (x1_v + x2_v - 1) > 1e-7:
        status = "Invalid ( $g_1 > 0$ )"
    elif (-2*x1_v + 2*x2_v - 1) > 1e-7:
        status = "Invalid ( $g_2 > 0$ )"

    # Check 3: Dual Feasibility ( $\lambda \geq 0$  for Max problem with  $L = f - \lambda g$ )
    elif l1_v < -1e-7 or l2_v < -1e-7:
        status = "Invalid ( $\lambda < 0$ )"

    # Calculate Objective
    obj_val = -x1_v**2 - x2_v**2

    print(f"({x1_v:.4f}, {x2_v:.4f}) | L1={l1_v:.4f}, L2={l2_v:.4f} | {obj_val:.4f} | ")

    if "Valid" in status and obj_val > best_f:
        best_f = obj_val
        best_sol = (x1_v, x2_v)

print("-" * 75)
if best_sol:
    print(f"\n Optimal Solution: x1 = {best_sol[0]}, x2 = {best_sol[1]}")
    print(f"    Max Objective Value = {best_f}")

```

Solving KKT system...

Found 4 candidate points. Filtering for optimality...

Point (x1, x2)	Multipliers	Objective	Status
(0.2500, 0.7500)	L1=-1.0000, L2=-0.2500	-0.6250	Invalid (lambda < 0)
(0.5000, 0.5000)	L1=-1.0000, L2=0.0000	-0.5000	Invalid (lambda < 0)
(-0.2500, 0.2500)	L1=0.0000, L2=-0.2500	-0.1250	Invalid (x < 0)
(0.0000, 0.0000)	L1=0.0000, L2=0.0000	-0.0000	Valid

Optimal Solution: x1 = 0.0, x2 = 0.0

Max Objective Value = -0.0

Example 3: Minimize $f(x_1, x_2) = 2x_1 + 6x_2$ subject to $x_1 - x_2 \leq 0$; $x_1^2 + x_2^2 \geq 4$;
 $x_1, x_2 \geq 0$.

Mathematical Formulation for **Sympy** requires constraints to be in the form $g(x) \geq 0$. We must rearrange the given inequalities: - *Objective:* Minimize $f(x) = 2x_1 + 6x_2$ - *Constraint 1:* $x_1 - x_2 \leq 0 \implies x_2 - x_1 \geq 0$ - *Constraint 2:* $x_1^2 + x_2^2 \geq 4 \implies x_1^2 + x_2^2 - 4 \geq 0$ - *Bounds:* $x_1, x_2 \geq 0$

```
import sympy as sp

# 1. Define Symbols
x1, x2 = sp.symbols('x1 x2', real=True)
lam1, lam2 = sp.symbols('lambda1 lambda2', real=True)

# 2. Define Objective (Minimization)
f = 2*x1 + 6*x2

# 3. Define Constraints in Standard Form (g(x) <= 0)
# Constraint 1: x1 - x2 <= 0
g1 = x1 - x2

# Constraint 2: x1^2 + x2^2 >= 4 --> 4 - x1^2 - x2^2 <= 0
g2 = 4 - x1**2 - x2**2

# 4. Formulate Lagrangian (Minimization: L = f + sum(lambda * g))
L = f + lam1 * g1 + lam2 * g2

# 5. KKT Equations
```

```

# A. Stationarity (Gradient of L = 0)
eq_x1 = sp.diff(L, x1)
eq_x2 = sp.diff(L, x2)

# B. Complementary Slackness (lambda * g = 0)
eq_slack1 = lam1 * g1
eq_slack2 = lam2 * g2

# 6. Solve the System
print("Solving KKT system equations...")
# This solves for stationary points and intersection points
solutions = sp.solve([eq_x1, eq_x2, eq_slack1, eq_slack2], (x1, x2, lam1, lam2), dict=True)

# 7. Filter & Validate Solutions
print(f"\nFound {len(solutions)} candidate points. Validating KKT conditions...")
print("-" * 85)
print(f"{'Point (x1, x2)':<20} | {'Multipliers':<20} | {'Cost':<10} | {'Status':<10}")
print("-" * 85)

optimal_val = float('inf')
optimal_sol = None

for sol in solutions:
    # Extract values (convert to float for comparison)
    x1_v = float(sol[x1])
    x2_v = float(sol[x2])
    l1_v = float(sol[lam1])
    l2_v = float(sol[lam2])

    # Validation Logic
    status = "Valid"

    # 1. Domain Check (x >= 0)
    if x1_v < -1e-7 or x2_v < -1e-7:
        status = "Invalid (x < 0)"

    # 2. Primal Feasibility (g <= 0)
    # Check g1: x1 - x2 <= 0
    elif (x1_v - x2_v) > 1e-7:
        status = "Invalid (g1 > 0)"
    # Check g2: 4 - x1^2 - x2^2 <= 0
    elif (4 - x1_v**2 - x2_v**2) > 1e-7:

```

```

        status = "Invalid (g2 > 0)"

# 3. Dual Feasibility (lambda >= 0 for Minimization)
elif l1_v < -1e-7 or l2_v < -1e-7:
    status = "Invalid (lambda < 0)"

# Calculate Cost
cost = 2*x1_v + 6*x2_v

print(f"({x1_v:.4f}, {x2_v:.4f})    | L1={l1_v:.4f}, L2={l2_v:.4f} | {cost:.4f}    | {status}")

if "Valid" in status and cost < optimal_val:
    optimal_val = cost
    optimal_sol = (x1_v, x2_v)

print("-" * 85)
if optimal_sol:
    print(f"\n Optimal Solution: x1 = {optimal_sol[0]:.4f}, x2 = {optimal_sol[1]:.4f}")
    print(f"    Minimum Value = {optimal_val:.4f}")

# Insight for the user
print("\nInsight: The solution lies at the intersection of the line x1=x2 and the circle")

```

Solving KKT system equations...

Found 4 candidate points. Validating KKT conditions...

Point (x1, x2)	Multipliers	Cost	Status
(-0.6325, -1.8974)	L1=0.0000, L2=-1.5811	-12.6491	Invalid (x < 0)
(0.6325, 1.8974)	L1=0.0000, L2=1.5811	12.6491	Valid
(-1.4142, -1.4142)	L1=2.0000, L2=-1.4142	-11.3137	Invalid (x < 0)
(1.4142, 1.4142)	L1=2.0000, L2=1.4142	11.3137	Valid

Optimal Solution: x1 = 1.4142, x2 = 1.4142
Minimum Value = 11.3137

Insight: The solution lies at the intersection of the line $x_1=x_2$ and the circle.

3.5.4 Support Vector Machine (SVM) Theory: A Constrained Optimization Perspective

Introduction & Geometric Intuition

The Support Vector Machine (SVM) is a supervised learning algorithm that finds the optimal hyperplane to separate two classes of data. Unlike other linear classifiers, SVM seeks the **widest possible separation** (margin) between the classes.

The Hyperplane Equation

A hyperplane is defined by the equation:

$$w^T x + b = 0$$

- w : The weight vector (normal to the hyperplane). - b : The bias term (position relative to origin). - x : The feature vector of a data point.

The Concept of the Margin

The “Margin” is the physical distance between the decision boundary and the closest data points (Support Vectors).

- **Positive Boundary:** $w^T x + b = +1$
- **Negative Boundary:** $w^T x + b = -1$

Mathematical Derivation of the Margin

To calculate the width of the margin (M), consider two support vectors, x_+ on the positive boundary and x_- on the negative boundary.

1. Equations:

- $w^T x_+ + b = 1$
- $w^T x_- + b = -1$

2. Difference: Subtracting the second from the first:

$$w^T (x_+ - x_-) = 2$$

3. Projection: The physical distance M is the projection of $(x_+ - x_-)$ onto the unit normal vector $\frac{w}{\|w\|}$:

$$M = (x_+ - x_-) \cdot \frac{w}{\|w\|} = \frac{w^T (x_+ - x_-)}{\|w\|} = \frac{2}{\|w\|}$$

Key Insight: To **maximize** the margin ($M = \frac{2}{\|w\|}$), we must **minimize** the norm of the weight vector ($\|w\|$).

The Constraint: Sign Agreement

For a classifier to be valid, it must correctly classify data points *outside* the margin. * If $y_i = +1$, we require $w^T x_i + b \geq 1$. * If $y_i = -1$, we require $w^T x_i + b \leq -1$.

These two conditions can be compressed into a single inequality:

$$y_i(w^T x_i + b) \geq 1 \quad \forall i$$

This constraint ensures that every point is both correctly classified and located safely outside the “no-man’s land” of the margin.

The Primal Optimization Problem

Minimizing $\|w\|$ involves a square root, which is computationally difficult. Instead, we minimize $\frac{1}{2}\|w\|^2$, which is a convex quadratic function with the same optimum.

Standard Form (Hard Margin SVM):

$$\begin{aligned} \text{Minimize} \quad & f(w, b) = \frac{1}{2}\|w\|^2 \\ \text{Subject to} \quad & y_i(w^T x_i + b) \geq 1, \quad i = 1, \dots, N \end{aligned}$$

Solving via Lagrange Multipliers (KKT Conditions) To solve this constrained problem, we construct the *Lagrangian Function*:

$$\mathcal{L}(w, b, \alpha) = \frac{1}{2}\|w\|^2 - \sum_{i=1}^N \alpha_i [y_i(w^T x_i + b) - 1]$$

where $\alpha_i \geq 0$ are the Lagrange Multipliers.

The Karush-Kuhn-Tucker (KKT) Conditions

For optimality, the following conditions must hold:

1. Stationarity ($\nabla \mathcal{L} = 0$):

- $\nabla_w \mathcal{L} = w - \sum \alpha_i y_i x_i = 0 \implies \mathbf{w} = \sum \alpha_i y_i \mathbf{x}_i$
- $\nabla_b \mathcal{L} = -\sum \alpha_i y_i = 0 \implies \sum \alpha_i y_i = 0$

2. Primal Feasibility:

- $y_i(w^T x_i + b) - 1 \geq 0$

3. Dual Feasibility:

- $\alpha_i \geq 0$

4. Complementary Slackness:

- $\alpha_i[y_i(w^T x_i + b) - 1] = 0$
- *Interpretation:* If $\alpha_i > 0$, the point lies exactly on the margin ($y_i(w^T x + b) = 1$). These points are the **Support Vectors**. If $\alpha_i = 0$, the point is irrelevant to the boundary.

Example Calculation

Data: Class +1 at (2, 2), Class -1 at (0, 0).

1. Lagrangian Formulation:

$$\mathcal{L} = \frac{1}{2}(w_1^2 + w_2^2) - \alpha_1(2w_1 + 2w_2 + b - 1) - \alpha_2(-b - 1)$$

2. Solving:

- From stationarity: $w_1 = 2\alpha, w_2 = 2\alpha$.
- From sum constraint: $\alpha_1 = \alpha_2 = \alpha$.
- From active constraints: $b = -1, w_1 + w_2 = 1$.

3. Result:

- $\alpha = 0.25$
- **Optimal Weights:** $w = [0.5, 0.5]$
- **Optimal Bias:** $b = -1$
- **Margin Width:** $2/||w|| \approx 2.82$

Python solution

```
import sympy as sp

# 1. Define Variables
w1, w2, b = sp.symbols('w1 w2 b', real=True)
lam1, lam2 = sp.symbols('lambda1 lambda2', real=True)

# 2. Define Objective (Minimize 1/2 ||w||^2)
f = 0.5 * (w1**2 + w2**2)

# 3. Define Constraints (g <= 0)
# Constraint for Point A (2, 2): 1 - y(wx+b) <= 0
g1 = 1 - (1 * (2*w1 + 2*w2 + b))
# Constraint for Point B (0, 0): 1 - y(wx+b) <= 0
g2 = 1 - (-1 * (0*w1 + 0*w2 + b))
```



```

# 4. Formulate Lagrangian
L = f + lam1 * g1 + lam2 * g2

# 5. KKT Conditions
# A. Stationarity (Gradient of L = 0)
stat_w1 = sp.diff(L, w1)
stat_w2 = sp.diff(L, w2)
stat_b = sp.diff(L, b)

# B. Complementary Slackness (lambda * g = 0)
slack_1 = lam1 * g1
slack_2 = lam2 * g2

# 6. Solve the System
print("Solving KKT system...")
# We explicitly ask for a dictionary result
solutions = sp.solve([stat_w1, stat_w2, stat_b, slack_1, slack_2],
                     (w1, w2, b, lam1, lam2), dict=True)

# 7. Validate Solutions
print(f"\nFound {len(solutions)} candidate solutions. Validating...")
print("-" * 60)

for sol in solutions:
    # Use .get() to handle cases where a variable is free/undetermined
    # If b is not in solution, it usually implies it's arbitrary in that specific branch
    # (e.g. if w=0, lambda=0, b might not be constrained by stationarity).
    # We default to 0.0 for checking purposes or flag it.
    try:
        val_w1 = float(sol.get(w1, 0))
        val_w2 = float(sol.get(w2, 0))
        val_b = float(sol.get(b, 0))
        val_l1 = float(sol.get(lam1, 0))
        val_l2 = float(sol.get(lam2, 0))
    except TypeError:
        print("Skipping a symbolic/complex solution that couldn't be converted to float.")
        continue

    status = "Valid Optimal Solution"

    # Check Primal Feasibility (g <= 0)
    # Using a small tolerance (1e-6)

```

```

if (1 - 2*val_w1 - 2*val_w2 - val_b) > 1e-6:
    status = "Invalid (Violates Point A Constraint)"
elif (1 + val_b) > 1e-6:
    status = "Invalid (Violates Point B Constraint)"

# Check Dual Feasibility (lambda >= 0)
elif val_l1 < -1e-6 or val_l2 < -1e-6:
    status = "Invalid (Negative Multiplier)"

# Print results
print(f"Solution: w=({val_w1:.4f}, {val_w2:.4f}), b={val_b:.4f}")
print(f"Multipliers: 1={val_l1:.4f}, 2={val_l2:.4f}")
print(f"Status: {status}")
print("-" * 60)

```

Solving KKT system...

Found 3 candidate solutions. Validating...

```

-----
Solution: w=(0.0000, 0.0000), b=0.0000
Multipliers: 1=0.0000, 2=0.0000
Status: Invalid (Violates Point A Constraint)
-----

```

```

-----
Solution: w=(0.0000, 0.0000), b=-1.0000
Multipliers: 1=0.0000, 2=0.0000
Status: Invalid (Violates Point A Constraint)
-----

```

```

-----
Solution: w=(0.5000, 0.5000), b=-1.0000
Multipliers: 1=0.2500, 2=0.2500
Status: Valid Optimal Solution
-----

```

3.5.5 Principal Component Analysis (PCA)

While often viewed as linear algebra, PCA is fundamentally a constrained optimization problem seeking the direction of maximum variance.

The Formulation

- **Objective:** Find a direction vector w that maximizes the variance of the projected data.

$$\text{Maximize } f(w) = w^T \Sigma w$$

(where Σ is the Covariance Matrix)

- **Constraint:** To prevent the vector length from growing infinitely to cheat the maximization, we fix its length to 1.

$$\text{Subject to } g(w) = w^T w - 1 = 0$$

The Lagrangian Solution

We formulate the Lagrangian with multiplier λ :

$$\mathcal{L}(w, \lambda) = w^T \Sigma w - \lambda(w^T w - 1)$$

- **Finding the Optimum:** Differentiating with respect to w yields:

$$2\Sigma w - 2\lambda w = 0 \implies \Sigma w = \lambda w$$

Insight

The optimal direction w is simply the **Eigenvector** of the covariance matrix, and the Lagrange multiplier λ is the **Eigenvalue** (representing the amount of variance).

3.5.6 Ridge Regression (L2 Regularization)

Ridge regression modifies standard least-squares fitting by imposing a budget on the size of the coefficients to prevent overfitting.

The Formulation

- **Objective:** Minimize the sum of squared prediction errors.

$$\text{Minimize } ||y - X\beta||^2$$

- **Constraint:** The total size (squared magnitude) of the coefficients must not exceed a budget t .

$$\text{Subject to } ||\beta||^2 \leq t$$

The Lagrangian Solution

$$\mathcal{L}(\beta, \lambda) = ||y - X\beta||^2 + \lambda(||\beta||^2 - t)$$

- **Resulting Update Rule:** Solving for $\nabla \mathcal{L} = 0$ gives the famous closed-form solution:

$$\hat{\beta} = (X^T X + \lambda I)^{-1} X^T y$$

i Insight:

The regularization parameter λ used in code is actually the Lagrange Multiplier corresponding to the weight constraint.

3.5.7 Maximum Entropy Models (MaxEnt)

Used in Natural Language Processing and ecology, **MaxEnt** seeks the most “unbiased” probability distribution that still fits the observed data.

The Formulation

- **Objective:** Maximize the Entropy (uncertainty) of the distribution $p(x)$.

$$\text{Maximize } H(p) = -\sum p(x) \log p(x)$$

- **Constraints:**

1. **Normalization:** The probabilities must sum to 1.

$$\sum p(x) = 1$$

2. **Feature Matching:** The expected value of features in our model must match the empirical averages seen in the training data.

$$\sum p(x) f_i(x) = \mathbb{E}_{data}[f_i]$$

The Lagrangian Solution

Solving this Lagrangian system yields the **Gibbs (Softmax) Distribution**:

$$p(y|x) = \frac{1}{Z} \exp \left(\sum \lambda_i f_i(x, y) \right)$$

i Insights:

This derivation serves as the theoretical foundation for **Logistic Regression** and the final layer of most **Neural Networks**.