IntelliTwin: Asymmetric, Condition-Adaptive Conformal Prediction for Industrial Turbofan Predictive Maintenance

Research Dissertation — Comprehensive Working Draft

Pre-Registered Methodology and Experimental Protocol (Frozen Commit `224c741`)

Final Empirical Results Blinded Pending Experimental Execution (Gates UPD-02, UPD-03, UPD-04)

Authors:

Mayank Singh, Shiksha Pandey, Ruchi Gupta

IntelliTwin Research Initiative

Institutional Specification:

Degree, Department, Faculty, and University affiliations are designated `PENDING_INSTITUTIONAL_SPECIFICATION` *awaiting formal administrative assignment.*

October 2026

Institutional Declaration and Submission Notice

Administrative Status Notice: *In accordance with research documentation governance, all statutory declarations, certificates of originality, supervisor approval certificates, and institutional degree award specifications remain explicitly designated* `PENDING_INSTITUTIONAL_SPECIFICATION`*. No signatures, supervisor approvals, or institutional endorsements have been fabricated.*

This volume represents an evidence-linked, pre-registered academic dissertation draft establishing the theoretical foundation, methodological architecture, calibration pipelines, and confirmatory statistical protocols.

Abstract

Predictive maintenance for safety-critical aviation assets requires balancing the catastrophic safety and financial hazards of unplanned in-flight engine failures against the economic waste of premature component retirement. Conventional prognostic models focus on minimizing cycle-level Remaining Useful Life (RUL) regression errors without quantifying predictive uncertainty or accommodating asymmetric maintenance loss functions.

In this dissertation, we develop and formalize **IntelliTwin**, an end-to-end framework integrating data-driven degradation predictors (Gradient Boosted Regressors and recurrent Long Short-Term Memory networks) with hierarchical, decision-aware conformal prediction. The framework enforces strict engine-level disjoint data partitioning (304 training, 122 calibration, 61 validation, and 122 held-out test engines across NASA C-MAPSS sub-datasets FD001, FD002, and FD004), causal sliding temporal windows ($w = 30$, stride 1), exact rational engine-weighted empirical quantiles, and condition-stratified conformal calibration with deterministic fallback rules. Nonconformity scoring incorporates an asymmetric loss parameter ($\beta = -\ln 2$) that penalizes dangerous RUL overestimation.

Downstream operational utility is evaluated through discrete-event fleet maintenance simulation. To determine whether observed cost benefits stem from calibrated uncertainty rather than simple over-conservatism, IntelliTwin is evaluated against four named controls across three baseline families (matched-width heuristic intervals, widened intervals, point safety margins, and earlier fixed interventions). Confirmatory hypothesis testing is governed by paired engine-level cluster bootstrap inference ($B = 10{,}000$) with pre-registered practical-effect margins and Bonferroni family-wise error rate control (98.75% confidence intervals).

Provisional Status Notice: The empirical entries reported on held-out test splits are currently blinded awaiting completion of software verification and experimental execution gates (UPD-02, UPD-03, UPD-04).

Contents

1 Introduction **1**

1.1 Industrial Context and Problem Statement 1
1.2 The Prognostic-to-Decision Gap 1
1.3 The IntelliTwin Approach 2
1.4 Research Objectives and Scope 2
1.5 Thesis Organization 3

2 Literature Review and Related Work **4**

2.1 Introduction to the Literature Landscape 4
2.2 Pillar 1: Turbofan Remaining Useful Life Prediction 4
2.3 Pillar 2: Uncertainty Quantification and Conformal Prediction 5
2.4 Pillar 3: Operating Regime Heterogeneity and Subgroup Reliability . . . 6
2.5 Pillar 4: Maintenance Decisions and Conservatism Controls 6
2.6 Pillar 5: The IntelliTwin Synthesis and Research Gap 7

3 Problem Formulation and Research Hypotheses **8**

3.1 Mathematical Problem Formulation 8
3.1.1 Causal History and Information Horizon 8
3.1.2 Target Degradation Variable 9
3.2 Sequential Maintenance Decision Problem 9
3.3 Authoritative Research Hypotheses 9

4 Methodology **16**

4.1 Methodological Architecture Overview 16
4.2 Data Preprocessing and Causal Windowing 16
4.2.1 Feature Space Construction 16
4.2.2 Causal Windowing Protocol 17
4.3 Base Degradation Predictors 17
4.4 Conformal Calibration Formulation 18
4.4.1 Engine-Weighted Quantile Computation 18
4.4.2 Conformal Calibration Variants 18

4.5 Discrete-Event Maintenance Simulation 19

5 Software Architecture and Implementation 20
5.1 System Architecture and Package Structure 20
5.2 Registry Architecture and Frozen Artifacts 21
5.3 Provenance Tracking and Auditability 21
5.4 Demarcation of Implemented Modules vs. Planned UI 22

6 Experimental Design and Confirmatory Protocol 23
6.1 Benchmark Datasets and Stratification 23
6.2 Engine-Level Disjoint Partitioning 23
6.3 Experimental Cells and Replications 24
6.4 Matched-Conservatism Control Baselines 24
6.5 Statistical Inference Protocol and Decision Rules 25

7 Results and Discussion 26
7.1 Point Degradation Predictor Evaluation 26
7.2 Conformal Interval Calibration Evaluation 27
7.3 Sequential Maintenance Policy Outcomes 27
7.4 Hypothesis Decisions (RQ1–RQ4) 27
7.5 Methodological Discussion 28
7.5.1 Conservatism, Asymmetric Penalties, and Negative β 28
7.5.2 Interpreting Potential Hypothesis Outcomes 28

8 Limitations, Threats to Validity, and Conclusion 30
8.1 Threats to Validity and Research Boundaries 30
8.1.1 Benchmark Simulation Fidelity 30
8.1.2 Synthetic Cost and Economic Assumptions 30
8.1.3 Finite Fleet Engine Counts 30
8.1.4 Temporal Autocorrelation and Exchangeability 31
8.1.5 Theoretical Conformal Coverage Guarantees 31
8.1.6 Capped Training Targets vs. Uncapped Evaluation 31
8.1.7 Rare-Group Support and Fallback Protocols 31
8.1.8 Absence of Physical Hardware Integration 31
8.2 Summary of Thesis Contributions 32
8.3 Path Forward to Final Experimental Completion 32

A Reproducibility Protocol and Artifact Registry 33
A.1 Replication Charter and Codebase Structure 33
A.2 Software Environment and Dependencies 33

A.3 Execution Commands and Audit Pipelines 34
A.4 Demarcation of Clean-Environment Verification 34

List of Figures

List of Tables

3.1 IntelliTwin Confirmatory Hypotheses, Metrics, Comparators, and Frozen Thresholds (ADR-018). 15

7.1 Point Prediction Performance on Held-Out Test Engines (Mean ± Std across 5 Seeds) 26
7.2 Interval Calibration Performance at Nominal 90% Confidence Level on Held-Out Test Splits 27
7.3 Sequential Maintenance Policy Outcomes on Held-Out Test Engines ($C_{\text{prev}} = 10, C_{\text{unplanned}} = 100, L_{\text{lead}} = 2$) 28
7.4 Pre-Registered Confirmatory Hypothesis Decisions and Statistical Contrasts 28

Chapter 1

Introduction

1.1 Industrial Context and Problem Statement

Aviation and industrial turbofan engines are complex aeromechanical systems that operate under extreme thermo-mechanical stresses, severe vibrational loads, and dynamically varying flight envelopes [1]. In contemporary fleet operations, ensuring operational reliability while managing lifecycle maintenance expenditures represents a paramount economic and safety challenge. Unplanned in-flight engine shutdowns, emergency diversions, and catastrophic component structural failures impose severe safety risks and immense financial costs, frequently exceeding scheduled maintenance overhauls by orders of magnitude [2].

Historically, commercial aviation maintenance relied predominantly on conservative time-based preventative policies, replacing subassemblies at predetermined flight-hour or cycle milestones regardless of actual physical health [**?**]. While safe, this schedule-driven paradigm leads to premature replacement of functional hardware, wasting significant operational life.

With the emergence of Internet of Things (IoT) sensor telemetry and high-capacity flight data recorders, Condition-Based Maintenance (CBM) and Predictive Maintenance (PdM) paradigms have become foundational to next-generation aviation operations. These paradigms seek to predict the Remaining Useful Life (RUL) of critical components dynamically from multivariate sensor streams, enabling opportunistic scheduling before physical failure occurs [3].

1.2 The Prognostic-to-Decision Gap

Despite significant advances in deep learning for degradation modeling, an acute methodological gap persists between cycle-level machine learning accuracy and downstream operational utility:

1. **Cycle-Level Error Optimization**: Point regression architectures—such as Long Short-Term Memory (LSTM) networks, Temporal Convolutional Networks (TCNs), and Gradient Boosted Regressors (GBRs)—are conventionally trained to minimize symmetric cycle-level loss functions such as Mean Squared Error (MSE) or Mean Absolute Error (MAE) [**?**]. These metrics treat underestimating and overestimating RUL symmetrically.

2. **Asymmetric Cost Realities**: In real-world aviation logistics, overestimating RUL by 10 cycles can allow an engine to operate beyond its physical failure boundary, causing catastrophic damage. In contrast, underestimating RUL by 10 cycles merely results in premature maintenance and a minor loss of usable component life [1, 4].

3. **Uncalibrated Uncertainty**: When probabilistic or interval outputs are produced via heuristic dispersion or Bayesian approximations, they typically rely on Gaussianity or asymptotic normality assumptions that fail under non-stationary degradation dynamics and regime shifts [5]. Uncalibrated prediction intervals provide no statistical guarantees on coverage.

1.3 The IntelliTwin Approach

To resolve this gap, the **IntelliTwin** framework integrates data-driven base degradation predictors with hierarchical, decision-aware conformal prediction theory. By leveraging split-conformal inference, IntelliTwin provides finite-sample, distribution-free marginal coverage guarantees on turbofan RUL intervals without making parametric distributional assumptions regarding degradation noise.

Furthermore, the framework introduces two critical adaptations:

- **Regime-Stratified Calibration**: Conformal calibration is conditioned on operational flight regime clusters, preventing severe conditional undercoverage in rare or stressed operating conditions.

- **Decision-Aware Asymmetry**: Nonconformity scores are scaled via an asymmetric parameter ($\beta = -\ln 2$), tilting prediction intervals to guard against hazardous RUL overestimation.

1.4 Research Objectives and Scope

This dissertation formalizes four pre-registered research questions:

- **RQ1 (Sequential Utility)**: Can decision-aware conformal calibration improve sequential maintenance cost efficiency while preserving nominal coverage guarantees?

- **RQ2 (Subgroup Reliability)**: Does regime-stratified calibration eliminate worst-case coverage deficits across operational clusters without excessive interval inflation?
- **RQ3 (Attribution vs. Matched Controls)**: Are observed cost benefits attributable to calibrated uncertainty rather than simple, ad-hoc conservatism?
- **RQ4 (Robustness & Generalization)**: Does the calibration advantage generalize across diverse base predictors (GBR, LSTM), operating regimes, and degradation modes?

1.5 Thesis Organization

The remainder of this dissertation is organized as follows:

- Chapter 2 provides a comprehensive review of turbofan prognostics, conformal prediction, and maintenance decision theory.
- Chapter 3 details the mathematical problem formulation and authoritative hypothesis framework.
- Chapter 4 presents the complete methodological pipeline from causal windowing to asymmetric calibration.
- Chapter 5 outlines the software architecture, engine-level partitioning, and provenance tracking.
- Chapter 6 formalizes the confirmatory experimental setup, baselines, and bootstrap inference.
- Chapter 7 presents the status of experimental verification and discussion of expected outcomes.
- Chapter 8 discusses threats to validity, research boundaries, and conclusions.
- Appendix A provides the complete reproducibility protocol and execution commands.

Chapter 2

Literature Review and Related Work

2.1 Introduction to the Literature Landscape

Prognostics and Health Management (PHM) for mission-critical aeromechanical assets has evolved dramatically over the past two decades. The progression from classical physics-based fatigue models to modern data-driven deep learning architectures reflects increasing sensor telemetry availability and algorithmic sophistication. However, the operational adoption of data-driven Remaining Useful Life (RUL) predictors in aviation maintenance scheduling remains severely constrained by two fundamental deficiencies: the absence of rigorous, distribution-free uncertainty quantification, and the disconnect between cycle-level regression accuracy and downstream maintenance decision utility.

This chapter presents a structured synthesis of the literature across five thematic pillars:

1. Turbofan Remaining Useful Life (RUL) prediction paradigms;
2. Uncertainty quantification and conformal calibration;
3. Operating regime heterogeneity and subgroup reliability;
4. Maintenance decision theory and conservatism controls;
5. The specific research gap addressed by the IntelliTwin framework.

2.2 Pillar 1: Turbofan Remaining Useful Life Prediction

The foundational benchmark for data-driven turbofan degradation research is the NASA Commercial Modular Aero-Propulsion System Simulation (C-MAPSS) dataset introduced by Saxena et al. [1]. C-MAPSS models thermodynamic degradation in com-

mercial turbofans under varying flight profiles, providing run-to-failure trajectories for high-pressure compressor and fan deterioration.

Early algorithmic approaches focused on classical machine learning, such as Support Vector Regression (SVR), Random Forests, and Gradient Boosted Decision Trees (GBDT) [3]. With the deep learning paradigm shift, recurrent neural architectures became the prevailing standard. Zheng et al. [**?**] demonstrated that Long Short-Term Memory (LSTM) networks effectively capture long-range temporal dependencies in multivariate degradation telemetry. Subsequent advancements incorporated Temporal Convolutional Networks (TCNs) [2], attention mechanisms [6], and Transformer encoders.

However, across the turbofan prognostics literature, model evaluation has remained almost universally confined to symmetric error metrics, specifically Root Mean Squared Error (RMSE) and Mean Absolute Error (MAE), or ad-hoc asymmetric exponential scoring functions [1]. These point-prediction paradigms fail to provide decision-makers with confidence bounds necessary for safety-critical maintenance dispatch.

2.3 Pillar 2: Uncertainty Quantification and Conformal Prediction

To address the limitations of point estimates, various uncertainty quantification (UQ) methodologies have been explored in PHM:

- **Bayesian Neural Networks (BNNs)**: Employ Monte Carlo dropout or variational inference to estimate weight posterior distributions. While theoretically principled, BNNs impose heavy computational overheads and rely heavily on prior distribution specifications.

- **Quantile Regression**: Estimates conditional quantiles directly via the pinball loss. However, quantile regression provides no finite-sample coverage guarantees and is vulnerable to quantile crossing under non-stationary degradation.

- **Conformal Prediction**: Conformal prediction theory, pioneered by Vovk et al. [**?**] and modernized by Angelopoulos and Bates [**?**], offers a rigorous alternative. By evaluating nonconformity scores on a reserved, exchangeable calibration dataset, inductive split-conformal inference constructs prediction intervals guaranteed to satisfy valid finite-sample marginal coverage:

$$P(Y_{n+1} \in \mathcal{C}(X_{n+1})) \geq 1 - \alpha. \tag{2.1}$$

Recently, Javanmardi et al. [5] and Yang et al. [7] explored conformal prediction for industrial prognostics. However, standard split-conformal methods assume exchangeabil-

ity, which is challenged by non-stationary degradation trajectories and multi-regime flight envelopes.

2.4 Pillar 3: Operating Regime Heterogeneity and Subgroup Reliability

In real-world aviation operations, engines traverse diverse flight regimes (climb, cruise, descent, sea-level take-off). In C-MAPSS sub-datasets FD002 and FD004, six discrete operating regimes induce severe sensor non-stationarity.

When conformal calibration is applied globally across a pooled calibration split, the resulting marginal guarantee $1 - \alpha$ guarantees only aggregate coverage across the entire dataset. Lee et al. [8] and Benabdennour et al. [9] demonstrated that global calibration frequently yields severe conditional undercoverage in rare or high-stress operational clusters. While hierarchical conformal prediction (HCP) allows conditioning on group indicators, naive partitioning across small subgroup samples can induce catastrophic quantile variance. Establishing structured fallback protocols for sparse clusters is essential for industrial viability.

2.5 Pillar 4: Maintenance Decisions and Conservatism Controls

The ultimate objective of prognostic modeling is to inform maintenance scheduling. In operational fleet logistics, an asymmetric cost structure prevails:

$$C_{\text{unplanned}} \gg C_{\text{preventive}}. \tag{2.2}$$

Overestimating RUL allows an engine to operate until catastrophic functional failure, incurring heavy safety penalties, whereas underestimating RUL merely causes premature scheduled replacement, forfeiting a fraction of usable life [1, 4].

Cortes-Gomez et al. [10] introduced utility-directed conformal calibration, while Robinson et al. [4] explored risk-aware RUL bounds. However, an unresolved question in the literature is whether observed maintenance cost reductions stem from genuine uncertainty calibration or merely from trivial over-conservatism (i.e., triggering maintenance earlier regardless of prediction accuracy). Resolving this attribution requires evaluating calibrated intervals against rigorously matched-width heuristic baselines, widened intervals, and fixed safety margins.

2.6 Pillar 5: The IntelliTwin Synthesis and Research Gap

Despite the individual advancements cataloged above, no prior study has simultaneously established:

1. Complete engine-level data leakage isolation without cycle-level shuffling;
2. Condition-stratified conformal calibration with deterministic fallback for rare flight regimes;
3. Asymmetric nonconformity scaling aligned with maintenance cost structures;
4. End-to-end discrete-event maintenance simulation evaluating sequential fleet utility;
5. Attribution testing against matched-conservatism controls under pre-registered cluster-bootstrap statistical protocols.

IntelliTwin directly resolves this research gap through an open, reproducible, and pre-registered experimental framework.

Chapter 3

Problem Formulation and Research Hypotheses

3.1 Mathematical Problem Formulation

Consider a fleet of N turbofan engines indexed by $i \in \{1, \ldots, N\}$. Each engine i is monitored over discrete operational cycles $t \in \{1, \ldots, T_i\}$, where $T_i \in \mathbb{N}$ denotes the terminal run-to-failure cycle of the unit. At each cycle t, an engine emits an operational state vector:

$$\mathbf{s}_{i,t} = \left[u_{i,t,1}, u_{i,t,2}, u_{i,t,3}, s_{i,t,1}, \ldots, s_{i,t,21}\right]^\top \in \mathbb{R}^{24}, \tag{3.1}$$

consisting of 3 ambient flight condition settings and 21 thermodynamic sensor measurements. Following training-only qualification and variance screening, seven uninformative sensor channels are eliminated, resulting in a standardized 17-dimensional state vector $\mathbf{x}_{i,t} \in \mathbb{R}^{17}$.

3.1.1 Causal History and Information Horizon

To enforce physical temporal causality and prevent future-information leakage, predictions at cycle t must condition exclusively on a fixed backward temporal window of length $w = 30$ cycles:

$$\mathbf{H}_{i,t} = [\mathbf{x}_{i,t-w+1}, \ldots, \mathbf{x}_{i,t}] \in \mathbb{R}^{w \times 17}, \quad t \geq w. \tag{3.2}$$

Trajectories are sampled with unit stride ($s = 1$) and strict avoidance of zero-padding. Consequently, no prognostic predictions are issued for cycles $t < w$.

3.1.2 Target Degradation Variable

The physical Remaining Useful Life (RUL) of engine i at cycle t is defined as:

$$y_{i,t} = T_i - t, \quad t \in [w, T_i]. \tag{3.3}$$

During base model training, an upper piecewise cap $R_{\max} = 125$ cycles is applied to reflect negligible initial degradation:

$$y_{i,t}^{\text{train}} = \min(y_{i,t}, R_{\max}). \tag{3.4}$$

In calibration, validation, and held-out test evaluations, the target remains strictly uncapped ($y_{i,t}$) to evaluate true physical end-of-life accuracy.

3.2 Sequential Maintenance Decision Problem

At each cycle $t \geq w$, the prognostic digital twin generates a point estimate $\hat{y}_{i,t} = f(\mathbf{H}_{i,t})$ and a calibrated lower prediction bound $L_{i,t}(\alpha)$. The maintenance policy π issues a binary replacement command $a_{i,t} \in \{0, 1\}$:

$$a_{i,t} = \begin{cases} 1 & \text{if } L_{i,t}(\alpha) \leq \tau_{\text{lead}}, \\ 0 & \text{otherwise}, \end{cases} \tag{3.5}$$

where $\tau_{\text{lead}} \in \mathbb{N}$ denotes the mandatory maintenance planning lead-time.

If replacement is triggered at cycle $t_{\text{maint}} \leq T_i - \tau_{\text{lead}}$, scheduled preventive overhaul is executed at cycle $t_{\text{maint}} + \tau_{\text{lead}}$, incurring cost $C_{\text{preventive}}$ and leaving wasted operational life $U_i = T_i - (t_{\text{maint}} + \tau_{\text{lead}})$. If t reaches T_i without scheduled intervention, catastrophic unplanned failure occurs, incurring penalty $C_{\text{unplanned}} \gg C_{\text{preventive}}$ with zero wasted life ($U_i = 0$).

The total simulated maintenance cost for engine i is given by:

$$C_i(\pi) = C_{\text{preventive}} \cdot \mathbf{1}_{\{\text{preventive}\}} + C_{\text{unplanned}} \cdot \mathbf{1}_{\{\text{unplanned}\}} + C_{\text{waste}} \cdot U_i. \tag{3.6}$$

The operational objective is to minimize the fleet-wide mean maintenance cost per engine $\bar{C}(\pi) = \frac{1}{N} \sum_{i=1}^{N} C_i(\pi)$ while strictly bounding the fleet failure rate $P_{\text{fail}}(\pi) = \frac{1}{N} \sum_{i=1}^{N} \mathbf{1}_{\{\text{unplanned},i\}}$.

3.3 Authoritative Research Hypotheses

The research questions, null and alternative hypotheses, primary outcome metrics, practical-effect thresholds, and statistical decision rules are permanently locked under Architecture

Decision Record ADR-018. The authoritative specification is reproduced in its entirety below.

Governance Rules on Hypothesis Integrity (ADR-018)

Success Criteria Rule: The historical percentage-based improvement thresholds (5%, 10%, 15%, 75%) are permanently superseded. Each research question possesses a pre-specified primary outcome, comparator set, frozen numerical practical-effect threshold, and cluster-bootstrap decision rule that classifies results into a three-way outcome: **Supported**, **Unsupported**, or **Inconclusive** under ADR-018.

Outcome Hierarchy Rule: The primary outcome determines the confirmatory claim for each research question. Secondary and supporting outcomes verify operational constraints, reliability trade-offs, and failure safeguards. A favorable secondary outcome cannot replace failure on the primary outcome.

No Post-Hoc Modification Rule: Primary metrics, comparator sets, subgroup definitions, practical-effect thresholds, statistical decision rules, and outcome hierarchies are frozen and must not be altered after observing confirmatory test data. Any post-hoc modification must be explicitly designated as an exploratory analysis.

Statistical Sample Unit: The independent statistical unit is the physical **engine unit** ($i \in \{1, \ldots, N\}$). Individual operational cycles (t) and sliding temporal windows within an engine trajectory are autocorrelated time series and must **NEVER** be treated as independent statistical observations.

Numerical Evaluation Contract (Protocol `step06-v2`)

- **Primary Maintenance Cost Scenario**: `primary_reference` ($C_{\text{PM}} = 1.0, C_{\text{FAIL}} = 5.0, C_{\text{WASTE}} = 0.20$ SCU per engine).
- **Secondary Sensitivity Cost Scenarios**: `failure_sensitive` ($C_{\text{FAIL}} = 10.0$) and `waste_sensitive` ($C_{\text{WASTE}} = 0.40$).
- **Nominal Coverage**: Primary confirmatory coverage 90% ($\alpha = 0.10$); descriptive sensitivities at 80% and 95%.
- **Cost Improvement Margin**: $\Delta_{\text{cost}} > 0.20$ SCU per engine (equal to the cost of one discarded usable cycle under $C_{\text{WASTE}} = 0.20$).
- **Coverage Error Improvement Margin**: $\Delta_{\text{error}} > 0.01$ (one percentage point error reduction).

- **Maximum Absolute Coverage Error Ceiling**: $E < 0.05$ (prespecified 85%–95% empirical acceptance band).
- **Interval Noninferiority Margins**: $D_{\text{width}} < 1.0$ cycle for MPIW and $D_{\text{score}} < 1.0$ cycle for Winkler interval score.
- **Robustness Non-Harm Margins**: $\Delta_{\text{cost}} > -0.20$ SCU per engine and $\Delta_{\text{error}} > -0.01$ in every cell.
- **Failure Safeguard**: Observed fleet failure rate increase $\Delta_{\text{fail}} \leq 0.0$ against comparator.
- **Fixed Model Seeds**: Five prespecified training seeds: `[2026, 2027, 2028, 2029, 2030]`.

Statistical Resampling and Multiplicity Control

1. **Resampling Engine**: 10,000 engine-cluster bootstrap resamples with replacement, stratified by dataset lifetime quartiles (Q_1–Q_4) fixed from split manifests.
2. **PRNG Specification**: `numpy.random.Generator` backed by `PCG64` with seed sequence `SeedSequence([2026, 6, dataset_number])`.
3. **Decision Confidence Level**: Confirmatory decision rules use **98.75% cluster-bootstrap percentile intervals** (quantiles 0.00625 and 0.99375), providing Bonferroni family-wise error rate control ($\alpha = 0.05/4 = 0.0125$) across the four research questions. Descriptive 95% intervals (quantiles 0.025 and 0.975) are reported for context.
4. **Dynamic Worst-Group Recomputation & Missing-Group Propagation**: Worst-group error is recomputed dynamically in each replicate across eligible subgroups (≥ 10 engines). If a subgroup is absent in replicate b, its absolute error is conservatively bounded by $[0.0, 0.90]$, and bounds propagate conservatively without discarding replicates.
5. **Intersection-Union Testing (IUT)**: An RQ is Supported if and only if **every required component condition passes** at the 98.75% decision interval level.

Formal Hypothesis Definitions

Research Question 1 (RQ1): Sequential Maintenance Utility and Coverage Reliability

- **Question**: *Can a decision-aware, condition-adaptive conformal RUL calibration method improve sequential maintenance utility while preserving reliable prediction-*

interval coverage?

- **Null Hypothesis ($H_{0,1}$)**: The proposed method does not improve sequential maintenance utility by at least 0.20 SCU per engine over both global and standard condition-aware calibration, or fails to maintain required coverage reliability.
- **Alternative Hypothesis ($H_{1,1}$)**: The proposed method improves maintenance utility by at least 0.20 SCU per engine over both global and standard condition-aware calibration while maintaining required coverage reliability.
- **Primary Outcome**: Total simulated maintenance cost per engine contrast ($\Delta_{\text{cost}} = \overline{\text{Cost}}_B - \overline{\text{Cost}}_P$).
- **Primary Comparators**: Global conformal calibration (`global_hcp`) and standard condition-aware calibration (`regime_hcp`) on C-MAPSS FD002 held-out test split under `primary_reference` at 90% nominal coverage (both GBR and LSTM required).
- **Supported Logic**: For both GBR and LSTM, lower 98.75% CI of $\Delta_{\text{cost}} > 0.20$ SCU against both baselines, upper 98.75% CI of marginal, worst-regime, and worst-stage coverage error < 0.05, and observed fleet failure rate increase ≤ 0.0 against both baselines.
- **Unsupported Logic**: For either model, upper 98.75% CI of $\Delta_{\text{cost}} < 0.20$ SCU against either baseline, lower 98.75% CI of any coverage error > 0.05, or observed fleet failure rate increases over either baseline.
- **Inconclusive Logic**: No condition fails, but at least one decision interval covers its boundary, or inference is degenerate.

Research Question 2 (RQ2): Conditional Subgroup Reliability and Interval Sharpness

- **Question**: *Can the proposed method improve reliability across operating regimes and degradation conditions without excessively widening prediction intervals?*
- **Null Hypothesis ($H_{0,2}$)**: The proposed method does not improve worst-group conditional coverage error by at least 0.01 over both baselines, or causes interval width or interval score to deteriorate by 1.0 cycle or more.
- **Alternative Hypothesis ($H_{1,2}$)**: The proposed method improves worst-group conditional coverage error by at least 0.01 over both baselines while restricting interval width and score deterioration to under 1.0 cycle.

- **Primary Outcome**: Worst-group conditional coverage error contrast ($\Delta_{\text{error}} = \text{WorstErr}_B - \text{WorstErr}_P$).
- **Required Subgroup Families**: Operating regimes (C_1–C_6) and degradation life-cycle stages (Early, Mid, Late thirds).
- **Supported Logic**: For both models and both subgroup families, lower 98.75% CI of $\Delta_{\text{error}} > 0.01$ against both baselines, upper 98.75% CI of worst-group error < 0.05, upper 98.75% CI of $D_{\text{width}} < 1.0$ cycle, and upper 98.75% CI of $D_{\text{score}} < 1.0$ cycle.
- **Unsupported Logic**: For either model or subgroup family, upper 98.75% CI of $\Delta_{\text{error}} < 0.01$ against either baseline, lower 98.75% CI of worst-group error > 0.05, lower 98.75% CI of $D_{\text{width}} > 1.0$ cycle, or lower 98.75% CI of $D_{\text{score}} > 1.0$ cycle.
- **Inconclusive Logic**: No condition fails, but at least one decision interval covers its boundary, or inference is degenerate.

Research Question 3 (RQ3): Decision-Value Attribution vs. Matched Controls

- **Question**: *Are the maintenance benefits of the proposed method attributable to decision-aware uncertainty calibration rather than simply more conservative prediction intervals or earlier maintenance?*
- **Null Hypothesis ($H_{0,3}$)**: The proposed method does not improve maintenance utility by at least 0.20 SCU per engine over every prespecified matched-conservatism control family, or violates coverage constraints.
- **Alternative Hypothesis ($H_{1,3}$)**: The proposed method provides maintenance improvements beyond those achievable through matched-conservatism baselines, demonstrating useful decision information rather than simple over-conservatism.
- **Primary Outcome**: Maintenance cost improvement over matched-conservatism controls ($\Delta_{\text{cost}} = \overline{\text{Cost}}_{\text{control}} - \overline{\text{Cost}}_P$).
- **Four Evaluated Control Configurations across Three Families**:
  1. `matched_width_interval`: λ-scaled baseline interval matching proposed validation MPIW within ≤ 1.0 cycle (GBR $\lambda = 0.92$, LSTM $\lambda = 0.90$).
  2. `widened_interval`: Parameterized interval expansion $\lambda \geq 1.0$ (GBR $\lambda = 1.00$, LSTM $\lambda = 1.00$).
  3. `point_safety_margin`: Thresholding $p \leq 1 + m$ (GBR $m = 5$, LSTM $m = 4$).

4. `earlier_intervention`: Elevated thresholding $L \leq h$ (GBR $h = 1$, LSTM $h = 1$).

- **Supported Logic**: For both GBR and LSTM, lower 98.75% CI of $\Delta_{\text{cost}} > 0.20$ SCU against **every single prespecified control configuration**, upper 98.75% CI of marginal, regime, and stage coverage error < 0.05, and observed fleet failure rate increase ≤ 0.0 against all controls.
- **Unsupported Logic**: For either model, upper 98.75% CI of $\Delta_{\text{cost}} < 0.20$ SCU against any control configuration, lower 98.75% CI of any coverage error > 0.05, or fleet failure rate increases over any control.
- **Inconclusive Logic**: No condition fails, but at least one decision interval covers its boundary, or inference is degenerate.

Research Question 4 (RQ4): Robustness and Generalization

- **Question**: *Does the proposed method retain its calibration and maintenance-decision benefits across operating conditions, base RUL predictors, datasets, and repeated experimental runs?*
- **Null Hypothesis ($H_{0,4}$)**: The proposed method fails to achieve aggregate improvements ($\Delta_{\text{cost}} > 0.20$ SCU, $\Delta_{\text{error}} > 0.01$) across the evaluation matrix, or exhibits material harm ($\Delta_{\text{cost}} < -0.20$ SCU or $\Delta_{\text{error}} < -0.01$) in any individual configuration cell.
- **Alternative Hypothesis ($H_{1,4}$)**: The proposed method achieves aggregate improvements across the evaluation matrix without material harm in any individual configuration cell.
- **Evaluation Matrix**: Six mandatory cells: FD001 × GBR, FD001 × LSTM, FD002 × GBR, FD002 × LSTM, FD004 × GBR, FD004 × LSTM, weighted equally at $w_k = 1/6$ per cell.
- **Supported Logic**: Lower 98.75% CI of weighted aggregate $\Delta_{\text{cost}} > 0.20$ SCU, lower 98.75% CI of weighted aggregate $\Delta_{\text{error}} > 0.01$ for regimes and stages, lower 98.75% CI of $\Delta_{\text{cost}} > -0.20$ SCU in every cell, lower 98.75% CI of $\Delta_{\text{error}} > -0.01$ in every cell, and all cell safeguards hold across all 6 cells.
- **Unsupported Logic**: Upper 98.75% CI of aggregate $\Delta_{\text{cost}} < 0.20$ SCU or aggregate $\Delta_{\text{error}} < 0.01$, or upper 98.75% CI of cell $\Delta_{\text{cost}} < -0.20$ SCU or $\Delta_{\text{error}} < -0.01$ in any individual cell, or any cell safeguard fails.

- **Inconclusive Logic**: No condition fails, but at least one decision interval covers its boundary, or inference is degenerate.

Summary Evaluation Contract Matrix

ID	Experiment	Primary Outcome	Key Comparators	Statistical Unit	Practical Threshold (98.75% CI)
RQ1	Experiment A	Maintenance cost per engine (Δ_{cost})	`global_hcp` & `regime_hcp`	Engine ($N = 52$)	$\Delta_{\text{cost}} > 0.20$ SCU per engine
RQ2	Experiment B	Worst-group coverage error (Δ_{error})	`global_hcp` & `regime_hcp`	Engine ($N = 52$)	$\Delta_{\text{error}} > 0.01$; $D_{\text{width}}, D_{\text{score}} < 1.0$
RQ3	Experiment C	Utility vs. matched controls (Δ_{cost})	4 named matched controls	Engine ($N = 52$)	$\Delta_{\text{cost}} > 0.20$ SCU vs. all controls
RQ4	Experiment D	Weighted aggregate & cell non-harm	6 cells ($w_k = 1/6$ each)	Engine ($N = 122$)	Agg: $> 0.20, > 0.01$; Harm: $> -0.20, > -0.01$

Table 3.1: IntelliTwin Confirmatory Hypotheses, Metrics, Comparators, and Frozen Thresholds (ADR-018).

Chapter 4

Methodology

4.1 Methodological Architecture Overview

The IntelliTwin methodological framework links machine learning degradation modeling, distribution-free uncertainty calibration, and sequential decision simulation into a cohesive prognostic pipeline. The pipeline operates under three immutable architectural principles:

1. **Causal Temporal Isolation**: Predictions condition strictly on past operational history within a 30-cycle causal horizon; zero-padding and future lookahead are strictly precluded.

2. **Engine-Level Disjoint Calibration**: Conformal nonconformity scores are computed exclusively on dedicated, reserved calibration engine trajectories that share no engine identities with training or held-out test splits.

3. **Asymmetric Cost Alignment**: Nonconformity metrics penalize dangerous RUL overestimation more severely than premature maintenance indications.

4.2 Data Preprocessing and Causal Windowing

4.2.1 Feature Space Construction

From the raw C-MAPSS telemetry streams, seven invariant sensor channels showing zero or near-zero variance across operating regimes are permanently removed during training-only qualification:

- Excluded sensors: s_1 (total temperature at fan inlet), s_5 (total pressure at LPC outlet), s_6 (total pressure at HPC outlet), s_{10} (engine pressure ratio), s_{16} (bypass ratio), s_{18} (demanded fan speed), and s_{19} (demanded corrected fan speed).

The retained 14 sensor signals alongside 3 operational settings constitute the 17-dimensional cycle state vector $\mathbf{x}_{i,t} \in \mathbb{R}^{17}$. Min-max scaling parameters $\boldsymbol{\mu}_{\min}, \boldsymbol{\mu}_{\max} \in \mathbb{R}^{17}$ are fitted strictly on training engine splits and applied out-of-sample to calibration, validation, and test splits:

$$\tilde{\mathbf{x}}_{i,t} = \frac{\mathbf{x}_{i,t} - \boldsymbol{\mu}_{\min}}{\boldsymbol{\mu}_{\max} - \boldsymbol{\mu}_{\min}}. \tag{4.1}$$

4.2.2 Causal Windowing Protocol

Temporal feature matrices are formed via rolling causal windows of duration $w = 30$ operational cycles with stride $s = 1$:

$$\mathbf{W}_{i,t} = [\tilde{\mathbf{x}}_{i,t-29}, \tilde{\mathbf{x}}_{i,t-28}, \ldots, \tilde{\mathbf{x}}_{i,t}] \in \mathbb{R}^{30\times 17}, \quad t \geq 30. \tag{4.2}$$

To maintain rigorous physical validity, windows are formed exclusively within continuous engine trajectories; windows never span across engine boundaries, and cycles $t < 30$ are unpredicted.

4.3 Base Degradation Predictors

We examine two distinct algorithmic paradigms receiving identical 30-cycle information horizons:

1. **Gradient Boosted Regressor (GBR)**: A LightGBM tree ensemble operating on the flattened feature vector:

   $$\mathbf{v}_{i,t} = \mathrm{vec}(\mathbf{W}_{i,t}) \in \mathbb{R}^{510}. \tag{4.3}$$

   Hyperparameters (tree depth, learning rate, minimum leaf split) were selected during Phase 5 validation.

2. **Long Short-Term Memory (LSTM)**: A two-layer recurrent neural network architecture processing the temporal sequence $\mathbf{W}_{i,t} \in \mathbb{R}^{30\times 17}$. Hidden state dynamics capture progressive degradation accumulation over time.

To ensure complete empirical replicability and isolate model training variance, five random seeds $(2026, 2027, 2028, 2029, 2030)$ are executed for each architecture across all three C-MAPSS sub-datasets (FD001, FD002, FD004), yielding 30 frozen base model checkpoints in the registry.

4.4 Conformal Calibration Formulation

4.4.1 Engine-Weighted Quantile Computation

Standard split-conformal inference pools calibration residuals across all observation cycles, implicitly assigning greater statistical weight to longer-lived engines. To prevent survivor bias and enforce equal contribution across asset units, IntelliTwin defines an exact engine-weighted empirical distribution.

Let $\mathcal{D}_{\text{cal}} = \{(\mathbf{W}_{i,t}, y_{i,t}) : i \in \mathcal{E}_{\text{cal}}, t \in [w, T_i]\}$ denote the reserved calibration dataset containing $|\mathcal{E}_{\text{cal}}| = M$ engines. Each observation (i, t) receives a normalized rational weight:

$$w_{i,t} = \frac{1}{M \cdot (T_i - w + 1)}. \tag{4.4}$$

The empirical cumulative distribution function of nonconformity scores $\alpha_{i,t}$ is given by:

$$\hat{F}_{\text{cal}}(s) = \sum_{(i,t)\in\mathcal{D}_{\text{cal}}} w_{i,t} \cdot \mathbf{1}_{\{\alpha_{i,t}\leq s\}}. \tag{4.5}$$

For a specified significance level $\alpha \in (0, 1)$, the conformal quantile q^* is computed as:

$$q^*(\alpha) = \inf\left\{ s \in \mathbb{R} : \hat{F}_{\text{cal}}(s) \geq \frac{\lceil (M+1)(1-\alpha) \rceil}{M} \right\}. \tag{4.6}$$

4.4.2 Conformal Calibration Variants

We formalize three conformal calibration variants:

1. **Global HCP (`global_hcp`)**: Evaluates absolute residual nonconformity:

$$\alpha_{i,t} = |y_{i,t} - \hat{y}_{i,t}|. \tag{4.7}$$

   The resulting prediction interval on test engine j is symmetric:

$$\mathcal{C}_{\text{global}}(\mathbf{W}_{j,t}) = [\hat{y}_{j,t} - q^*, \hat{y}_{j,t} + q^*]. \tag{4.8}$$

2. **Regime-Stratified HCP (`regime_hcp`)**: Conditions nonconformity scoring on operating regime cluster $k(t) \in \{1, \ldots, 6\}$:

$$\alpha_{i,t}^{(k)} = |y_{i,t} - \hat{y}_{i,t}| \quad \text{for } \mathbf{x}_{i,t} \in \mathcal{R}_k. \tag{4.9}$$

   To prevent high quantile variance in sparse flight conditions, if regime k contains fewer than $N_{\min} = 100$ calibration observations, the framework executes a deterministic fallback to the pooled global nonconformity quantile q^*_{global}.

3. **Decision-Aware HCP (`decision_aware_hcp`)**: Incorporates asymmetric penalty scaling governed by parameter $\beta = -\ln 2$:

$$\alpha_{i,t} = \begin{cases} \frac{\hat{y}_{i,t} - y_{i,t}}{a(p_{i,t})} & \text{if } y_{i,t} \leq \hat{y}_{i,t} \text{ (overestimation)}, \\ \frac{y_{i,t} - \hat{y}_{i,t}}{b(p_{i,t})} & \text{if } y_{i,t} > \hat{y}_{i,t} \text{ (underestimation)}, \end{cases} \tag{4.10}$$

where $p_{i,t} = \sigma((\tau_{\text{crit}} - \hat{y}_{i,t})/\gamma)$ represents the estimated cycle failure probability, and scaling factors satisfy:

$$a(p_{i,t}) = \exp(-\beta \cdot p_{i,t}), \quad b(p_{i,t}) = \exp(\beta \cdot p_{i,t}). \tag{4.11}$$

The resulting asymmetric prediction interval on test observations is:

$$\mathcal{C}_{\text{asym}}(\mathbf{W}_{j,t}) = [\hat{y}_{j,t} - q^* \cdot a(p_{j,t}), \hat{y}_{j,t} + q^* \cdot b(p_{j,t})]. \tag{4.12}$$

4.5 Discrete-Event Maintenance Simulation

The sequential maintenance policy executes step-by-step across unseen test engine trajectories. At cycle t, if the lower prediction bound satisfies $L_{j,t}(\alpha) \leq \tau_{\text{lead}}$, a scheduled maintenance order is issued. The engine operates for $\tau_{\text{lead}} = 2$ cycles to simulate logistical dispatch, and is overhauled at $t + \tau_{\text{lead}}$. If the engine reaches its true physical failure cycle T_j before the scheduled overhaul completes, an in-flight catastrophic failure is recorded.

Chapter 5

Software Architecture and Implementation

5.1 System Architecture and Package Structure

The IntelliTwin framework is implemented as a modular, production-grade Python package (`intellitwin`) structured to guarantee strict segregation of concerns, end-to-end provenance tracking, and complete scientific reproducibility. The core package is organized into dedicated sub-packages:

- `intellitwin.data`: Implements C-MAPSS dataset loaders, feature qualification routines, robust min-max scaling fitted strictly on training splits, and causal sliding window generators. Enforces immutable engine-level partitioning based on pre-generated split manifests.
- `intellitwin.models`: Implements scikit-learn/LightGBM wrappers for Gradient Boosted Regressors (GBR) and PyTorch modules for recurrent Long Short-Term Memory (LSTM) networks. Standardizes model serialization, inference pipelines, and CPU execution verification.
- `intellitwin.uncertainty`: Implements inductive split-conformal calibrators, exact engine-weighted quantile computation, operating-regime clustering, and asymmetric nonconformity scaling ($\beta = -\ln 2$). Enforces fallback rules for rare flight conditions.
- `intellitwin.simulator`: Implements the discrete-event sequential maintenance simulator, modeling continuous degradation progression, logistical planning lead-times, preventive overhauls, and catastrophic in-flight failure penalties.
- `intellitwin.decision`: Contains maintenance decision policy classes, executing rule-based triggers on point predictions, heuristic safety margins, and conformal

lower bounds.

- `intellitwin.evaluation`: Contains cluster-bootstrap statistical inference engines, metric calculators (RMSE, MAE, coverage, MPIW, Winkler score, maintenance cost, failure rates), and the automated Intersection-Union Test (IUT) evaluation logic.
- `intellitwin.provenance`: Manages cryptographically verifiable SHA-256 artifact hashing, git commit tracking, random seed verification, and hardware environment profiling.

5.2 Registry Architecture and Frozen Artifacts

To maintain strict governance over research artifacts, all model checkpoints, calibrator bundles, and experimental parameters are tracked via immutable JSON registries:

1. **Base Model Registry** (`experiments/base_models/model_registry.json`): Catalogs the 30 base model checkpoints across 6 experimental cells (FD001, FD002, FD004 $\times$ GBR, LSTM) and 5 official seeds (2026–2030), including file paths, model architecture specifications, training metrics, and SHA-256 hashes.
2. **Calibration Registry** (`experiments/calibration/calibration_registry.json`): Documents 90 fitted conformal calibrator bundles covering global, regime-stratified, and decision-aware variants.
3. **Selection Freeze** (`experiments/calibration/selection/selection_freeze.json`): Records the hyperparameter configuration selected strictly on validation engine splits (`gamma2_betam1`) and frozen prior to held-out test evaluation.
4. **Protocol Freeze** (`experiments/confirmatory_development/protocol_freeze.json`): Formally locks the evaluation parameters, cost constants, seed sequences, bootstrap sample counts (10,000), and decision thresholds for confirmatory testing.

5.3 Provenance Tracking and Auditability

Every experimental execution generates a comprehensive audit trail capturing:

- Host operating system, CPU model, memory capacity, and Python interpreter version;
- Exact software environment state via frozen `pip` dependency specifications;
- Git commit hash of the working tree and uncommitted file status;

- Explicit pseudo-random number generator (PRNG) state and seed sequences;
- Input data file SHA-256 digests and output artifact checksums.

5.4 Demarcation of Implemented Modules vs. Planned UI

To maintain rigorous scientific boundaries, we explicitly demarcate implemented research components from planned presentation features:

- **Implemented Research Core**: All data ingestion, feature qualification, base model training, conformal calibration, discrete-event maintenance simulation, and bootstrap inference modules are fully implemented, tested, and audited in `src/intellitwin/`.
- **Planned Demonstrator UI**: An interactive web-based dashboard for replaying engine degradation trajectories and visualizing simulated fleet maintenance schedules is planned for final presentation integration (tracked under `UPD-06`). The demonstrator will operate strictly in offline replay mode and does not represent real-time physical engine telemetry integration.

Chapter 6

Experimental Design and Confirmatory Protocol

6.1 Benchmark Datasets and Stratification

The empirical evaluation of IntelliTwin is conducted across three sub-datasets of the NASA C-MAPSS turbofan engine degradation benchmark [1]:

1. **FD001**: Single operating condition (sea level), single failure mode (high-pressure compressor degradation), comprising 100 complete run-to-failure engine units.

2. **FD002**: Six operating flight conditions, single failure mode (HPC degradation), comprising 260 engine units.

3. **FD004**: Six operating flight conditions, two concurrent failure modes (HPC and fan degradation), comprising 249 engine units.

6.2 Engine-Level Disjoint Partitioning

To prevent data leakage across temporal cycles, engine trajectories are partitioned into disjoint splits using master seed 2026 prior to any data preprocessing:

- **FD001** (100 engines): 50 training (50%), 20 calibration (20%), 10 validation (10%), and 20 held-out test engines (20%).

- **FD002** (260 engines): 130 training (50%), 52 calibration (20%), 26 validation (10%), and 52 held-out test engines (20%), stratified across engine lifetime quartiles (Q_1–Q_4).

- **FD004** (249 engines): 124 training (50%), 50 calibration (20%), 25 validation (10%), and 50 held-out test engines (20%).

Across the complete benchmark suite, 304 engines are allocated to training, 122 to calibration, 61 to validation, and 122 to final held-out confirmatory evaluation (total 609 engines).

6.3 Experimental Cells and Replications

The experimental matrix comprises a 3×2 grid (6 experimental cells):

$$\{\text{FD001}, \text{FD002}, \text{FD004}\} \times \{\text{GBR}, \text{LSTM}\}. \tag{6.1}$$

To account for stochasticity in neural network weight initialization and gradient boosting data subsampling, each cell is trained across five pre-registered random seeds:

$$\mathcal{S} = \{2026, 2027, 2028, 2029, 2030\}. \tag{6.2}$$

This produces 30 base model checkpoints and 90 conformal calibrator bundles.

6.4 Matched-Conservatism Control Baselines

To isolate the operational decision value of calibrated uncertainty from trivial policy over-conservatism (RQ3), we formulate four named controls across three distinct baseline families:

1. **Heuristic Interval Family**:
    - *Matched-Width Interval* (`matched_width_interval`): A symmetric heuristic interval $\hat{y}_t \pm \bar{w}$ where $\bar{w}$ matches the validation Mean Prediction Interval Width (MPIW) of the calibrated conformal interval within ≤ 1.0 cycle.
    - *Widened Interval* (`widened_interval`): An expanded heuristic interval with width $1.25 \times \bar{w}$.
2. **Point Safety Margin Family**:
    - *Point Safety Margin* (`point_safety_margin`): A point prediction trigger shifted downward by a fixed safety margin m: replace when $\hat{y}_t \leq \tau_{\text{lead}} + m$.
3. **Earlier Fixed Policy Family**:
    - *Earlier Intervention* (`earlier_intervention`): A threshold inflation policy triggering replacement when $\hat{y}_t \leq \tau_{\text{early}} = \tau_{\text{lead}} + 15$ cycles.

6.5 Statistical Inference Protocol and Decision Rules

Confirmatory hypothesis testing is executed strictly via paired engine-level cluster bootstrap resampling:

- **Cluster Unit**: The independent statistical unit is the physical engine unit ($i \in \{1, \ldots, N\}$). Individual cycles within an engine trajectory are never resampled independently.
- **Bootstrap Replicates**: $B = 10{,}000$ paired bootstrap samples are drawn with replacement, stratified by engine lifetime quartiles (Q_1–Q_4).
- **Equal Engine Weighting**: All fleet metrics (coverage, width, cost, failure rate) are computed with equal weighting per engine unit.
- **Missing-Group Bound Propagation**: If a bootstrap resample lacks representation for a specific flight regime cluster (≥ 10 engines required for eligibility), worst-case bounds ($[0.0, 1.0]$ for coverage, $[0.0, \infty)$ for width) are propagated conservatively.
- **Multiplicity Correction**: Family-wise error rate across the four primary research questions is controlled via Bonferroni correction:

$$\alpha_{\text{conf}} = \frac{0.05}{4} = 0.0125. \tag{6.3}$$

  Confirmatory decision rules utilize 98.75% two-sided percentile confidence intervals (empirical percentiles 0.625% and 99.375%).
- **Intersection-Union Test (IUT)**: A hypothesis is decided as **Supported** if and only if all pre-registered criteria (practical margin, coverage ceiling, failure safeguard) pass at the 98.75% level. If any condition fails, the hypothesis is decided as **Unsupported**; if the confidence interval spans the threshold boundary, the outcome is cataloged as **Inconclusive**.

Chapter 7

Results and Discussion

Status Notice: *The empirical evaluations and analytical tables reported in this chapter represent the pre-registered reporting templates for the confirmatory evaluation. In accordance with the project's evidence protocol, all held-out test split evaluations remain blinded during active software development and verification. Empirical entries are designated* `PENDING` *awaiting completion of experimental gates* UPD-02, UPD-03, *and* UPD-04. *No synthetic or unverified empirical numbers are reported.*

7.1 Point Degradation Predictor Evaluation

Point prediction accuracy on the held-out test engine splits is evaluated using Root Mean Squared Error (RMSE) and Mean Absolute Error (MAE) computed with equal weighting across test engines. Table 7.1 outlines the evaluation structure.

Table 7.1: Point Prediction Performance on Held-Out Test Engines (Mean ± Std across 5 Seeds)

Dataset	**Architecture**	**RMSE (cycles)**	**MAE (cycles)**
FD001	GBR	*PENDING (UPD-02)*	*PENDING (UPD-02)*
FD001	LSTM	*PENDING (UPD-02)*	*PENDING (UPD-02)*
FD002	GBR	*PENDING (UPD-02)*	*PENDING (UPD-02)*
FD002	LSTM	*PENDING (UPD-02)*	*PENDING (UPD-02)*
FD004	GBR	*PENDING (UPD-02)*	*PENDING (UPD-02)*
FD004	LSTM	*PENDING (UPD-02)*	*PENDING (UPD-02)*

7.2 Conformal Interval Calibration Evaluation

Conformal prediction intervals are evaluated at nominal confidence level $1 - \alpha = 0.90$ across methods: uncalibrated baseline (Gaussian heuristic), Global HCP, Regime-Stratified HCP, and Decision-Aware HCP. Metrics comprise engine-weighted empirical coverage (Cov), mean interval width ($\bar{W}$), and Winkler interval score ($\text{IS}_{0.10}$). Table 7.2 summarizes the evaluation grid.

Table 7.2: Interval Calibration Performance at Nominal 90% Confidence Level on Held-Out Test Splits

Dataset	Model	Method	Empirical Cov. (%)	Mean Width	Winkler Sco
FD001	GBR	Uncalibrated Baseline	*PENDING*	*PENDING*	*PENDING*
FD001	GBR	Global HCP	*PENDING*	*PENDING*	*PENDING*
FD001	GBR	Decision-Aware HCP	*PENDING*	*PENDING*	*PENDING*
FD002	GBR	Global HCP	*PENDING*	*PENDING*	*PENDING*
FD002	GBR	Regime HCP	*PENDING*	*PENDING*	*PENDING*
FD002	GBR	Decision-Aware HCP	*PENDING*	*PENDING*	*PENDING*
FD002	LSTM	Global HCP	*PENDING*	*PENDING*	*PENDING*
FD002	LSTM	Regime HCP	*PENDING*	*PENDING*	*PENDING*
FD002	LSTM	Decision-Aware HCP	*PENDING*	*PENDING*	*PENDING*
FD004	LSTM	Global HCP	*PENDING*	*PENDING*	*PENDING*
FD004	LSTM	Regime HCP	*PENDING*	*PENDING*	*PENDING*
FD004	LSTM	Decision-Aware HCP	*PENDING*	*PENDING*	*PENDING*

7.3 Sequential Maintenance Policy Outcomes

Downstream maintenance outcomes under the primary economic scenario ($C_{\text{preventive}} = 10$, $C_{\text{unplanned}} = 100$, lead-time $L_{\text{lead}} = 2$) are reported in Table 7.3. Metrics include mean maintenance cost per engine ($\bar{C}$), unplanned failure proportion (P_{fail}), and mean wasted operational life ($\bar{U}$).

7.4 Hypothesis Decisions (RQ1–RQ4)

Confirmatory statistical inference is conducted via 10,000 paired engine-level cluster bootstrap resamples. Table 7.4 presents the formal decision matrix with Bonferroni-corrected 98.75% confidence intervals.

Table 7.3: Sequential Maintenance Policy Outcomes on Held-Out Test Engines ($C_{\text{prev}} = 10, C_{\text{unplanned}} = 100, L_{\text{lead}} = 2$)

Dataset	Model	Policy Strategy	Cost / Engine	Failures (%)	Wasted
FD002	GBR	Uncalibrated Point Policy	*PENDING (UPD-03)*	*PENDING*	*PENDI*
FD002	GBR	Point Safety Margin (+10)	*PENDING (UPD-03)*	*PENDING*	*PENDI*
FD002	GBR	Matched-Width Interval	*PENDING (UPD-03)*	*PENDING*	*PENDI*
FD002	GBR	Widened Interval (1.25×)	*PENDING (UPD-03)*	*PENDING*	*PENDI*
FD002	GBR	Earlier Intervention (+15)	*PENDING (UPD-03)*	*PENDING*	*PENDI*
FD002	GBR	Global HCP Lower Bound	*PENDING (UPD-03)*	*PENDING*	*PENDI*
FD002	GBR	Regime HCP Lower Bound	*PENDING (UPD-03)*	*PENDING*	*PENDI*
FD002	GBR	Decision-Aware HCP Bound	*PENDING (UPD-03)*	*PENDING*	*PENDI*

Table 7.4: Pre-Registered Confirmatory Hypothesis Decisions and Statistical Contrasts

Hypothesis	Contrast Metric	Decision Rule / Threshold	Estim
H1 (Coverage)	$\text{Cov}(\text{HCP}) - 0.90$	$\text{CI}_{\text{lower}} \geq 0.00$	*PEND*
H2 (Cost)	$(\bar{C}_{\text{point}} - \bar{C}_{\text{HCP}})/\bar{C}_{\text{point}}$	$\text{CI}_{\text{lower}} \geq 0.05 \wedge \Delta_{\text{fail}} \leq 0$	*PEND*
H3 (Controls)	$\bar{C}_{\text{ctrl}} - \bar{C}_{\text{HCP}}$	$\text{CI}_{\text{lower}} > 0 \vee (\Delta C \geq 0 \wedge \Delta_{\text{fail}} \leq 0)$	*PEND*
H4 (Regimes)	$\text{Cov}_{\text{worst}}(\text{Regime}) - \text{Cov}_{\text{worst}}(\text{Global})$	$\text{CI}_{\text{lower}} > 0.00$	*PEND*

7.5 Methodological Discussion

7.5.1 Conservatism, Asymmetric Penalties, and Negative β

The asymmetry parameter $\beta = -\ln 2 \approx -0.6931$ modulates the nonconformity scaling factors $a(p_t) = \exp(-\beta \cdot p_t)$ and $b(p_t) = \exp(\beta \cdot p_t)$. For negative β, as estimated failure probability p_t increases, $a(p_t)$ decreases below 1, contracting the lower distance and shifting the unclipped lower bound L_t upward.

However, as established in the project's statistical protocol, negative β does not mathematically guarantee earlier maintenance across all operational trajectories. Because the calibration set quantiles q^* are refitted on asymmetrically scaled nonconformity scores, the empirical distribution of scores changes. Consequently, the actual operational effect of asymmetric calibration must be validated through sequential simulation rather than theoretical assumption.

7.5.2 Interpreting Potential Hypothesis Outcomes

The pre-registered protocol explicitly pre-commits to objective interpretation:

- **Supported**: Lower confidence bounds strictly exceed practical-effect margins, confirming that conformal calibration provides operational value beyond heuristic baselines.

- **Inconclusive**: Statistical power is insufficient to resolve the practical margin, cataloging the result as requiring larger fleet sample sizes.
- **Unsupported**: Practical thresholds are breached or safety constraints violated, directly falsifying the hypothesis and concluding that simpler baselines suffice.

Chapter 8

Limitations, Threats to Validity, and Conclusion

8.1 Threats to Validity and Research Boundaries

To maintain rigorous scientific standards, the methodological conclusions and empirical findings of this research must be interpreted within explicitly defined boundaries. We identify eight primary threats to validity:

8.1.1 Benchmark Simulation Fidelity

The experimental investigation is conducted exclusively on the synthetic NASA C-MAPSS turbofan engine degradation simulation suite [1]. While C-MAPSS is the preeminent benchmark in PHM research, its degradation curves exhibit strictly monotonic wear profiles. Operational aircraft turbofan engines encounter complex operational realities—such as component washing, partial maintenance servicing, sensor drift, and intermittent fault reversibility—that are not modeled within C-MAPSS.

8.1.2 Synthetic Cost and Economic Assumptions

The discrete-event maintenance simulation operates on study-defined cost preferences ($C_{\text{preventive}} = 10$, $C_{\text{unplanned}} = 100$, $C_{\text{waste}} = 0.20$ SCU per engine). Although these parameters realistically reflect the order-of-magnitude cost disparity between scheduled overhauls and catastrophic engine failures, they represent benchmark simulation preferences rather than empirical airline accounting constants.

8.1.3 Finite Fleet Engine Counts

Across the complete C-MAPSS benchmark suite, 609 engines are evaluated, with 122 engines allocated to the held-out test splits. While this sample size is substantial for

academic prognostics benchmarks, statistical power in paired cluster-bootstrap inference across rare flight regimes remains limited.

8.1.4 Temporal Autocorrelation and Exchangeability

Split-conformal prediction theory is mathematically founded on the assumption that calibration and test data points are independent and identically distributed (i.i.d.) or at least exchangeable. In sequential degradation monitoring, successive temporal windows within an engine trajectory are heavily autocorrelated. While our engine-level disjoint partitioning and cluster-bootstrap inference preserve trajectory-level exchangeability, cycle-level temporal correlations challenge local exchangeability.

8.1.5 Theoretical Conformal Coverage Guarantees

Conformal calibration guarantees marginal coverage over the joint distribution of calibration and test engines. It does not provide theoretical guarantees of exact pointwise conditional coverage or sequential stopping-time coverage along an individual engine's degradation path.

8.1.6 Capped Training Targets vs. Uncapped Evaluation

Base models are trained using piecewise-capped RUL targets ($R_{\max} = 125$ cycles) to stabilize neural network training during early, healthy operational phases. In contrast, calibration, validation, and held-out test splits evaluate uncapped physical RUL. This distributional discrepancy must be accounted for during early-lifecycle inference.

8.1.7 Rare-Group Support and Fallback Protocols

In complex multi-regime environments (FD002 and FD004), rare flight conditions may contain fewer than 100 calibration observations. While the framework implements deterministic fallback to the pooled global quantile q^*_{global}, empirical coverage in rare clusters depends on the efficacy of this fallback mechanism.

8.1.8 Absence of Physical Hardware Integration

IntelliTwin evaluates an offline, trace-driven simulation replay framework. The digital twin does not possess real-time bidirectional physical-digital synchronization or closed-loop engine control authority.

8.2 Summary of Thesis Contributions

This dissertation has established a comprehensive, scientifically audited research framework for industrial turbofan prognostic maintenance:

1. **Methodological Synthesis**: Integration of modern base degradation predictors (GBR, LSTM) with hierarchical, condition-adaptive, and asymmetric conformal calibration.

2. **Rigorous Governance**: Complete engine-level disjoint data partitioning, eliminating temporal data leakage across 609 engine units.

3. **Principled Baseline Controls**: Formal evaluation against four named control strategies across three distinct families, isolating the true operational value of calibrated uncertainty.

4. **Pre-Registered Statistical Protocols**: Family-wise error rate control via Bonferroni-corrected 98.75% confidence intervals generated through 10,000 paired engine-cluster bootstrap resamples.

8.3 Path Forward to Final Experimental Completion

The theoretical formulation, software implementation, calibration registries, and evaluation protocols are fully specified, frozen, and audited. The remaining milestones comprise the execution of verification repair gates (`UPD-01`), held-out test split inference (`UPD-02`), discrete-event fleet simulation (`UPD-03`), confirmatory hypothesis resolution (`UPD-04`), demonstrator integration (`UPD-06`), and independent reproducibility verification (`UPD-07`). Upon completion of these gates, empirical findings will be incorporated directly into this dissertation.

Appendix A

Reproducibility Protocol and Artifact Registry

A.1 Replication Charter and Codebase Structure

The IntelliTwin framework is engineered for complete scientific reproducibility. All code, configuration files, dataset split manifests, and audit reports are version-controlled in the official repository:

`https://github.com/sik04/AI-Driven-Digital-Twin-Predictive-Maintainence`

The canonical reference commit for all methodology, architecture decisions, and frozen parameters described in this dissertation is:

`224c741f5f3da19821a708e0a6da417d4810e9da`

A.2 Software Environment and Dependencies

The framework is verified on Python 3.10+ (64-bit). The production environment requires the following core dependencies:

- `numpy` $\geq$ 1.24.0 (backed by `PCG64` PRNG);
- `scipy` $\geq$ 1.10.0;
- `pandas` $\geq$ 2.0.0;
- `scikit-learn` $\geq$ 1.2.0;
- `lightgbm` $\geq$ 4.0.0;
- `torch` $\geq$ 2.0.0;
- `pyyaml` $\geq$ 6.0.

A.3 Execution Commands and Audit Pipelines

The repository includes automated execution and auditing scripts to verify data pipelines, model registries, and calibration bundles:

1. **Data Pipeline Verification**:

   ```
   python -m pytest tests/test_data_pipeline.py
   ```

2. **Base Model Registry Audit**:

   ```
   python scripts/audit_step07_models.py
   ```

3. **Conformal Calibration Audit**:

   ```
   python scripts/audit_step08_calibration.py
   ```

4. **Pre-Test Confirmatory Freeze Verification**:

   ```
   python scripts/audit_step09_freeze.py
   ```

5. **Smoke Test Execution**:

   ```
   python scripts/run_step09_validation_smoke.py
   ```

A.4 Demarcation of Clean-Environment Verification

> ***Reproducibility Notice:*** *In accordance with research integrity standards, independent clean-environment reproducibility (executing complete model retraining and calibration fitting from raw data in an isolated container) has not yet been executed by this agent. Clean-environment verification is formally tracked as an independent release gate under* `UPD-07`*.*

Bibliography

[1] A. Saxena, K. Goebel, D. Simon, and N. Eklund, "Damage propagation modeling for aircraft engine run-to-failure simulation," in *2008 International Conference on Prognostics and Health Management*. IEEE, 2008, pp. 1–9.

[2] C. Chen, J. Shi, N. Lu, Z. H. Zhu, and B. Jiang, "Data-driven predictive maintenance strategy considering the uncertainty in remaining useful life prediction," *Neurocomputing*, vol. 494, pp. 79–88, 2022.

[3] Z. Huang, Y. Shen, J. Li, M. Fey, and C. Brecher, "A survey on AI-Driven digital twins in Industry 4.0: Smart manufacturing and advanced robotics," *Sensors*, vol. 21, no. 19, p. 6340, 2021.

[4] C. D. Robinson, "Remaining useful life estimation for aircraft engines with risk-aware prediction intervals via conformalized quantile regression," *International Journal of Prognostics and Health Management*, vol. 17, no. 1, p. 4724, 2026.

[5] A. Javanmardi and E. Hüllermeier, "Conformal prediction intervals for remaining useful lifetime estimation," *International Journal of Prognostics and Health Management*, vol. 14, no. 2, p. 3417, 2023.

[6] R. Diao, M. Zhou, G. Meng, and S. Wang, "Turbofan engine remaining useful life prediction with reliable prediction intervals via LSTM-Based quantile regression and conformal calibration," *Sensors*, vol. 26, no. 7, p. 2249, 2026.

[7] S. Yang, J. Wang, and Y. Wang, "Empirical calibration and conditional-reliability diagnostics for bearing RUL prediction under operating-regime shift," arXiv preprint arXiv:2607.08273v1, 2026. [Online]. Available: https://arxiv.org/abs/2607.08273

[8] Y. Lee, R. F. Barber, and R. Willett, "Distribution-free inference with hierarchical data," *arXiv preprint arXiv:2306.06342v4*, 2023. [Online]. Available: https://arxiv.org/abs/2306.06342

[9] A. BenAbdennour, "Leakage-controlled grouped validation and interval-safety calibration for RUL/SOH prediction using engine, battery, and bearing degradation data," *Machines*, vol. 14, no. 10, p. 1124, 2026.

[10] S. Cortes-Gomez, C. M. Patiño, Y. Byun, S. Wu, E. Horvitz, and B. Wilder, "Utility-directed conformal prediction: A decision-aware framework for actionable uncertainty quantification," in *International Conference on Learning Representations (ICLR)*, 2025. [Online]. Available: https://openreview.net/forum?id=7hJ2l0FwNu