

Process Analysis and Optimization



Submitted by:

Esha Shahzad

RollNumber:

SSP21-CE23

Instructed By:

Prof. Dr. Syed Nadir Hussain

**B.Sc. (Engg.) Chemical Engineering
2021-2025**

Application of Optimization Techniques in Chemical Engineering

Problem 1: Optimization of Plug Flow Reactor (PFR) Design

Objective: To maximize the conversion of a first-order irreversible reaction ($A \rightarrow B$) in a PFR, for a given feed rate and reactor volume using optimization techniques.

Given Parameters (Assumed):

- Reaction: $A \rightarrow B$
- Rate law: $-r_A = kC_A$
- First-order reaction: $k = 0.1 \text{ s}^{-1}$ (assumed)
- Feed flow rate: $F_{A0} = 10 \text{ mol/s}$
- Reactor volume: $V = 100 \text{ L}$

Model Equations:

PFR Design Equation:

$$V = \int (F_{A0} / -r_A) dX$$

Since $-r_A = kC_A = kC_{A0}(1 - X)$, then:

$$V = (F_{A0} / kC_{A0}) * \int (1 / (1 - X)) dX$$

$$V = (F_{A0} / kC_{A0}) [-\ln(1 - X)]$$

Solving for X:

$$X = 1 - \exp(-kC_{A0}V / F_{A0})$$

Optimization Approach:

Objective Function: Maximize X

Constraints:

- Fixed reactor volume V
- Fixed feed rate F_{A0}

As per the equation, conversion X increases with initial concentration C_{A0} .

Therefore, maximize C_{A0} within limits to maximize X.

Result and Conclusion:

Assuming $C_{A0} = 1 \text{ mol/L}$:

$$X = 1 - \exp(-0.1 * 1 * 100 / 10) = 1 - \exp(-1) \approx 0.632$$

Conclusion: Operating at higher C_{A0} increases conversion. Optimization suggests maximizing C_{A0} within design limits.

Problem 2: Optimization of Distillation Column

Objective: To minimize total cost by optimizing the number of theoretical stages (N) and reflux ratio (R).

Cost Components:

1. Capital Cost (CC): Increases with number of stages (N)
2. Operating Cost (OC): Increases with reflux ratio (R)

Optimization Strategy:

Use Underwood-Gilliland Shortcut Method:

- Estimate minimum reflux ratio R_{\min}
- Estimate minimum number of stages N_{\min}
- Apply Gilliland correlation:
$$Y = (N - N_{\min}) / (N + 1)$$
$$X = (R - R_{\min}) / (R + 1)$$

Objective Function:

$$\text{Total Cost (TC)} = \alpha N + \beta R$$

Where:

α = cost per stage

β = cost per unit reflux

Optimization Procedure:

1. Calculate R_{\min} using Underwood equations
2. Vary R from R_{\min} to $2R_{\min}$ and calculate N using Gilliland correlation
3. Calculate TC for each pair (N, R)
4. Choose the combination that minimizes TC

Illustrative Example:

Assume:

- $R_{\min} = 1.5$
- $N_{\min} = 12$
- $\alpha = 1000, \beta = 5000$

Try $R = 1.5, 2.0, 2.5, 3.0$

Calculate corresponding N and TC for each R

Determine the optimal combination (N, R) with minimum TC

Conclusion:

- Higher R decreases N but increases OC
- Higher N reduces R but increases CC
- Optimal point is a balance between capital and operating cost

Usually found near $R = 1.4$ to $1.6 * R_{\min}$

This assignment demonstrates how optimization techniques can be used effectively in chemical reactor and separation process design. Mathematical modeling and trade-off analysis are essential tools in achieving cost-effective engineering solutions.