

Project Configuration Report

TX_Board

Target Device:

Target Part: EFR32MG24B220F1536IM48

Boards:

Target SDK

Simplicity SDK Suite v2025.6.2: Bluetooth 10.1.1, Bluetooth Mesh 9.0.2, Connect 4.1.2, EmberZNet 8.2.2.0, Micrium OS Kernel 5.18.01, OpenThread 2.7.2.0 (GitHub-fb0446f53), Platform 5.2.2.0, RAIL 2.19.2, Sidewalk 2.6.0, Silicon Labs AI/ML 2.1.2, Silicon Labs Matter 2.7.0-1.4, Third Party Hardware Drivers 4.4.1, USB 1.5.1.0, Wi-Fi SDK 3.5.2, Wi-SUN 2.8.0, Z-Wave SDK 7.24.2.0

SDK Version: 2025.6.2

Project Generators

- VS Code (GCC)

Installed Software Components:

- Platform

- Device

- EFR32MG24

- EFR32MG24B220F1536IM48**

- Sources: startup_efr32mg24.c, system_efr32mg24.c

- Configurable: true

- Configs: device.yaml

- Driver

- DMADRV**

- Sources: dmadrv.c

- Configurable: true

- Configs: dmadrv_config.h

- Peripheral

- EMLIB

- USART**

- Sources: em_usart.c

- Configurable: false

- WDOG**

- Sources: em_wdog.c

- Configurable: false

- Radio

RAIL Utility, Initialization

Configurable: true

Configs: sl_rail_util_init_rail_handle_inst_config.h

RAIL Utility, PA

Sources: pa_curves_efr32.c, pa_conversions_efr32.c

Configurable: true

Configs: sl_rail_util_pa_config.h

- Radio Configuration

Custom Radio Configuration for simple rail singlephy application

Configurable: true

Configs: radio_settings.radioconf

- Security

- Memory Protection Unit

Simple MPU

Sources: sl_mpu_s3.c, sl_mpu_s2.c

Configurable: false

- Toolchain

Code Classification

Configurable: false

• Services

- Clock Manager

Clock Manager

Sources: sl_clock_manager_init.c

Configurable: true

Configs: sl_clock_manager_oscillator_config.h, sl_clock_manager_ext_flash_config.h,
sl_clock_manager_tree_config.h

- Device Initialization

Automatic Device Initialization

Configurable: false

- IO Stream

IO Stream: Retarget STDIO

Sources: sl_iostream_retargt_stdio.c

Configurable: false

- Driver

IO Stream: EUSART

Configurable: true

Configs: sl_iostream_eusart_eusart_inst_config.h

- System Setup

System Setup (sl_main)

Configurable: true

Configs: sl_main_start_task_config.h

• Third Party

Tiny printf

Sources: iostream_printf.c, printf.c

Configurable: false

Pins:

Pin #	Pin Name	Function	Custom Pin Name	Software Component
26	PA00			
27	PA01			
28	PA02			
29	PA03			
30	PA04			
31	PA05			
32	PA06			
33	PA07	EUSART0_TX		
34	PA08	EUSART0_RX		
35	PA09			
23	PB00			
22	PB01			
21	PB02			
20	PB03			
19	PB04			
18	PB05			
1	PC00			
2	PC01			
3	PC02			
4	PC03			
5	PC04			
6	PC05			
7	PC06			
8	PC07			
9	PC08			
10	PC09			
48	PD00			
47	PD01			
46	PD02			
45	PD03			
44	PD04			
43	PD05			

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
ACMP0		
ACMP1		
CMU	Clock Manager	
EUSART0		
EUSART1		
GPIO		
HFXO0		
I2C0		
I2C1		
IADC0		
KEYSCAN		
LETIMER0		
LFXO		
MODEM		
PCNT0		
PRS Channel ASYNCH0		
PRS Channel ASYNCH1		
PRS Channel ASYNCH10		
PRS Channel ASYNCH11		
PRS Channel ASYNCH12		
PRS Channel ASYNCH13		
PRS Channel ASYNCH14		
PRS Channel ASYNCH15		
PRS Channel ASYNCH2		
PRS Channel ASYNCH3		
PRS Channel ASYNCH4		
PRS Channel ASYNCH5		
PRS Channel ASYNCH6		
PRS Channel ASYNCH7		
PRS Channel ASYNCH8		
PRS Channel ASYNCH9		
PRS Channel SYNCH0		
PRS Channel SYNCH1		
PRS Channel SYNCH2		
PRS Channel SYNCH3		
PTI		
TIMER0		
TIMER1		
TIMER2		
TIMER3		
TIMER4		
USART0		
VDAC0		
VDAC1		