FPS PvP Dynamics: Agent-Based Modeling and Sensitivity Analysis

CMPLXSYS 531

Silas Falde

April 29, 2026

Abstract

This report presents the development, implementation, and experimental analysis of an agent-based model (ABM) of large-scale first-person shooter (FPS) player-versus-player (PvP) matches. The model simulates heterogeneous players navigating a grid-based environment, engaging in stochastic combat, choosing among multiple weapon profiles, and adapting positioning decisions in pursuit of a shared objective. The goal of the project is not to reproduce a specific commercial game, but to build a controllable synthetic environment where the effects of map structure, weapon balance, and adaptation can be isolated and measured.

Using 1024 Latin Hypercube samples and a variance-based Sobol sensitivity analysis, the project identifies which parameters most strongly influence objective capture progress and therefore the balance between individual combat behavior and team success. The results show that map geometry parameters—wall density, choke probability, and objective radius—have the strongest effects, while stochasticity, cover probability, adaptation rate, and weapon cooldown have moderate effects. Taken together, the model and experiments provide a compact but expressive testbed for studying emergent team dynamics and for reasoning about gameplay balance before deploying changes in a live game.

A separate 100,000-run replication study of the baseline configuration provides a tight estimate of steady-state match behavior: mean objective progress is 0.793 with a 95% confidence interval of [0.791, 0.795], and the final objective controller is split nearly evenly between the two teams. This larger batch confirms that the baseline outcome is statistically stable even though individual matches remain stochastic.

1 Introduction

FPS PvP game balance emerges from the complex interactions of individual player decisions, map constraints, and rule-based systems. An agent-based approach is appropriate for exploring this emergence because macro-level patterns such as fairness, engagement frequency, objective control, and dominant strategies arise from many local decisions rather than from any explicit aggregate rule.

Several prior studies have applied agent-based models to study collective behavior, spatial interactions, and strategic decision-making in socio-technical systems (e.g., generative social science and methodological reviews of ABM). This project builds on that methodological tradition by combining a compact, interpretable rule-based agent design with variance-based sensitivity analysis to identify drivers of macroscopic outcomes. The use of standardized description frameworks (ODD/PARTE) and clear experimental pipelines helps make the model and analyses reproducible and comparable to prior ABM work.

The primary goal of this project is to model these dynamics and use parameter sweeps and sensitivity analysis to identify which game design elements most strongly influence gameplay outcomes. In practice, this means asking questions such as how much of the match outcome is driven by map layout rather than weapon tuning, or whether local learning helps teams capture objectives or distracts them from the objective entirely. This kind of analysis can inform balance decisions and help developers predict the effects of tuning changes before implementing them in live games.

2 Model Description and Design

This section follows the spirit of standard ABM description frameworks (ODD: Overview, Design concepts, Details; PARTE: Purpose, Agents, Rules, Time, Experiment) so that a reader could reimplement the model from the description below.

2.A) Core Concepts

The model implements six key design concepts that drive the emergent dynamics of FPS PvP matches:

Emergence: Team-level fairness and engagement patterns emerge from heterogeneous agent decisions about positioning, weapon selection, and engagement timing. No explicit rules enforce balanced outcomes, so the match state is determined by the accumulated effect of many local actions.

Adaptation: Agents modify behavior based on local information: visible enemies, map terrain, team objectives, and recent engagement outcomes. Weapon selection is adapted based on skill level, with DMR users acting as higher-skill marksmen, SMG users acting as aggressive close-range fighters, and rifle users representing a balanced baseline.

Objectives: Individual agents pursue personal goals such as eliminating enemies and surviving while also contributing to a team objective centered on capturing and holding a central point. This creates strategic tension between individual K/D ratios and team success, which is exactly the tension the sensitivity analysis is meant to illuminate.

Learning: Agents update aggression based on recent kill/death ratios within a match, reinforcing successful strategies over time. This gives the model a simple in-match feedback loop without introducing a full reinforcement learning system.

Heterogeneity: Players have random skill levels (sampled uniformly from 0.2 to 0.95), aggression levels, and risk tolerance. These traits influence movement behavior, engagement decisions, and weapon adaptation, ensuring that the population is not homogeneous and that the same map can produce different match trajectories.

Stochasticity: Combat outcomes include randomness via skill-dependent hit probability and damage rolls, preventing deterministic play even from identical initial conditions. This keeps the model from collapsing into a purely deterministic shortest-path problem and makes the output suitable for variance-based analysis.

2.B) Model Structure

2.B.I) Environment

The environment is a 40×30 grid representing an FPS arena. Each cell stores:

- **Terrain type:** open lane, cover, choke point, spawn zone, objective zone, or wall.
- **Dynamic state:** occupant IDs, objective progress, controlling team, and combat heat (recent engagement intensity).

Terrain is generated procedurally at the start of each match using wall, cover, and choke probabilities. The objective is a circular zone at the map center with a configurable radius, which makes the model easy to interpret because every team starts from the same broad spatial relationship to the goal. Non-wrapping boundaries enforce arena-like geometry and prevent agents from escaping the play space.

2.B.II) Agents

Each agent maintains:

- Persistent state: ID, team, position, health (0–100), alive status, cooldown timer, kill/death counts.
- Behavioral parameters: skill (accuracy and engagement probability), aggression (preference for offensive action), risk tolerance (retreat tendency under fire), weapon (rifle, SMG, or DMR).
- Facing direction and targeting information.

Agents use one of three weapons with distinct properties:

- Rifle: baseline damage, range, and cooldown.
- SMG: lower damage/range but faster fire rate (shorter cooldown).
- DMR: higher damage and range but slower fire rate.

These weapon classes are intentionally simple. The purpose is to capture the broad gameplay tradeoff between rate of fire, range, and impact, not to model every mechanical detail of a specific FPS. That keeps the state space compact enough for sensitivity analysis while still allowing weapon balance to matter in the match outcome.

2.B.III) Tick Schedule

Each discrete time step follows a synchronous schedule:

1. **Sense:** Alive agents detect nearby enemies (within detection radius, optionally with line-of-sight check) and nearby cover. Dead agents decrement respawn timers.
2. **Decide:** Agents choose an action (engage, push objective, hold position, reposition toward cover, or retreat) based on visible enemies, objective status, and internal state.
3. **Move:** Movement actions update agent positions, respecting obstacles and occupancy constraints. Facing direction is updated to reflect movement direction.
4. **Combat:** Nearest visible enemy is targeted. Hit probability is computed from skill, distance, weapon range, and stochasticity. On hit, damage is applied; on death, respawn timer is started.
5. **Update Objectives:** Objective progress is incremented if only one team occupies the objective; progress decays under contested conditions.
6. **Adapt & Respawn:** Agents update aggression based on kill/death ratio; eligible agents respawn at spawn points with adaptive weapon selection.
7. **Metrics:** Per-tick metrics (alive counts, kill counts, objective control) are logged for later analysis.

2.C) Movement and Pathfinding

Rather than random wandering, agents use a distance field to navigate toward the objective:

- A breadth-first search computes shortest traversable path distances from the objective to all cells.
- When pushing the objective, agents move to the neighbor with minimum distance.
- When repositioning or retreating, agents evaluate neighbors using a weighted score that balances distance, cover availability, occupancy, and recent combat intensity.

This greedy pathfinding produces more realistic objective-oriented behavior than pure random movement.

2.C.I) Example Simulation Snapshots

The model also produces animated environment GIFs during simulation runs. To make the report easier to read, two representative still frames were extracted from those GIFs and included below. The first shows an early match state with initial spread, while the second shows a later state where movement and objective pressure have already begun to shape the spatial structure of the match.



Figure 1: *
Early-match snapshot from an environment GIF.



Figure 2: *
Mid-match snapshot from an environment GIF.

Figure 3: Still frames extracted from the generated environment GIFs. The images show how agent motion, map structure, and objective pressure shape the evolving match state.

2.D) Combat Resolution

The hit probability is computed as:

$$p_{\text{hit}} = \text{clamp}(0.25 + 0.65 \cdot \text{skill} - 0.35 \cdot \max(0, d - r)/r, 0.05, 0.95)$$

where d is distance, r is weapon range, and skill is the agent's skill parameter (0 to 1). Stochasticity adds noise: $p_{\text{hit}} \leftarrow p_{\text{hit}} + \mathcal{U}(-\sigma, \sigma)$ where σ is the stochasticity parameter.

If the random shot lands, damage is applied: $\text{dmg} = d_{\text{base}}(1 + \mathcal{U}(-\sigma, \sigma))$. On lethal damage, the target dies, respawn timer is set, and the attacker earns a kill. On missed shots, low-risk-tolerance agents may retreat.

3 Experimental Design

3.A) Parameter Space

Seven parameters were swept over their ranges:

Parameter	Min	Max
Objective radius	3	12
Wall probability	0.0	0.25
Cover probability	0.0	0.2
Choke probability	0.0	0.1
Weapon cooldown ticks	1	3
Stochasticity	0.0	0.5
Adaptation rate	0.0	0.2

3.B) Sampling Strategy

3.B.I) Latin Hypercube Sampling

Latin Hypercube Sampling (LHS) was used to generate 1024 parameter combinations uniformly covering the 7-dimensional parameter space. LHS divides each dimension into N strata, permutes indices, and samples one point from each stratum, ensuring good marginal coverage and reduced clustering. This matters because the model is nonlinear: if the sample cloud was too clustered, the experiment could miss important regions of the parameter space and the summary statistics would become unstable.

All 1024 samples were executed in parallel using multiprocessing (one sample per CPU core), with each run saving:

- Per-tick trace (agent positions, events) in JSON format.
- Per-tick metrics CSV (alive counts, kill counts, objective control).
- Summary JSON with final objective progress, objective controller, and all parameter values.

The marginal distributions are plotted separately for the first three sampled parameters because their scales are not comparable on a shared histogram. Separating them makes it much easier to inspect whether the stratification is actually uniform across each dimension.

3.B.II) Saltelli Sobol Sampling

For variance-based sensitivity analysis, Saltelli's sampling scheme (implemented in SALib) was used with base sample size $N = 128$. This generates $(2K + 2) \times N = (2 \times 7 + 2) \times 128 = 2048$ model runs to compute first-order and total Sobol indices. Saltelli sampling provides balanced samples for estimating both S_1 (first-order effect) and S_T (total effect including interactions), which is important because the model contains several interacting mechanisms rather than a single linear cause-and-effect chain.

3.C) Output Metric

The primary output was **objective progress** at the end of each 200-tick match. This represents the cumulative capture progress by the team controlling the objective, ranging from 0 to 1. A value of 1 indicates complete capture; 0 indicates no progress or contested/lost control. This study focuses on this metric because it directly measures whether the model is producing coordinated team play rather than just isolated combat.

4 Results

4.A) LHS Exploration

To verify that the Latin Hypercube Sampling (LHS) covered the parameter space uniformly, the Kolmogorov-Smirnov (KS) statistic was computed for each of the seven swept parameters. The KS test measures how closely the marginal distribution of each parameter matches a uniform distribution; values near 0 indicate excellent uniformity, while larger values indicate systematic bias. Across all 1024 samples, the maximum KS statistic observed was 0.00098 (well below the conventional critical threshold of 0.037 for $n = 1024$ at significance level $\alpha = 0.05$), with all parameters yielding KS p-values of 1.0, confirming that LHS achieved its intended goal: stratified coverage without clustering or gaps.

This validation is important because the model is highly nonlinear. If the sample cloud was too clustered, the experiment could miss important regions of the parameter space and the summary statistics would become unstable. Verification of near-perfect uniformity ensures that downstream sensitivity analysis (e.g., Sobol indices) is not biased by poor sampling coverage.

Summary statistics from the 1024 LHS runs:

- Mean objective progress: 0.456 ± 0.448 (1 std).
- Median: 0.45.
- Range: 0.0 to 1.0.
- Fraction of runs reaching full capture (progress = 1.0): 32%.
- Fraction with no progress (progress = 0.0): 19%.

4.B) Sobol Sensitivity Analysis

Figure 4 displays the first-order Sobol indices (S_1), which measure the main effect of each parameter on objective progress variance. In this context, a large positive index means that changing the parameter alone explains a meaningful portion of the observed variation in objective progress. Small or slightly negative estimates should be interpreted as near-zero main effects with sampling noise, not as literal negative contributions to variance.



Figure 4: First-order Sobol indices for objective progress. Positive values indicate parameters that increase progress; negative values indicate those that decrease it. Larger magnitudes reflect stronger main effects.

4.B.I) Key Findings

Wall probability ($S_1 = 0.44$): The strongest main effect on objective progress. Higher wall density creates choke points and cover, encouraging teams to cluster around the objective and contest it intensely. Densely walled maps favor organized team play and increase capture progress because movement choices become constrained and the objective becomes a more natural focal point.

Choke probability ($S_1 = 0.40$): The second-strongest effect. Chokepoints similarly funnel agents toward concentrated engagement zones, increasing pressure on the objective. The comparable magnitude to wall probability suggests that both spatial constraints drive team cohesion.

Objective radius ($S_1 = 0.38$): Larger objective zones make it easier for teams to contest and capture the goal. A wider capture area reduces the precision required to enter the zone, allowing more agents to contribute to objective progress simultaneously.

Weapon cooldown ($S_1 = 0.36$): Positive effect: longer cooldowns (slower weapons) increase objective progress. This suggests that measured, careful engagement patterns favor team coordination over raw fire rate, allowing agents to maintain focus on the objective rather than engaging in continuous skirmishes.

Cover probability ($S_1 = 0.24$): Moderate positive effect. Cover availability supports sustained engagements around the objective by reducing the lethality of open-field fights. Teams can hold positions longer, leading to more stable objective control.

Stochasticity ($S_1 = 0.23$): Moderate positive effect. Contrary to intuition, added randomness increases objective progress. This may indicate that stochasticity prevents agents from getting locked into purely defensive patterns; variability keeps gameplay dynamic and allows breakthrough moments.

Adaptation rate ($S_1 = 0.21$): Weak positive effect. Agents that adapt their strategy based on match conditions show modest improvements to objective progress. This suggests that learning helps teams adjust to the evolving state of the match.

4.C) Large Replication Study

To check baseline stability under repeated random seeds, 100,000 independent matches were run with the default 200-tick setup and distinct seeds. Unlike the LHS and Sobol studies, this batch did not vary the parameters; it instead measured how much outcome variation remains when the model is held fixed.

The aggregate results are summarized in Table 1. The confidence interval on objective progress is narrow relative to the observed standard deviation because the sample size is large. The final objective controller also splits almost evenly between the two teams, suggesting that the default configuration is not trivially biased toward one side.

Metric	**Value**	**95% CI / Share**
Mean objective progress	0.7930	[0.7910, 0.7949]
Objective progress standard deviation	0.3168	–
Final objective controller = 0	51,697 runs	51.7%
Final objective controller = 1	48,303 runs	48.3%

Table 1: Aggregate results from the 100,000-run replication study of the baseline configuration.

5 Discussion

5.A) Map Design Insights

The sensitivity analysis reveals that environmental geometry (walls) is the dominant influence on objective capture progress. Maps with moderate wall density (around 0.1–0.15) create natural bottlenecks and encourage conflict concentration, leading to higher objective engagement and capture rates. This result is useful because it suggests that level design can be just as important as unit balance when shaping whether a match feels like an objective game or a roaming deathmatch.

In contrast, pure open maps (wall_prob = 0) result in sparse, unconstrained player movement, reducing the urgency of objective play. Conversely, extremely dense walls may fragment the player base into isolated regions, which can reduce meaningful contesting if teams cannot reach the same spaces reliably.

5.B) Weapon Balance Implications

Slower weapons (longer cooldown) show a stronger positive effect on objective progress than faster weapons, suggesting that measured, deliberate engagement patterns support team coordination better than high fire rates. This aligns with real-world FPS design: weapons designed for close-range skirmishes (like SMGs with short cooldowns) prioritize dueling and individual survival, while longer-cooldown weapons encourage careful positioning and objective focus. The result suggests that weapon tuning should balance rate of fire with the desire to encourage team play.

5.C) Adaptation and Learning

Adaptation rate shows a modest positive effect on objective progress, indicating that in-match learning helps teams adjust to evolving conditions and improve their ability to contest the objective. Rather than conflict with team success, the ability to adapt strategy based on recent match events appears to support coordination. This aligns with the intuition that dynamic teams outperform rigid ones, though the modest effect size suggests that learning is only one of many factors influencing objective play.

5.D) Baseline Stability

The large replication study provides a useful sanity check for the model's default behavior. Even with 100,000 distinct random seeds, the final objective-progress estimate stays tightly centered near 0.793, and the final controller split remains close to 50/50. That result matters because it shows the model is stochastic enough to support sensitivity analysis, but not so noisy that aggregate conclusions become unstable.

5.E) Limitations and Future Work

- The model assumes perfect information within detection radius and line-of-sight; real FPS players often use audio cues and minimap information.
- Agent behavior is rule-based (not learned via reinforcement learning), limiting how far from the hand-crafted policy agents can evolve.
- The grid environment is abstract; real FPS maps have continuous space, diagonal sight lines, and elevation changes.
- Second-order and interaction effects (visible in Sobol S_2 matrix) are not yet fully explored; future work should characterize pairwise and higher-order effects.
- Validation against real FPS data is not yet performed; empirical calibration would strengthen claims about balance.

These limitations are acceptable for a first-pass systems model because the goal is explanatory insight rather than photorealistic simulation. Still, each limitation points to a clear next step if the model is extended into a more predictive tool.

6 Reproducibility

All experiments and intermediate outputs are saved in the `out/` directory of the repository found at https://github.com/silasfalde/fps-pvp-dynamics:

- `out/samples/`: Per-sample traces (JSON) and metrics (CSV).
- `out/experiments/`: Aggregate summary CSVs (LHS summary, parameter sweeps).

- `out/experiments/large_replication_study/`: 100,000-run baseline replication outputs and confidence-interval summaries.
- `out/analysis/`: Plot tables (CSV), sensitivity results (JSON), extracted GIF frames, and derived analysis outputs.
- `out/videos/`: Animated GIFs generated from simulation runs.

To reproduce the analysis:

```
cd fps-pvp-dynamics
source .venv/bin/activate
python3 scripts/experiments_pipeline.py
python3 scripts/run_large_replication_study.py --samples 100000
```

The pipeline is parameterized; the sample sizes and base_N can be modified in the main() function, and the replication study sample count can be changed with the `--samples` flag.

Environment and package versions

- **Recommended Python:** Python 3.11 (any 3.10+ interpreter should work).
- **Dependencies:** See `requirements.txt` for exact package requirements; install with `pip install -r requirements.txt`.
- **Tests:** Unit tests are provided in the `tests` directory. Run them with `pytest teststest_model.py` after activating the virtual environment.
- **Code quality:** The model code includes docstrings and inline documentation in `srcfps_pvp_abm`. See README in the repository root for additional developer notes.

Notes: the analysis pipeline was developed against Python 3.11 and the packages listed in `requirements.txt` (e.g., `mesa`, `numpy`, `pandas`, `matplotlib`, `SALib`).

7 Conclusion

This report demonstrated the application of agent-based modeling and variance-based sensitivity analysis to understand FPS PvP dynamics. Through 1024 LHS samples and 2048 Saltelli samples for Sobol analysis, the study identified map geometry—specifically wall density, choke probability, and objective radius—as the dominant influences on objective capture progress. A separate 100,000-run replication study showed that the baseline configuration is stable under repeated sampling, with mean objective progress near 0.793 and a nearly even final controller split.

These findings provide quantitative support for design hypotheses: densely walled maps with natural choke-points encourage objective play, larger objective zones facilitate capture, and measured weapon pacing supports team coordination better than rapid fire rates. Adaptation and learning mechanics show modest positive effects, suggesting that dynamic strategic adjustment helps teams succeed. The replication results add a second layer of evidence by showing that the baseline outcome is reproducible at scale rather than being a one-off artifact of a particular seed. Future work could extend the model with reinforcement learning agents, continuous space, richer interaction metrics, and empirical calibration against real game data.