

ENDURANCE TIER • SOLAR • BATTERY • HVO GENERATOR


Harka Hybrid

An autonomous 6 m mast platform for surveillance, communications and sensor payloads on sites with no mains supply and no fuel convoy.

Solar and battery carry the payload in silence. A Stage V generator running on HVO renewable diesel engages only to recharge the pack, guaranteeing uptime through low light, deep winter and heavy loads. The platform is delivered open: the universal head mount and internal equipment bay accept the operator's own cameras, lighting, sensors and radios.

KEY FEATURES

- 6 m hot-dip galvanised manual mast, mechanical safety brake; automatic patent winch brake available
- Hybrid energy pack: 24 VDC 220 Ah AGM battery with Stage V backup generator on HVO
- 3 × 360 W book-opening solar array, manual deployment, no tools
- Generator engages at 20% depth of discharge and shuts down once recharged
- Open head mount compatible with all major camera and lighting systems
- Lockable steel compartment for operator electronics, 370 × 200 × 470 mm
- Silent, zero-emission operation in battery mode
- Forklift pockets, all-terrain transport, ten units per truck



1,840 h	45 h	1,080 W	6 m
TOTAL RUNNING TIME BEFORE REFUELLING	BATTERY ONLY, GENERATOR IDLE	INSTALLED SOLAR ARRAY	MANUAL MAST HEIGHT

Autonomy figures based on continuous 24/7 operation at 100 W payload draw.

DEPLOYMENT

Remote construction & highways Compounds and corridors with no supply.	Oil, gas & mining Isolated assets, long service intervals.	Defence & border surveillance Low signature, full autonomy.
Critical national infrastructure Pipelines, substations, dams, telecoms.	Secured public & private zones Events, compounds, restricted areas.	Environmental monitoring Dust, gas, weather and traffic sensing.

MAST		RUNNING TIME AT 100 W	
Lifting method	Manual	Battery only	45 hrs
Maximum height	6 m	Total before refuelling	1,840 hrs
Rotation	None	DIMENSIONS & WEIGHT	
Safety brake	Mechanical	Transport L × W × H	1200 × 1700 × 2580 mm
Body	Hot-dip galvanised	In operation L × W × H	3280 × 2500 × 6000 mm
BATTERY		Weight	1,368 kg
Type & number	AGM × 2	Equipment bay, internal	370 × 200 × 470 mm
Power pack	24 VDC – 220 Ah	TRANSPORT & HANDLING	
Expected cycles	500	– Ten units per truck, packaged for rapid unloading	
Solar array	3 × 360 W, manual	– Forklift pockets; transportable across all terrains	
GENERATOR SET		– Mast raised manually in minutes by one operator, no tools or electric motors	
Engine	Kubota Z482 Stage V	– Solar array opens by hand; no technicians required on site	
Speed	1,500 rpm		
Alternator	Linz Electric 3.5 kVA		
Output	220 V – 50 Hz		
Fuel	HVO renewable diesel		

YOUR PAYLOAD, OUR POWER

Delivered as an open, ready-to-use platform. Operators integrate their own systems, or Melrakki specifies them:

- HD CCTV, PTZ and IP cameras
 - LTE, 5G and Wi-Fi router modules
 - Motion and environmental sensors
 - Remote access panel and software
- LED matrix or infrared floodlighting
 - GPS tracking and geofencing
 - Alarms, sirens and UPS
 - Operator branding and colour

COMMON QUESTIONS

- What makes the platform hybrid?**

Battery-first operation with solar recharge; the generator engages at 20% depth of discharge to recharge the pack, then stops.
- How loud is it?**

Silent on battery. The generator is low-RPM and noise-insulated.
- Does it need routine attendance?**

No. It is designed for long unattended operation on remote sites.
- Is it secure against tampering?**

All sensitive components are housed in a lockable steel compartment.



Tell us the load, the location and the conditions.

We engineer the platform that keeps it alive, and support it for the life of the deployment.

ENQUIRIES
www.melrakki.systems
hello@melrakki.systems
01227 202122

SUPPLY & SUPPORT
Lead time, commissioning, spares and warranty terms confirmed at quotation. Technical support direct from Melrakki Systems.