


23 JTable and JTree



JTable


JTable is a Swing component that displays data in rows and columns in a two-dimensional grid.



Country	Capital	Population in Millions	Democracy
USA	Washington DC	280	true
Canada	Ottawa	32	true
United Kingdom	London	60	true
Germany	Berlin	83	true
France	Paris	60	true
Norway	Oslo	4.5	true
India	New Delhi	1046	true

JTable and Its Supporting Models

NOTE: All the supporting interfaces and classes for JTable are grouped in the javax.swing.table package.




The JTable Class

javax.swing.JTable	
-autoCreateColumnsFromModel: boolean	Indicates whether the columns are created in the table (default: true).
-autoResizeMode: int	Specifies how columns are resized (default: SUBSEQUENT_COLUMNS).
-cellEditor: TableCellEditor	Specifies a cell editor.
-cellSelectionEnabled: boolean	Specifies whether individual cells can be selected (Obsolete since JDK 1.3).
-columnModel: TableColumnModel	Maintains the table column data.
-columnSelectionAllowed: boolean	Specifies whether the rows can be selected (default: false).
-editingColumn: int	Specifies the column of the cell that is currently being edited.
-editingRow: int	Specifies the row of the cell that is currently being edited.
-gridColor: java.awt.Color	The color used to draw grid lines ((default: GRAY).
-intercellSpacing: Dimension	Specifies the horizontal and vertical margins between cells (default: 1, 1).
-model: TableModel	Maintains the table model.
-rowCount: int	Read-only property that counts the number of rows in the table.
-rowHeight: int	Specifies the row height of the table (default: 16 pixels).
-rowMargin: int	Specifies the vertical margin between rows (default: 1 pixel).
-rowSelectionAllowed: boolean	Specifies whether the rows can be selected (default: true).
-selectionBackground: java.awt.Color	The background color of selected cells.
-selectionForeground: java.awt.Color	The foreground color of selected cells.
-showGrid: boolean	Specify whether the grid lines are displayed (write-only, default: true).
-selectionMode: int	Specifies a selection mode (write-only).
-selectionModel: ListSelectionModel	Specifies a selection model.
-showHorizontalLines: boolean	Specifies whether the horizontal grid lines are displayed (default: true).
-showVerticalLines: boolean	Specifies whether the vertical grid lines are displayed (default: true).
-tableHeader: JTableHeader	Specifies a table header.
+JTable()	Creates a default JTable with all default models.
+JTable(numRows: int, numColumns: int)	Creates a JTable with the specified number of empty rows and columns.
+JTable(rowData: Object[][], columnData: Object[])	Creates a JTable with the specified row data and column header names.
+JTable(dm: TableModel)	Creates a JTable with the specified table model.
+JTable(dm: TableModel, cm: TableColumnModel)	Creates a JTable with the specified table model and table column model.
+JTable(dm: TableModel, cm: TableColumnModel, sm: ListSelectionModel)	Creates a JTable with the specified table model, table column model, and selection model.
+JTable(rowData: Vector, columnNames: Vector)	Creates a JTable with the specified row data and column data in vectors.
+addColumn(aColumn: TableColumn): void	Adds a new column to the table.
+clearSelection(): void	Deselects all selected columns and rows.
+editCellAt(row: int, column: int): void	Edits the cell if it is editable.
+getDefaultEditor(column: Class): TableCellEditor	Returns the default editor for the column.
+getDefaultRenderer(col: Class): TableCellRenderer	Returns the default renderer for the column.
+setDefaultEditor(column: Class, editor: TableCellEditor): void	Sets the default editor for the column.
+setDefaultRenderer(column: Class, editor: TableCellRenderer): void	Sets the default renderer for the column.


Example: Table Properties Demo

Problem: This example demonstrates the use of several JTable properties. The example creates a table and allows the user to choose an **Auto Resize Mode**, specify the row height and margin, and indicate whether the grid is shown.



The screenshot shows the 'TablePropertiesDemo' window. At the top, there's a title bar with the window name and standard OS controls. Below the title bar, there's a dropdown menu for 'autoResizeMode' set to 'AUTO_RESIZE_ALL_COLUMNS'. The main area contains a table with four columns: 'Country', 'Capital', 'Population in ...', and 'Democracy'. The table has seven rows of data. At the bottom, there are three controls: 'rowHeight' with a spinner set to 19, 'rowMargin' with a spinner set to 1, and a 'showGrid' checkbox which is currently unchecked.

Country	Capital	Population in ...	Democracy
USA	Washington DC	280	true
Canada	Ottawa	32	true
United Kingdom	London	60	true
Germany	Berlin	83	true
France	Paris	60	true
Norway	Oslo	4.5	true
India	New Deli	1046	true



This screenshot is identical to the previous one, but the 'showGrid' checkbox at the bottom right is now checked, and the table is displayed with blue grid lines.

Country	Capital	Population in ...	Democracy
USA	Washington DC	280	true
Canada	Ottawa	32	true
United Kingdom	London	60	true
Germany	Berlin	83	true
France	Paris	60	true
Norway	Oslo	4.5	true
India	New Deli	1046	true

TablePropertiesDemo

Run

```
// Create table column names
private String[] columnNames =
    {"Country", "Capital", "Population in Millions", "Democracy"};

// Create table data
private Object[][] rowData = {
    {"USA", "Washington DC", 280, true},
    {"Canada", "Ottawa", 32, true},
    {"United Kingdom", "London", 60, true},
    {"Germany", "Berlin", 83, true},
    {"France", "Paris", 60, true},
    {"Norway", "Oslo", 4.5, true},
    {"India", "New Delhi", 1046, true}
};

// Create a table
private JTable jTable1 = new JTable(rowData, columnNames);
```

```
// Initialize jTable1
jTable1.setAutoResizeMode(JTable.AUTO_RESIZE_OFF);
jTable1.setGridColor(Color.BLUE);
jTable1.setSelectionMode(ListSelectionModel.SINGLE_SELECTION);
jTable1.setSelectionBackground(Color.RED);
jTable1.setSelectionForeground(Color.WHITE);
```

```
// Register and create a listener for jsplRowHeight
jsplRowHeight.addChangeListener(new ChangeListener() {
    public void stateChanged(ChangeEvent e) {
        jTable1.setRowHeight(
            ((Integer) (jsplRowHeight.getValue())).intValue()
        );
    }
});
```

```
// Register and create a listener for jsplRowMargin
jsplRowMargin.addChangeListener(new ChangeListener() {
    public void stateChanged(ChangeEvent e) {
        jTable1.setRowMargin(
            ((Integer) (jsplRowMargin.getValue())).intValue()
        );
    }
});
```

```
// Register and create a listener for jchkShowGrid
jchkShowGrid.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        jTable1.setShowGrid(jchkShowGrid.isSelected());
    }
});
```

```
// Register and create a listener for jchoAutoResizeMode
jchoAutoResizeMode.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        String selectedItem =
            (String) jchoAutoResizeMode.getSelectedItemAt();

        if (selectedItem.equals("AUTO_RESIZE_OFF"))
            jTable1.setAutoResizeMode(JTable.AUTO_RESIZE_OFF);
        else if (selectedItem.equals("AUTO_RESIZE_LAST_COLUMN"))
            jTable1.setAutoResizeMode(JTable.AUTO_RESIZE_LAST_COLUMN);
        else if (selectedItem.equals
            ("AUTO_RESIZE_SUBSEQUENT_COLUMNS"))
            jTable1.setAutoResizeMode(
                JTable.AUTO_RESIZE_SUBSEQUENT_COLUMNS);
        else if (selectedItem.equals("AUTO_RESIZE_NEXT_COLUMN"))
            jTable1.setAutoResizeMode(JTable.AUTO_RESIZE_NEXT_COLUMN);
        else if (selectedItem.equals("AUTO_RESIZE_ALL_COLUMNS"))
            jTable1.setAutoResizeMode(JTable.AUTO_RESIZE_ALL_COLUMNS);
    }
});
```

Table Models

JTable delegates **data storing and processing to its table data model**. A table data model must implement the TableModel interface, which defines the methods for registering table model listeners, manipulating cells, and obtaining row count, column count, column class, and column name.

The DefaultTableModel provides concrete storage for data using a vector.

The AbstractTableModel class provides partial implementations for most of the methods in TableModel. It takes care of the management of listeners and provides some conveniences for **generating TableModelEvents and dispatching them to the listeners.**




Table Column Model

javax.swing.table.TableColumnModel

```
+addColumn(aColumn: TableColumn): void
+getColumn(columnIndex: int): TableColumn
+getColumnCount(): int
+getColumnIndex(columnIdentifier: Object): int
+getColumnMargin(): int
+getColumns(): Enumeration
+getColumnSelectionAllowed(): boolean
+getSelectedColumnCount(): int
+getSelectedColumns(): void
+getSelectionModel(): ListSelectionModel
+getTotalColumnWidth(): int
+moveColumn(columnIndex: int, newIndex: int): void
+removeColumn(column: TableColumn): void
+setColumnMargin(newMargin: int): void
+setColumnSelectionAllowed(flag: boolean): void
+setSelectionModel(newModel: ListSelectionModel): void
```

javax.swing.table.DefaultTableColumnModel

javax.swing.table.TableColumn

Table column models manage columns in a table. They can be used to select, add, move, and remove table columns. A table column model must implement the TableColumnModel interface, which defines the methods for registering table column model listeners, and for accessing and manipulating columns.

DefaultTableColumnModel is a concrete class that implements TableColumnModel and stores its columns in a vector and contains an instance.



The TableColumn Class

The column model deals with all the columns in a table. The [TableColumn](#) class is used to model an individual column in the table. An instance of [TableColumn](#) for a specified column can be obtained using the [getColumn\(index\)](#) method in [TableColumnModel](#) or the [getColumn\(columnIdentifier\)](#) method in [JTable](#).

javax.swing.table.TableColumn	
+cellEditor: TableCellEditor	The editor for editing a cell in this column.
+cellRenderer: TableCellRenderer	The renderer for displaying a cell in this column.
+headerRenderer: TableCellRenderer	The renderer for displaying the header of this column.
+headerValue: Object	The header value of this column.
+identifier: Object	The identifier for this column.
+maxWidth: int	The maximum width of this column.
+minWidth: int	The minimum width of this column (default: 15 pixels).
+modelIndex: int	The index of the column in the table model (default: 0).
+preferredWidth: int	The preferred width of this column (default: 75 pixels).
+resizable: boolean	Indicates whether this column can be resized (default: true).
+width: int	Specifies the width of this column (default: 75 pixels).
<hr/>	
+TableColumn()	Constructs a default table column.
+TableColumn(modelIndex: int)	Constructs a table column for the specified column.
+TableColumn(modelIndex: int, width: int)	Constructs a table column with the specified column and width.
+TableColumn(modelIndex: int, width: int, cellRenderer: TableCellRenderer)	Constructs a table column with the specified column, width, and cell renderer.
+setWidthToFit(): void	Resizes the column to fit the width of its header cell.



The JTableHeader Class

JTableHeader is a GUI component that manages the header of the JTable (see Figure 36.29). When you create a JTable, an instance of JTableHeader is automatically created and stored in the tableHeader property.

javax.swing.table.JTableHeader

+columnModel: TableColumnModel
+draggedColumn: TableColumn
+draggedDistance: TableCellRenderer
+reorderingAllowed: boolean
+resizingAllowed: boolean
+resizingColumn: TableColumn
+table: JTable

+JTableHeader()
+JTableHeader(TableColumnModel cm)

The TableColumnModel of the table header.

The column being dragged.

The distance from its original position to the dragged position.

Whether reordering of columns is allowed (default: true).


Whether resizing of columns is allowed (default: true).

The column being resized.

The table for which this object is the header.

Constructs a JTableHeader with a default TableColumnModel.


Constructs a JTableHeader with with a TableColumnModel.



Auto Sort and Filtering

Auto sort and filtering are two useful new features in JDK 1.6. To enable auto sort on any column in a JTable, create an instance of TableRowSet with a table model and set JTable's rowSorter with this TableRowSet instance, as follows:

```
TableRowSorter<TableModel> sorter =  
new TableRowSorter<TableModel>(tableModel);  
jTable.setRowSorter(sorter);
```



Country ▲	Capital	Population in Millions	Democracy
Canada	Ottawa	32	true
France	Paris	60	true
Germany	Berlin	83	true
India	New Delhi	1046	true
Norway	Oslo	4.5	true
United Kingdom	London	60	true
USA	Washington DC	280	true

Sepecify a word to match:

TestTableSortFilter

Run



```
// Enable auto sorter  
jTable1.setRowSorter(sorter);
```

```
JPanel panel = new JPanel(new java.awt.BorderLayout());  
panel.add(new JLabel("Specify a word to match:"),  
    BorderLayout.WEST);  
panel.add(jtfFilter, BorderLayout.CENTER);  
panel.add(btFilter, BorderLayout.EAST);
```

```
add(panel, BorderLayout.SOUTH);  
add(new JScrollPane(jTable1), BorderLayout.CENTER);
```

```
btFilter.addActionListener(new java.awt.event.ActionListener() {  
    @Override  
    public void actionPerformed(java.awt.event.ActionEvent e) {  
        String text = jtfFilter.getText();  
        if (text.trim().length() == 0)  
            sorter.setRowFilter(null);  
        else  
            sorter.setRowFilter(RowFilter.regexFilter(text));  
    }  
});
```



Example:

Modifying Rows and Columns

Problem: This example demonstrates the use of table models, table column models, list-selection models, and the TableColumn class. The program allows the user to choose selection mode and selection type, to add or remove rows and columns, and to save, clear, and restore table.

The **ModifyTable** window features a selection mode dropdown set to **SINGLE_SELECTION**. Below it are checkboxes for **RowSelectionAllowed** (unchecked) and **ColumnSelectionAllowed** (checked). A table displays data with columns: Country, Capital, Population i..., Democracy, and Area. The table contains rows for USA, Canada, United Kin..., Germany, France, and Norway. At the bottom, there are buttons for **Save**, **Clear**, **Restore**, **Add New Row**, **Add New Column**, **Delete Selected Row**, and **Delete Selected Column**.

Country	Capital	Population i...	Democracy	Area
USA	Washingto...	280	true	
Canada	Ottawa	32	true	
United Kin...	London	60	true	
Germany	Berlin	83	true	
France	Paris	60	true	
Norway	Oslo	4.5	true	

The **Input** dialog box prompts for a **New Column Name**. It contains a text field with the value **Area** and **OK** and **Cancel** buttons.

ModifyTable

Run

```

jbtAddRow.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        if (jTable1.getSelectedRow() >= 0)
            tableModel.insertRow(jTable1.getSelectedRow(),
                new java.util.Vector<String>());
        else
            tableModel.addRow(new java.util.Vector<String>());
    }
});

```

```

jbtAddColumn.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        String name = JOptionPane.showInputDialog("New Column");
        tableModel.addColumn(name, new java.util.Vector());
    }
});

```

```

jbtDeleteRow.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        if (jTable1.getSelectedRow() >= 0)
            tableModel.removeRow(jTable1.getSelectedRow());
    }
});

```

```

jbtDeleteColumn.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        if (jTable1.getSelectedColumn() >= 0) {
            TableColumnModel columnModel = jTable1.getColumnModel();
            TableColumn tableColumn =
                columnModel.getColumn(jTable1.getSelectedColumn());
            columnModel.removeColumn(tableColumn);
        }
    }
});

```

```

jbtClear.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        tableModel.setRowCount(0);
    }
});

```

```

jcbSelectionMode.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        String selectedItem =
            (String)jcbSelectionMode.getSelectedItem();

        if (selectedItem.equals("SINGLE_SELECTION"))
            jTable1.setSelectionMode(
                ListSelectionModel.SINGLE_SELECTION);
        else if (selectedItem.equals("SINGLE_INTERVAL_SELECTION"))
            jTable1.setSelectionMode(
                ListSelectionModel.SINGLE_INTERVAL_SELECTION);
        else if (selectedItem.equals("MULTIPLE_INTERVAL_SELECTION"))
            jTable1.setSelectionMode(
                ListSelectionModel.MULTIPLE_INTERVAL_SELECTION);
    }
});

```

```

jchkRowSelectionAllowed.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        jTable1.setRowSelectionAllowed(
            jchkRowSelectionAllowed.isSelected());
    }
});

```

```

jchkColumnSelectionAllowed.addActionListener(
    new ActionListener() {
        @Override
        public void actionPerformed(ActionEvent e) {
            jTable1.setColumnSelectionAllowed(
                jchkColumnSelectionAllowed.isSelected());
        }
    }
);

```


Table Renderers and Editors

Table cells are painted by cell renderers. By default, a cell object's string representation (`toString()`) is displayed and the string can be edited as it was in a text field. **JTable** maintains a set of predefined renderers and editors, listed in Table 36.1, which can be specified to replace default string renderers and editors.

The predefined renderers and editors are automatically located and loaded to match the class returned from the `getColumnClass()` method in the table model. To use a predefined renderer or editor for a class other than `String`, you need to create your own table model **by extending a subclass of `TableModel`**. In your table model class, you need to **override** the `getColumnClass()` method to return the class of the column, as follows:


```
public Class getColumnClass(int column) {  
    return getValueAt(0, column).getClass();  
}
```




By default, all cells are editable. To prohibit a cell from being edited, override the `isCellEditable(int rowIndex, int columnIndx)` method in `TableModel` to return `false`. By default, this method returns `true` in `AbstractTableModel`.



Example: Using Predefined Table Renderers and Editors

Problem: Write a program that displays a table for the books. The table consists of three rows with column names Title, Copies Needed, Publisher, Date Published, In-Stock, and Book Photo, as shown in Figure 36.32. **Display all the columns using the predefined renderers and editors.** Assume dates and icons are not editable; prohibit users from editing of these two columns.



Title	Copies Needed	Publisher	Date Published	In-stock	Book Photo
Introduction to Java Programming	120	Que Ed...	Jan 6, 1998	<input type="checkbox"/>	
Introduction to Java Programming, 2E	220	Que Ed...	Jan 6, 1999	<input checked="" type="checkbox"/>	
Introduction to Java Programming, 3E	220	Prentice...	Nov 30, 20...	<input checked="" type="checkbox"/>	

MyTableModel

TableCellRendererEditorDemo

Run


```
// Create image icons
private ImageIcon intro1eImageIcon = new ImageIcon(
    getClass().getResource("/image/intro1e.gif"));
private ImageIcon intro2eImageIcon = new ImageIcon(
    getClass().getResource("/image/intro2e.gif"));
private ImageIcon intro3eImageIcon = new ImageIcon(
    getClass().getResource("/image/intro3e.jpg"));
```

```
// Create table data
private Object[][] rowData = {
    {"Introduction to Java Programming", 120,
     "Que Education & Training",
     new GregorianCalendar(1998, 1-1, 6).getTime(),
     false, intro1eImageIcon},
    {"Introduction to Java Programming, 2E", 220,
     "Que Education & Training",
     new GregorianCalendar(1999, 1-1, 6).getTime(),
     false, intro2eImageIcon},
    {"Introduction to Java Programming, 3E", 220,
     "Prentice Hall",
     new GregorianCalendar(2000, 12-1, 0).getTime(),
     true, intro3eImageIcon},
};
```

```
// Create a table model
private MyTableModel tabl
    rowData, columnNames);

// Create a table
private JTable jTable1 =
```

```
/** Override this method to return a class for the column */
public Class getColumnClass(int column) {
    return getValueAt(0, column).getClass();
}
```

```
/** Override this method to return true if cell is editable */
public boolean isCellEditable(int row, int column) {
    Class columnClass = getColumnClass(column);
    return columnClass != ImageIcon.class &&
        columnClass != Date.class;
}
```

MyTableModel


Custom Table Renderers and Editors

Predefined renderers and editors are convenient and easy to use, but their functions are limited. The predefined image icon renderer displays the image icon in a label. The image icon cannot be scaled. If you want the whole image to fit in a cell, you need to create a custom renderer.

A custom renderer can be created by extending the `DefaultTableCellRenderer`, which is a default implementation for the `TableCellRenderer` interface. The custom renderer must **override** the `getTableCellRendererComponent()` to return a component for rendering the table cell. The `getTableCellRendererComponent()` is defined as follows:


```
public Component getTableCellRendererComponent  
(JTable table, Object value, boolean isSelected,  
boolean isFocused, int row, int column)
```




This method signature is very similar to the `getListCellRendererComponent()` method used to create custom list cell renderers.



Example: Using Custom Table Renderers and Editors

Problem: Revise Example 36.9, “Using Predefined Table Renderers and Editors,” to **display scaled image icons** and to **use a custom combo editor** to edit the cells in the Publisher column.



Title	Copies Needed	Publisher	Date Publis...	In-stock	Book P...
Introduction to Java Programming	120	Que Edu...	Jan 6, 1998	<input type="checkbox"/>	
Introduction to Java Programming, 2E	220	Que Edu...	Jan 6, 1999	<input checked="" type="checkbox"/>	
Introduction to Java Programming, 3E	220	Prentice ...	Nov 30, 2000	<input checked="" type="checkbox"/>	

CustomTableCellRendererEditorDemo

Run

```
// Set custom renderer for displaying images
TableColumn bookCover = jTable1.getColumn("Book Photo");
bookCover.setCellRenderer(new MyImageCellRenderer());
```

```
// Create a combo box for publishers
JComboBox jcboPublishers = new JComboBox();
jcboPublishers.addItem("Prentice Hall");
jcboPublishers.addItem("Que Education & Training");
jcboPublishers.addItem("McGraw-Hill");

// Set combo box as the editor for the publisher column
TableColumn publisherColumn = jTable1.getColumn("Publisher");
publisherColumn.setCellEditor(
    new DefaultCellEditor(jcboPublishers));
```

```
public class MyImageCellRenderer extends DefaultTableCellRenderer {
    /** Override this method in DefaultTableCellRenderer */
    public Component getTableCellRendererComponent
        (JTable table, Object value, boolean isSelected,
         boolean isFocused, int row, int column) {
        Image image = ((ImageIcon)value).getImage();
        ImageViewer imageViewer = new ImageViewer(image);

        return imageViewer;
    }
}
```

```

4 public class ImageViewer extends JPanel {
5     /** Hold value of property image */
6     private java.awt.Image image;
7
8     /** Hold value of property stretched */
9     private boolean stretched = true;
10
11     /** Hold value of property xCoordinate */
12     private int xCoordinate;
13
14     /** Hold value of property yCoordinate */
15     private int yCoordinate;
16
17     /** Construct an empty image viewer */
18     public ImageViewer() {
19     }
20
21     /** Construct an image viewer for a specified Image object */
22     public ImageViewer(Image image) {
23         this.image = image;
24     }
25
26     @Override
27     protected void paintComponent(Graphics g) {
28         super.paintComponent(g);
29
30         if (image != null)
31             if (isStretched())
32                 g.drawImage(image, xCoordinate, yCoordinate,
33                     getSize().width, getSize().height, this);
34             else
35                 g.drawImage(image, xCoordinate, yCoordinate, this);
36     }
37
38     /** Return value of property image */
39     public java.awt.Image getImage() {
40         return image;
41     }
42
43     /** Set a new value for property image */
44     public void setImage(java.awt.Image image) {
45         this.image = image;
46         repaint();
47     }

```

Table Events

JTable does not fire table events.

It fires the events such as MouseEvent, KeyEvent, and ComponentEvent inherited from its superclass JComponent.

Table events are fired by table models, table column models, and table-selection models whenever changes are made to these models.

Table models fire TableModelEvent when table data are changed.


Table column models fire TableColumnModelEvent when columns are added, removed, or moved, or when the column selection changes.

Table-selection models fire ListSelectionEvent when the selection changes.



Example: Using Table Events

Problem: This example demonstrates handling table events. The program displays messages on a text area when a row or a column is selected, when a cell is edited, or when a column is removed.



TableEventDemo

Run



```
tableModel.addTableModelListener(new TableModelListener() {
    @Override
    public void tableChanged(TableModelEvent e) {
        jtaMessage.append("Table changed at row " +
            e.getFirstRow() + " and column " + e.getColumn() + "\n");
    }
});
```

```
tableColumnModel.addColumnModelListener(
    new TableColumnModelListener() {
        @Override
        public void columnRemoved(TableColumnModelEvent e) {
            jtaMessage.append("Column indexed at " + e.getFromIndex() +
                " is deleted \n");
        }
    }
);
```

```

@Override
public void columnAdded(TableColumnModelEvent e) {
}

@Override
public void columnMoved(TableColumnModelEvent e) {
}

@Override
public void columnMarginChanged(TableColumnModelEvent e) {
}


@Override
public void columnSelectionChanged(ListSelectionEvent e) {
}
});
```

```
selectionModel.addListSelectionListener(
    new ListSelectionListener() {
        @Override
        public void valueChanged(ListSelectionEvent e) {
            jtaMessage.append("Row " + jTable1.getSelectedRow() +
                " and column " + jTable1.getSelectedColumn() +
                " selected\n");
        }
    }
);
```


JTree

JTree is a Swing component that displays data in a treelike hierarchy.

Root




Leaf



Tree Models

While JTree displays the tree, the data representation of the tree is handled by TreeModel, TreeNode, and TreePath. TreeModel represents the entire tree, TreeNode represents a node, and TreePath represents a path to a node. Unlike the ListModel or TableModel, **the tree model does not directly store or manage tree data**. Tree data are stored and managed in TreeNode and TreePath.



The TreeSelectionModel interface handles tree node selection.

The DefaultTreeCellRenderer class provides a default tree node renderer that can display a label and/or an icon in a node.

The DefaultTreeCellEditor can be used to edit the cells in a text field.⁶

```

145 @SuppressWarnings("serial")
146 public class JTree extends JComponent implements Scrollable, Accessible
147 {
148     /**
149      * @see #getUIClassID
150      * @see #readObject
151      */
152     private static final String uiClassID = "TreeUI";
153
154     /**
155      * The model that defines the tree displayed by this object.
156      */
157     transient protected TreeModel treeModel;
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

```

DefaultTreeModel


- ◊ root : **TreeNode**
- ◊ listenerList : **EventListenerList**
- ◊ asksAllowsChildren : **boolean**
- DefaultTreeModel(TreeNode)
- DefaultTreeModel(TreeNode, boolean)
- setAsksAllowsChildren(boolean) : **void**
- asksAllowsChildren() : **boolean**
- setRoot(TreeNode) : **void**
- getRoot() : **Object**
- getIndexOfChild(Object, Object) : **int**
- getChild(Object, int) : **Object**
- getChildCount(Object) : **int**
- isLeaf(Object) : **boolean**
- reload() : **void**
- valueForPathChanged(TreePath, Object) : **void**
- insertNodeInto(MutableTreeNode, MutableTreeNode, int) : **void**
- removeNodeFromParent(MutableTreeNode) : **void**
- nodeChanged(TreeNode) : **void**
- reload(TreeNode) : **void**
- nodesWereInserted(TreeNode, int[]) : **void**
- nodesWereRemoved(TreeNode, int[], Object[]) : **void**
- nodesChanged(TreeNode, int[]) : **void**
- nodeStructureChanged(TreeNode) : **void**
- getPathToRoot(TreeNode) : **TreeNode[]**
- ◊ getPathToRoot(TreeNode, int) : **TreeNode[]**
- addTreeModelListener(TreeModelListener) : **void**
- removeTreeModelListener(TreeModelListener) : **void**
- getTreeModelListeners() : **TreeModelListener[]**
- ◊ fireTreeNodesChanged(Object, Object[], int[], Object)
- ◊ fireTreeNodesInserted(Object, Object[], int[], Object)
- ◊ fireTreeNodesRemoved(Object, Object[], int[], Object)
- ◊ fireTreeStructureChanged(Object, Object[], int[], Object)
- fireTreeStructureChanged(Object, TreePath) : **void**
- getListeners(Class<T>) <T extends EventListener> : **EventListenerList**
- writeObject(ObjectOutputStream) : **void**

The JTree Class

javax.swing.JTree	
#cellEditor: TreeCellEditor	Specifies a cell editor used to edit entries in the tree.
#cellRenderer: TreeCellRenderer	Specifies whether individual cells can be selected (Obsolete since JDK 1.3).
#editable: boolean	Specifies whether the cells are editable (default: false).
#model: TreeModel	Maintains the tree model.
#rootVisible: boolean	Specifies whether the root is displayed (depending on the constructor).
#rowHeight: int	Specifies the height of the row for the node displayed in the tree (default: 16 pixels).
#scrollsOnExpand: boolean	If true, when a node is expanded, as many of the descendants are scrolled to be visible (default: 16 pixels).
#selectionModel: TreeSelectionModel	Models the set of selected nodes in this tree.
#showsRootHandles: boolean	Specifies whether the root handles are displayed (default: true).
#toggleClickCount: int	Number of mouse clicks before a node is expanded (default: 2).
-anchorSelectionPath: TreePath	The path identified as the anchor.
-expandsSelectedPaths: boolean	True if paths in the selection should be expanded (default: true).
-leadSelectionPaths: TreePath	The path identified as the lead.
+JTree()	Creates a JTree with a sample tree model, as shown in Figure 24.35.
+JTree(value: java.util.Hashtable)	Creates a JTree with an invisible root and the keys in the Hashtable key/value pairs as its children.
+JTree(value: Object[])	Creates a JTree with an invisible root and the elements in the array as its children.
+JTree(newModel: TreeModel)	Creates a JTree with the specified tree model.
+JTree(root: TreeNode)	Creates a JTree with the specified tree node as its root.
+JTree(root: TreeNode, asksAllowsChildren: boolean)	Creates a JTree with the specified tree node as its root and decides whether a node is a leaf node in the specified manner.
+JTree(value: Vector)	Creates a JTree with an invisible root and the elements in the vector as its children.
+addSelectionPath(path: TreePath): void	Adds the specified TreePath to the current selection.
+addSelectionPaths(paths: TreePath[]): void	Adds the specified TreePaths to the current selection.
+addSelectionRow(row: int): void	Adds the path at the specified row to the current selection.
+addSelectionRows(rows: int[]): void	Adds the path at the specified rows to the current selection.
+clearSelection(): void	Clears the selection.
+collapsePath(path: TreePath): void	Ensures that the node identified by the specified path is collapsed and viewable.
+getSelectionPath(): TreePath	Returns the path from the root to the first selected node.
+getSelectionPaths(): TreePath[]	Returns the paths from the root to all the selected nodes.
+getLastSelectedPathComponent()	Returns the last node in the first selected TreePath.
+getRowCount(): int	Returns the number of rows currently being displayed.
+removeSelectionPath(path: TreePath): void	Removes the node in the specified path.
+removeSelectionPaths(paths: TreePath[]): void	Removes the node in the specified paths.

Example: Simple Tree Demo

Problem: Write a program to create four trees: a default tree using the no-arg constructor, a tree created from an array of objects, a tree created from a vector, and a tree created from a hash table. Enable the user to dynamically set the properties for rootVisible, rowHeight, and showsRootHandles.



SimpleTreeDemo

Run

```

boolean rootVisible =
    jcbRootVisible.getSelectedItemAt().equals("true");
jTree1.setRootVisible(rootVisible);
jTree2.setRootVisible(rootVisible);
jTree3.setRootVisible(rootVisible);
jTree4.setRootVisible(rootVisible);

```

```



boolean showsRootHandles =
    jcbShowsRootHandles.getSelectedItemAt().equals("true");
jTree1.setShowsRootHandles(showsRootHandles);
jTree2.setShowsRootHandles(showsRootHandles);
jTree3.setShowsRootHandles(showsRootHandles);
jTree4.setShowsRootHandles(showsRootHandles);

```

```

int height =
    ((Integer)(jSpinnerRowHeight.getValue())).intValue();
jTree1.setRowHeight(height);
jTree2.setRowHeight(height);
jTree3.setRowHeight(height);
jTree4.setRowHeight(height);


```



TreeModel and DefaultTreeModel

TreeModel contains the **structural information** about the tree, and **tree data are stored and managed by TreeNode**.

DefaultTreeModel is a concrete implementation for TreeModel that uses TreeNodes.



A diagram showing a red arrow pointing from the `DefaultTreeModel` class box to the `TreeModel` class box, indicating inheritance. A dashed red arrow points from the `DefaultTreeModel` box to the text on the left.

<i>javax.swing.tree.TreeModel</i>
<i>+getChild(parent: Object, index: int): Object</i> <i>+getChildCount(parent: Object): int</i> <i>+getIndexOfChild(parent: Object, child: Object): int</i> <i>+getRoot(): Object</i> <i>+isLeaf(node: Object): boolean</i> <i>+addTreeModelListener(listener: TreeModelListener): void</i> <i>+removeTreeModelListener(listener: TreeModelListener): void</i> <i>+valueForPathChanged(path: TreePath, newValue: Object): void</i>

Returns the child of parent at the index in the parent's child array.
Returns the number of children of the specified parent in the tree model.
Returns the index of child in parent. If parent or child is null, returns -1.
Returns the root of the tree. Returns null if the tree is empty.
Returns true if the specified node is a leaf.
Adds a listener for the TreeModelEvent posted after the tree changes.
Removes a listener previously added with addTreeModelListener.
Messaged when the user has altered the value for the item identified by path to newValue.

<i>javax.swing.tree.DefaultTreeModel</i>
<i>#asksAllowsChildren: Boolean</i> <i>#root: TreeNode</i>
<i>+DefaultTreeModel(root: TreeNode)</i> <i>+DefaultTreeModel(root: TreeNode, asksAllowsChildren: boolean)</i> <i>+asksAllowsChildren(): boolean</i> <i>+getPathToRoot(aNode: TreeNode): TreeNode[]</i> <i>+insertNodeInto(newChild: MutableTreeNode, parent: MutableTreeNode, index: int): void</i> <i>+reload(): void</i> <i>+removeNodeFromParent(node: MutableTreeNode): void</i>

Tells how leaf nodes are determined. True if only nodes that do not allow children are leaf nodes, false if nodes that have no children are leaf nodes.
The root of the tree.
Creates a DefaultTreeModel with the specified root.
Creates a DefaultTreeModel with the specified root and decides whether a node is a leaf node in the specified manner.
Returns asksAllowsChildren.
Returns the nodes in an array from root to the specified node.
Inserts newChild at location index in parents children.
Reloads the model (invoke this method if the tree has been modified)
Removes the node from its parent.

TreeNode, MutableTreeNode, and DefaultMutableTreeNode

TreeNode stores models a single node in the tree.

MutableTreeNode defines a subinterface of TreeNode with additional methods for changing the content of the node, for inserting and removing a child node, for setting a new parent, and for removing the node itself.

DefaultMutableTreeNode is a concrete implementation of MutableTreeNode.

<i>javax.swing.tree.TreeNode</i>
<i>+children(): java.util.Enumeration</i>
<i>+getAllowsChildren(): boolean</i>
<i>+getChildAt(childIndex: int): TreeNode</i>
<i>+getChildCount(): int</i>
<i>+getIndex(node: TreeNode): int</i>
<i>+getParent(): TreeNode</i>
<i>+isLeaf(): boolean</i>

Returns the children of this node.
Returns true if this node can have children.
Returns the child *TreeNode* at index *childIndex*.
Returns the number of children under this node.
Returns the index of the specified node in the current node's children.
Returns the parent of this node.
Returns true if this node is a leaf.

<i>javax.swing.tree.MutableTreeNode</i>
<i>+insert(child: MutableTreeNode, index: int): void</i>
<i>+remove(index: int): void</i>
<i>+remove(node: MutableTreeNode): void</i>
<i>+removeFromParent(): void</i>
<i>+setParent(newParent: MutableTreeNode): void</i>
<i>+setUserObject(object: Object): void</i>


Adds the specified child under this node at the specified index.
Removes the child at the specified index from this node's child list.
Removes the specified node from this node's child list.
Removes this node from its parent.
Sets the parent of this node to the specified *newParent*.
Resets the user object of this node to the specified object.

<i>javax.swing.tree.DefaultMutableTreeNode</i>
<i>#allowsChildren: Boolean</i>
<i>#parent: MutableTreeNode</i>
<i>#userObject: Object</i>
<i>+DefaultMutableTreeNode()</i>
<i>+DefaultMutableTreeNode(userObject: Object)</i>
<i>+DefaultMutableTreeNode(userObject: Object, allowsChildren: boolean)</i>
<i>+add(MutableTreeNode newChild)</i>
<i>+getChildAfter(aChild: TreeNode): TreeNode</i>
<i>+getChildBefore(aChild: TreeNode): TreeNode</i>
<i>+getFirstChild(): TreeNode</i>
<i>+getLastChild(): TreeNode</i>
<i>+getFirstLeaf(): DefaultMutableTreeNode</i>
<i>+getLastLeaf(): DefaultMutableTreeNode</i>
<i>+getNextLeaf(): DefaultMutableTreeNode</i>
<i>+getPreviousLeaf(): DefaultMutableTreeNode</i>
<i>+getLeafCount(): int</i>
<i>+getDepth(): int</i>
<i>+getLevel(): int</i>
<i>+getNextNode(): DefaultMutableTreeNode</i>
<i>+getPreviousNode(): DefaultMutableTreeNode</i>
<i>+getSiblingCount(): int</i>
<i>+getNextSibling(): DefaultMutableTreeNode</i>
<i>+getPath(): TreeNode[]</i>
<i>+getRoot(): TreeNode</i>
<i>+isRoot(): boolean</i>
<i>+breadthFirstEnumeration(): Enumeration</i>
<i>+depthFirstEnumeration(): Enumeration</i>
<i>+postorderEnumeration(): Enumeration</i>
<i>+preorderEnumeration(): Enumeration</i>

True if the node is able to have children.
Stores the parent of this node.
Stores the content of this node.
Creates a tree node without user object, and allows children.
Creates a tree node with the specified user object, and allows children.
Creates a tree node with the specified user object and the specified mode to indicate whether children are allowed.
Adds the specified node to the end of this node's child vector.
Returns the next (previous) sibling of the specified child in this node's child vector.
These two methods return this node's first (last) child in the child's vector of this node.
These four methods return the first (last, next, and previous) leaf that is a descendant of this node. The first (last, next, and previous) leaf is recursively defined as the first (last, next, and previous) child's first (last, next, and previous) leaf.
Returns the total number of leaves that are descendants of this node.
Returns the depth of the tree rooted at this node.
Returns the distance from the root to this node.
Returns the node that follows (precedes) this node in a preorder traversal of this node.
Returns the number of siblings of this node.
Returns the next sibling of this node in the parent's child vector.
Returns the path from the root to this node.
Returns the root of the tree that contains this node.
Returns true if this node is the root of the tree.
Creates and returns an enumeration that traverses the subtree rooted at this node in breadth-first order (depth-first order, postorder, preorder). These traversals were discussed in Chapter 17, "Data Structure Implementations."

Example: Tree Model Demo

Problem: Write a program to create two trees that displays world, continents, countries and states. The two trees display identical contents. The program also displays the properties of the tree in a text area.



TreeNodeDemo

Run

```
// Create the first tree
DefaultMutableTreeNode root, europe, northAmerica, us;

europe = new DefaultMutableTreeNode("Europe");
europe.add(new DefaultMutableTreeNode("UK"));
europe.add(new DefaultMutableTreeNode("Germany"));
europe.add(new DefaultMutableTreeNode("France"));
europe.add(new DefaultMutableTreeNode("Norway"));

northAmerica = new DefaultMutableTreeNode("North America");

// Get tree information
jtaMessage.append("Depth of the node US is " + us.getDepth());
jtaMessage.append("\nLevel of the node US is " + us.getLevel());
jtaMessage.append("\nFirst child of the root is " +
    root.getFirstChild());
jtaMessage.append("\nFirst leaf of the root is " +
    root.getFirstLeaf());
jtaMessage.append("\nNumber of the children of the root is " +
    root.getChildCount());
jtaMessage.append("\nNumber of leaves in the tree is " +
    root.getLeafCount());
String breadthFirstSearchResult = "";

// Breadth-first traversal
Enumeration bf = root.breadthFirstEnumeration();
while (bf.hasMoreElements())
    breadthFirstSearchResult += bf.nextElement().toString() + " ";
jtaMessage.append("\nBreath-first traversal from the root is "
    + breadthFirstSearchResult);
```

TreeNodeDemo

World

- Europe
 - UK
 - Germany
 - France
 - Norway
- North America

World

- Europe
- North America

Depth of the node US is 1
Level of the node US is 2
First child of the root is Europe
First leaf of the root is UK
Number of the children of the root is 2
Number of leaves in the tree is 10
Breath-first traversal from the root is World Europe North America UK Germany France Norway US
Canada California Texas New York Florida Illinois



The TreePath Class


The TreePath class represents a path from an ancestor to a descendant in a tree.

javax.swing.tree.TreePath	
+TreePath(singlePath: Object)	Constructs a TreePath containing only a single element.
+TreePath(path: Object[])	Constructs a path from an array of objects.
+getLastPathComponent(): Object	Returns the last component of this path.
+getParentPath(): TreePath	Returns a path containing all but the last path component.
+getPath(): Object[]	Returns an ordered array of objects containing the components of this TreePath.
+getPathComponent(element: int): Object	Returns the path component at the specified index.
+getPathCount(): int	Returns the number of elements in the path.
+isDescendant(aTreePath: TreePath): Boolean	Returns true if aTreePath contains all the components in this TreePath.
+pathByAddingChild(child: Object): TreePath	Returns a new path containing all the elements of this TreePath plus child.



TreeSelectionModel and DefaultTreeSelectionModel

The selection of tree nodes is defined in the TreeSelectionModel interface.




Adds the specified `TreePath` to the current selection.
Adds the specified `TreePaths` to the current selection.
Clears the selection.
Returns the last path in the selection.
Returns the number of paths in the selection.
Returns the first path in the selection.
Returns all the paths in the selection.
Returns the current selection mode,
Removes path from the selection.
Removes paths from the selection.
Sets the selection mode.
Sets the selection to path.
Sets the selection to paths.
Register a `TreeSelectionListener`.
Remove a `TreeSelectionListener`.

The DefaultTreeSelectionModel class is a concrete implementation of the TreeSelectionModel, which maintains an array of TreePath objects representing the current selection.

Example: Modifying Trees

Problem: Write a program to create two trees that displays the same contents: world, continents, countries and states, as shown in Figure 36.44. For the left tree on the left, enable the user to **choose a selection mode**, add a **new child under the first selected node**, and **remove all the selected nodes**.



ModifyTree

Run

```
// Register listeners
jcbSelectionMode.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        if (jcbSelectionMode.getSelectedItem().
            equals("CONTIGUOUS_TREE_SELECTION"))
            jTree1.getSelectionModel().setSelectionMode(
                TreeSelectionMode.CONTIGUOUS_TREE_SELECTION);
        else if (jcbSelectionMode.getSelectedItem().
            equals("DISCONTIGUOUS_TREE_SELECTION"))
            jTree1.getSelectionModel().setSelectionMode(
                TreeSelectionMode.DISCONTIGUOUS_TREE_SELECTION);
        else
            jTree1.getSelectionModel().setSelectionMode(
                TreeSelectionMode.SINGLE_TREE_SELECTION);
    }
});

jchkEditable.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        jTree1.setEditable(jchkEditable.isSelected());
    }
});
```



```

jbtAdd.addActionListener(new ActionListener() {
    @Override
    public void actionPerformed(ActionEvent e) {
        DefaultMutableTreeNode parent = (DefaultMutableTreeNode)
            jTree1.getLastSelectedPathComponent();

        if (parent == null) {
            JOptionPane.showMessageDialog(null,
                "No node in the left tree is selected");
            return;
        }

        // Enter a new node
        String nodeName = JOptionPane.showInputDialog(
            null, "Enter a child node for " + parent, "Add a Child",
            JOptionPane.QUESTION_MESSAGE);

        // Insert the new node as a child of treeNode
        parent.add(new DefaultMutableTreeNode(nodeName));

        // Reload the model since a new tree node is added
        ((DefaultTreeModel) (jTree1.getModel())).reload();
        ((DefaultTreeModel) (jTree2.getModel())).reload();
    }
});

```

```

jbtRemove.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) {
        // Get all selected paths
        TreePath[] paths = jTree1.getSelectionPaths();

        if (paths == null) {
            JOptionPane.showMessageDialog(null,
                "No node in the left tree is selected");
            return;
        }

        // Remove all selected nodes
        for (int i = 0; i < paths.length; i++) {
            DefaultMutableTreeNode node = (DefaultMutableTreeNode)
                (paths[i].getLastPathComponent());

            if (node.isRoot()) {
                JOptionPane.showMessageDialog(null,
                    "Cannot remove the root");
            }
            else
                node.removeFromParent();
        }


        // Reload the model since a new tree node is added
        ((DefaultTreeModel) (jTree1.getModel())).reload();
        ((DefaultTreeModel) (jTree2.getModel())).reload();
    }
});

```

Tree Node Rendering

DefaultTreeCellRenderer renderer =

```
(DefaultTreeCellRenderer)jTree1.getCellRenderer();  
renderer.setLeafIcon(yourCustomLeafImageIcon);  
renderer.setOpenIcon(yourCustomOpenImageIcon);  
renderer.setClosedIcon(yourCustomClosedImageIcon);  
renderer.setBackgroundSelectionColor(Color.red);
```



Tree Editing

// Customize editor

```
JComboBox jcboColor = new JComboBox();
```

```
jcboColor.addItem("red");
```

```
jcboColor.addItem("green");
```

```
jcboColor.addItem("blue");
```

```
jcboColor.addItem("yellow");
```

```
jcboColor.addItem("orange");
```

```
jTree1.setCellEditor(new DefaultCellEditor(jcboColor));
```

```
jTree1.setEditable(true);
```



Tree Rendering and Editing

```
jTree1.setCellEditor
```

```
(new DefaultTreeCellEditor(jTree1,  
    new DefaultTreeCellRenderer(),  
    new DefaultCellEditor(jcboColor))));
```



TreeCellRendererEditorDemo

Tree Events

JTree can fire TreeSelectionEvent and TreeExpansionEvent, among many other events.

Whenever a new node is selected, JTree fires a TreeSelectionEvent.
Whenever a node is expanded or collapsed, JTree fires a TreeExpansionEvent.

To handle the tree selection event, a listener must implement the TreeSelectionListener interface, which contains a single handler named valueChanged method.

TreeExpansionListener contains two handlers named treeCollapsed and treeExpanded for handling node expansion or node closing.

