

AshLib Reference Documentation

Documentation for AshLib v3.4.0, by Siljam

<https://github.com/siljamdev/AshLib>



Documentation for AshLib v3.4.0, by siljam.

<https://github.com/siljamdev/AshLib>

Index

Structs	13
Color3	13
Namespace	13
Constructors	13
<i>Color3(byte, byte, byte)</i>	13
<i>Color3(string)</i>	13
Fields	13
<i>R</i>	13
<i>G</i>	14
<i>B</i>	14
<i>Black</i>	14
<i>White</i>	14
<i>Gray</i>	14
<i>Magenta</i>	14
<i>Cyan</i>	14
<i>Yellow</i>	15
<i>Blue</i>	15
<i>Green</i>	15
<i>Red</i>	15
Methods	15
<i>Parse</i>	15
<i>TryParse</i>	15
<i>FromHSV</i>	16
<i>ToVec</i>	16
<i>Equals</i>	16
<i>ToString</i>	16
Operators	16
<i>Operator == (Color3, Color3)</i>	16
<i>Operator != (Color3, Color3)</i>	16
<i>Implicit Operator Color (Color3)</i>	17
<i>Implicit Operator Color3 (Color)</i>	17
Vec2	17
Namespace	17
Constructors	17
<i>Vec2(float, float)</i>	17
Fields	17
<i>X</i>	17

Y.....	18
Methods.....	18
<i>Equals</i>	18
<i>ToString</i>	18
Operators	18
Operator == (Vec2, Vec2)	18
Operator != (Vec2, Vec2)	18
Vec3	18
Namespace	19
Constructors	19
<i>Vec3(float, float, float)</i>	19
Fields	19
X.....	19
Y.....	19
Z.....	19
Methods.....	19
<i>Equals</i>	19
<i>ToString</i>	20
Operators	20
Operator == (Vec3, Vec3)	20
Operator != (Vec3, Vec3)	20
Vec4	20
Namespace	20
Constructors	20
<i>Vec4(float, float, float, float)</i>	20
Fields	21
X.....	21
Y.....	21
Z.....	21
W	21
Methods.....	21
<i>Equals</i>	21
<i>ToString</i>	21
Operators	22
Operator == (Vec4, Vec4)	22
Operator != (Vec4, Vec4)	22
Date	22
Namespace	22
Constructors	22
<i>Date(byte, byte, byte, byte, byte, ushort)</i>	22
<i>Date(string)</i>	22
Properties.....	23
<i>seconds</i>	23
<i>minutes</i>	23

<i>hours</i>	23
<i>days</i>	23
<i>months</i>	23
<i>years</i>	23
Methods	24
<i>ToCPTF</i>	24
<i>FromCPTF</i>	24
<i>Equals</i>	24
<i>ToString</i>	24
Operators	24
Operator == (<i>Date</i> , <i>Date</i>)	24
Operator != (<i>Date</i> , <i>Date</i>)	24
Explicit Operator <i>DateTime</i> (<i>Date</i>)	25
Explicit Operator <i>Date</i> (<i>DateTime</i>)	25
AshFileFormatConfig	25
Namespace	25
Constructors	25
<i>AshFileFormatConfig</i> (<i>bool</i> , <i>bool</i> , <i>bool</i>)	25
<i>AshFileFormatConfig</i> (<i>byte</i>)	25
Fields	26
<i>compactBools</i>	26
<i>maskCampNames</i>	26
<i>maskStrings</i>	26
<i>Default</i>	26
Methods	26
<i>ToByte</i>	26
Enums	27
AshFileTypeOld	27
Namespace	27
Fields	27
<i>ByteArray</i>	27
<i>String</i>	27
<i>Byte</i>	27
<i>Ushort</i>	27
<i>UInt</i>	28
<i>Ulong</i>	28
<i>Sbyte</i>	28
<i>Short</i>	28
<i>Int</i>	28
<i>Long</i>	28
<i>Color</i>	28
<i>Float</i>	29
<i>Double</i>	29
<i>Vec2</i>	29

<i>Vec3</i>	29
<i>Vec4</i>	29
<i>Bool</i>	29
<i>UbyteArray</i>	29
<i>UshortArray</i>	30
<i>UIntArray</i>	30
<i>UlongArray</i>	30
<i>SbyteArray</i>	30
<i>ShortArray</i>	30
<i>IntArray</i>	30
<i>LongArray</i>	30
<i>FloatArray</i>	31
<i>DoubleArray</i>	31
<i>Date</i>	31
AshFileType	31
Namespace	31
Fields	31
<i>Default</i>	31
<i>String</i>	31
<i>Byte</i>	32
<i>Ushort</i>	32
<i>UInt</i>	32
<i>Ulong</i>	32
<i>Sbyte</i>	32
<i>Short</i>	32
<i>Int</i>	32
<i>Long</i>	33
<i>Color3</i>	33
<i>Float</i>	33
<i>Double</i>	33
<i>Vec2</i>	33
<i>Vec3</i>	33
<i>Vec4</i>	33
<i>Bool</i>	34
<i>Date</i>	34
ModelInstanceOperation	34
Namespace	34
Fields	34
<i>Delete</i>	34
<i>Exists</i>	34
<i>Type</i>	34
<i>TypeCast</i>	35
<i>Value</i>	35
<i>None</i>	35

Classes	35
DeltaHelper	35
Namespace	35
Properties	35
<i>deltaTime</i>	35
<i>fps</i>	36
<i>stableFps</i>	36
Methods	36
<i>Start</i>	36
<i>Frame</i>	36
<i>Target</i>	36
<i>TargetLazy</i>	36
<i>SetStableUpdateTime</i>	37
<i>GetTime</i>	37
TimeTool	37
Namespace	37
Constructors	37
<i>TimeTool(params string[])</i>	37
Fields	37
<i>maxHistory</i>	37
Properties	38
<i>categoryNames</i>	38
Methods	38
<i>Reset</i>	38
<i>LoopStart</i>	38
<i>CategoryEnd()</i>	38
<i>CategoryEnd(int)</i>	38
<i>LoopEnd</i>	39
<i>LastLoopInfo</i>	39
<i>LastLoopString</i>	39
<i>MeanInfo</i>	39
<i>MaxInfo</i>	39
<i>MeanString</i>	39
TreeNode<T>	40
Namespace	40
Constructors	40
<i>TreeNode(T)</i>	40
<i>TreeNode(T, List<TreeNode<T>>)</i>	40
Fields	40
<i>value</i>	40
Properties	40
<i>children</i>	40
<i>parent</i>	41

<i>isLeaf</i>	41
<i>isRoot</i>	41
Methods.....	41
<i>AddChild</i>	41
<i>RemoveChild</i>	41
<i>ClearChildren</i>	41
<i>CountChildren</i>	42
<i>Clone()</i>	42
<i>Clone(Converter<TreeNode<T>, TreeNode<T2>>)</i>	42
<i>FindRoot</i>	42
<i>CountDescendants</i>	42
<i>CountLeafs</i>	42
<i>DetermineTreeDepth</i>	42
<i>GetAllNodes</i>	43
<i>GetAllLeafNodes</i>	43
<i>TraversePreOrder</i>	43
<i>TraversePostOrder</i>	43
<i>TraverseLevelOrder</i>	43
<i>TraverseLeafsOnly</i>	43
<i>GetDepth</i>	44
<i>GetPathToRoot</i>	44
<i>FindNode(T)</i>	44
<i>FindNode(Predicate<TreeNode<T>>)</i>	44
<i>FindNode(Func<T, bool>)</i>	44
<i>FindChildNode(T)</i>	44
<i>FindChildNode(Predicate <TreeNode<T>>)</i>	45
<i>FindChildNode(Predicate <T>)</i>	45
<i>ToStringFormat</i>	45
<i>ParseStringFormat(string)</i>	45
<i>ParseStringFormat(string, Func<string, T>)</i>	45
<i>TryParseStringFormat(string, out TreeNode<string>)</i>	46
<i>TryParseStringFormat(string, Func<string, T>, out TreeNode<string>)</i>	46
<i>ToString</i>	46
<i>ToFormattedString</i>	46
Dependencies.....	46
Namespace.....	46
Constructors	47
<i>Dependencies(string, bool, string[], string[])</i>	47
Fields	47
<i>path</i>	47
<i>config</i>	47
Methods.....	47
<i>ReadFileText</i>	47
<i>ReadAshFile</i>	47

<i>SaveFileText</i>	48
<i>SaveAshFile</i>	48
<i>CreateDir</i>	48
TreeLog	48
Namespace	48
Methods	48
<i>GetLog</i>	48
<i>Clear</i>	48
<i>Deep</i>	49
<i>Shallow</i>	49
<i>Write(string)</i>	49
<i>Write(object)</i>	49
AshFileException	49
Namespace	49
Properties	50
<i>errorCode</i>	50
Methods	50
<i>GetFullMessage</i>	50
<i>ToString</i>	50
<i>GetObjectData</i>	50
CharFormat	50
Namespace	50
Constructors	51
<i>CharFormat(byte?, bool?, byte?, bool?, Color3?, bool, Color3?, bool)</i>	51
<i>CharFormat(Color3?, bool, Color3?, bool)</i>	51
<i>CharFormat(Color3?, Color3?)</i>	51
<i>CharFormat(Color3?, bool)</i>	51
<i>CharFormat(Color3?)</i>	51
<i>CharFormat()</i>	52
Fields	52
<i>ResetAll</i>	52
Properties	52
<i>density</i>	52
<i>italic</i>	52
<i>underline</i>	52
<i>strikeThrough</i>	52
<i>foreground</i>	53
<i>foregroundReset</i>	53
<i>background</i>	53
<i>backgroundReset</i>	53
Methods	53
<i>ToString</i>	53
<i>Equals</i>	53

Operators	54
Operator ==(CharFormat, CharFormat)	54
Operator !=(CharFormat, CharFormat)	54
FormatString	54
Namespace	54
Constructors	54
FormatString()	54
FormatString(FormatString)	54
FormatString(FormatString)	55
FormatString(string)	55
FormatString (string, CharFormat?)	55
Fields	55
addFinalReset	55
usesColors	55
Properties	55
content	55
format	56
built	56
Length	56
Count	56
IsReadOnly	56
Methods	56
Clear	56
Clone()	57
Clone(FormatString)	57
GetEnumerator	57
Append(string, IEnumerable<CharFormat?>	57
Append(string, CharFormat?)	57
Append(object, CharFormat?)	57
Append(FormatString)	57
Append((char, CharFormat?))	58
Append(string)	58
Add	59
Contains	59
Substring	59
SplitIntoLines	59
RemoveFromStart	59
RemoveFromEnd	59
Remove	59
RemoveRange	60
CopyTo	60
Equals(object)	60
Equals(FormatString?)	60
ToString	60

Operators	60
Operator +(FormatString, FormatString)	60
Operator +(string, FormatString)	61
Operator +(FormatString, string)	61
Operator +(char, FormatString)	61
Operator +(FormatString, char)	61
Operator *(FormatString, CharFormat?)	61
Operator ==(FormatString, FormatString)	61
Operator !=(FormatString, FormatString)	61
Implicit Operator FormatString(string)	62
AshFile	62
Namespace	62
Constructors	62
AshFile()	62
AshFile(AshFile)	62
AshFile(IDictionary<string, object>)	62
AshFile(string)	63
Fields	63
path	63
format	63
compactBools	63
maskCampNames	63
maskStrings	63
defaultSeparator	64
currentVersion	64
Properties	64
FormatConfig	64
Count	64
Keys	64
Values	64
IsReadOnly	65
IsFixedSize	65
Methods	65
Clear	65
Clone()	65
Clone(AshFile)	65
Merge	65
GetEnumerator	66
Visualize	66
VisualizeFormatted	66
ImportFormatConfig	66
Load(string)	66
Load()	66
Save(string)	67

Save()	67
ReadFromFile	67
ReadFromBytes(byte[], out byte, out AshFileFormatConfig)	67
ReadFromBytes(byte[])	67
WriteToFile	67
WriteToBytes(Dictionary<string, CampValue>, byte)	68
WriteToBytes()	68
GetErrorCount	68
GetErrorLog	68
EmptyErrors	68
ApplyModel(AshFileModel)	68
ApplyModel(AshFile, AshFileModel)	69
GetCampTree	69
GetValueTree	69
VisualizeAsTree	69
GetFormattedValueTree	69
VisualizeAsFormattedTree	70
ContainsKey	70
Contains	70
Set	70
Add(string, object)	70
Add(KeyValuePair<string, object>)	70
Initialize	71
GetValue	71
TryGetValue	71
GetValue<T>	71
TryGetValue<T>	71
GetOrDefault<T>	71
GetValueype	72
TryGetValueType	72
Remove(string)	72
Remove(KeyValuePair<string, object>)	72
RemoveAll	72
Rename	72
CopyTo	73
Equals(object)	73
Equals(AshFile?)	73
Parse	73
TryParse	74
ToString	74
ToStringCompact	74
ToJson	75
Operators	75
Operator [string]	75

Operator == (AshFile, AshFile)	75
Operator != (AshFile, AshFile)	75
Operator + (AshFile, AshFile)	75
Operator * (AshFile, AshFileModel)	75
Explicit Operator AshFile (Dictionary<string, CampValue>).....	76
ModelInstance	76
Namespace	76
Constructors	76
<i>ModelInstance(ModelInstanceOperation, string, object)</i>	76
Fields	76
<i>operation</i>	76
<i>name</i>	76
<i>value</i>	77
AshFileModel	77
Namespace	77
Constructors	77
<i>AshFileModel(params ModelInstance[])</i>	77
Fields	77
<i>allowUnsupportedTypes</i>	77
<i>deleteNotMentioned</i>	77
<i>DeleteUnsupportedTypes</i>	78
Properties	78
<i>instances</i>	78
<i>actions</i>	78
Methods	78
<i>Merge</i>	78
Operators	78
Operator + (AshFileModel, AshFileModel)	78
ReactiveList<T>	79
Namespace	79
Properties	79
<i>Length</i>	79
<i>OnChanged</i>	79
Methods	79
<i>Move</i>	79

Contents

Structs

Color3

Used for holding the values of a RGB color

Namespace

```
AshLib
```

Constructors

Color3(byte, byte, byte)

```
1. public Color3(byte r, byte g, byte b)
```

Initializes a new color taking in arguments for red, green, and blue channels.

Color3(string)

```
1. public Color3(string hex)
```

Initializes a new color taking in argument for the color in hex format. As an example of valid strings are:

```
"ffffff", "#020202", "#eFE02D"
```

Fields

R

```
1. public byte R;
```

Red channel of the color. Ranges 0-255

G

```
1. public byte G;
```

Green channel of the color. Ranges 0-255

B

```
1. public byte B;
```

Blue channel of the color. Ranges 0-255

Black

```
1. public static readonly Color3 Black = new Color3(0, 0, 0);
```

A completely black color

White

```
1. public static readonly Color3 White = new Color3(255, 255, 255);
```

A completely white color

Gray

```
1. public static readonly Color3 Gray = new Color3(150, 150, 150);
```

A medium gray color

Magenta

```
1. public static readonly Color3 Magenta = new Color3(255, 0, 255);
```

A magenta color

Cyan

```
1. public static readonly Color3 Cyan = new Color3(0, 255, 255);
```

A cyan color

Yellow

```
1. public static readonly Color3 Yellow = new Color3(255, 255, 0);
```

A yellow color

Blue

```
1. public static readonly Color3 Blue = new Color3(0, 0, 255);
```

A pure blue color

Green

```
1. public static readonly Color3 Green = new Color3(0, 255, 0);
```

A pure green color

Red

```
1. public static readonly Color3 Red = new Color3(255, 0, 0);
```

A pure red color

Methods

Parse

```
1. public static Color3 Parse (string hex)
```

Attempts to parse the string in hex format. Same as constructor. Might throw an Exception

TryParse

```
1. public static bool TryParse (string hex, out Color3 col)
```

Attempts to parse and returns true if it was possible. The out argument is the parsed Color if successful

FromHSV

```
1. public static Color3 FromHSV (int h, int s, int v)
```

Transforms a HSV color to RGB. h is from 0 to 360, s from 0 to 100 and v from 0 to 100

ToVec

```
1. public Vec3 ToVec ()
```

Transforms the color into a 3 component vector. Each channel is mapped from 0(0) to 1 (255)

Equals

```
1. public override bool Equals (object obj)
```

Checks if two Color3 are equals

ToString

```
1. public override string ToString ()
```

Returns the color data in the format:

```
"#RRGGBB"
```

Operators

Operator == (Color3, Color3)

```
1. public static bool operator == (Color3 a, Color3 b)
```

Checks if two Color3 are equals

Operator != (Color3, Color3)

```
1. public static bool operator != (Color3 a, Color3 b)
```

Checks if two Color3 are not equals

Implicit Operator Color (Color3)

```
1. public static implicit operator System.Drawing.Color (Color3 col)
```

Casts into a System.Drawing.Color

Implicit Operator Color3 (Color)

```
1. public static implicit operator Color3(System.Drawing.Color col)
```

Casts into a Color3

Vec2

Struct for holding two floats, components of a bidimensional vector

Namespace

```
AshLib
```

Constructors

Vec2(float, float)

```
1. public Vec2 (float x, float y)
```

Initializes with x and y component

Fields

X

```
1. public float X;
```

X component of the Vector

Y

```
1. public float Y;
```

Y component of the Vector

Methods

Equals

```
1. public override bool Equals (object obj)
```

Checks if two Vec2 contain the same data

ToString

```
1. public override string ToString ()
```

Returns the vector components in the format:

```
“(X, Y)”
```

Operators

Operator == (Vec2, Vec2)

```
1. public static bool operator == (Vec2 a, Vec2 b)
```

Checks if two Vec2 contain the same data

Operator != (Vec2, Vec2)

```
1. public static bool operator != (Vec2 a, Vec2 b)
```

Checks if two Vec2 do not contain the same data

Vec3

Struct for holding three floats, components of a tridimensional vector

Namespace

```
AshLib
```

Constructors

Vec3(float, float, float)

```
1. public Vec3 (float x, float y, float z)
```

Initializes with x, y and z component

Fields

X

```
1. public float X;
```

X component of the Vector

Y

```
1. public float Y;
```

Y component of the Vector

Z

```
1. public float Z;
```

Z component of the Vector

Methods

Equals

```
1. public override bool Equals (object obj)
```

Checks if two Vec3 contain the same data

ToString

```
1. public override string ToString ()
```

Returns the vector components in the format:

```
"(X, Y, Z)"
```

Operators

Operator == (Vec3, Vec3)

```
1. public static bool operator == (Vec3 a, Vec3 b)
```

Checks if two Vec3 contain the same data

Operator != (Vec3, Vec3)

```
1. public static bool operator != (Vec3 a, Vec3 b)
```

Checks if two Vec3 do not contain the same data

Vec4

Struct for holding four floats, components of a four-dimensional vector

Namespace

```
AshLib
```

Constructors

Vec4(float, float, float, float)

```
1. public Vec4 (float x, float y, float z, float w)
```

Initializes with x, y, z and w component

Fields

X

```
1. public float X;
```

X component of the Vector

Y

```
1. public float Y;
```

Y component of the Vector

Z

```
1. public float Z;
```

Z component of the Vector

W

```
1. public float W;
```

W component of the Vector

Methods

Equals

```
1. public override bool Equals (object obj)
```

Checks if two Vec4 contain the same data

ToString

```
1. public override string ToString ()
```

Returns the vector components in the format:

```
"(X, Y, Z, W)"
```

Operators

Operator == (Vec4, Vec4)

```
1. public static bool operator == (Vec4 a, Vec4 b)
```

Checks if two Vec4 contain the same data

Operator != (Vec4, Vec4)

```
1. public static bool operator != (Vec4 a, Vec4 b)
```

Checks if two Vec4 do not contain the same data

Date

Represents a time between the year 1488 and 2511, down to seconds. It's most important characteristic is CPTF(Compressed printable date format), which will transform the date into a 6 characters long string in base64

Namespace

```
AshLib.Dates
```

Constructors

Date(byte, byte, byte, byte, byte, ushort)

```
1. public Date(byte s, byte m, byte h, byte d, byte mo, ushort y)
```

Initializes the Date with seconds, minutes, hours, days, months, and years(in that order). Numbers will be cropped (seconds 0-59...)

Date(string)

```
1. public Date(string cptf)
```

Initializes the Date directly from CPTF format.

Properties

seconds

```
1. public byte seconds {get;}
```

The seconds of the Date(0-59)

minutes

```
1. public byte minutes {get;}
```

The minutes of the Date(0-59)

hours

```
1. public byte hours {get;}
```

The hours of the Date(0-23)

days

```
1. public byte days {get;}
```

The day of the Date(1-31)

months

```
1. public byte months {get;}
```

The month of the Date(1-12)

years

```
1. public ushort years {get;}
```

The year of the Date(1488-2511)

Methods

ToCPTF

```
1. public string ToCPTF ()
```

Transforms the Date instance into the CPTF format

FromCPTF

```
1. public static Date FromCPTF (string cptf)
```

Transforms a date in CPTF format into an instance. Does the same as the constructor

Equals

```
1. public override bool Equals (object obj)
```

Checks if two Dates are the same

ToString

```
1. public override string ToString ()
```

Returns the Date in the format:

```
"Day/Month/Year Hour:Minute:Second"
```

Operators

Operator == (Date, Date)

```
1. public static bool operator == (Date a, Date b)
```

Checks if two Dates are equals

Operator != (Date, Date)

```
1. public static bool operator != (Date a, Date b)
```

Checks if two Dates are not equals

Explicit Operator DateTime (Date)

```
1. public static explicit operator DateTime (Date d)
```

Casts to DateTime

Explicit Operator Date (DateTime)

```
1. public static explicit operator Date (DateTime d)
```

Casts to Date from DateTime

AshFileFormatConfig

Represents the config of the AshFile byte format

Namespace

```
AshLib.AshFiles
```

Constructors

AshFileFormatConfig(bool, bool, bool)

```
1. public AshFileFormatConfig(bool compactBoo, bool maskCampNam, bool maskStr)
```

Creates a new instance with the three bools

AshFileFormatConfig(byte)

```
1. public AshFileFormatConfig(byte compactByte)
```

Creates a new instance from a compact bool. Used in the byte format

Fields

compactBools

```
1. public bool compactBools;
```

If the bools and bool arrays will compact to occupy 8 bools per byte instead of 1 bool per byte

maskCampNames

```
1. public bool maskCampNames;
```

If the camp names will be masked so it is impossible to read them when viewed as raw text

maskStrings

```
1. public bool maskStrings;
```

If the string values will be masked so it is impossible to read them when viewed as raw text

Default

```
1. public static readonly AshFileFormatConfig Default = new AshFileFormatConfig(true, true, true);
```

The default configuration

Methods

ToByte

```
1. public byte ToByte ()
```

Transforms into a compact bool. Used in the byte format

Enums

AshFileTypeOld

Represents the type of value in an AshFile camp. No longer used in AshFiles V3

Namespace

```
AshLib.AshFiles
```

Fields

ByteArray

```
1. ByteArray = 0;
```

Array of bytes type

String

```
1. String = 1;
```

String type

Byte

```
1. Byte = 2;
```

Byte type. 1 byte unsigned integer

Ushort

```
1. Ushort = 3;
```

Unsigned short type. 2 byte unsigned integer

UInt

```
1. UInt = 4;
```

Unsigned int type. 4 byte unsigned integer

Ulong

```
1. Ulong = 5;
```

Unsigned long type. 8 byte unsigned integer

Sbyte

```
1. Sbyte = 6;
```

Signed byte type. 1 byte signed integer

Short

```
1. Short = 7;
```

Signed short type. 2 byte signed integer

Int

```
1. Int = 8;
```

Signed int type. 4 byte signed integer

Long

```
1. Long = 9;
```

Signed long type. 8 byte signed integer

Color

```
1. Color = 10;
```

Color3 type. Struct defined earlier

Float

```
1. Float = 11;
```

Float type. 4 byte floating point number

Double

```
1. Double = 12;
```

Double type. 8 byte floating point number

Vec2

```
1. Vec2 = 13;
```

Vec2 type. 2 component vector, struct defined earlier

Vec3

```
1. Vec3 = 14;
```

Vec3 type. 3 component vector, struct defined earlier

Vec4

```
1. Vec4 = 15;
```

Vec4 type. 4 component vector, struct defined earlier

Bool

```
1. Bool = 16;
```

Boolean type

UbyteArray

```
1. UbyteArray = 17;
```

Array of bytes type. 1 byte unsigned integer array

UshortArray

```
1. UshortArray = 18;
```

Array of ushort type. 2 byte unsigned integer array

UIntArray

```
1. UIntArray = 19;
```

Array of uint type. 4 byte unsigned integer array

UlongArray

```
1. UshortArray = 20;
```

Array of ulong type. 4 byte unsigned integer array

SbyteArray

```
1. SbyteArray = 21;
```

Array of sbyte type. 1 byte signed integer array

ShortArray

```
1. ShortArray = 22;
```

Array of short type. 2 byte signed integer array

IntArray

```
1. IntArray = 23;
```

Array of int type. 4 byte signed integer array

LongArray

```
1. LongArray = 24;
```

Array of long type. 8 byte signed integer array

FloatArray

```
1. FloatArray = 25;
```

Array of floats type. 4 byte floating point number array

DoubleArray

```
1. DoubleArray = 26;
```

Array of doubles type. 8 byte floating point number array

Date

```
1. Date = 27;
```

Date type. Struct defined earlier

AshFileType

Represents the type of value in an AshFile camp. Used in AshFiles V3

Namespace

```
AshLib.AshFiles
```

Fields

Default

```
1. Default = 0;
```

Default type, often used for invalid types and error checking.

String

```
1. String = 1;
```

String type

Byte

```
1. Byte = 2;
```

Byte type

Ushort

```
1. Ushort = 3;
```

Unsigned short type

Uint

```
1. Uint = 4;
```

Unsigned int type

Ulong

```
1. Ulong = 5;
```

Unsigned long type

Sbyte

```
1. Sbyte = 6;
```

Signed byte type

Short

```
1. Short = 7;
```

Short type

Int

```
1. Int = 8;
```

Int type

Long

```
1. Long = 9;
```

Long type

Color3

```
1. Color3 = 10;
```

Color3 type. Struct defined earlier

Float

```
1. Float = 11;
```

Float type

Double

```
1. Double = 12;
```

Double type

Vec2

```
1. Vec2 = 13;
```

Two component vector type. Struct defined earlier

Vec3

```
1. Vec3 = 14;
```

Three component vector type. Struct defined earlier

Vec4

```
1. Vec4 = 15;
```

Four component vector type. Struct defined earlier.

Bool

```
1. Bool = 16;
```

Boolean type

Date

```
1. Date = 17;
```

Date type. Struct defined earlier

ModelInstanceOperation

Determines the operation that an instance of an AshFile model will do

Namespace

```
AshLib.AshFiles
```

Fields

Delete

```
1. Delete
```

The name mentioned will be deleted

Exists

```
1. Exists
```

Ensures the camp exists

Type

```
1. Type
```

Ensures that a camp is of a determined type

TypeCast

```
1. TypeCast
```

Ensures that a camp is of a determined type of one that can be casted

Value

```
1. Value
```

Ensures that a camp has a specific value

None

```
1. None
```

Does nothing. Mainly used to stop a camp being deleted by deleteNotMentioned

Classes

DeltaHelper

Class used for easily calculating fps and deltaTime

Namespace

```
AshLib.Time
```

Properties

deltaTime

```
1. public double deltaTime {get;}
```

Time that passes between frames, in milliseconds

fps

```
1. public double fps {get;}
```

Frames per second. Is calculated each frame, and so it fluctuates rapidly

stableFps

```
1. public double stableFps {get;}
```

Frames per second. Will update once every second(default behavior, can be changed). Thought for displaying current fps

Methods

Start

```
1. public void Start ()
```

Has to be called to start the utility. Will initialize the internal clock. Call it once at the start of the application

Frame

```
1. public void Frame ()
```

Call it at the very end of each frame, every frame. Updates all the values

Target

```
1. public void Target (double FPS)
```

Call it at the end of each frame, but before Frame(), to achieve the desired fps(the argument)

TargetLazy

```
1. public void TargetLazy (double FPS)
```

Call it at the end of each frame, but before Frame(), to achieve the desired fps(the argument). The wait time will not be exact or precise, but CPU usage wont be maxed

SetStableUpdateTime

```
1. public void SetStableUpdateTime (double milliseconds)
```

Changes how often will the stableFps update

GetTime

```
1. public double GetTime ()
```

Returns the whole time since start, in seconds

TimeTool

Class used for calculating the time things take, and calculating what percentage of time. Each loop(tick, frame...) is divided into categories. Useful for debugging what is holding fps down

Namespace

```
AshLib.Time
```

Constructors

TimeTool(params string[])

```
1. public TimeTool(params string[] categNames)
```

Starts a new instance with an empty history and the names of the categories

Fields

maxHistory

```
1. public int maxHistory
```

The maximum number of loops stored, used for calculating the mean. The default value is 1000

Properties

categoryNames

```
1. public string[] categoryNames {get;}
```

The category names

Methods

Reset

```
1. public void Reset ()
```

Resets the instance and deletes history

LoopStart

```
1. public void LoopStart ()
```

Meant to be executed at the start of each loop

CategoryEnd()

```
1. public void CategoryEnd ()
```

Ends the next category, in order. When executed after LoopStart, ends recording for the category in index 0. Next call for the one in index 1, etc.

CategoryEnd(int)

```
1. public void CategoryEnd (int i)
```

Ends a category specifying its index. The index will be saved and used for next. Useful for categories with parted times. For example:

```
LoopStart();  
CategoryEnd(); //Ends 0  
CategoryEnd(); //Ends 1  
CategoryEnd(0); //Ends 0 again, times added  
CategoryEnd(); //Ends 1 again
```

LoopEnd

```
1. public void LoopEnd ()
```

Ends the loop

LastLoopInfo

```
1. public double[] LastLoopInfo ()
```

Returns a double array with how much time each category took in the last loop. They are ordered according to index, and the last extra element is the total loop time

LastLoopString

```
1. public string LastLoopString ()
```

Returns a nicely formatted string with all the useful information about last loop

MeanInfo

```
1. public double[] MeanInfo ()
```

Returns a double array with how much time each category took on average in all recorded loops. They are ordered according to index, and the last extra element is the average loop time

MaxInfo

```
1. public double[] MaxInfo ()
```

Returns a double array with the maximum time each category took in all recorded loops. They are ordered according to index, and the last extra element is the maximum loop time

MeanString

```
1. public string MeanString ()
```

Generates a nicely formatted string with all the mean and max information of the recorded loops

TreeNode<T>

A class that represents a node of a tree graph. It can also represent a tree in itself with its children

Namespace

```
AshLib.Trees
```

Constructors

TreeNode(T)

```
1. public TreeNode (T val)
```

Initializes the node with its value

TreeNode(T, List<TreeNode<T>>)

```
1. public TreeNode (T val, List<TreeNode<T>> childlist)
```

Initializes the node with its value and the list of children nodes

Fields

value

```
1. public T value;
```

The value of the node

Properties

children

```
1. public List<TreeNode<T>> children {get;}
```

The list of child nodes

parent

```
1. public TreeNode<T>? parent {get;}
```

The parent node, if it exists

isLeaf

```
1. public bool isLeaf {get;}
```

A leaf node is a node with no children

isRoot

```
1. public bool isRoot {get;}
```

A Root node is the node that has no parent

Methods

AddChild

```
1. public void AddChild (TreeNode<T> node)
```

Adds a child node. Please use this method instead of directly adding to the children list, because this sets the parent too

RemoveChild

```
1. public bool RemoveChild (TreeNode<T> node)
```

Attempts to remove a child node and returns true if it was successful

ClearChildren

```
1. public void ClearChildren ()
```

Clears all children nodes

CountChildren

```
1. public int CountChildren ()
```

Returns the number of direct children

Clone()

```
1. public TreeNode<T> Clone ()
```

Clones the tree

Clone(Converter<TreeNode<T>, TreeNode<T2>>)

```
1. public TreeNode<T2> Clone<T2> (Converter<TreeNode<T>, TreeNode<T2>> f)
```

Clones the tree transforming the type with a converter

FindRoot

```
1. public TreeNode<T> FindRoot ()
```

Searches for the root of the tree

CountDescendants

```
1. public int CountDescendants ()
```

Counts the number of children and their children, recursively, giving the number of nodes of the tree downwards

CountLeafs

```
1. public int CountLeafs ()
```

Counts the number of leaf nodes in the descendants

DetermineTreeDepth

```
1. public int DetermineTreeDepth ()
```

Returns the max levels that the tree has until its deepest node. A single root node has a depth of 1

GetAllNodes

```
1. public List<TreeNode<T>> GetAllNodes ()
```

Returns all nodes of the tree in a flat list

GetAllLeafNodes

```
1. public List<TreeNode<T>> GetLeafNodes ()
```

Returns all leaf nodes in a flat list

TraversePreOrder

```
1. public void TraversePreOrder (Action<TreeNode<T>> action)
```

Traverses the tree, calling the action on each node, first calling the node and then its children, recursively

TraversePostOrder

```
1. public void TraversePostOrder (Action<TreeNode<T>> action)
```

Traverses the tree, calling the action on each node, first calling its children, and then the node itself, recursively

TraverseLevelOrder

```
1. public void TraverseLevelOrder (Action<TreeNode<T>> action)
```

Traverses the tree, calling the action on each node, calling first all nodes of the higher levels and then going down level by level

TraverseLeafsOnly

```
1. public void TraverseLeafsOnly (Action<TreeNode<T>> a)
```

Traverses the tree, calling the action on each leaf node

GetDepth

```
1. public int GetDepth ()
```

Gets the depth of a node respecting its general root. Root itself has depth 0

GetPathToRoot

```
1. public List<TreeNode<T>> GetPathToRoot ()
```

Gets the Node Path that is followed from the general root to the current node

FindNode(T)

```
1. public TreeNode<T>? FindNode (T target)
```

Searches for a node in all the descendants with a value that matches the target

FindNode(Predicate<TreeNode<T>>)

```
1. public TreeNode<T>? FindNode (Predicate<TreeNode<T>> condition)
```

Searches for a node in all the descendants based on a function that returns a boolean in function of each node searched

FindNode(Func<T, bool>)

```
1. public TreeNode<T>? FindNode(Predicate<T> condition)
```

Searches for a node in all the descendants based on a function that returns a boolean in function of the value of the node searched

FindChildNode(T)

```
1. public TreeNode<T>? FindChildNode (T target)
```

Searches for a node in the direct children with a value that matches the target

FindChildNode(Predicate <TreeNode<T>>)

```
1. public TreeNode<T>? FindChildNode (Predicate <TreeNode<T>> condition)
```

Searches for a node in the direct children based on a function that returns a boolean in function of each node searched

FindChildNode(Predicate <T>)

```
1. public TreeNode<T>? FindChildNode(Predicate <T> condition)
```

Searches for a node in the direct children based on a function that returns a boolean in function of the value of the node searched

ToStringFormat

```
1. public string ToStringFormat ()
```

Transforms the tree into a string format that looks like this:

```
>R:1,2:3,4;5;
```

The tree always starts with > and the root element. Then, “:” is used for opening the list of child nodes, “,” is used for specifying the next parallel child node, and “;” is used for closing the list of child nodes

ParseStringFormat(string)

```
1. public static TreeNode<string> ParseStringFormat (string s)
```

Parses the string format to a string tree, because it is just text. Might throw an Exception

ParseStringFormat(string, Func<string, T>)

```
1. public static TreeNode<T> ParseStringFormat (string s, Func<string, T> parseFunc)
```

Parses a tree into any type, providing a parsing function for that type

TryParseStringFormat(string, out TreeNode<string>)

```
1. public static bool TryParseStringFormat (string s, out TreeNode<string> tree)
```

Tries parsing from the string, and if it was possible, returns true and the parsed tree in the out argument

TryParseStringFormat(string, Func<string, T>, out TreeNode<string>)

```
1. public static bool TryParseStringFormat (string s, Func<string, T> parseFunc, out  
TreeNode<string> tree)
```

Tries parsing from the string, and if it was possible, returns true and the parsed tree in the out argument

ToString

```
1. public override string ToString ()
```

Generates a nicely formatted way to visualize the tree indented. Do not mistake this with the string format

ToFormattedString

```
1. public FString ToFormattedString (CharFormat? lines, CharFormat? val)
```

Generates a nicely formatted string representation of the tree. The lines CharFormat will be used for the line chars, and the val for the value of the nodes.

Dependencies

Used for handling files in a central folder of the application. Reminiscent of “.minecraft” folder

Namespace

```
AshLib.Folders
```

Constructors

Dependencies(string, bool, string[], string[])

```
1. public Dependencies (string path, bool config, string[] directories, string[] files)
```

Initializes the utility. The first argument is the main path, the second is if you want the config AshFile to be created, the directories array specifies folders inside the main path that will be created, and the files array specifies files that will be created inside the main path or subfolders, will be created empty.

Fields

path

```
1. public string path;
```

The master path. For example:

```
"C://Users/user22/AppData/Roaming/HelloWorld"
```

config

```
1. public AshFile config;
```

The main configuration, in an AshFile. The path to it is "mainpath/config.ash"

Methods

ReadFileText

```
1. public string ReadFileText (string p)
```

Will read the contents of a file as text of the file in masterpath + argument

ReadAshFile

```
1. public AshFile ReadAshFile (string p)
```

Will read the contents of a file as an AshFile of the file in masterpath + argument

SaveFileText

```
1. public void SaveFileText (string p, string t)
```

Will save the text(argument t) in a file in masterpath + argument p

SaveAshFile

```
1. public void SaveAshFile (string p, AshFile a)
```

Will save the text(argument t) in a file in masterpath + argument p

CreateDir

```
1. public void CreateDir (string p)
```

Will create a new directory in masterpath + argument

TreeLog

Utility that helps you create a collapsible and indented, easy to read log with a tree structure. If you use notepad++ there is a custom language available for it

Namespace

```
AshLib.Logging
```

Methods

GetLog

```
1. public string GetLog ()
```

Returns the whole string of the log

Clear

```
1. public void Clear ()
```

Resets the content and level of the log

Deep

```
1. public void Deep (string s)
```

Increases the level of the log. You can include a message

Shallow

```
1. public void Shallow ()
```

Decreases the level of the log

Write(string)

```
1. public void Write (string s)
```

Writes content to the log

Write(object)

```
1. public void Write (object s)
```

Writes content to the log

AshFileException

Used internally for all exceptions that happen surrounding AshFiles

```
1. [Serializable]  
2. internal class AshFileException : Exception
```

Namespace

```
AshLib.AshFiles
```

Properties

errorCode

```
1. public int errorCode {get;}
```

Different errors give different codes

Methods

GetFullMessage

```
1. public string GetFullMessage ()
```

Returns the whole information needed about the exception(error code, message, stack trace...) in a nice format

ToString

```
1. public override string ToString ()
```

Returns the same as GetFullMessage

GetObjectData

```
1. public override void GetObjectData(SerializationInfo info, StreamingContext context)
```

Does something about Serialization. Honestly no idea

CharFormat

Used to determine the format of a character

Namespace

```
AshLib.Formatting
```

Constructors

CharFormat(byte?, bool?, byte?, bool?, Color3?, bool, Color3?, bool)

```
1. public CharFormat(byte? dens, bool? ital, byte? uline, bool? sthrough, Color3? fgcolor, bool fgreset, Color3? bgcolor, bool bgreset)
```

Initializes with density, italic, underlined, strikethrough, foreground color, foreground reset, background color, background reset

CharFormat(Color3?, bool, Color3?, bool)

```
1. public CharFormat(Color3? fgcolor, bool fgreset, Color3? bgcolor, bool bgreset)
```

Initializes with foreground color, foreground reset, background color, background reset. The rest of the formatting properties are initialized to same as last

CharFormat(Color3?, Color3?)

```
1. public CharFormat(Color3? fgcolor, Color3? bgcolor)
```

Initializes with foreground color, and background color. The rest of the formatting properties are initialized to same as last, and false for the resets

CharFormat(Color3?, bool)

```
1. public CharFormat(Color3? fgcolor, bool fgreset)
```

Initializes with foreground color and foreground reset. The rest of the formatting properties are initialized to same as last

CharFormat(Color3?)

```
1. public CharFormat(Color3? fgcolor)
```

Initializes with foreground color. The rest of the formatting properties are initialized to same as last

CharFormat()

```
1. public CharFormat()
```

Initializes all formatting properties to same as last

Fields

ResetAll

```
1. public static CharFormat ResetAll = new CharFormat(0, false, 0, false, null, true, null, true);
```

A format that resets all formatting options.

Properties

density

```
1. public byte? density {get;}
```

Font density. 0 is normal, 1 is bold, 2 is thin. Null is same as last character format

italic

```
1. public bool? Italic {get;}
```

If the font is in italic or not. Null is same as last character format

underline

```
1. public byte? underline {get;}
```

0 is not underlined, 1 is single underline, 2 is double underline. Null is same as last character format

strikeThrough

```
1. public bool? strikeThrough {get;}
```

If the has a strike through or not. Null is same as last character format

foreground

```
1. public Color3? foreground {get;}
```

Foreground (character) color. Null is same as last character format

foregroundReset

```
1. public bool foregroundReset {get;}
```

If the foreground color is reset to the terminal default

background

```
1. public Color3? background {get;}
```

Background color. Null is same as last character format

backgroundReset

```
1. public bool backgroundReset {get;}
```

If the background color is reset to the terminal default

Methods

ToString

```
1. public override string ToString ()
```

Represents all the class properties in a nice format

Equals

```
1. public override bool Equals (object obj)
```

Checks if two formats are the same

Operators

Operator ==(CharFormat, CharFormat)

```
1. public static bool operator == (CharFormat a, CharFormat b)
```

Checks if two formats are the same

Operator !=(CharFormat, CharFormat)

```
1. public static bool operator != (CharFormat a, CharFormat b)
```

Checks if two formats are not the same

FormatString

```
1. public class FormatString : ICollection<(char, CharFormat?)>, ICloneable,
   IEquatable<FormatString>
```

A formatted string with support for colors and many more. (Note that windows 10 terminal only correctly supports colors and lacks support for other options). It uses ANSI escape sequences

Namespace

```
AshLib.Formatting
```

Constructors

FormatString()

```
1. public FormatString ()
```

Initializes an empty string

FormatString(FormatString)

```
1. public FormatString (FormatString fs)
```

Clones another FormatString

FormatString(FormatString)

```
1. public FormatString (ICollection<(char, CharFormat?)> fs)
```

Clones a collection of chars and charFormats

FormatString(string)

```
1. public FormatString (string s)
```

Initializes an string with content. Here, you can use the string formatting, explained later

FormatString (string, CharFormat?)

```
1. public FormatString (string s, CharFormat? f)
```

Initializes a new FormatString from a string applying the same format to all chars

Fields

addFinalReset

```
1. public bool addFinalReset;
```

If the built string will reset back to the terminal default at the end. Default is true

usesColors

```
1. public static bool usesColors;
```

If the outputted string has coloring. It is automatically set to false if the environment variable NO_COLOR exists

Properties

content

```
1. public string content {get;}
```

Gets the text content

format

```
1. public List<CharFormat?> format {get;}
```

Gets the format in the form of CharFormat, class defined earlier

built

```
1. public string built {get;}
```

The built string with the format applied

Length

```
1. public int Length {get;}
```

The length of the string

Count

```
1. public int Count {get;}
```

The length of the string

IsReadOnly

```
1. public bool IsReadOnly {get;}
```

Always return false

Methods

Clear

```
1. public void Clear ()
```

Clears the content of the string

Clone()

```
1. public object Clone ()
```

Clones the current instance

Clone(FormatString)

```
1. public static FormatString Clone (FormatString fs)
```

Clones the passed instance

GetEnumerator

```
1. public IEnumerator<char, CharFormat?> GetEnumerator ()
```

Gets the enumerator

Append(string, IEnumerable<CharFormat?>)

```
1. public void Append (string s, IEnumerable<CharFormat?> f)
```

Appends text with a specific format. Each character has its own format

Append(string, CharFormat?)

```
1. public void Append (string s, CharFormat? f)
```

Appends text with a specific format. Each character has the same format

Append(object, CharFormat?)

```
1. public void Append (object s, CharFormat? f)
```

The object is transformed to string and the text is text is appended. Each character has the same format

Append(FormatString)

```
1. public void Append (FormatString f)
```

Appends a whole FormatString wit its format

Append((char, CharFormat?))

```
1. public void Append ((char, CharFormat?) f)
```

Appends a single char with its format

Append(string)

```
1. public void Append (string s)
```

Text is appended, and text formatting can be used. Text formatting determined the format of the next characters. It is started with / and enclosed in []. You can prevent this from happening escaping with \: \[wont be parsed as a format. Inside, the different values and options are separated by commas. This are all the options as examples:

```
"/[B>Hello World!" //Bold text
"/[T>Hello World!" //Thin text
"/[D>Hello World!" //Normal density text
"/[RT>Hello World!" //Normal density text
"/[RD>Hello World!" //Normal density text

"/[I>Hello World!" //Italic text
"/[RI>Hello World!" //Not italic text
```

```
"/[U>Hello World!" //Underlined text
"/[DU>Hello World!" //Double underlined text
"/[RU>Hello World!" //Not underlined text

"/[S>Hello World!" //Strike-through text
"/[RS>Hello World!" //No strike-through text

"/[C,255,0,0>Hello World!" //Red colored text(RGB)
"/[F,255,0,0>Hello World!" //Red colored text(GB)
"/[C#,ff0000>Hello World!" //Red colored text(hex)
"/[F#,ff0000>Hello World!" //Red colored text(hex)
"/[RC>Hello World!" //Reset color to the terminal default text
"/[RF>Hello World!" //Reset color to the terminal default text

"/[BG,255,0,0>Hello World!" //Red background text(GB)
"/[BG#,ff0000>Hello World!" //Red background text(hex)
"/[RB>Hello World!" //Reset background color to the terminal default text

"/[0>Hello World!" //ALL properties reset to the terminal default text

"/[C#,10ff30,B#,ffffff>Hello World!" //Green text over white background text.
//Multiple properties can be set at once
```

Add

```
1. public void Add ((char, CharFormat?) f)
```

Appends a single char

Contains

```
1. public bool Contains ((char, CharFormat?) f)
```

Returns true if the string contains a char with a format

Substring

```
1. public FString Substring (int si, int n)
```

Returns a substring using si as the start index and n as number of chars

SplitIntoLines

```
1. public FString[] SplitIntoLines ()
```

Splits the current instance into multiple lines using all the possible newline combinations as separators

RemoveFromStart

```
1. public bool RemoveFromStart (int n)
```

Removes n chars from the start of the content and returns true if it was possible

RemoveFromEnd

```
1. public bool RemoveFromEnd (int n)
```

Removes n chars from the end of the content and returns true if it was possible

Remove

```
1. public bool Remove ((char, CharFormat?) f)
```

Removes a char from the string and returns true if it was possible

RemoveRange

```
1. public bool RemoveRange (int si, int n)
```

Removes n chars using as starting index si (0 indexing) and returns true if it was possible

CopyTo

```
1. public void CopyTo ((char, CharFormat?)[] array, int index)
```

Copies to an array

Equals(object)

```
1. public override bool Equals (object obj)
```

Checks if two FormatStrings are equal

Equals(FormatString?)

```
1. public bool Equals (FormatString? fs)
```

Checks if two FormatStrings are equal

ToString

```
1. public override string ToString ()
```

Returns the text with the ANSI format applied. Same as built property

Operators

Operator +(FormatString, FormatString)

```
1. public static FormatString operator + (FormatString a, FormatString b)
```

Appends together two FormatStrings

Operator +(string, FormatString)

```
1. public static FormatString operator + (string a, FormatString b)
```

Appends together a string and a FormatString

Operator +(FormatString, string)

```
1. public static FormatString operator + (FormatString a, string b)
```

Appends together a FormatString and a string

Operator +(char, FormatString)

```
1. public static FormatString operator + (char a, FormatString b)
```

Appends together a char and a FormatString

Operator +(FormatString, char)

```
1. public static FormatString operator + (FormatString a, char b)
```

Appends together a FormatString and a char

Operator *(FormatString, CharFormat?)

```
1. public static FormatString operator * (FormatString a, CharFormat? b)
```

Applies a format to all characters in a FormatString

Operator ==(FormatString, FormatString)

```
1. public static bool operator == (FormatString a, FormatString b)
```

Checks if two FormatStrings are equal

Operator !=(FormatString, FormatString)

```
1. public static bool operator != (FormatString a, FormatString b)
```

Checks if two FormatStrings are not equal

Implicit Operator FormatString(string)

```
1. public static implicit operator FormatString (string s)
```

Casts a string to a FormatString

AshFile

```
1. public class AshFile : IDictionary<string, object>, ICloneable,  
IEquatable<AshFile>
```

A Data structure made up from camps, that each have a key and a value(represented by an object because it can be of many types).

This structure makes it easy to be saved into a file in a new file format (.ash).

It also allow to be easily shared as text with its human-readable string format.

Namespace

```
AshLib.AshFiles
```

Constructors

AshFile()

```
1. public AshFile()
```

Initializes a new empty AshFile

AshFile(AshFile)

```
1. public AshFile()
```

Clones an existing AshFile

AshFile(IDictionary<string, object>)

```
1. public AshFile(IDictionary<string, object> d)
```

Initializes a new AshFile using an existing IDictionary, the structure used internally

AshFile(string)

```
1. public AshFile(string path)
```

Loads an AshFile from the specified path

Fields

path

```
1. public string? path;
```

The path of the file, if it has any

format

```
1. public byte format;
```

Specifies the format in which the file will be saved. Latest format is 3

compactBools

```
1. public bool compactBools;
```

Config value for the file format. If set to true, bools will be compacted together using less space. Default is true

maskCampNames

```
1. public bool maskCampNames;
```

Config value for the file format. If set to true, camp names will be masked so they are not readable when the file is viewed as raw text. Default is true

maskStrings

```
1. public bool maskStrings;
```

Config value for the file format. If set to true, string values will be masked so they are not readable when the file is viewed as raw tex. Default is true

defaultSeparator

```
1. public const string defaultSeparator = ".";
```

The default separator for tree structures

currentVersion

```
1. public const int currentVersion = 3;
```

The current AshFile version(latest)

Properties

FormatConfig

```
1. public AshFileFormatConfig FormatConfig {get;}
```

Gets the file format config as a AshFileFormatConfig struct, defined earlier

Count

```
1. public int Count {get;}
```

Returns the number of camps

Keys

```
1. public ICollection<string> Keys
```

The collection of all keys

Values

```
1. public ICollection<object> Values
```

The collection of all values

IsReadOnly

```
1. public int IsReadOnly {get;}
```

Always returns false

IsFixedSize

```
1. public int IsFixedSize {get;}
```

Always returns false

Methods

Clear

```
1. public void Clear ()
```

Deletes all camps

Clone()

```
1. public object Clone ()
```

Clones all the camps from this AshFile to a new one, keeping the references different

Clone(AshFile)

```
1. public static AshFile Clone (AshFile a)
```

Clones all the camps from one AshFile to a new one, keeping the references different

Merge

```
1. public static AshFile Merge (AshFile a1, AshFile a2)
```

Merges two AshFiles into 1. The second AshFile has priority if two camps are named the same

GetEnumerator

```
1. public IEnumerator<KeyValuePair<string, object>> GetEnumerator ()
```

Gets the enumerator

Visualize

```
1. public string Visualize ()
```

Produces a list of all the elements. Arrays show all elements. The format is:

```
"Name1: Value1  
Name2: Value2"
```

VisualizeFormatted

```
1. public FormatString VisualizeFormatted (CharFormat? name, CharFormat? val)
```

Same as Visualize, but gives the string formatting. name will be applied to the camp names and val to values

ImportFormatConfig

```
1. public void ImportFormatConfig (AshFileFormatConfig conf)
```

Loads the format config from a struct

Load(string)

```
1. public void Load (string path)
```

Loads the file from the path and save the path internally

Load()

```
1. public void Load ()
```

Loads the file from the path saved internally

Save(string)

```
1. public void Save (string path)
```

Saves the file from the path and saves the path internally

Save()

```
1. public void Save ()
```

Saves the file from the internal path

ReadFromFile

```
1. public static Dictionary<string, object> ReadFromFile(string path, out byte f, out AshFileFormatConfig conf)
```

Reads the file from the path argument and returns it. Outputs the format in the f argument and the format config in conf

ReadFromBytes(byte[], out byte, out AshFileFormatConfig)

```
1. public static Dictionary<string, object> ReadFromFile(byte[] fileBytes, out byte f, out AshFileFormatConfig conf)
```

Reads the file from the byte array and returns it. Outputs the format in the f argument

ReadFromBytes(byte[])

```
1. public static AshFile ReadFromBytes (byte[] fileBytes)
```

Loads an AshFile from a byte array. Auto handles format and format config

WriteToFile

```
1. public static void WriteToFile (string path, Dictionary<string, object> dictionary, byte format, AshFileFormatConfig conf)
```

Writes the data into a file in the path argument. Format and config can be specified

WriteToBytes(Dictionary<string, CampValue>, byte)

```
1. public static byte[] WriteToBytes (Dictionary<string, object> dictionary, byte format, AshFileFormatConfig conf)
```

Transforms the data into the byte representation. Format and config can be specified

WriteToBytes()

```
1. public byte[] WriteToBytes ()
```

Transforms the current instance into the byte representation.

GetErrorCount

```
1. public static ulong GetErrorCount ()
```

Gets the number of errors that occurred. These errors occur while converting to/from file

GetErrorLog

```
1. public static string GetErrorLog ()
```

Gets the whole log of errors that occurred, nicely formatted. These errors occur while converting to/from file

EmptyErrors

```
1. public static void EmptyErrors ()
```

Empties all the errors and sets the count to zero.

ApplyModel(AshFileModel)

```
1. public void ApplyModel (AshFileModel m)
```

Applies a model to the AshFile

ApplyModel(AshFile, AshFileModel)

```
1. public static AshFile ApplyModel (AshFile a, AshFileModel m)
```

Applies a model to an AshFile and returns a new one. Original one is not modified

GetCampTree

```
1. public TreeNode<string> GetKeyTree (string separator)
```

Gets a string tree with the camp structure, using a string as separator. If not specified, defaultSeparator will be used as separator

GetValueTree

```
1. public TreeNode<string> GetValueTree (string separator)
```

Gets a string tree with all the camps visualized nicely in a tree structure using a separator. Arrays show all elements too. If not specified, defaultSeparator will be used as separator

VisualizeAsTree

```
1. public string VisualizeAsTree (string separator)
```

Returns the tree gotten with GetValueTree as a string, a nicely formatted tree structure. If not specified, defaultSeparator will be used as separator

GetFormattedValueTree

```
1. public TreeNode<FormatString> GetFormattedValueTree (CharFormat? name, CharFormat? val, string separator)
```

Gets a formatted string tree with all the camps visualized nicely in a tree structure using a separator. Arrays show all elements too. name will be used for camp names and val for camp value. If not specified, defaultSeparator will be used as separator

VisualizeAsFormattedTree

```
1. public FString VisualizeAsFormattedTree (CharFormat? line, CharFormat? name, CharFormat? val, string separator)
```

Returns the tree gotten with GetValueTree as a formatted string, a nicely formatted tree structure. line will be used for tree lines, name will be used for camp names and val for camp value. If not specified, defaultSeparator will be used as separator

ContainsKey

```
1. public bool ContainsKey (string key)
```

Checks if a specific camp exists, returns true if it does.

Contains

```
1. public bool Contains (KeyValuePair<string, object> kvp)
```

Checks if a specific camp exists, returns true if it does.

Set

```
1. public void Set (string key, object val)
```

Sets the camp with the argument key to the object. It can be of any type

Add(string, object)

```
1. public void Add (string key, object val)
```

Sets the camp with the argument key to the object. It can be of any type

Add(KeyValuePair<string, object>)

```
1. public void Add (KeyValuePair<string, object> kvp)
```

Sets the camp with the argument key to the object. It can be of any type

Initialize

```
1. public void Initialize (string key, object val)
```

If the camp with that key exists, nothing will happen. If the camp with that key doesn't exist, it will set it to that object

GetValue

```
1. public object GetValue (string key)
```

Returns the value of a camp. If the camp doesn't exist, a null object will be returned

TryGetValue

```
1. public bool TryGetValue (string key, out object val)
```

If the camp doesn't exist, returns false. If it is possible to get the value, it will return true and output the value in the out argument

GetValue<T>

```
1. public T GetValue<T> (string key)
```

If the camp doesn't exist or isn't of the type T, it will return the default value of the T type. Else it will return the camp value directly cast

TryGetValue<T>

```
1. public bool TryGetValue<T> (string key, out T val)
```

If the camp doesn't exist or isn't of the type T, it will return false. Else it will return true and the camp value directly cast in the out argument

GetOrDefault<T>

```
1. public T GetOrDefault<T> (string key, T def)
```

If the camp doesn't exist or isn't of the type T, it will return the default value given in the arguments. Else it will return the camp value directly cast

GetValueType

```
1. public Type GetValueType (string key)
```

Returns the Type of value of a camp. If the camp doesn't exist, null will be returned

TryGetValueType

```
1. public bool TryGetValueType (string name, out Type t)
```

If the camp doesn't exist, returns false. If it is possible to get the type of value, it will return true and output the type in the out argument

Remove(string)

```
1. public bool Remove (string key)
```

Removes the camp with that key if it exists and outputs true, else will output false

Remove(KeyValuePair<string, object>)

```
1. public bool Remove (KeyValuePair<string, object> kvp)
```

Removes the camp with that key and value if it exists and outputs true, else will output false

RemoveAll

```
1. public int RemoveAll (Predicate<KeyValuePair<string, object>> condition)
```

Removes all camps that return true in the passed condition and returns the count of removed camps

Rename

```
1. public bool Rename (string oldKey, string newKey)
```

Renames the camp with the new key if it exists and output true, else will output false

CopyTo

```
1. public void CopyTo (KeyValuePair<string, object>[] array, int arrayIndex)
```

Copies content to an array

Equals(object)

```
1. public override bool Equals (object obj)
```

Checks if the contents of two AshFiles are the same

Equals(AshFile?)

```
1. public bool Equals (AshFile? af)
```

Checks if the contents of two AshFiles are the same

Parse

```
1. public static AshFile Parse (string s)
```

Parses an AshFile from a string in the AshFile string format. This is its structure of a camp:

```
<name> : type : value ; nextCamp...  
<name> : type : [value1; value2; value3]; //For arrays
```

Note that the spaces can be any whitespace of any length. Here is the list of all types(same as supported by the file format):

```
@: string, values must be enclosed with ""
ub: byte
us: ushort
ui: uint
ul: ulong
sb: sbyte
s: short
n: int
i: int
l: long
#: Color3, struct defined earlier, values must be in hex
f: float
d: double
v2: Vec2, struct defined earlier, 2 float values are expected serparated by commas
v3: Vec3, struct defined earlier, 3 float values are expected serparated by commas
v4: Vec4, struct defined earlier, 4 float values are expected serparated by commas
b: boolean
dt: Date, struct defined earlier, 6 numbers are expected separated by /, day, month,
year, hour, minute, second
```

Here is an example of an AshFile in this string format:

```
<names> :@: ["Julian"; "George"; "Donald"; "Viktor"; "Theodore"];
<todayDate>:dt: 13/4/2006/12/31/9; <message>:@:"Hello! Good morning!";
<emailID> :ul: 1298908;
```

TryParse

```
1. public static bool TryParse (string s, out AshFile a)
```

Tries parsing and returns true if its possible along with the parsed object in the out argument

ToString

```
1. public override string ToString ()
```

Returns the string representation of the AshFile

ToStringCompact

```
1. public string ToStringCompact ()
```

Returns the most compact form of the string representation of the AshFile

ToJson

```
1. public string ToJson ()
```

Returns the json representation of the AshFile

Operators

Operator [string]

```
1. public object this[string key] {get; set;}
```

Equivalent to GetValue(key) and Set(key, value) methods

Operator == (AshFile, AshFile)

```
1. public static bool operator == (AshFile a1, AshFile a2)
```

Checks if the contents of two AshFiles are the same

Operator != (AshFile, AshFile)

```
1. public static bool operator != (AshFile a1, AshFile a2)
```

Checks if the contents of two AshFiles are not the same

Operator + (AshFile, AshFile)

```
1. public static AshFile operator + (AshFile a1, AshFile a2)
```

Will merge the two data structures. If both contain a camp with the same name, the second operand (a2) will have priority and put its camps over

Operator * (AshFile, AshFileModel)

```
1. public static AshFile operator * (AshFile b, AshFileModel m)
```

Will apply a model to an AshFile

Explicit Operator AshFile (Dictionary<string, CampValue>)

```
1. public static implicit operator AshFile (Dictionary<string, object> d)
```

Casts a dictionary into an AshFile. Create a new AshFile with the Dictionary as data

ModelInstance

An instance for the AshFileModel

Namespace

```
AshLib.AshFiles
```

Constructors

ModelInstance(ModelInstanceOperation, string, object)

```
1. public ModelInstance (ModelInstanceOperation o, string nam, object val)
```

Initlaizes a new ModelInstance with its type of operation, the target camp(name), and the value of the camp

Fields

operation

```
1. public ModelInstanceOperation operation;
```

The mode of operation of the instance

name

```
1. public string name;
```

The target camp name

value

```
1. public object value;
```

The value of the camp, its use depends on the operation mode

AshFileModel

Helps putting an AshFile into a correct format for easy use. It has instances, that will do a different number of things to camps, and actions, that are functions that will execute for all camps

Namespace

```
AshLib.AshFiles
```

Constructors

AshFileModel(params ModelInstance[])

```
1. public AshFileModel (params ModelInstance[] insArray)
```

Initializes a new model with the instances passed as arguments

Fields

allowUnsupportedTypes

```
1. public bool allowUnsupportedTypes;
```

If object types not supported by the file format of string format(they are the same) will be deleted. Default is true

deleteNotMentioned

```
1. public bool deleteNotMentioned;
```

If the camps not mentioned in the instance will be deleted. Default is false

DeleteUnsupportedTypes

```
1. public static readonly AshFileModel DeleteUnsupportedTypes;
```

A model that will delete all camps with types not supported

Properties

instances

```
1. public List<ModelInstance> instances {get;}
```

The instances of the model

actions

```
1. public List<Action<AshFile, string, object>> actions {get;}
```

The list of actions of the model that will be executed for all camps after the instances

Methods

Merge

```
1. public void Merge (AshFileModel m)
```

Merges into the current instance another model. Only instances and actions will be merged

Operators

Operator + (AshFileModel, AshFileModel)

```
1. public static AshFileModel operator + (AshFileModel m1, AshFileModel m2)
```

Merges two models. The first model is the modified one and is also the one returned.

ReactiveList<T>

```
1. public class ReactiveList<T> : IList<T>, System.Collections.IList,
   IReadOnlyList<T>
```

A list class that has an action on change, apart from other additions. This class is **EXACTLY** the same as List<T> unless specified. Only additions will be reviewed, please refer to official documentation for other members, equal to those of List<T>

Namespace

```
AshLib.Lists
```

Properties

Length

```
1. public int Length {get;}
```

Same as Count, returns length of the list

OnChanged

```
1. public Action? OnChanged {set;}
```

Action that will be called whenever the elements of the list are changed. Adding, setting, removing, inserting and moving elements will trigger it, as well as clearing, reversing or sorting the list.

Methods

Move

```
1. public void Move (int index, int newIndex)
```

Moves an item in an index to a new index