Akatab Documentation

Smart Font Features

Graphite and OpenType features are used by software shaping (aka rendering) engines to render the proper shaping of Tifinagh characters, whether typed from left to right or right to left. Some features such as the forming of bi-consonant ligatures and contextual upward shifting of the *yal* and *yan* characters are done automatically. In addition, some applications let the user select certain optional features.

Default shaping by Graphite and OpenType

The forming of bi-consonant ligatures is done automatically by the shaping engine. For example, if the following Tifinagh characters are entered in sequence: O (yar), ___(Tifinagh consonant joiner) and + (yat), the result is O+ as the bi-consonant ligature. Examples of bi-consonant ligatures are shown on page three.

Another function of the shaping engine is to output alternate glyphs in certain contexts. An example is an | (yan) | followed by another | (yan) | e.g. | | See page 4 for configuration instructions for Microsoft Word.

Rendering of right to left text

These are the default *left to right* Tifinagh characters in the Akatab font:


```
·:: ···:: :: 0 0 0 0 0 1 V E C E I 1 4 & X i | | | | + C + : # # X X J
```

These are the *right to left* Tifinagh characters in the Akatab font (note the orientation of characters is changed):

There are two special characters that are used to change the direction and the text for the Tifinagh characters:

- 1. U+202E (RIGHT TO LEFT OVERRIDE) for *right to left* Tifinagh
 Use this character at the beginning of a string of Tifinagh text. The following text will be *right to left* and the directionality of characters is changed to *right to left*. You may want to format the text to align right.
- 2. U+202C (POP DIRECTIONAL FORMATTING) to change direction
 Use this character to change the direction of a string of any text. In this context, the following text will revert to *left to right*.

Example:



Selecting variant characters

Sometimes a variant character is needed in place of one of the default characters. Some applications allow the user to select the correct character variants. There are two features that are used for variants—Stylistic Sets and Character Variants.

Microsoft Word and Adobe InDesign have a user interface to select the Stylistic Sets features. Akatab has seven stylistic sets (ss01 through ss07). See the help in the application for assistance in using this feature.

Akatab has 17 Character Variant features with 21 selections (cv01-cv07 and cv31-cv40). See the next section for help in using these features in LibreOffice¹. In the *web* folder of the font download, there are examples for Character Variants using .css and .html files to use in web programming.

¹ See https://www.libreoffice.org/ to download this free office suite.

Using Akatab in LibreOffice

Akatab character variants (using cvxx feature)

To get a variant, select the character(s) and type the feature code into the font dialog box as shown in the examples.

Default	Variant	Font feature code	Examples in LibreOffice			
•	٥	Akatab:cv01=1	Format Styles Table Form			
30	I	Akatab:cv02=1				
X	8	Akatab:cv03=1	•	·	Akatab:cv01=1	
†	‡	Akatab:cv04=1	II X	_ U	Akatab:cv02=1 Akatab:cv03=1	
:	:	Akatab:cv05=1	Δ	U	rindae.eroo 1	
*	#	Akatab:cv06=1				
X	X	Akatab:cv07=1				
O+	Θ	Akatab:cv31=1				
O+	Ф	Akatab:cv32=1	F <u>o</u> rmat Styles T <u>a</u> ble Fo <u>r</u> m			
O+	\oplus	Akatab:cv32=2				
O+	⊕	Akatab:cv33=1	O+	•	Akatab:cv32=1	
O+	•	Akatab:cv33=2	O+	(0)	Akatab:cv32=2 Akatab:cv33=1	
C,	Đ	Akatab:cv34=1	⊙+	T	Akatab.cv35=1	
3Ç,	3 [+	Akatab:cv35=1				
Ϊ	ĵ	Akatab:cv36=1				
+	ŀ	Akatab:cv37=1				
 +	Т	Akatab:cv37=2				
l +	H	Akatab:cv38=1				
;;	#	Akatab:cv39=1				
#+	#+	Akatab:cv40=1				
#	#	Akatab:cv40=2				

Bi-consonants (ligature lookups based on default characters)

These ligatures are formed after typing the character sequences shown in the examples below. Type the first character e.g. Θ , the joiner (using the Right+Alt or AltGr key – see keyboard documentation) and then the second character e.g. +, to get the Θ + (BT) ligature.

θ+	0+	ВТ	Ι.Λ	Λ	ND	ΙX	X	NGHH	6 :	Ë	SHK
Φ.+	Ф+	B(alt)T	<u>I</u> V	٧	NDH	LΪ	Ÿ	NJ	1.6	€	NSH
0 :	Ö	RK	<u> </u>	Ç,	МТ	Ϊ+	Ή	JT	6+	6	SHT
0 +	O+	RT	<u>]][</u>	H	NF	1:	Î	NK	: +	#	WT
0 ;	Ö	SK][_+	3 Ç	FT	1+	 +	NT	#_+	#+	ZZT
1.0	Ð	NS	ξ +	ξ,	YT	<u> :</u>	ίί	LK	X +	*	ZT
0 +	O+	ST	<u>X</u> +	X +	GHHT	<u> +</u>	l +	LT	X +	¥	ZHT

Bi-consonant variants (ligature lookups based on variant characters)

These variants are formed by applying the font feature code either to the character (as above) or to the whole ligature.

Ŧ	NF	ligature using an alternate F	Akatab:cv02=1
ŀ	FT	ligature using an alternate F	Akatab:cv02=1
8+	GHH T	ligature using an alternate GHH	Akatab:cv03=1
8	NGH H	ligature using an alternate GHH	Akatab:cv03=1
#	WT	ligature using an alternate W	Akatab:cv05=1
#	ZT	ligature using an alternate Z	Akatab:cv06=1
片	ZHT	ligature using an alternate ZH	Akatab:cv07=1

Contextual substitutions (raised variants)

These will substitute automatically as the characters are typed.

l ₁	NN	11 11	LL
1,11	NL	111	LN

Diacritics and superscript vowels (for research and literacy aids)

Type the Tifinagh character followed by either a combining acute (U+0301) or tilde (U+0303).

ÍÍM THÉ ĐÓ Ó Ó Á V É Ć É ÍL Á É Á Í Í Í Í É Ć Á Í Á Í Á Í ĨÍM THÍ Ì ĐÕ Õ Õ Ā V Ē Č Ē ĪL Á Ē X Î Ĩ Ĩ Ī Ē Ē Ā Ē Ā Ā X X

Type the Tifinagh character followed by either a combining dot above (U+0307) or ring above (U+030A).

Ĭŀŀŀ!ĬŎŎŎŎŇŸĔĔĔĬĬŹŠĬĬĴĬĬŧĊŀŀ#XX

Superscript vowels (U+E300 – U+304 respectively) shown between Tifinagh characters $|\dot{}| |\dot{}| |\dot{}| |\dot{}| |\dot{}| |\dot{}|$


Configuring Microsoft Word

Since Akatab uses OpenType features to display ligatures and contextual alternates, the user needs to check the OpenType settings in Microsoft Word to ensure they are enabled.

Select all (Ctrl+A) or a select portion of the text then follow the instructions by number in the illustration.

- 1. Click the Font dialog box launcher.
- 2. Select the Advanced tab.
- 3. Select which ligatures you want to display (Standard and Contextual is all that is needed).
- 4. The Use Contextual Alternates box should be ticked.

Click OK to close the dialog box.



To enable Stylistic Sets, select the text where you want to show the alternate style. Open the Font dialog as instructed above. In the *Stylistic sets* drop-down box, select the number that corresponds with the desired style.

