Harmattan Features

The Harmattan font includes a number of optional features that provide alternative rendering that might be preferable for use in some contexts. The chart below enumerates the details of these features. Whether these features are available to users will depend on both the application and the rendering technology (Graphite or OpenType) being used. Most features are available in both Graphite and OpenType, though there may be minor differences in their implementation.

Features

When Harmattan is used in applications that support Graphite or OpenType, and that provide an appropriate user interface, various user-controllable font features are available allowing access to alternatively-designed glyphs.

The table below gives a visual representation of the featured character glyphs in the font. Note that within each feature the top-most value is the default. The other lines show the first alternate and, if available, the second or third alternates.

List of Graphite features and OpenType Character Variants

Feature Name	Feature ID	Feature Setting (top-most in each section is default)	Character Shapes	Implementation Notes ¹
Alef diacritic placement (U+0623, U+0625, U+0627, U+064E, U+0650, U+0654, U+0655)	cv02	0=Standard	ٳؙٳٙ۩ؘٳؙڵٳڵٳڵ	G,O,T
		1=Hamza touching	ٳٳؘٳٳٳؙڵٳڵٳ	
		2=Touching	וֹוווֹוֹן עֹּעְ	
Jeem/Hah (U+062C, U+062D, U+062E, U+0682, U+0683, U+0684, U+0685, U+0686, U+06BF, U+0757, U+0758, U+08A2)	cv08	0=Standard	ج ججج ح ححح خ خخخ خ خخخ چ چچچ ۾ ڄڄڄ څ څڅڅ چ چچچ چ چچچ څ څخچ	G,O,T
		1=Handwritten	ﺝ ﺟﺒﺝ ﺡ ﺣﺒﺢ ﺥ ﺧﻨځ ځ ﺧﻠځ ﺝ ﺣﻴﺞ ۾ ﺟﺒڄ దే ﺧﺜద ﭼ ﭼﭙﺞ ﭺ ﺧﭙﻨﺝ ﺡ ﺣﺘﺢ ۾ ﺣﻴﺞ ﺝ ﺟﺒﺞ	

¹ Implementation Notes: G=Implemented in Graphite; O=Implemented in OpenType; T=Implemented in TypeTuner (command line version: http://scripts.sil.org/TypeTuner and web-based version: http://scripts.sil.org/TypeTuner and web-based version: http://scripts.sil.org/TypeTuner and web-based version: http://scripts.sil.org/TypeTuner and web-based version: http://scripts.sil.org/ttw).

Feature Name	Feature ID	Feature Setting (top-most in each section is default)	Character Shapes	Implementation Notes
Dal	cv12	0=Standard	د ذ ڈ ډ ڊ ݙ ڌ ڍ ڎ ڏ ڐ ۮ ݙ ݚ ﭘ	G,O,T
(U+062F, U+0630, U+0688, U+0689, U+068A, U+068B, U+068C, U+068D, U+068E, U+068F, U+0690, U+06EE, U+0759, U+075A, U+08AE)		1=Alternate XeTeX: "Scheherazade/GR:Dal=Alternate"	ح خ ځ چ چ څ څ څ څ څ چ چ چ	
Sad/Dad (U+0635, U+0636, U+069D, U+069E, U+06FB, U+08AF)	cv20	0=Standard	ص صصص ض ضضض ص صصص ض خفض	G,O,T
			ۻ ۻۻۻ ڝ ڝڝڝ	
		1=Half XeTeX: "Harmattan/GR:Sad/Dad=Half"	م صصم فر ضضفر ۾ صصع فر شقش	
			خر ضضر چر چچچر	
Meem (U+0645, U+0765, U+0766, U+08A7)	cv44	0=Standard	م ممم فر مففر ۾ مِمِم ۾ مُقْثِ	G,O,T
		1=Sindhi-style XeTeX: "Harmattan/GR:Meem=Sindhi-style"	م ممم ف ففف به مِمِم څ څڅڅ	
Heh (U+0647)	cv48	0=Standard	ه ههه	G,O,T
		3=Kurdish-style XeTeX: "Harmattan/GR:Heh=Kurdish-style"	න හ	
		1=Sindhi-style XeTeX: "Harmattan/GR:Heh=Sindhi-style"	മമമ മ	
		2=Urdu-style XeTeX: "Harmattan/GR:Heh=Urdu-style"	ه ېه	
Arabic U (U+0677, U+06C7)	cv50	0=Standard	ۇ ۋ	G,O,T
		1=Filled XeTeX: "Harmattan/GR:Arabic U=Filled"	9 9	
Maddah (U+0622, U+0627+U+0653, U+0653)	cv60	0=Small	ិ	G,O,T
		1=Large	<u>ិ</u> រិ រិ	

Feature Name	Feature ID	Feature Setting (top-most in each section is default)	Character Shapes	Implementation Notes
Shadda+kasra placement (U+064D, U+0650 with U+0651)	cv62	0=Default	្ខំ ្ខំ ្	G,T
		1=Lowered XeTeX: "Harmattan/GR:Shadda+kasra placement=Raised"	្ខ័ ្ខ័ ្	
		2=Raised XeTeX: "Harmattan/GR:Shadda+kasra placement=Raised"	ឺ 👢 ឺ 😷	
Damma (U+064F)	cv70	0=Standard	ံ	G,O,T
		1=Filled XeTeX: "Harmattan/GR:Damma=Short"	ِ بُ	
		2=Short XeTeX: "Harmattan/GR:Damma=Filled"	ံ ဟု	
Dammatan (U+064C)	cv72	0=Standard	ి	G,O,T
		1=Six-nine XeTeX: "Harmattan/GR:Dammatan=Six-nine"	ో ఈ	
Inverted Damma	cv74	0=Standard	်	G,O,T
		1=Hollow XeTeX: "Harmattan/GR:Inverted Damma=Hollow"	်	
Superscript Alef (U+0670 on all yeh, sad and seen-like characters U+0649 U+064A U+06D0 U+06D1 U+066C U+0635 U+0636 U+069D U+069E U+06FB U+08AF U+0633 U+0634 U+069A U+069B U+069C U+06FA U+076D U+077E)	cv76	0=Small	ىٰ ىلىٰ يٰ يٰلِيٰ ېٰ ہٖڹٖؠٰ يٰ پٰڸۑٰ ىٰ يٰلىٰ ص ططص ض ظظض ص ططع ش ظظش ض ظظف حل چلچ س سلسس ش ششش بن بنلبنلبن س چل پلپلپن ش شلشش ش شلشلش ن بنلبنلنن س بلپلپن ش شلشلش ش شلشلش ش ننلبنلن	

Feature Name	Feature ID	Feature Setting (top-most in each section is default)	Character Shapes	Implementation Notes
		1=Large XeTeX: "Harmattan/GR:Superscript Alef=Large"	ی للی ی یلی کې ېېلې کې پلپې ی یلیی ص ططص ض ظظض ص	
			طِطِصِ مَٰ طُطْمُ مِن طَطْمِن	
			چل چلچل سل سلسلسل شل شلشلشل بنيل بنلينبلين	
			س پلىپلىپرا ش شلىشلىش ش شلىشلىش ش شلىشلىش	
			ش شلشلش	
Sukun (U+0652)	cv78	0=Closed	ံ ငှ	G,O,T
		1=Open down XeTeX: "Harmattan/GR:Sukun=Open down"	<u>ိ</u> ငှ	
		2=Open left XeTeX: "Harmattan/GR:Sukun=Open left"	ئ ث	
End of ayah (U+06DD)	cv80	0=Standard	(123)	G,O,T
		1=Simplified A XeTeX: "Harmattan/GR:End of ayah=Simplified A"	123	
		2=Simplified B XeTeX: "Harmattan/GR:End of ayah=Simplified B"	123	
Eastern digits (U+06F4, U+06F6, U+06F7)	cv82	0=Standard	۴۵۶۷	G,O,T
		1=Sindhi-style XeTeX: "Harmattan/GR:Eastern digits=Sindhi- style"	۴۵٦۷	
		2=Urdu-style XeTeX: "Harmattan/GR:Eastern digits=Urdu-style"	۳۵٦۷	
		3=Kurdish-style	۴۵۶۷	
		4=Rohingya-style	٦٢٥٤	

Feature Name	Feature ID	Feature Setting (top-most in each section is default)	Character Shapes	Implementation Notes
Comma (U+060C, U+061B)	cv84	0=Upward	٤،	G,O,T
		1=Downward XeTeX: "Harmattan/GR:Comma=Downward"	, ;	
Line spacing		Normal Loose 1.0 Compatible Normal 1.0 Compatible Loose	Allows for adjustment of the default line spacing in the font.	Т

List of Language-specific features

The language-specific features that are in the font are demonstrated below:

Language	Language ID	Feature Setting (top-most in each section is default)	Character Shapes	Implementation Notes ²
Default			د ذ ڈ ډ ڊ ڋ ڌ ڍ ڎ ڏ ڏ ڋ ڋ ډ ۾ ممم	G,O,T
Kurdish (Northern)	ku	Language set to Kurdish XeTeX: "Harmattan/GR:language=ku" (Graphite) XeTeX: "Harmattan:language=ku" (OpenType) HTML: lang="ku"	د ذ ڈ ډ ڊ ڋ ڌ ڍ ڎ ڏ ڏ ڋ ڋ ډ ۾ ممم	
Rohingya	rhg	Language set to Rohingya XeTeX: "Harmattan/GR:language=rhg" (Graphite) XETeX: "Harmattan:language=rhg" (OpenType) HTML: lang="rhg"	د ذ ڈ ډ ڊ ڋ ڌ ڍ ڎ ڏ ڏ ڋ ڋ ډ ۾ ممم	
Sindhi	sd	Language set to Sindhi XeTeX: "Harmattan/GR:language=sd" (Graphite) XeTeX: "Harmattan:language=sd" (OpenType) HTML: lang="sd"	د ذ ڈ ډ ڊ ڋ ڌ ڍ ڎ ڏ ڏ ڳ ڊ ډ م ممم نه نفنه ۾ مِمِم هُ هُمُهُ ه همه ١٣٥٦ تِ	
Urdu	ur	Language set to Urdu XeTeX: "Harmattan/GR:language=ur" (Graphite) XeTeX: "Harmattan:language=ur" (OpenType) HTML: lang="ur"	د ذ ڈ ډ ڊ ڋ ڌ ڍ ڎ ڏ ڏ ڋ ڋ ډ ۾ ممم	
Wolof	wo	Language set to Wolof XeTeX: "Harmattan/GR:language=wo" (Graphite) XeTeX: "Harmattan:language=wo" (OpenType) HTML: lang="wo"	ڂڂڂڿڿڂڐڂڐڂڴڴڴڿڿ؈ڡڡڡۻڞڣڣڣڔ؈ڣۺڟڞڨڨ؋؈ڡۿ ۴۵۶۷ ؚٞ	

² Implementation Notes: G=Implemented in Graphite; O=Implemented in OpenType; T=Implemented in TypeTuner (command line version: http://scripts.sil.org/TypeTuner and web-based version: http://scripts.sil.org/ttw).

Use of Graphite Features, OpenType Character Variants, and Language-specific features

LibreOffice


In LibreOffice 3.4+³ there are a few steps the user may need to do before using Arabic script and language support. The font would be set to "Harmattan" and then the language must be selected in the application. In LibreOffice, first enable complex text layout (**Tools / Options / Language Settings / Languages** and then select **Enabled for complex text layout (CTL).** Then, select the text, click on the status bar to change the language, select the language (if it is not displayed, click on "More...").

The font features can be turned on by choosing the font (ie Harmattan), followed by a colon, followed by the feature ID, and then followed by the feature setting. So, for example, if the "Jeem/Hah" handwriting variant is desired, the font selection would be "Harmattan:cv08=1".



If you wish to apply two (or more) features, you can separate them with an "&". Thus, "Harmattan:cv08=1&cv20=1" would apply the "Jeem/Hah" plus the "Sad/Dad" feature.

Newer versions of LibreOffice have a user interface which allows selection of the Font Features. Select your text (or style) and go to **Format / Character**. Choose the Harmattan font and click on **Features**. Then select the features you wish to select.



3 Download here: http://www.libreoffice.org/download.

LibreOffice allows the user to select languages (or even add a language); the default glyphs will change based on the language preferences. Currently LibreOffice allow for the selection of Kurdish, Sindhi, and Urdu. If an application allows you to select any of the languages, the default glyphs will change based on the language preferences.

In the following screenshot, the Sindhi language has been selected.



It is also possible to choose the language through the font menu in LibreOffice:

Wolof: چ چ ځ ځ ځ ځ ځ ځ ځ ځ ځ ځ ځ ځ ځ ډ (Harmattan:lang=wo)

(Harmattan:lang=sd) م ممم نه نففه به مِمِه هُ مُقْمُهُ ه ههه

Microsoft Word

Word does not allow for the selection of Character Variants. However, it does support language selection of Urdu and Sindhi.

Before opening Word, go to Start / All Programs / Microsoft Office / Microsoft Office 2010 Tools / Microsoft Office 2010 Language Preferences and add any editing languages you want to use.

XeTeX

For XeTeX⁴, Graphite Feature IDs are not used. Use the **Feature Name** and **Feature setting**, e.g., if Character Variant 12 was desired, the font selection would be: "Harmattan/GR:Dal=Alternate" at 12pt

Languages in XeTeX can be accessed by using: "Harmattan/GR:language=ur" (for Graphite) or "Harmattan:Arab:language=URD" (for OpenType).

4 http://tug.org/xetex/

OpenType Character Variants

Currently there are very few applications which support OpenType Character Variants.

For applications which do support OpenType Character Variants, such as in CSS, the Character Variant ID and setting is chosen. For example, in CSS, if cv32, is desired, you might have this code in your .css:

```
@font-face {
  font-family: Harmattan;
    src: url(Harmattan-Regular.woff);
}
.cv120 {
  font-family: Harmattan;
  font-feature-settings: "cv12" 0;
}
.cv121 {
  font-family: Harmattan;
  font-family: Harmattan;
  font-feature-settings: "cv12" 1;
}
```

and this in your .html:

Which would produce this:

```
د ذ ڈ ډ ڊ ڋ ڌ ڍ ڎ ڏ ڐ ۮ ڋ ݚ ݚ
< خ ڈ ڈ ډ ڋ ڋ ۃ ڍ ڎ ڏ ڐ ۮ ڋ ݚ ݚ
```

TypeTuner

At this point, most applications do not make use of these features (neither Graphite or OpenType Character Variants nor language features) so another solution is needed to use the variant characters. TypeTuner creates tuned fonts that use the variant glyph in place of the standard glyph. The TypeTuner Web site is http://scripts.sil.org/ttw/fonts2go.cgi.