


Wireless Screen Transmitter

Empower next-level collaboration



Follow us on social media to get the latest product and solution information



Product Specification

Disclaimer

Due to the product configuration and manufacturing process, the actual body size/weight may vary, please refer to the actual product.

The product pictures in this specification are for illustration only, the actual product effect (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product.

In order to provide accurate specifications as much as possible, the content of this specification may be adjusted and revised in real time to match the actual product performance, specifications and other information.



| Product Datasheets

I/O Interfaces	USB Type-C	1 (Type-A functionality only
	USB Type-A (Adapter)	1
Functional characteristics	Maximum Connection Distance	12M
	Supported Operating Systems	win7/win10/win11/Mac OS 10.12 and above
	Fastest Boot Time	128
	Transmission Delay	\$120ms
	Maximum Resolution	Default 1920x1080@60Hz
	Touch Return	Maximum Support 2560×1440@25Hz
Bluetooth	Version	5.2
	Operating Frequency	2.4GHz
	Working distance	0-12m
Wi-Fi	Version	802.11a/n/ac/ax
	Operating Frequency	5GHz
	Working distance	0~12m

Product Datasheets

Electrical Parameters	Input power parameters (voltage, frequency)		5V@500mA
	Whole machine power consumption		\$2.5W
Structural Parameters	Position and number of keys		Center Round Button, 1pc
	Dimension of the whole machine (lengthxwidth thickness)		183.3×77.3×18.5mm
	Package size (LxThickness High)	1pcs	196×110×28mm
		60pcs	418×356×340mm
	Net Weight		TBD
	Gross Weight	1pcs	TBD
		60pcs	TBD
Environmental factors	Working Temperature		0°C~40°C
	Operating Humidity		10%~90% RH
	Storage Temperature		20°C~60°C
	Storage Humidity		10%~90% RH