ADVANCED JAVA

JAVA VIRTUAL MACHINE

Vivek Shah bonii@di.ku.dk

August 20, 2018

DIKU, University of Copenhagen

OUTLINE

Java Technology Overview

JVM Tuning Options

Profiling and Other Utilities

JAVA TECHNOLOGY OVERVIEW



Overview of Java Development Process (Oracle Docs)



Overview of Java Development Process (Oracle Docs)

Source programs are written in plain-text in .java files



Overview of Java Development Process (Oracle Docs)


- Source programs are written in plain-text in .java files
- Java compiler compiles them into .class files (consisting of bytecodes)



Overview of Java Development Process (Oracle Docs)

- Source programs are written in plain-text in .java files
- Java compiler compiles them into .class files (consisting of bytecodes)
- The Java Virtual Machine runs the .class files

OVERVIEW OF JVM



Overview of JVM (Oracle Docs)

JVM AND BYTECODE

- Bytecodes
 - · Instruction set of the JVM
 - Both a stack and register machine

JVM AND BYTECODE

- Bytecodes
 - · Instruction set of the IVM
 - · Both a stack and register machine
- · Java Virtual Machine
 - Abstract machine that can execute Java byte-code → Java software processor
 - · JVM components
 - 1. Bytecode verifier
 - 2. Memory manager
 - 3. Execution engine (Interpreter/JIT compiler)

WHY USE A JVM?

Why do we need a JVM to interpret the .class file instead of compiling to machine code?

WHY USE A JVM?

- Platform independence → Source and compiled code is independent of hardware and operating system platform
 - Compiled code is just dependent on the JVM platform
- 2. Allows distribution of binaries (.class files)
- Compilation process is platform independent but compilers are not always
- 4. Compile once, run anywhere
- 5. Allows sand-boxing e.g., Applets
- 6. Allows instrumentation. Dynamic memory management.

WHY USE A JVM? (CONTD.)

- 7. Provides Extensibility
 - Any language that can compile down to bytecode can be interpreted (e.g., Scala, Kotlin)
- 8. Only JVM needs to be platform dependent. JVM writers can focus on efficient processing of bytecodes instead of the whole upper language stack
- Has overheads. Various optimizations like JIT compilation, hardware processors supporting bytecodes

JVM TUNING OPTIONS

TUNING THE JVM

- JVM provides a tunable execution environment
- · Various ways to affect performance of programs by tuning JVM
 - 1. Memory management (heap tuning and garbage collection)
 - 2. Code generation (e.g., control inlining of code)
 - 3. Configuration of environment variables using properties
 - 4. Usage of JVM hooks
- Use limited profiling support to understand program performance
- More than meets the eye (Use extreme care)

JVM TUNING OPTIONS

Meaning of the option prefix

- $\mathbf{x} \to \mathbf{non}$ standard across different VM, subject to change without notice
- $-xx \rightarrow Non$ standard and not stable

For standard options see the reference pages for the platform

Option	Meaning

Option	Meaning
-classpath	Directories to search for class files

Option	Meaning
-classpath	Directories to search for class files
-d32 or -d64	Run in 32 bit or 64 bit enviroment

Option	Meaning
-classpath	Directories to search for class files
-d32 or -d64	Run in 32 bit or 64 bit enviroment
-server	Turns on optimizing JIT

Option	Meaning
-classpath	Directories to search for class files
-d32 or -d64	Run in 32 bit or 64 bit enviroment
-server	Turns on optimizing JIT
-verbose	Runs in verbose mode

Option	Meaning
-classpath	Directories to search for class files
-d32 or -d64	Run in 32 bit or 64 bit enviroment
-server	Turns on optimizing JIT
-verbose	Runs in verbose mode
-jar	Execute a program in a jar file

Option	Meaning
-classpath	Directories to search for class files
-d32 or -d64	Run in 32 bit or 64 bit enviroment
-server	Turns on optimizing JIT
-verbose	Runs in verbose mode
-jar	Execute a program in a jar file
-Xint	Turns off compilation to native code, only interpretation

Option	Meaning

Option	Meaning
-Xms	Initial size of heap e.g., -Xms1024m

Option	Meaning
-Xms	Initial size of heap e.g., -Xms1024m
-Xmx	Maximum size of heap e.g., -Xmx8192m

Option	Meaning
-Xms	Initial size of heap e.g., -Xms1024m
-Xmx	Maximum size of heap e.g., -Xmx8192m
-Xss	Sets the stack size, -Xss4096k ← this value will be multiplied by the number of threads

- Tuning garbage collection is not only about setting parameters but understanding the process
- · Generational garbage collection
- · Can choose the type of garbage collector
- Blocking versus Incremental versus Concurrent

Option	Meaning

Option	Meaning
-XX:+UseSerialGC	Enables the use of the serial garbage collector (Good when running many JVM's)

Option	Meaning
-XX:+UseSerialGC	Enables the use of the serial garbage collector (Good when running many JVM's)
-XX:+UseParallelGC	Enables the use of the parallel scavenge garbage collector (also known as the throughput collector)

Option	Meaning
-XX:+UseSerialGC	Enables the use of the serial garbage collector (Good when running many JVM's)
-XX:+UseParallelGC	Enables the use of the parallel scavenge garbage collector (also known as the throughput collector)
-XX:+UseParallelOldGC	Enables the use of the parallel garbage collector for full GCs (heavy duty, long pauses)

Option	Meaning


Option	Meaning
-XX:+UseConcMarkSweepGC	Enables the use of the CMS garbage collector for the old generation (short pauses)

Option	Meaning
-XX:+UseConcMarkSweepGC	Enables the use of the CMS garbage collector for the old generation (short pauses)
-XX:+UseG1GC	Enables the use of the garbage-first (G1) garbage collector (better CMS)

Option	Meaning
-XX:+UseConcMarkSweepGC	Enables the use of the CMS garbage collector for the old generation (short pauses)
-XX:+UseG1GC	Enables the use of the garbage-first (G1) garbage collector (better CMS)

Use these options <u>only</u> if you understand the process and its impact

HEAP STRUCTURES FOR GARBAGE COLLECTION





Option	Meaning

Option	Meaning
-XX:NewSize	Size of new generation

Option	Meaning
-XX:NewSize	Size of new generation
-XX:MaxNewSize	Maximum size of new generation

Option	Meaning
-XX:NewSize	Size of new generation
-XX:MaxNewSize	Maximum size of new generation
-XX:NewRatio	Ratio of old/new generations

Option	Meaning
-XX:NewSize	Size of new generation
-XX:MaxNewSize	Maximum size of new generation
-XX:NewRatio	Ratio of old/new generations
-XX:SurviverRatio	Ratio of eden/survivor space

Option	Meaning
-XX:NewSize	Size of new generation
-XX:MaxNewSize	Maximum size of new generation
-XX:NewRatio	Ratio of old/new generations
-XX:SurviverRatio	Ratio of eden/survivor space

Lots more!! Use these options <u>only</u> if you understand them

Option	Meaning


Option	Meaning
-XX:MaxInlineSize	Sets the maximum size in bytes of bytecode that will be inlined

Option	Meaning
-XX:MaxInlineSize	Sets the maximum size in bytes of bytecode that will be inlined
-XX:FreqInlineSize	Sets the maximum size in bytes of bytecode of frequently executed method that will be inlined

Option	Meaning
-XX:MaxInlineSize	Sets the maximum size in bytes of bytecode that will be inlined
-XX:FreqInlineSize	Sets the maximum size in bytes of bytecode of frequently executed method that will be inlined
-XX:LoopUnrollLimit=n	Unrolls loops with a compiler internal representation node count of less than n

CONFIGURING PROPERTIES

- Properties passed using -Dproperty=p
- Retrieve the property value using System.getProperty(p)
- Some property keys are already predefined from which certain environment values can be retrieved
- Use .properties file instead of long list of properties in command line



PROFILING

- Profiling is done in order to understand performance trade-offs
 - Use a profiler to understand your code better
- $\mathsf{-Xprof} \to \mathsf{option}$ for some basic profiling

PROFILING

- Profiling is done in order to understand performance trade-offs
 - · Use a profiler to understand your code better
- $-Xprof \rightarrow option for some basic profiling$
- JVM Monitor has nice integration with Eclipse
- Most full featured profilers are commercial

- 1. jdb Java debugger
- 2. javap Java disassembler
- 3. javadoc Java document generator