

KidsTennis Send Notifications

/kidstennis-send-notifications POST [🔗](#)

Send notifications to recipients.
Returns success status and an error message if needed. Output formatting is JSON.

Parameters:

Name	Required	Values	Default	Description
lang	no	de, fr, it	de	Language for sending message.
title	yes		none	Title of notification
message	yes		none	Message of notification
recipients	yes		none	Array of recipients
replyToEmail	no		none	reply-to email address
replyToName	no		none	reply-to name

Request Body (JSON):

```
1 {
2   "title": "Some notification title",
3   "message": "Some notification message"
4   "recipients": [
5     {
6       "firstName": "John",
7       "lastName": "Doe",
8       "email": "john.doe@domain.com"
9     },
10    {
11      "firstName": "Samantha",
12      "lastName": "Doe",
13      "email": "samantha.doe@domain.com"
14    }
15  ],
16  "replyToEmail": "replyto@domain.com",
17  "replyToName": "Reply To"
18 }
```

PHP example:

```
1 $token = '{{BEARER_AUTH_TOKEN}}';
2 $ch = curl_init('{{API_URL}}/kidstennis-send-notifications?lang=de');
3 $data = [
4   'title' => 'Some notification title',
5   'message' => 'Some notification message',
```

```

6     'recipients' => [
7         [
8             'firstName' => 'John',
9             'lastName' => 'Doe',
10            'email' => 'john.doe@domain.com',
11        ],
12        [
13            'firstName' => 'Samantha',
14            'lastName' => 'Doe',
15            'email' => 'samantha.doe@domain.com',
16        ],
17    ],
18    'replyToEmail' => 'replyto@domain.com',
19    'replyToName' => 'Reply To',
20 ];
21 $json = json_encode($data);
22
23 curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
24 curl_setopt($ch, CURLOPT_POST, true);
25 curl_setopt($ch, CURLOPT_HTTPHEADER, array(
26     'Content-Type: application/json',
27     'Authorization: Bearer ' . $token,
28 ));
29 curl_setopt($ch, CURLOPT_POSTFIELDS, $json);
30
31 $data = curl_exec($ch);
32 curl_close($ch);

```

Response example (SUCCESS):

```

1 {
2     "success": true
3 }

```

Response example (ERROR):

```

1 {
2     "success": false,
3     "message": "Input parameter title is empty!"
4 }

```