

-- Criação do banco de dados para o cenário de E-commerce

```
create database ecommerce;
```

```
use ecommerce;
```

-- criar tabela cliente

```
create table clients(  
  idClient int auto_increment primary KEY,  
  Fname varchar(10),  
  MName varchar(3),  
  LName varchar(20),  
  Document varchar(11),  
  Address varchar(45),  
  BDate date,  
  constraint unique_cpf_client unique (Document)  
);
```

```
desc clients;
```

```
alter table clients auto_increment = 1;
```

```
insert into clients (Fname,MName,LName,Document,Address) values
```

```
('Maria','M','Silva','123456789','endereço 1'),
```

```
('Jose','J','Silva','111111111','endereço 2'),
```

```
('Pedro','P','Silva','222222222','endereço 3'),
```

```
('Paulo','PA','Silva','33333333','endereço 4');
```

```
select * from clients;
```

-- criar tabela produto

```
create table product(  

```

```
idProduct int auto_increment primary KEY,  
Pname varchar(10) not null,  
Classification_kids boolean default false,  
category enum('eletronico','vestimenta','brinquedos','alimentos'),  
valuation float default 0,  
size varchar(10)  
);
```

-- criar tabela payment

```
create table payments(  
idClient int,  
idPayment int,  
typePayment enum('Boleto','Cartão', 'Dois Cartões'),  
limitAvailable float,  
primary key (idClient, idPayment)  
);
```

-- criar tabela pedido

```
create table orders(  
idOrders int auto_increment primary KEY,  
idClient int,  
orderStatus enum('Cancelado','Confirmado','Em processamento') default 'Em processamento',  
orderDescription varchar(255),  
sendValue float default 10,  
paymentCash bool default false,  
constraint fk_orders_client foreign key (idClient) references clients(idClient)  
);
```

-- criar tabela estoque

```
create table produtStorage(  
idprodStorage int auto_increment primary KEY,
```

```
storageLocation varchar(255),  
quantity int default 0  
);
```

-- criar tabela fornecedor

```
create table supplier(  
idSupplier int auto_increment primary KEY,  
SocialName varchar(255) not null,  
CNPJ char(15) not null,  
contact char(11) not null,  
constraint unique_supplier unique (CNPJ)  
);
```

-- criar tabela vendedor

```
create table seller(  
idSeller int auto_increment primary KEY,  
SocialName varchar(255) not null,  
AbstName varchar(255),  
CNPJ char(15),  
CPF char(9),  
location varchar(255),  
contact char(11) not null,  
constraint unique_cnpj_seller unique (CNPJ),  
constraint unique_cpf_seller unique (CPF)  
);
```

-- criar tabela produto vendedor

```
create table productSeller(  
idSeller int,  
idProduct int,
```

```
ProdQuantity int default 1,  
constraint primary key (idSeller, idProduct),  
constraint fk_product_seller foreign key (idSeller) references Seller(idSeller),  
constraint fk_product_product foreign key (idProduct) references Product(idProduct)  
);
```

```
-- criar tabela produto pedido  
create table productOrder(  
idProduct int,  
idOrder int,  
poQuantity int default 1,  
poStatus enum('Disponivel','Sem Estoque') default 'Disponivel',  
constraint primary key (idOrder, idProduct),  
constraint fk_productorder_seller foreign key (idProduct) references Product(idProduct),  
constraint fk_productorder_product foreign key (idOrder) references orders(idOrders)  
);
```

```
-- criar tabela estoque  
create table storageLocation(  
idProduct int,  
idStorage int,  
location varchar(255) default 1,  
constraint primary key (idProduct, idStorage),  
constraint fk_storagelocation_product foreign key (idProduct) references Product(idProduct),  
constraint fk_storagelocation_storage foreign key (idStorage) references  
produtStorage(idprodStorage)  
);
```

```
create table productSupplier(  
idSupplier int,  
idProduct int,
```

```
quantity int not null,  
  
constraint primary key (idSupplier, idProduct),  
  
constraint fk_product_supplier_supplier foreign key (idSupplier) references Supplier(idSupplier),  
constraint fk_product_supplier_product foreign key (idProduct) references product(idProduct)  
);
```

```
show tables;
```

```
show databases;
```

```
use information_schema;
```

```
desc referential_constraints;
```

```
select * from referential_constraints;
```