iRacing.com Motorsport Simulations
lotus49 setup: 261005_jr_ww103
track: monza nochicane

Wolfgang Wagner's GPL setup WW103 (Wat10361WW.kj1, Watkins Glen 1:03.61) carried to iRacing's garage. Typed out for entering by hand (iRacing cannot load a sheet). Grey = WW103's own GPL value, and why the iRacing value differs where it does.

You may not need to type anything: this is the setup you built on 5 October and saved as **261005_jr_ww103**. Re-doing the conversion on 19 October with everything learned since (the garage's real ranges, the springs' motion ratios, each anti-roll bar hole's stiffness) gives the same values. If 261005_jr_ww103 is still in your garage, load it and compare it with this sheet; if it is lost, enter the values below on **261010_rung_official** and save as **261005_jr_ww103**.

Order: Tires, then Chassis (springs, then perches until the ride heights and cross weight below are shown, then the rest), then Drivetrain. Wait 3 seconds after each change until no label has an asterisk.

LEFT FRONT:

Cold pressure: 152 kPa GPL 19 psi = 131 kPa; 152 kPa is iRacing's lowest

LEFT REAR:

Cold pressure: 152 kPa GPL 20 psi = 138 kPa; 152 kPa is iRacing's lowest

RIGHT FRONT:

Cold pressure: 152 kPa GPL 20 psi = 138 kPa; 152 kPa is iRacing's lowest

RIGHT REAR:

Cold pressure: 152 kPa GPL 20 psi = 138 kPa; 152 kPa is iRacing's lowest

FRONT:

ARB arms: 5 GPL bar 200 lb/in, 1.25x a typical GPL front bar; see the roll-balance note
ARB diameter: 0.375"
Brake bias: 54.00% GPL 54 %
Toe-in: -6 mm GPL -0.5 in = -12.7 mm toe-out; -6 mm is the most tech allows (-7 fails)
Steering ratio: 10:1 GPL 16:1; iRacing's Lotus offers 10:1 only
Cross weight: 50.0% check value, set by the perches

LEFT FRONT:

Corner weight: 1351 N check value
Ride height: 84.7 mm check value (GPL ride heights are not comparable)
Shock deflection: 61.4 mm of 104.6 mm check value
Spring perch offset: 134.9 mm set until the ride heights and cross weight above are shown
Spring rate: 18 N/mm GPL wheel rate 50 lb/in = 13.3 N/mm spring; 18 is iRacing's softest front
Packer: 0.0 mm
Bump stiffness: +6 clicks GPL bump 3, rebound 4 of 1..5
Rebound stiffness: +9 clicks
Camber: -0.4 deg GPL -0.75 deg; more negative than -0.4 fails tech

LEFT REAR:

Corner weight: 1640 N check value
Ride height: 104.8 mm check value (GPL ride heights are not comparable)
Shock deflection: 59.6 mm of 113.0 mm check value
Spring perch offset: 104.0 mm set until the ride heights and cross weight above are shown
Spring rate: 48 N/mm GPL 120 lb/in = 47 N/mm spring; 48 keeps it the setup julia's WW103 is fitted to (2 % apart)
Packer: 0.0 mm
Bump stiffness: +9 clicks GPL bump 4, rebound 5 (its stiffest) of 1..5
Rebound stiffness: +12 clicks
Camber: -0.4 deg GPL -0.5 deg; -0.5 fails tech

RIGHT FRONT:

Corner weight: 1325 N check value
Ride height: 86.0 mm check value (GPL ride heights are not comparable)
Shock deflection: 58.8 mm of 104.6 mm check value
Spring perch offset: 131.0 mm set until the ride heights and cross weight above are shown
Spring rate: 18 N/mm as LF
Packer: 0.0 mm
Bump stiffness: +6 clicks as LF
Rebound stiffness: +9 clicks
Camber: -0.1 deg GPL 0.0 deg; the garage shows -0.1 (the nearest it reaches)

RIGHT REAR:

Corner weight: 1620 N check value
Ride height: 106.2 mm check value (GPL ride heights are not comparable)
Shock deflection: 59.9 mm of 113.0 mm check value
Spring perch offset: 104.8 mm set until the ride heights and cross weight above are shown
Spring rate: 48 N/mm as LR
Packer: 0.0 mm
Bump stiffness: +9 clicks as LR
Rebound stiffness: +12 clicks
Camber: +0.2 deg GPL +0.25 deg

REAR:

Fuel level: 43.2 L the test fuel, as every test since 4 October; WW103's race fuel is 4 US gal = 15 L
ARB diameter: 0.6875"
ARB arms: firm GPL bar 200 lb/in, 1.33x a typical GPL rear bar; firm is iRacing's stiffest rear
Toe-in: +3 mm GPL +0.125 in = 3.2 mm

Transmission:

Final drive: 3.78 GPL final 3.1 with gears 2.286/1.706/1.474/1.286/1.160 (a close-ratio Glen box)
First Gear: 2.23 140.7 Km/h GPL 1st tops out at 167 km/h; 2.23 is iRacing's tallest 1st
Second Gear: 1.40 224.0 Km/h GPL 224 km/h
Third Gear: 1.21 259.2 Km/h GPL 260 km/h
Fourth Gear: 1.04 301.6 Km/h GPL 297 km/h
Fifth Gear: 0.958 327.4 Km/h GPL 330 km/h

Differential:

Clutch plates: 4 GPL 4
Preload: 41 Nm GPL has no preload: iRacing's default kept
Drive ramp angle: 35 deg GPL 30 deg (locks hard on power); 35 is iRacing's lowest
Coast ramp angle: 85 deg GPL 85 deg (nearly free off throttle)

Notes (julia racer, 19 October 2026):

Roll balance (why front arms 5 and rear firm). WW103 is loose because its roll stiffness leans to the rear: against a typical GPL Lotus setup it has +11 % at the front and +31 % at the rear (soft front springs, both bars stiff). In iRacing, with the softest front springs, julia's per-hole bar model gives:

Bars (front / rear)	Front roll stiffness	Rear	Front share
default car: 0.375" arms 2 / 0.6875" arms 5	reference	reference	41 %
this sheet: 0.375" arms 5 / 0.6875" firm	+6 %	+19 % (iRacing's most)	**38 %**
importer's literal pick: arms 3 / arms 6	-14 %	+10 %	36 %
WW103 in GPL, for comparison	+11 %	+31 %	37 %

iRacing's rear bar cannot reach WW103's +31 %, so the sheet keeps the rear at its stiffest and sets the front for the balance. Front arms 5 lands within 1 point of WW103's 37 % front share while keeping the car's total roll stiffness up. Arms 4 (36 %) would be the other choice, a touch looser.

What iRacing's ranges cut: tyre pressures (152 kPa minimum), the front springs (18 N/mm minimum), front toe-out (-6 mm tech limit), the left-side camber (tech), the 30 deg drive ramp (35 minimum), GPL's 16:1 steering (10:1 only) and the 1st gear (iRacing's tallest 1st is shorter). GPL's ride heights and bump rubbers are measured differently and are not carried over.

Corner weights, ride heights, shock deflections are what your own 18 October sheet of 261005_jr_ww103 shows at Monza: check values, not knobs.