

CZECH TECHNICAL UNIVERSITY IN PRAGUE,
FACULTY OF ELECTRICAL ENGINEERING

MASTER'S THESIS

Dual Circularly Polarized Waveguide Antenna

Author

M. ŠIMÁK

DEPARTMENT OF
ELECTROMAGNETIC FIELD

Supervisor

doc. Ing. P. HAZDRA, Ph.D.

DEPARTMENT OF
ELECTROMAGNETIC FIELD



December 2024

[THIS PAGE INTENTIONALLY LEFT BLANK.]

I. Personal and study details

Student's name: **Šimák Martin**

Personal ID number: **483523**

Faculty / Institute: **Faculty of Electrical Engineering**

Department / Institute: **Department of Electromagnetic Field**

Study program: **Electronics and Communications**

Specialisation: **Radio Communications and Systems**

II. Master's thesis details

Master's thesis title in English:

Dual Circularly Polarized Waveguide Antenna

Master's thesis title in Czech:

Duálně kruhově polarizovaná vlnovodová anténa

Guidelines:

Research different polarizers in a metallic waveguide, consider round or square transversal shape of the guide. Inspired by circularly polarized patch antenna with chamfered corners, adapt this technique to the waveguide technology (the frequency should be used to be appropriate for easy fabrication, say around 5 GHz). Perform 2D eigenmode analysis of round and square waveguides with inserted metal triangles, and compare the results with the theory of patch antennas of such shapes. Choose one of the waveguide with the polarizer and optimize it to provide the best bandwidth and radiation properties, also design the transition from coaxial cable, preferably with the ability to excite both RHCP and LHCP patterns. Add a small horn (say 15 dBi) to the waveguide and finally optimise the whole structure. Build and measure the whole structure, compare to simulation results.

Bibliography / sources:

- 1/ Polarizers on sections of square waveguides with inner corner ridges | IEEE Conference Publication | IEEE Xplore
- 2/ Compact reconfigurable waveguide circular polarizer | IEEE Conference Publication | IEEE Xplore
- 3/ Design of Wideband Quad-Ridge Waveguide Polarizer | IEEE Conference Publication | IEEE Xplore
- 4/ Optimum-Iris-Set Concept for Waveguide Polarizers | IEEE Journals & Magazine | IEEE Xplore
- 5/ Novel square/rectangle waveguide septum polarizer | IEEE Conference Publication | IEEE Xplore
- 6/ Broadband Septum Polarizer With Triangular Common Port | IEEE Journals & Magazine | IEEE Xplore
- 7/ New Tunable Iris-Post Square Waveguide Polarizers for Satellite Information Systems | IEEE Conference Publication | IEEE Xplore
- 8/ Hexagonal waveguides: New class of waveguides for mm-wave circularly polarized horns | IEEE Conference Publication | IEEE Xplore
- 9/ Hexagonal Waveguide Based Circularly Polarized Horn Antennas for Sub-mm-Wave/Terahertz Band | IEEE Journals & Magazine | IEEE Xplore
- Bow-Tie-Shaped Radiating Element for Single and Dual Circular 10/ Polarization | IEEE Journals & Magazine | IEEE Xplore
- 11/ A Wideband Circularly Polarized Horn Antenna With a Tapered Elliptical Waveguide Polarizer | IEEE Journals & Magazine | IEEE Xplore

Name and workplace of master's thesis supervisor:

doc. Ing. Pavel Hazdra, Ph.D. FEE CTU in Prague, K 13117

Name and workplace of second master's thesis supervisor or consultant:

Date of master's thesis assignment: **04.09.2024**

Deadline for master's thesis submission: _____

Assignment valid until: **15.02.2026**

doc. Ing. Pavel Hazdra, Ph.D.
Supervisor's signature

Head of department's signature

prof. Mgr. Petr Páta, Ph.D.
Dean's signature

III. Assignment receipt

The student acknowledges that the master's thesis is an individual work. The student must produce his thesis without the assistance of others, with the exception of provided consultations. Within the master's thesis, the author must state the names of consultants and include a list of references.

Date of assignment receipt

Student's signature

Contents

Introduction	2
1 Electrodynamics of guided waves	3
1.1 Fundamentals of electrodynamics	3
1.1.1 Maxwell's equations	3
1.1.2 Electromagnetic properties of matter	4
1.1.3 Boundary conditions	6
1.2 Electromagnetic waves	6
1.2.1 The wave equations	6
1.2.2 Monochromatic plane waves	7
1.2.3 Guided waves	10
Conclusion	14
Glossary of Symbols	15
Bibliography	16
Index	17

Introduction

Do not write a couple of words on literature survey. Present the difference construction and design choices, compare them both theoretically and by the results presented in gathered papers, but in their respective sections of the design process. Use them a nice foreword for each of the parts, going through existing approaches.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Throughout the theoretical chapter, I omit using the common *del*, or *nabla*, notation for the vector differential operator ∇ which gives rise to the formally proper differential operators of gradient (∇), divergence ($\nabla \cdot$), curl ($\nabla \times$), and sometimes even the Laplace operator ($\nabla \cdot \nabla$ or ∇^2). Instead, I will use the standard notations of grad, div, curl, and Δ , respectively. While I am aware of the mnemonic merits it brings when working in coordinates, this does not come to fruition as I do not carry out any computations in this text. On the other hand, there are various reasons to avoid it, such as that it promotes a notational ambiguity with the covariant derivative used in differential geometry, or to distinguish the individual operators at first sight better.

Synopsis. In **chapter 1**, Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Methodology. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Chapter 1

Electrodynamics of guided waves

This chapter establishes the theoretical foundation for the analysis and design of a waveguide-based antenna system. Beginning with Maxwell's equations and general description of electromagnetic fields in various settings relevant to this work, the wave equations governing guided waves are derived, and their solutions are analysed to elucidate the behaviour of electromagnetic fields within waveguides. This analysis provides a framework for understanding the operation of structures designed in the following chapters. While focusing on the essential elements of waveguide theory, this chapter provides a comprehensive treatment of the subject and establishes the notation used throughout this work.

The exposition endeavours to build upon the foundations laid in [1]–[3], incorporating personal insights and notational preferences to present a cohesive foundation for further chapters.

1.1 Fundamentals of electrodynamics

In this section, the fundamental principles of electromagnetism are presented, starting with Maxwell's equations, which encapsulate the relationships between electric and magnetic fields and their sources. The response of different materials to these fields is then explored through the introduction of *constitutive relations*. Finally, the focus is shifted to the behaviour of electromagnetic fields at material boundaries, providing essential *boundary conditions* for solving electromagnetic problems.

1.1.1 Maxwell's equations

The differential form of Maxwell's equations, as presented below, constitutes the cornerstone of classical electromagnetism, providing a complete¹ framework for analysing electromagnetic phenomena at any point in space and time. These equations summarize the relations between *electric field intensity* \mathbf{E} and *magnetic flux density* \mathbf{B} and their sources due to charge densities ρ , current densities \mathbf{J} , or the changing of the fields themselves. To ensure the validity of these expressions, let us assume that the field vectors are well-behaved functions, exhibiting continuity and possessing continuous derivatives. This assumption holds for most electromagnetic systems, with exceptions

¹For actual completeness, save for some special properties stemming from interactions in matter, the equations must also be supplemented by the Lorentz's force law $\mathbf{F} = q(\mathbf{E} + \mathbf{v} \times \mathbf{B})$.

arising at interfaces between distinct media where abrupt changes in charge and current densities may occur.

$$\operatorname{div} \mathbf{E} = \frac{1}{\epsilon_0} \rho_e, \quad (1.1a) \quad \operatorname{div} \mathbf{B} = \mu_0 \rho_m, \quad (1.1c)$$

$$\operatorname{curl} \mathbf{E} = -\mu_0 \mathbf{J}_m - \partial_t \mathbf{B}, \quad (1.1b) \quad \operatorname{curl} \mathbf{B} = \mu_0 \mathbf{J}_e + \mu_0 \epsilon_0 \partial_t \mathbf{E}, \quad (1.1d)$$

There is one oddity about equations (1.1) and that is the inclusion of the magnetic charge density ρ_m and magnetic current density \mathbf{J}_m which are part of the ‘generalized concept’. Although these quantities, in spite of diligent search, were never physically observed, their introduction establishes a pleasing balance in Maxwell’s equations while being theoretically sound as well. This concept is further utilized when solving advanced physical problems in applied physics and engineering. This is facilitated by the introduction of equivalent magnetic charge and current which can be used to conveniently express fields as if generated by these fictitious sources, especially in problems where the exact form of the electromagnetic field would otherwise be complicated to elucidate.

Mathematically, equations (1.1), like any differential equations, form a complete problem only when supplemented with suitable boundary conditions in a more traditional sense, such as behaviour of the vector fields ‘in infinity’. These are typically ‘obvious’ from the problem-solving context, e.g., fields vanishing at large distance from localized charge distribution, etc.

1.1.2 Electromagnetic properties of matter

Although Maxwell’s equations in their fundamental form (1.1) provide a complete description of electromagnetic phenomena, an alternative formulation offers a more convenient approach for analysing materials susceptible to electric and magnetic polarization. Within such media, the total electric charge density ρ_e can be expressed as a sum of the *free charge* density ρ_f , which constitutes the *actual source* charge,² and the *bound charge* $\rho_b = -\operatorname{div} \mathbf{P}$, produced by an electric polarization \mathbf{P} of the material. Moreover, changing electric fields also induce changing polarization, producing *polarization current* $\mathbf{J}_p = \partial_t \mathbf{P}$ which add to the *free current* \mathbf{J}_f . Similarly to electric polarization, a magnetic polarization \mathbf{M} results in a bound current $\mathbf{J}_b = \operatorname{curl} \mathbf{M}$. These effects, inherently connected to the susceptibility of materials to be polarized, hence influence the total electromagnetic field in their vicinity. This led to the introduction of convenient field quantities that account for the presence of such media.

Within the framework of Maxwell’s equations, *electric flux density* \mathbf{D} (also called the *electric displacement field*) and the *magnetic field intensity* \mathbf{H} offer a more convenient representation, explicitly separating the free and bound sources. This approach allows for expressing Maxwell’s equations in a form that directly relates the fields to the free charge and free current, which are sources that can be controlled directly. Using these field quantities, equations (1.1) read

$$\operatorname{div} \mathbf{D} = \rho_f, \quad (1.2a) \quad \operatorname{div} \mathbf{B} = \mu_0 \rho_m, \quad (1.2c)$$

$$\operatorname{curl} \mathbf{E} = -\mathbf{J}_m - \partial_t \mathbf{B}, \quad (1.2b) \quad \operatorname{curl} \mathbf{H} = \mathbf{J}_f + \partial_t \mathbf{D}, \quad (1.2d)$$

While equations (1.2) effectively express electromagnetic laws within media, their

²It is important to reinforce the idea that the magnetic charge and current are fictitious ‘source’ quantities. Therefore, they are already, by definition, purely *free* quantities.

hybrid notation, involving both \mathbf{E} and \mathbf{D} , and both \mathbf{B} and \mathbf{H} , necessitates the use of *constitutive relations*. These relations, which establish correspondence between the respective electric and magnetic field quantities, are material-dependent and reflect the specific response of a medium to electric and magnetic fields. In general, these relationships can be expressed as

$$\mathbf{D} = \hat{\epsilon} * \mathbf{E}, \quad (1.3a)$$

$$\mathbf{B} = \hat{\mu} * \mathbf{H}, \quad (1.3b)$$

where $\hat{\epsilon}$ and $\hat{\mu}$ are the material's *permittivity* and *permeability*, respectively, and the asterisk denotes *convolution*.

Remark 1.1.1. In formulations of akin to equations (1.2), with emphasis on the separation of free and bound sources, some authors prefer to further dissect the free current, too. This current is generally conceptualized as the current ‘not directly tied to the bound charges’ within a material. To name a few commonly recognized, *convection current*, *beam current*, or *conduction current*. It is the conduction current which is, in electrical engineering, especially worth mentioning because it arises from the movement of charges, typically electrons, that can move freely throughout the material. This kinetic energy of charges in conductors is the main cause of losses in waveguides and can be expressed by

$$\mathbf{J}_c = \hat{\sigma} * \mathbf{E}, \quad (1.4)$$

where $\hat{\sigma}$ is the material's *conductivity*. Equation (1.4), together with equations (1.3), completes the required set of constitutive relations.

The *constitutive parameters* $\hat{\epsilon}$, $\hat{\mu}$, and $\hat{\sigma}$, generally represented as complex second-rank tensors, establish the relationship between the applied electromagnetic fields and the material's response. The functional dependencies of these tensors provide a classification scheme for material properties:

- *Linearity*: A material is classified as linear if its constitutive parameters are independent of the applied field strength; otherwise, it is considered nonlinear.
- *Homogeneity*: If the constitutive parameters are invariant with respect to position within the material, it is deemed homogeneous; conversely, spatial dependence indicates an inhomogeneous medium.
- *Isotropy*: Materials exhibiting constitutive parameters independent of the applied field's direction are classified as isotropic. Conversely, direction-dependent parameters signify an anisotropic material, with crystals being a prime example.
- *Dispersion*: Materials whose constitutive parameters exhibit frequency dependence are categorized as dispersive. While some materials demonstrate negligible frequency dependence and can be effectively considered nondispersive, all materials encountered in practice exhibit some degree of dispersion.

Example 1.1.2 [Constitutive relations in free space]. In the simplest case of free space, equations (1.3a), (1.3b), and (1.4) become

$$\hat{\epsilon} = \epsilon_0 \approx 8.854 \times 10^{-12} \text{ F m}^{-1}, \quad (1.5a)$$

$$\hat{\mu} = \mu_0 = 4\pi \times 10^{-7} \text{ H m}^{-1}, \quad (1.5b)$$

$$\hat{\sigma} = \sigma_0 = 0 \text{ S m}^{-1}. \quad (1.5c)$$

1.1.3 Boundary conditions

While the differential form of Maxwell's equations is a powerful tool for analysing electromagnetic fields within continuous media, material boundaries introduce discontinuities that require special treatment. These discontinuities in the fields arise at interfaces between media with different electrical properties or at surfaces carrying charge or current densities. To accurately describe the behaviour of the fields across such boundaries, Maxwell's equations in their integral form, which naturally incorporate these discontinuities, are more convenient. This form is obtained by applying integral theorems from vector calculus to equations (1.2) which then take on the form of

$$\oint_S \mathbf{D} \cdot d\mathbf{a} = Q_e, \quad (1.6a)$$

$$\oint_{\partial S} \mathbf{E} \cdot d\mathbf{l} = - \int_S \mathbf{J}_m \cdot d\mathbf{a} - \frac{d}{dt} \int_S \mathbf{B} \cdot d\mathbf{a}, \quad (1.6b)$$

$$\oint_S \mathbf{B} \cdot d\mathbf{a} = Q_m, \quad (1.6c)$$

$$\oint_{\partial S} \mathbf{H} \cdot d\mathbf{l} = \int_S \mathbf{J}_e \cdot d\mathbf{a} + \frac{d}{dt} \int_S \mathbf{D} \cdot d\mathbf{a}, \quad (1.6d)$$

where S is any closed surface.

Consider a boundary between two different media. The first medium is characterized by permittivity ϵ_1 and permeability μ_1 , while the second medium is characterized by permittivity ϵ_2 and permeability μ_2 . At this interface, electric and magnetic surface charge densities, denoted by q_f and q_m , respectively, may be present. Additionally, electric and magnetic surface current densities, denoted by j_f and j_m , respectively, may also exist. The general *boundary conditions* for electrodynamics are then obtained by applying equations (1.6) to arbitrary surfaces encompassing a portion of the interface, yielding

$$\mathbf{e}_n \cdot (\mathbf{D}_1 - \mathbf{D}_2) = q_f, \quad (1.7a) \quad \mathbf{e}_n \cdot (\mathbf{B}_1 - \mathbf{B}_2) = q_m, \quad (1.7c)$$

$$-\mathbf{e}_n \times (\mathbf{E}_1 - \mathbf{E}_2) = \mathbf{j}_m, \quad (1.7b) \quad \mathbf{e}_n \times (\mathbf{H}_1 - \mathbf{H}_2) = \mathbf{j}_f. \quad (1.7d)$$

1.2 Electromagnetic waves

Having established the foundations of electromagnetism, the focus is now shifted to one of its most significant consequences: the existence of electromagnetic waves. In this section, the manner in which Maxwell's equations predict the propagation of these waves is explored. The wave equations for the electric and magnetic fields are derived, revealing their interconnected nature and their ability to sustain each other even in the absence of sources. Subsequently, the simplest and most fundamental solutions to these equations, *monochromatic plane waves*, are investigated. Finally, the confinement and guidance of these plane waves within conducting cavities is examined, laying the groundwork for understanding waveguides and resonant structures.

1.2.1 The wave equations

Maxwell's equations provide a comprehensive description of electromagnetic phenomena, but their coupled nature can make them challenging to solve directly. To

facilitate analysis, particularly in source-free regions, it's often advantageous to decouple the equations and express them in terms of the electric and magnetic fields individually. Inside regions with no *free* charge or *free* current, Maxwell's equations (1.2) take on the form of

$$\operatorname{div} \mathbf{D} = 0, \quad (1.8a) \quad \operatorname{div} \mathbf{B} = 0, \quad (1.8c)$$

$$\operatorname{curl} \mathbf{E} = -\partial_t \mathbf{B}, \quad (1.8b) \quad \operatorname{curl} \mathbf{H} = \sigma \mathbf{E} + \partial_t \mathbf{D}. \quad (1.8d)$$

Furthermore, if the medium is *linear* and *homogeneous*, equation (1.8d) can be fully expressed in terms of \mathbf{E} . With this simplification, applying the curl to equations (1.8b) and (1.8d) yields

$$\Delta \mathbf{E} = \mu\sigma\partial_t \mathbf{E} + \mu\epsilon\partial_t^2 \mathbf{E}, \quad (1.9a) \quad \Delta \mathbf{B} = \mu\sigma\partial_t \mathbf{B} + \mu\epsilon\partial_t^2 \mathbf{B}. \quad (1.9b)$$

Therefore, electric and magnetic fields in linear homogeneous media both clearly satisfy the wave equation with a linear damping term $\mu\sigma\partial_t$, introduced by conductive losses. Moreover, in regions with $\sigma = 0$, such as free space or ideal insulators, equations (1.9) simplify even more to

$$\Delta \mathbf{E} = \mu\epsilon\partial_t^2 \mathbf{E}, \quad (1.10a) \quad \Delta \mathbf{B} = \mu\epsilon\partial_t^2 \mathbf{B}, \quad (1.10b)$$

taking on the form of classical wave equations which are ubiquitous in physics. This also immediately gives rise to the formula

$$v = \frac{1}{\sqrt{\epsilon\mu}} = \frac{c}{\sqrt{\epsilon_r\mu_r}} \quad (1.11)$$

for the speed of electromagnetic waves in linear homogeneous media.

Remark 1.2.1. Compared with the original Maxwell's equations (1.2), these equations form two systems of second-order partial differential equations but are now decoupled and provide us with an additional solving method for given boundary-value problems. However, it is important to note that the wave equations (1.9a) and (1.9b) were derived from Maxwell's equations (1.8) by differentiation. This impedes their mathematical equivalence. More specifically, as stated in [2], whereas every solution to Maxwell's equations is also a solution for the wave equations, the converse is not true.

1.2.2 Monochromatic plane waves

The electromagnetic theory presented thus far describes general vector fields that vary in space and time. However, as shown in section 1.2.1, electromagnetic fields in source-free regions exhibit wave behaviour. Nonetheless, these time-varying vector fields remain complex and challenging to analyse in practical systems. Consider the elementary solution to the wave equation

$$\hat{\psi}(\mathbf{r}, t) = \hat{\Psi}_0 \exp \left[i \left(\hat{\mathbf{k}} \cdot \mathbf{r} - \omega t \right) \right]. \quad (1.12)$$

Here, $\hat{\mathbf{k}}$ is the complex *wave vector* indicating the direction of wave propagation, and ω is the angular frequency of the wave. Equation (1.12) is expressed in terms of a *complex wave function* with a *complex amplitude* $\hat{\Psi}_0 \equiv \Psi_0 e^{i\varphi}$. This quantity encapsulates both the *real amplitude* Ψ_0 and the *phase shift* φ , of the physical wave. A sinusoidal wave

representing this solution in physical reality can be extracted from equation (1.12) using the *Euler's formula*, yielding

$$\psi(\mathbf{r}, t) = \operatorname{Re} \left[\hat{\Psi}_0 \exp \left[i \left(\hat{\mathbf{k}} \cdot \mathbf{r} - \omega t + \varphi \right) \right] \right] = \operatorname{Re} \left[\hat{\psi}(\mathbf{r}, t) \right]. \quad (1.13)$$

Remark 1.2.2. Clearly, if equation (1.13) satisfies equations (1.10) and Maxwell's equations, the same holds true for equation (1.12), as the imaginary part differs from the real part only by the replacement of sine with cosine.

Equation (1.12) serves as an established elementary solution to the general wave equation, and hence also to equations (1.10). Substituting this solution into equations (1.9), it becomes evident that these 'lossy wave equations' also admit plane-wave solutions. Furthermore, this substitution allows for the derivation of a general formula for the complex *wavenumber*

$$\hat{k}^2 = \hat{\mathbf{k}} \cdot \hat{\mathbf{k}} = \mu \epsilon \omega^2 + i \mu \sigma \omega. \quad (1.14)$$

In the context of equation (1.12), it is evident that the real part of the complex wavenumber \hat{k} is the *actual* wavenumber as it determines the change of phase with spatial propagation. For this reason, the real part is simply denoted k and is called the *phase constant*. In contrast, the imaginary part of \hat{k} is responsible for the exponential damping, or attenuation, in conductive media, and hence is called the *attenuation constant*.

Waves described by equation (1.12) are called *monochromatic*, or *time-harmonic*, *plane* waves. Monochromaticity refers to the fact that the wave oscillates at a single frequency ω through time, while planarity indicates that the fields are uniform over every plane perpendicular to the direction of propagation. Although less common, plane waves could alternatively be called *space-harmonic*,³ as both of these terms signify a sinusoidal dependence on a given variable. In the case of monochromaticity, the variable is time, oscillating with an angular frequency ω . Similarly, planarity reflects the waveform repetition in the spatial coordinates, projected into the propagation direction, with a well-defined spatial frequency k .

The significance of this particular solution stems from the fact that, in practice, any wave we will be dealing with can be expressed as a linear combination of these monochromatic plane waves, i.e.,

$$\hat{\psi}(\mathbf{r}, t) = \int_{\mathbb{R}^3} \hat{\Psi}_0(\mathbf{k}) \exp \left[i \left(\hat{\mathbf{k}} \cdot \mathbf{r} - \omega t \right) \right] d\mathbf{k}. \quad (1.15)$$

This superposition principle mathematically reflects the Fourier transform over every plane wave corresponding to a given frequency ω . With this formally sound mathematical description, the existence of a unique linear combination for 'any wave we will be dealing with', as vaguely stated above, can be rigorously established through the following theorem.

Theorem 1.2.3 [Dirichlet-Jordan test]. *Let f be a function in $L^1(-\infty, \infty)$ and of bounded variation in a neighbourhood of the point x . Then*

$$\frac{1}{\pi} \lim_{M \rightarrow \infty} \int_0^M du \int_{\mathbb{R}} f(t) \cos(u(x - t)) dt = \lim_{\epsilon \rightarrow 0} \frac{f(x + \epsilon) + f(x - \epsilon)}{2}. \quad (1.16)$$

If f is continuous in an open interval, then the integral on the left-hand side converges uniformly in the interval, and the limit on the right-hand side is $f(x)$.

³Therefore, monochromatic plane waves are something one could call *spacetime-harmonic* or simply *harmonic*.

More details on this mathematical theory can be found in [4]. A version of theorem 1.2.3, retaining the original form due to Dirichlet, is often used in signal processing. More details on that formulation can be found, e.g., in [5].

Since any physically realizable signal is square-integrable and has compact support,⁴ this text's attention is confined to monochromatic plane waves. Therefore, the fields take on the form of

$$\hat{\mathbf{E}}(\mathbf{r}, t) = \hat{\mathbf{E}}_0 \exp \left[i \left(\hat{\mathbf{k}} \cdot \mathbf{r} - \omega t \right) \right], \quad (1.17a)$$

$$\hat{\mathbf{B}}(\mathbf{r}, t) = \hat{\mathbf{B}}_0 \exp \left[i \left(\hat{\mathbf{k}} \cdot \mathbf{r} - \omega t \right) \right], \quad (1.17b)$$

where $\hat{\mathbf{E}}_0$ and $\hat{\mathbf{B}}_0$ are complex amplitudes.

As discussed in remark 1.2.1, satisfying the wave equations does not guarantee solutions to Maxwell's equations. Substituting the solutions of the wave equations into Maxwell's equations is necessary, as it might refine the solutions or yield more information. As an example, consider the plane waves in vacuum.

Example 1.2.4 [Monochromatic plane waves in free space]. Substituting equations (1.17a) and (1.17b) for the electric and magnetic field in the free-space version of equations (1.8a) and (1.8c) read

$$\mathbf{k} \cdot \hat{\mathbf{E}}_0 = \mathbf{k} \cdot \hat{\mathbf{B}}_0 = 0, \quad (1.18)$$

i.e., the electromagnetic fields are *transverse*. Furthermore, either of equations (1.8b) and (1.8d) yields

$$\hat{\mathbf{B}}_0 = \frac{1}{\omega} \left(\mathbf{k} \times \hat{\mathbf{E}}_0 \right) = \frac{1}{c} \left(\mathbf{e}_k \times \hat{\mathbf{E}}_0 \right). \quad (1.19)$$

Clearly, in free space, \mathbf{E} and \mathbf{B} are *mutually perpendicular* and *in phase*, meaning their oscillations reach their peaks and troughs simultaneously.

To further characterize the plane wave, a *polarization vector* is introduced. This unit vector points in the direction of electric field oscillations, i.e.,

$$\mathbf{e}_n \cdot \mathbf{E} = E \quad \|\mathbf{e}_n\| = 1. \quad (1.20)$$

With this definition, the complete solution to Maxwell's equations for a plane wave in free space takes the form of

$$\mathbf{E}(\mathbf{r}, t) = E_0 \cos(\mathbf{k} \cdot \mathbf{r} - \omega t + \varphi) \mathbf{e}_n, \quad (1.21)$$

$$\mathbf{B}(\mathbf{r}, t) = \frac{1}{c} E_0 \cos(\mathbf{k} \cdot \mathbf{r} - \omega t + \varphi) (\mathbf{k} \times \mathbf{e}_n). \quad (1.22)$$

It's important to note that this transversality of the electromagnetic fields is a specific property of plane waves in free space or lossless media. When waves are confined in waveguides or propagate through lossy media, the fields generally have longitudinal components as well. This distinction arises because the boundary conditions imposed by the waveguide or the interactions with the medium can alter the field structure.

⁴In the field of signal processing, these signal properties are often described as having *finite energy* and *duration*, respectively.

1.2.3 Guided waves

The behaviour of electromagnetic waves within a waveguide is now explored. To provide a clear framework for analysis, it is assumed that the waveguide walls are perfect electric conductors (PEC), implying the absence of surface sources. This idealization leads to specific boundary conditions

$$\mathbf{e}_n \times \mathbf{E} = 0, \quad (1.23a)$$

$$\mathbf{e}_n \cdot \mathbf{B} = 0. \quad (1.23b)$$

It is important to recognize that free charges and currents will be induced on the surface precisely to enforce these constraints.

Furthermore, the focus is placed on monochromatic plane waves propagating along the waveguide. This implies that the electric and magnetic fields have a harmonic time dependence with a single angular frequency ω . The $\hat{\cdot}$ notation is dispensed with as \hat{k} is real for the cases of interest. The general form of the fields is then given by equations (1.17) where the z -axis is aligned with the waveguide's longitudinal direction. The complex amplitudes of the fields,

$$\hat{\mathbf{E}}_0 = E_x \mathbf{e}_x + E_y \mathbf{e}_y + E_z \mathbf{e}_z, \quad (1.24a)$$

$$\hat{\mathbf{B}}_0 = B_x \mathbf{e}_x + B_y \mathbf{e}_y + B_z \mathbf{e}_z, \quad (1.24b)$$

are functions of the transverse coordinates, x and y , reflecting the spatial variations of the fields within the waveguide cross-section.

To further simplify the analysis, the waveguide is considered to be source-free, meaning that there are no free charges or currents *impressed* within the waveguide itself. This allows the utilization of the simplified form of Maxwell's equations (1.8). Due to the assumed linearity of the medium within the waveguide, these equations are expressed in terms of E and B .

With these assumptions in place, the wave behaviour within the waveguide can be analysed. From equations (1.8b) and (1.8d), adapted for a linear medium, a set of coupled differential equations relating the transverse components of the electric and magnetic fields is obtained. These equations can be solved to express the transverse field components in terms of the longitudinal components, taking the form of

$$E_x = \zeta (k \partial_x E_z + \omega \partial_y B_z), \quad (1.25a) \quad B_x = \zeta \left(k \partial_x B_z - \frac{\omega}{c^2} \partial_y E_z \right), \quad (1.25c)$$

$$E_y = \zeta (k \partial_y E_z - \omega \partial_x B_z), \quad (1.25b) \quad B_y = \zeta \left(k \partial_y B_z + \frac{\omega}{c^2} \partial_x E_z \right), \quad (1.25d)$$

where $\zeta = i/((\omega/c)^2 - k^2)$. Finally, substituting equations (1.25) into equations (1.8a) and (1.8c) leads to uncoupled equations

$$\left[\partial_x^2 + \partial_y^2 + \left(\frac{\omega}{c} \right)^2 - k^2 \right] E_z = 0, \quad (1.26a)$$

$$\left[\partial_x^2 + \partial_y^2 + \left(\frac{\omega}{c} \right)^2 - k^2 \right] B_z = 0. \quad (1.26b)$$

These equations, often referred to as the *Helmholtz equations*, govern the longitudinal field components and play a crucial role in determining the allowed modes of propagation within the waveguide. These modes are categorized based on the presence or absence of longitudinal components in the electric and magnetic fields. *Transverse electric* (TE) waves have $E_z = 0$, while *transverse magnetic* (TM) waves have $B_z = 0$. The simplest waves, with both $E_z = B_z = 0$ are called *transverse electromagnetic* (TEM) waves, but these cannot exist within a hollow waveguide due to boundary conditions.

Remark 1.2.5 [Non-existence of TEM waves in hollow waveguides]. To further illustrate this point, consider the case of a waveguide with perfectly conducting walls.

Beginning with the scenario where the longitudinal component of the electric field, E_z , is zero, it follows from equation (1.8a) that the divergence of the electric field in the transverse plane must also be zero. Similarly, when the longitudinal component of the magnetic field, B_z , is zero, equation (1.8b) dictates that the curl of the electric field in the transverse plane must vanish.

Combining these results, the complex amplitude of the electric field, $\hat{\mathbf{E}}_0$, can be expressed as the gradient of a scalar potential φ that satisfies the Laplace's equation $\Delta\varphi = 0$. However, the boundary condition on the electric field, as expressed in equation (1.23a), enforces an equipotential at the conductor surface. Since Laplace's equation admits no local extrema, the potential must be constant throughout the waveguide, leading to a zero electric field.

Remark 1.2.6 [Modal decomposition of guided waves]. The equations for E_z and B_z , equations (1.26), are instances of the *Helmholtz equation* with Dirichlet and Neumann boundary conditions, respectively. This mathematical structure the eigenvalue problem for the Laplace operator arising in various physical contexts.

For instance, the same equation and boundary conditions govern the vertical displacements of a vibrating drumhead. In this analogy, TM modes correspond to a drumhead with fixed boundaries, while TE modes correspond to a drumhead with free boundaries. The TM case is also isomorphic to the Schrödinger problem for the wave functions and energy eigenvalues of a free particle in a two-dimensional box with hard walls. Seeking inspiration in these analogous problems provides useful intuition when thinking about the modal eigenfunctions and eigenvalues of a waveguide. Some key mathematical results stemming from these analogies include:

- (a) There are an infinite number of TE- and TM-mode eigenfunctions.
- (b) The eigenvalues are all real and positive.
- (c) The eigenfunctions can always be chosen real.
- (d) The eigenfunctions form a complete set of functions.
- (e) Eigenfunctions belonging to different eigenvalues are orthogonal.

Perhaps the most significant result in terms of applied electrodynamics is the completeness of the eigenfunctions, which implies that any field within a waveguide can be composed of its modes. Specifically, if α denotes a distinct mode⁵ then any wave travelling in the positive direction (denoted by the $+$ superscript) can be decomposed as

$$\hat{\mathbf{E}}^+ = \sum_{\alpha} C_{\alpha}^+ \left[\hat{\mathbf{E}}_{0,\alpha} + \mathbf{e}_z E_{z,\alpha} \right] \exp(-ik_{\alpha}z), \quad (1.27)$$

$$\hat{\mathbf{B}}^+ = \sum_{\alpha} C_{\alpha}^+ \left[\hat{\mathbf{B}}_{0,\alpha} + \mathbf{e}_z B_{z,\alpha} \right] \exp(-ik_{\alpha}z). \quad (1.28)$$

Similarly, for the negative direction (denoted by the $-$ superscript), the decomposition

⁵For example, in the case of a rectangular waveguide, a mode is given by the combination of two integers, m and n .

is given by

$$\hat{\mathbf{E}}^- = \sum_{\alpha} C_{\alpha}^- \left[\hat{\mathbf{E}}_{0,\alpha} - \mathbf{e}_z E_{z,\alpha} \right] \exp(i k_{\alpha} z), \quad (1.29)$$

$$\hat{\mathbf{B}}^- = \sum_{\alpha} C_{\alpha}^- \left[-\hat{\mathbf{B}}_{0,\alpha} + \mathbf{e}_z B_{z,\alpha} \right] \exp(i k_{\alpha} z). \quad (1.30)$$

Furthermore, thanks to the mutual orthogonality of modes, the modal decomposition is uniquely given by the orthogonal projection

$$C_{\alpha}^{\pm} = \frac{1}{2} \frac{\int_S \left[\hat{\mathbf{E}}_{0,\alpha}^* \cdot \hat{\mathbf{E}} \pm \left(\frac{\omega}{k_{\alpha}} \right)^2 \hat{\mathbf{B}}_{0,\alpha}^* \cdot \hat{\mathbf{B}} \right] dS}{\int_S \hat{\mathbf{E}}_{0,\alpha}^* \cdot \hat{\mathbf{E}}_{0,\alpha} dS} \exp(\pm i k_{\alpha} z), \quad (1.31)$$

where S is an arbitrary cross-section of the waveguide.

These two results combined lead to a powerful conclusion: the tangential fields within an arbitrary cross-section of the waveguide fully determine the field everywhere within the waveguide. This means that if the tangential components of the electric and magnetic fields are known on a single transverse plane, the entire field distribution within the waveguide can be uniquely determined, both in the transverse plane and along the direction of propagation.

Example 1.2.7 [TE waves in a rectangular waveguide]. This example delves into the specific case of TE waves within a rectangular waveguide. A waveguide with height a in the x -direction and width b in the y -direction is considered, the z -axis again being aligned with the waveguide's longitudinal direction. The objective is to derive an expression for the longitudinal component of the magnetic field, B_z , using the method of separation of variables. This method involves assuming that, for every x and y , $B_z(x, y)$ can be expressed as the product of two independent functions, $X(x)$ and $Y(y)$.

Substituting this product into equation (1.26b) yields a differential equation that can be rearranged by dividing through by B_z . This rearranged equation reveals that the x -dependent and y -dependent terms must be constant, leading to two ordinary differential equations,

$$\frac{1}{X} X'' = -k_x^2, \quad (1.32a) \quad \frac{1}{Y} Y'' = -k_y^2. \quad (1.32b)$$

Additionally, a relationship between the separation constants, k_x and k_y , and the wave number, k , is established as

$$-k_x^2 - k_y^2 + \left(\frac{\omega}{c} \right)^2 - k^2 = 0. \quad (1.33)$$

Equation (1.32a) is a simple second-order ordinary differential equation, with a general solution of the form

$$X(x) = A \sin(k_x x) + B \cos(k_x x). \quad (1.34)$$

To determine the particular solution, boundary conditions must be applied. The boundary condition (1.23b) enforces the vanishing of B_x at $x = 0$ and $x = a$. According to equation (1.25c), this translates to enforcing the vanishing of $\partial_x B_z = X'$ at those points. This implies $A = 0$ and the separation constant k_x must satisfy the condition

$$k_x = \frac{m\pi}{a}, \quad m \in \mathbb{N}_0. \quad (1.35)$$

Similarly, for the function $Y(y)$, the boundary condition leads to the condition

$$k_y = \frac{n\pi}{b}, \quad n \in \mathbb{N}_0. \quad (1.36)$$

Combining these results, the particular solution for B_z takes the form of

$$B_z(x, y) = B_0 \cos\left(\frac{m\pi}{a}x\right) \cos\left(\frac{n\pi}{b}y\right), \quad (1.37)$$

representing the TE_{mn} wave with the corresponding wavenumber given by equation (1.33). This information is a complete solution to the wave propagation since the remaining field components are given by equations (1.25).

Examining equation (1.33), it becomes evident that if the frequency falls below a certain *cutoff frequency*,

$$f_{mn} \equiv \frac{c}{2} \sqrt{\left(\frac{m}{a}\right)^2 + \left(\frac{n}{b}\right)^2}, \quad (1.38)$$

the wavenumber becomes imaginary. This signifies that the wave cannot propagate and instead decays exponentially within the waveguide. Such solutions are referred to as *evanescent waves*. This cutoff frequency depends on the mode numbers (m, n) and the dimensions of the waveguide (a, b) . Modes having the same cutoff frequency are called *degenerate*.

The wavelength corresponding to wavenumber k in the direction of guided wave propagation is called the *guide wavelength* and is given by

$$\lambda_g \equiv \frac{2\pi}{k} = \frac{\lambda}{\sqrt{1 - \left(\frac{f_{mn}}{f}\right)^2}} = \frac{\lambda}{\sqrt{1 - \left(\frac{\lambda}{\lambda_{mn}}\right)^2}}. \quad (1.39)$$

This guide wavelength is related to the free-space wavelength, λ , and the cutoff wavelength, λ_{mn} , for the TE_{mn} mode.

To do: Maybe add some talk about modes to finish the theoretical chapter smoothly. Perhaps something about frequency dependence of modes' evanescence or something along the lines of that...

Conclusion

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

Aliquam lectus. Vivamus leo. Quisque ornare tellus ullamcorper nulla. Mauris porttitor pharetra tortor. Sed fringilla justo sed mauris. Mauris tellus. Sed non leo. Nullam elementum, magna in cursus sodales, augue est scelerisque sapien, venenatis congue nulla arcu et pede. Ut suscipit enim vel sapien. Donec congue. Maecenas urna mi, suscipit in, placerat ut, vestibulum ut, massa. Fusce ultrices nulla et nisl.

Glossary of Symbols

curl	curl
Δ	Laplace operator
div	divergence
ϵ	permittivity
grad	gradient
μ	permeability
$\partial\Omega$	boundary of set Ω
∂_ξ	partial derivative w.r.t. variable ξ
ρ_e	electric charge density
ρ_m	magnetic charge density
σ	conductivity
\boldsymbol{B}	magnetic flux density
\boldsymbol{D}	electric flux density
\boldsymbol{E}	electric field intensity
\boldsymbol{e}_ξ	unit vector in the ξ -direction
\boldsymbol{e}_n	polarization vector
\boldsymbol{H}	magnetic field intensity
\boldsymbol{J}_e	source electric current density
\boldsymbol{J}_m	magnetic current density
\boldsymbol{k}	wave vector

Bibliography

- [1] C. Balanis, *Advanced Engineering Electromagnetics*. Wiley, 2012, ISBN: 9781118213483. [Online]. Available: <https://books.google.com.tw/books?id=2eMbAAAAQBAJ>.
- [2] D. Griffiths, *Introduction to Electrodynamics* (Pearson international edition). Prentice Hall, 1999, ISBN: 9780139199608. [Online]. Available: <https://books.google.com.tw/books?id=x0akQgAACAAJ>.
- [3] A. Zangwill, *Modern Electrodynamics* (Modern Electrodynamics). Cambridge University Press, 2013, ISBN: 9780521896979. [Online]. Available: <https://books.google.com.tw/books?id=tEYSUegp9WYC>.
- [4] E. Titchmarsh, *Introduction to the Theory of Fourier Integrals*. Clarendon Press, 1948, ISBN: 9780608133492. [Online]. Available: <https://books.google.com.tw/books?id=1BMIAQAAIAAJ>.
- [5] A. Oppenheim, A. Willsky and S. Nawab, *Signals & Systems* (Prentice-Hall signal processing series), 2nd ed. Prentice-Hall International, 1997, ISBN: 9780136511755. [Online]. Available: <https://books.google.com.tw/books?id=09ZHSAACAAJ>.

Index

boundary conditions, [6](#)

constitutive parameters, [5](#)

constitutive relations, [5](#)

cutoff frequency, [13](#)

degenerate modes, [13](#)

guide wavelength, [13](#)

Helmholtz equations, [10](#)

modal decomposition, [11](#)

monochromatic plane wave, [7](#)

polarization vector, [9](#)